

Monopole PCB Antenna with Single or Dual Band Option

By Richard Wallace

Keywords

- Single Band Mode (868 MHz, 915 MHz or 920 MHz)
- Dual Band Mode (868 MHz & 2440 MHz)
- PCB Antenna
- Monopole Antenna
- Excellent Efficiency
- Recommended Antenna Design for 868 MHz, 915 MHz & 920 MHz
- OTA Measurements

1 Introduction

This document describes a PCB antenna that can be configured in two different modes of operation: the antenna can be tuned for a single frequency for operation in the 868 MHz (Europe), 915 MHz (USA) and 920 MHz (Japan) ISM bands; or the antenna can be configured as a dual band antenna which can operate at 868 MHz and 2440 MHz.

This antenna can be used with all transceivers and transmitters from Texas Instruments which operates in these frequency bands.

Overall size requirements for this antenna are 38 x 25 mm. Thus this is a medium size, low cost antenna solution. Figure 1 shows a picture the board being used to develop and characterize this antenna.

This antenna design is one of the several antenna reference designs available on www.ti.com/lpw and is included in the Comprehensive Antenna Selection Guide [6] and the Antenna Selection Quick Guide [7].




Figure 1. CC-Antenna-DK, Board #6 PCB Monopole Antenna

Table of Contents

KEYWORDS	1
1 INTRODUCTION	1
2 ABBREVIATIONS	2
3 DESCRIPTION OF THE PCB ANTENNA	3
3.1 IMPLEMENTATION OF THE MEANDERING MONOPOLE ANTENNA	3
4 RESULTS	5
4.1 RADIATION PATTERN	5
4.2 SINGLE BAND OPTION DESIGN FOR 868 / 915 / 920 MHz	6
4.2.1 <i>Antenna Match</i>	6
4.2.1.1 Smith Chart – No Antenna Match Components	6
4.2.1.2 Theoretical Smith Chart Match	7
4.2.2 <i>Bandwidth</i>	8
4.3 DUAL BAND OPTION DESIGN FOR 868 & 2440 MHz	9
4.3.1 <i>Antenna Match</i>	9
4.3.1.1 Smith Chart – No Antenna Match Components	9
4.3.2 <i>Bandwidth</i>	12
4.4 OTA MEASUREMENT SUMMARY	13
5 CONCLUSION	14
6 REFERENCES	15
7 DOCUMENT HISTORY	16

2 Abbreviations

AUT	Antenna Under Test
BOM	Bill Of Materials
BW	Bandwidth
CF	Correction Factor
CITA	Cellular Telecommunications Industry Association
DK	Development Kit
EB	Evaluation Board
EIRP	Effective Isotropic Radiated Power
EM	Evaluation Module
ISM	Industrial, Scientific, Medical
NC	Not Connected
NHPRP	Near Horizon Partial Radiated Power
NHPRP45	Near Horizon Partial Radiated Power within 45 degrees angle
OTA	Over The Air
PCB	Printed Circuit Board
RF	Radio Frequency
SWR	Standing Wave Ratio
TRP	Total Radiated Power

3 Description of the PCB Antenna

The antenna described in this document is a meandering monopole. The impedance of this antenna depends on the mode used. Referring to Figure 2, if the length of L4 is kept as shown then this is beneficial for the Dual Band Mode. If L4 is shortened to the silkscreen marking, then this is beneficial for the Single Band Mode.

It is recommended to use a pi-matching network at the feed point of the antenna as shown in Figure 2 since the geometry of the ground plane affects the impedance of the antenna. The pi-network can be used to compensate for detuning caused by plastic encapsulation and other objects in close vicinity of the antenna. For further information on impedance matching and impedance measurements, see AN058 [6].

The antenna layout is positioned on the top and bottom layer of the board; this enables a lower resistive loss and gives a slightly wider bandwidth compared to a single sided layout solution. With a single sided layout; the area underneath the antenna can not be used for any other routing so it is more useful to utilize this area to optimize the antenna's performance.

3.1 Implementation of the Meandering Monopole Antenna

To obtain optimum performance it is important to make an exact copy of the antenna dimensions. The antenna was implemented on a 1.6 mm thick FR4 substrate. Since there is no ground plane beneath the antenna the PCB thickness is not critical, but if a different thickness is being used it will be necessary to change the matching network to obtain optimum performance.

One approach to implement the antenna in a PCB CAD tool is to import the antenna layout from a Gerber file. Such a file is included in the CC-Antenna-DK Reference Design [8]. The CC-Antenna-DK contains 16 different board designs [1] and the gerbers from board 6 can be copied for this antenna design.

If the antenna is implemented on a PCB that is wider than the antenna it is important to avoid placing components or having a ground plane close to each side of the antenna. If the CAD tool being used does not support import of Gerber files, Figure 2 and Table 1 can be used.




Figure 2. Antenna Dimensions

L1	9.0 mm	Y	43.0 mm
L2	18.0 mm	X1	63.0 mm
L3	3.0 mm	X2	25.0 mm
L4	38.0 mm	W	2.0 mm
L5	1.0 mm		

Table 1. Antenna Dimensions

Optimum length for the last antenna segment is dependent on the geometry of the ground plane. The antenna can also be used for 915 & 920 MHz. For larger ground planes L4 would have to be further reduced or the antenna match re-calculated.

4 Results

The CTIA measurement summary results are presented in this section. Note that the performance will be affected by the size and shape of the ground plane.

4.1 Radiation Pattern

Figure 3 and Figure 4 shows how to relate the radiation patterns in this section to the orientation of the antenna. A link to the full measurement report is included in the measurement summary. For reference purposes; measurements have also been performed on the standard whip SMA antennas that are supplied with the EM boards [3], [4].

Note that the size of the ground plane will affect the radiation pattern. Thus implementing this antenna on a board with a different size and shape of the ground plane will most likely affect the radiation pattern.




Figure 3. Coordinates for the Radiation Patterns when used as a stand alone board




Figure 4. Coordinates for the Radiation Patterns when used with the EM & EB

4.2 Single band Option Design for 868 / 915 / 920 MHz

4.2.1 Antenna Match

4.2.1.1 Smith Chart – No Antenna Match Components

Even with no antenna match components (Z62: 0 ohm), the SWR at 868 MHz is 1.8 and this is a good match (SWR < 2.0) but still recommend inserting the matching components to be able to tune the antenna furthermore if so required due to surroundings may affect the resonance.




Figure 5: Start Match Value with 0 ohm resistor

4.2.1.2 Theoretical Smith Chart Match




Figure 6: Antenna Match – 868 MHz

With a series 1.8nH inductor (Z62) and a shunt capacitor (Z61), the match theoretically should be improved to SWR of 1.1. The BOM used for this match can be found in Table 2.

Size	Width (mm)	Height (mm)
PCB Board	45	95
GND	43	63

BOM	Ref. Designator	Murata Part Number	Value
	Z61	GRM1555C1H2R7CZ01D	2.7 pF
	Z62	LQG15HS1N8S02D	1.8 nH
	Z63	NC	-

Table 2: BOM for Board #6: Single Band Antenna – 868 MHz

To confirm the theoretical match, the impedance is measured again and was the match could be confirmed as shown in Figure 7 with a SWR of 1.1.

Note that the match for this Single Mode configuration is good at 868 MHz and poor at 2.4 GHz.




Figure 7: Matched Antenna at 868 MHz

4.2.2 Bandwidth

As can be seen from Figure 8, the bandwidth with a SWR of 2.0 (-10 dB RL) is 913 MHz – 825 MHz = 88 MHz.




Figure 8: 88 MHz Bandwidth Measurement (868 MHz) @ SWR of 2.0

4.3 Dual band Option Design for 868 & 2440 MHz

4.3.1 Antenna Match

4.3.1.1 Smith Chart – No Antenna Match Components

With no antenna match components (Z_{62} : 0 ohm), at 868 MHz the match is poor with SWR 2.9 and excellent at 2.44 GHz with SWR 1.2. The match needs to be improved at 868 MHz with the matching network.




Figure 9: Start Match Value with 0 ohm resistor

The tricky part is to have a good match at both 868 MHz and 2.44 GHz. A series capacitor was chosen at 3.9 pF; theoretically the new match at 868 MHz should be improved to SWR 1.3 and at 2.44 GHz the new match will be slightly worse from the original value but still with a good SWR 1.6. The match value at 2.44 GHz is a compromise because of the shared match value used at 868 MHz. The effects of the theoretical match values can be seen in Figure 10 and Figure 11.

4.3.1.2 Theoretical Smith Chart Match




Figure 10: Antenna Match – 868 MHz




Figure 11: Antenna Match – 2.44 GHz

Design Note DN024

With a series 3.9 pF capacitor (Z62), the BOM used for this match can be found in Table 3.

Size	Width (mm)	Height (mm)
PCB Board	45	95
GND	43	63

BOM	Ref. Designator	Murata Part Number	Value
	Z61	NC	-
	Z62	GRM1555C1H3R9CZ01D	3.9 pF
	Z63	NC	-

Table 3: BOM for Board #6: Dual Band Antenna – 868 MHz & 2.4 GHz

To confirm the theoretical match, the impedance is measured again and was the match could be confirmed as shown in Figure 12 with a SWR 1.2 for 868 MHz and SWR 1.6 for 2.44 GHz.

Note that the match for this Dual Mode configuration is good at both 868 MHz and 2.4 GHz.




Figure 12: Matched Antenna at 868 MHz and 2.44 GHz

4.3.2 Bandwidth

As can be seen from Figure 13, the bandwidth with a SWR of 2.0 (-10 dB RL) at 868 MHz is 893 MHz – 820 MHz = 73 MHz and at 2.4 GHz is 2740 MHz – 2386 MHz = 354 MHz.




Figure 13: 73 MHz (868 MHz) & 354 MHz (2.4 GHz) Bandwidth Measurement @ SWR of 2.0

4.4 OTA Measurement Summary

Table 4 summarizes the OTA measurements reports from the antenna configured as a Single Band Mode Antenna and as a Dual Band Antenna. The full version of the CTIA OTA report can be found in DN616 [5].

	Board 6 Single Band Mode (868 MHz)	Board 6 Dual Band Mode (868 MHz)	Board 6 Dual Band Mode (2440 MHz)
Full CTIA Report	DN616	DN616	DN616
Test Description	Test Result	Test Result	Test Result
Total Radiated Power	-0.10 dBm	-0.25 dBm	-0.21 dBm
Peak EIRP	5.05 dBm	4.85 dBm	3.35 dBm
Directivity	5.15 dBi	5.09 dBi	3.56 dBi
Efficiency	-0.10 dB	-0.25 dB	-0.21 dB
Efficiency	97.67 %	94.48 %	95.35 %
Gain	5.05 dBi	4.85 dBi	3.35 dBi
NHPRP 45°	-2.77 dBm	-2.87 dBm	-1.92 dBm
NHPRP 45° / TRP	-2.67 dB	-2.62 dB	-1.71 dB
NHPRP 45° / TRP	54.13 %	54.65 %	67.38 %
NHPRP 30°	-4.79 dBm	-4.85 dBm	-3.72 dBm
NHPRP 30° / TRP	-4.69 dB	-4.61 dB	-3.51 dB
NHPRP 30° / TRP	33.97 %	34.61 %	44.54 %
NHPRP 22.5°	-6.05 dBm	-6.10 dBm	-4.98 dBm
NHPRP 22.5° / TRP	-5.94 dB	-5.85 dB	-4.77 dB
NHPRP 22.5° / TRP	25.44 %	25.98 %	33.35 %
UHRP	-3.75 dBm	-3.94 dBm	-3.25 dBm
UHRP / TRP	-3.65 dB	-3.69 dB	-3.04 dB
UHRP / TRP	43.18 %	42.75 %	49.62 %
LHRP	-2.56 dBm	-2.67 dBm	-3.18 dBm
LHRP / TRP	-2.45 dB	-2.42 dB	-2.98 dB
LHRP / TRP	56.82 %	57.25 %	50.38 %
Front/Back Ratio	3.78	3.28	1.39
PhiBW	293.4 deg	300.3 deg	91.9 deg
PhiBW Up	212.0 deg	230.8 deg	39.7 deg
PhiBW Down	81.5 deg	69.5 deg	52.2 deg
ThetaBW	75.5 deg	59.9 deg	119.4 deg
ThetaBW Up	34.2 deg	20.6 deg	102.8 deg
ThetaBW Down	41.3 deg	39.3 deg	16.6 deg
Boresight Phi	135 deg	120 deg	90 deg
Boresight Theta	180 deg	180 deg	45 deg
Maximum Power	5.05 dBm	4.85 dBm	3.35 dBm
Minimum Power	-11.70 dBm	-11.84 dBm	-7.53 dBm
Average Power	1.12 dBm	0.96 dBm	-0.03 dBm
Max/Min Ratio	16.75 dB	16.69 dB	10.88 dB
Max/Avg Ratio	3.93 dB	3.89 dB	3.38 dB
Min/Avg Ratio	-12.82 dB	-12.80 dB	-7.50 dB
Best Single Value	4.24 dBm	4.15 dBm	2.62 dBm
Best Position	Phi = 105 deg; Theta = 165 deg; Pol = Hor	Phi = 90 deg; Theta = 165 deg; Pol = Hor	Phi = 75 deg; Theta = 60 deg; Pol = Ver

Table 4: Measurement Summary for both Single and Dual Band Mode

5 Conclusion

The antenna in this design note can be used in two different modes. When configured as Single Band Mode, this is ideal for 868 MHz, 915 MHz or 920 MHz operation. The antenna can also be configured in Dual Band Mode then the operation can also be at 868 MHz and 2.4 GHz. All modes of operation have a Transmitted Radiated Efficiency > 90 % and still maintaining a wide bandwidth [5].

The Dual Band Mode is ideal when the radio solution is working at both 868 MHz and 2.4 GHz. When using the Dual Band Mode it is important to keep the 3rd harmonic of the 868 MHz (2.604 GHz) underneath the regulatory limits since the 2.4 GHz antenna (2.74 GHz to 2.38 GHz) will also radiate the 3rd harmonic as well. If the reference design of the radio is followed, then the harmonic levels are well within the regulatory standards.

It is recommended to follow the antenna dimensions as shown in Figure 2, size of the antenna is 38 x 25 mm. The maximum gain is approximately 3 to 5 dBi which is typical for a monopole antenna.

Measurements of reflection show that the center frequency is dependent on the size of the ground plane, but this is easily compensated for by adjusting the antenna length or the antenna match network.

6 References

- [1] DN031 ([SWRA328.PDF](#)) – CC-Antenna-DK Documentation and Antenna Measurements Summary
- [2] DN603 ([SWRA332.PDF](#)) – Full CTIA Measurement Report for board 6
- [3] DN613 ([SWRA342.PDF](#)) - Standard Whip Antenna for 868 MHz & 915 MHz EM boards
- [4] DN614 ([SWRA343.PDF](#)) - Standard Whip Antenna for 2.4 GHz EM boards
- [5] DN616 ([SWRA345.PDF](#)) - CC-Antenna-DK, board #6 as stand alone in Single & Dual Mode
- [6] AN058 ([SWRA161.PDF](#)) – Antenna Selection Guide
- [7] DN035 ([SWRA351.PDF](#)) – Antenna Selection Quick Guide
- [8] CC-Antenna-DK Rev 1.0.0. Reference Design ([SWRR070.ZIP](#))

7 Document History

Revision	Date	Description/Changes
SWRA227E	2013.02.22	Updated with OTA CTIA Measurements and Dual-Band Option Mode
SWRA227D	2009.08.20	Added CC430 to list of devices
SWRA227C	2009.07.15	Corrected link to CC1110EM Meander Antenna Reference Design
SWRA227B	2009.04.14	Added EB to Abbreviations. Cosmetic changes
SWRA227A	2009.03.17	Updated with 955 MHz. Removed logo from header
SWRA227	2007.04.16	Initial release.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com

Test Report for DN024 (CC-Antenna-DK Board #6)

By Richard Wallace

Table of Contents

1	SINGLE BAND MODE	2
1.1	OTA TEST RESULTS FOR FREQUENCY 868.000 MHz	2
1.1.1	RP_868.000_tot	3
1.1.2	RP_868.000_hor	4
1.1.3	RP_868.000_ver	5
1.1.4	Radiation Patterns	6
2	DUAL BAND MODE	8
2.1	OTA TEST RESULTS FOR FREQUENCY 868.000 MHz	8
2.1.1	RP_868.000_tot	9
2.1.2	RP_868.000_hor	10
2.1.3	RP_868.000_ver	11
2.1.4	Radiation Patterns	12
2.2	OTA TEST RESULTS FOR FREQUENCY 2440.000 MHz	14
2.2.1	RP_2440.000_tot	15
2.2.2	RP_2440.000_hor	16
2.2.3	RP_2440.000_ver	17
2.2.4	Radiation Patterns	18
3	GENERAL INFORMATION	20
3.1	DOCUMENT HISTORY	20

Application Note DN616

1 SINGLE BAND MODE

1.1 OTA Test Results for Frequency 868.000 MHz

Total Radiated Power	-0.10 dBm
Peak EIRP	5.05 dBm
Directivity	5.15 dBi
Efficiency	-0.10 dB
Efficiency	97.67 %
Gain	5.05 dBi
NHPRP 45°	-2.77 dBm
NHPRP 45° / TRP	-2.67 dB
NHPRP 45° / TRP	54.13 %
NHPRP 30°	-4.79 dBm
NHPRP 30° / TRP	-4.69 dB
NHPRP 30° / TRP	33.97 %
NHPRP 22.5°	-6.05 dBm
NHPRP 22.5° / TRP	-5.94 dB
NHPRP 22.5° / TRP	25.44 %
UHRP	-3.75 dBm
UHRP / TRP	-3.65 dB
UHRP / TRP	43.18 %
LHRP	-2.56 dBm
LHRP / TRP	-2.45 dB
LHRP / TRP	56.82 %
Front/Back Ratio	3.78
PhiBW	293.4 deg
PhiBW Up	212.0 deg
PhiBW Down	81.5 deg
ThetaBW	75.5 deg
ThetaBW Up	34.2 deg
ThetaBW Down	41.3 deg
Boresight Phi	135 deg
Boresight Theta	180 deg
Maximum Power	5.05 dBm
Minimum Power	-11.70 dBm
Average Power	1.12 dBm
Max/Min Ratio	16.75 dB
Max/Avg Ratio	3.93 dB
Min/Avg Ratio	-12.82 dB
Best Single Value	4.24 dBm
Best Position	Phi = 105 deg; Theta = 165 deg; Pol = Hor

Application Note DN616

1.1.1 RP_868.000_tot

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.00	0.25	0.39	1.35	3.43	1.73	-5.42	-0.30	-1.15
15.00	0.56	0.37	1.37	3.47	1.19	-5.94	0.04	-0.08
30.00	0.88	0.68	0.82	3.18	-0.07	-6.04	0.26	0.31
45.00	1.34	0.44	0.53	2.36	-1.27	-6.48	-0.26	0.06
60.00	1.64	0.51	-0.41	1.44	-3.46	-6.03	-1.00	-0.73
75.00	2.01	0.10	-1.23	-0.02	-6.07	-5.69	-2.09	-2.04
90.00	2.22	-0.32	-1.66	-1.69	-9.13	-4.52	-2.91	-2.81
105.00	2.57	-0.53	-1.80	-3.33	-10.79	-3.13	-2.78	-2.56
120.00	2.91	0.02	-1.24	-4.45	-7.84	-2.01	-1.96	-0.90
135.00	3.29	0.63	0.12	-3.88	-5.87	-1.02	-1.04	0.54
150.00	3.49	1.65	1.01	-2.51	-3.72	-0.49	-0.70	1.28
165.00	3.89	2.38	2.13	-1.07	-2.39	-0.26	-0.87	1.59
180.00	4.07	3.22	2.77	0.30	-1.54	-0.09	-1.69	1.09
195.00	4.25	4.00	3.31	0.78	-0.98	-0.04	-2.74	0.28
210.00	4.27	4.36	3.39	0.89	-1.69	-0.14	-4.25	-0.91
225.00	4.34	4.47	3.33	0.08	-2.74	-0.60	-5.62	-2.26
240.00	3.84	4.47	3.03	-1.03	-5.09	-1.75	-6.37	-3.44
255.00	3.56	4.06	2.49	-2.53	-7.61	-3.19	-6.38	-4.16
270.00	3.12	3.30	1.85	-4.01	-7.48	-5.46	-5.22	-4.52
285.00	2.47	2.36	1.30	-3.41	-3.95	-7.27	-3.67	-3.85
300.00	1.79	1.53	1.08	-1.45	-1.97	-6.84	-2.34	-4.03
315.00	1.27	0.82	1.11	0.40	0.20	-5.90	-1.32	-3.68
330.00	0.85	0.38	1.24	1.79	1.19	-4.88	-0.82	-3.45
345.00	0.71	0.49	1.59	2.91	1.77	-4.89	-0.65	-2.37
360.00	0.31	0.39	1.62	3.39	1.42	-5.47	-0.34	-1.22

(continuation of the "RP_868.000_tot" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.00	0.51	4.19	3.56	2.37	1.46
15.00	0.49	4.36	3.61	2.41	1.16
30.00	-0.13	3.92	3.47	2.71	1.24
45.00	-1.95	3.16	3.49	3.11	1.75
60.00	-4.81	2.21	3.57	3.74	2.28
75.00	-7.98	1.23	3.66	3.97	3.21
90.00	-8.05	0.50	3.83	4.26	4.05
105.00	-4.18	0.15	4.12	4.59	4.69
120.00	-1.17	0.73	4.26	4.62	4.95
135.00	0.98	1.31	4.32	4.51	5.05
150.00	2.00	1.78	4.00	4.20	4.92
165.00	2.35	1.99	3.59	3.85	4.52
180.00	2.07	1.50	2.93	3.50	3.90
195.00	1.50	0.54	1.83	3.16	3.35
210.00	0.53	-0.82	0.74	3.10	2.84
225.00	-0.39	-3.53	-0.38	2.76	2.85
240.00	-1.43	-7.46	-1.74	2.67	2.84
255.00	-2.14	-11.70	-2.04	2.58	3.14
270.00	-2.22	-8.06	-1.31	2.58	3.28
285.00	-1.99	-3.70	0.05	2.61	3.46
300.00	-1.19	-0.94	1.21	2.44	3.55
315.00	-0.85	1.10	2.42	2.58	3.23
330.00	-0.13	2.52	2.82	2.34	2.92
345.00	0.09	3.54	3.43	2.15	2.11
360.00	0.63	4.01	3.49	2.22	1.70

Application Note DN616

1.1.2 RP_868.000_hor

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-9.44	-14.82	-16.34	-8.91	-10.57	-15.91	-16.16	-10.41
15.0	-7.86	-11.19	-11.51	-6.28	-10.46	-12.91	-12.70	-7.31
30.0	-4.05	-6.25	-7.17	-4.41	-11.15	-9.80	-8.60	-5.47
45.0	-1.02	-3.34	-4.52	-3.91	-11.69	-8.25	-6.03	-4.03
60.0	0.60	-1.49	-3.48	-3.48	-13.35	-6.51	-4.53	-3.17
75.0	1.67	-0.80	-2.93	-3.97	-15.27	-5.91	-3.93	-3.14
90.0	1.97	-0.78	-2.76	-4.30	-16.63	-5.40	-3.69	-3.11
105.0	1.74	-1.39	-3.49	-4.88	-17.24	-5.53	-3.85	-3.55
120.0	0.94	-2.49	-4.73	-5.90	-18.51	-6.07	-4.33	-3.46
135.0	-0.37	-4.74	-6.58	-7.53	-21.81	-6.93	-4.84	-4.45
150.0	-2.92	-8.55	-10.02	-9.68	-22.90	-7.93	-6.09	-5.25
165.0	-7.02	-17.21	-13.69	-12.60	-22.90	-10.64	-7.62	-7.07
180.0	-13.09	-11.28	-11.16	-14.66	-22.90	-12.69	-10.98	-9.98
195.0	-9.32	-5.18	-6.19	-11.82	-21.59	-13.01	-15.92	-14.93
210.0	-4.20	-1.73	-3.13	-8.54	-17.29	-10.69	-18.19	-16.23
225.0	-1.37	0.37	-0.66	-5.89	-13.37	-9.26	-12.31	-10.93
240.0	0.53	1.91	0.63	-4.46	-11.88	-8.18	-8.63	-8.06
255.0	1.81	2.50	1.49	-3.77	-10.68	-7.51	-6.89	-6.10
270.0	2.50	2.63	1.60	-4.18	-10.64	-8.19	-6.18	-5.24
285.0	2.38	2.24	1.20	-5.26	-11.09	-9.12	-6.08	-4.73
300.0	1.64	1.39	0.21	-7.20	-13.35	-10.05	-6.56	-6.13
315.0	0.38	-0.35	-1.81	-11.03	-16.87	-11.72	-8.29	-7.76
330.0	-1.59	-2.84	-4.17	-18.07	-18.11	-13.71	-10.26	-11.12
345.0	-4.71	-6.35	-8.73	-14.71	-15.59	-16.67	-15.53	-13.20
360.0	-9.06	-11.00	-15.19	-10.44	-12.30	-16.83	-20.45	-12.78

(continuation of the "RP_868.000_hor" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	-9.49	-10.68	-5.18	-6.50	-14.23
15.0	-12.05	-6.48	-3.36	-4.04	-12.02
30.0	-13.12	-4.43	-0.94	-1.07	-4.05
45.0	-13.29	-2.49	1.00	1.33	-0.18
60.0	-13.31	-1.27	2.60	3.06	1.75
75.0	-12.82	-0.35	3.40	3.85	3.12
90.0	-14.73	0.05	3.79	4.21	3.85
105.0	-16.93	-0.13	3.83	4.24	4.01
120.0	-17.46	-0.59	3.39	3.55	3.60
135.0	-17.27	-1.42	2.59	2.39	2.60
150.0	-18.67	-2.63	1.00	0.40	0.75
165.0	-15.92	-4.45	-0.86	-2.20	-2.28
180.0	-14.84	-6.49	-3.40	-5.27	-7.87
195.0	-11.69	-9.36	-5.61	-6.01	-16.99
210.0	-8.68	-11.74	-5.94	-3.20	-7.03
225.0	-6.40	-14.57	-4.65	-0.79	-1.83
240.0	-4.54	-14.90	-3.61	0.96	0.83
255.0	-3.32	-14.43	-2.36	2.00	2.56
270.0	-2.64	-12.75	-1.69	2.50	3.22
285.0	-2.57	-12.86	-1.48	2.42	3.31
300.0	-2.60	-12.94	-1.82	1.68	2.88
315.0	-3.86	-15.90	-2.72	0.37	1.57
330.0	-5.38	-16.85	-4.03	-1.83	-0.48
345.0	-7.38	-15.27	-5.16	-4.74	-4.34
360.0	-9.81	-11.89	-5.57	-6.28	-11.29

Application Note DN616

1.1.3 RP_868.000_ver

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-0.25	0.25	1.27	3.17	1.47	-5.83	-0.42	-1.70
15.0	-0.12	0.06	1.14	2.98	0.88	-6.91	-0.20	-0.99
30.0	-0.81	-0.30	0.06	2.35	-0.42	-8.41	-0.34	-1.03
45.0	-2.43	-1.92	-1.09	1.19	-1.68	-11.21	-1.59	-2.09
60.0	-5.06	-3.84	-3.37	-0.25	-3.93	-15.79	-3.55	-4.39
75.0	-9.23	-7.17	-6.11	-2.26	-6.63	-18.73	-6.71	-8.51
90.0	-10.23	-10.36	-8.14	-5.15	-9.98	-11.86	-10.78	-14.62
105.0	-4.99	-8.00	-6.73	-8.58	-11.90	-6.85	-9.40	-9.49
120.0	-1.47	-3.56	-3.82	-9.92	-8.22	-4.17	-5.71	-4.40
135.0	0.85	-0.86	-0.92	-6.33	-5.99	-2.31	-3.39	-1.12
150.0	2.36	1.21	0.65	-3.44	-3.77	-1.35	-2.18	0.18
165.0	3.53	2.33	2.01	-1.39	-2.43	-0.68	-1.90	0.95
180.0	3.98	3.06	2.59	0.16	-1.57	-0.34	-2.23	0.74
195.0	4.05	3.44	2.79	0.53	-1.02	-0.27	-2.96	0.15
210.0	3.60	3.13	2.30	0.36	-1.81	-0.54	-4.43	-1.04
225.0	2.99	2.33	1.11	-1.19	-3.13	-1.23	-6.67	-2.89
240.0	1.10	0.95	-0.68	-3.65	-6.10	-2.87	-10.29	-5.28
255.0	-1.23	-1.13	-4.38	-8.56	-10.56	-5.19	-15.90	-8.61
270.0	-5.67	-5.18	-10.75	-17.97	-10.35	-8.76	-12.23	-12.68
285.0	-14.67	-13.27	-15.04	-8.01	-4.89	-11.87	-7.36	-11.24
300.0	-13.00	-13.58	-6.36	-2.79	-2.29	-9.66	-4.41	-8.19
315.0	-6.04	-5.45	-1.99	0.08	0.12	-7.22	-2.29	-5.83
330.0	-2.80	-2.44	-0.23	1.74	1.14	-5.49	-1.35	-4.26
345.0	-0.76	-0.52	1.17	2.83	1.69	-5.19	-0.79	-2.75
360.0	-0.22	0.06	1.53	3.20	1.24	-5.80	-0.38	-1.54


(continuation of the "RP_868.000_ver" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	0.05	4.04	2.93	1.76	1.34
15.0	0.24	3.98	2.63	1.29	0.95
30.0	-0.36	3.23	1.52	0.35	-0.28
45.0	-2.28	1.78	-0.11	-1.63	-2.70
60.0	-5.48	-0.38	-3.41	-4.66	-7.14
75.0	-9.71	-3.94	-8.68	-11.75	-13.97
90.0	-9.10	-9.62	-17.21	-15.05	-9.42
105.0	-4.42	-11.79	-7.74	-6.57	-3.70
120.0	-1.27	-5.08	-3.16	-2.00	-0.79
135.0	0.92	-2.00	-0.52	0.39	1.40
150.0	1.96	-0.17	0.98	1.86	2.82
165.0	2.29	0.87	1.65	2.61	3.51
180.0	1.98	0.75	1.78	2.88	3.60
195.0	1.28	0.08	0.96	2.61	3.31
210.0	-0.02	-1.18	-0.31	1.93	2.37
225.0	-1.64	-3.89	-2.41	0.24	1.04
240.0	-4.33	-8.32	-6.32	-2.20	-1.48
255.0	-8.38	-15.00	-13.46	-6.42	-5.89
270.0	-12.56	-9.86	-12.10	-15.23	-14.87
285.0	-11.05	-4.26	-5.22	-11.00	-11.40
300.0	-6.77	-1.23	-1.78	-5.53	-4.89
315.0	-3.86	1.01	0.83	-1.42	-1.74
330.0	-1.67	2.47	1.81	0.24	0.26
345.0	-0.76	3.48	2.78	1.16	0.99
360.0	0.22	3.89	2.92	1.56	1.48


Application Note DN616

1.1.4 Radiation Patterns


Theta = 90, Phi = 0



Theta = 90, Phi = 90




Theta = 0, Phi = 0




Application Note DN616


Theta = 90, Phi = 180



Theta = 90, Phi = 270



Theta = 180, Phi = 0



Application Note DN616

2 DUAL BAND MODE

2.1 OTA Test Results for Frequency 868.000 MHz

Total Radiated Power	-0.25 dBm
Peak EIRP	4.85 dBm
Directivity	5.09 dBi
Efficiency	-0.25 dB
Efficiency	94.48 %
Gain	4.85 dBi
NHPRP 45°	-2.87 dBm
NHPRP 45° / TRP	-2.62 dB
NHPRP 45° / TRP	54.65 %
NHPRP 30°	-4.85 dBm
NHPRP 30° / TRP	-4.61 dB
NHPRP 30° / TRP	34.61 %
NHPRP 22.5°	-6.10 dBm
NHPRP 22.5° / TRP	-5.85 dB
NHPRP 22.5° / TRP	25.98 %
UHRP	-3.94 dBm
UHRP / TRP	-3.69 dB
UHRP / TRP	42.75 %
LHRP	-2.67 dBm
LHRP / TRP	-2.42 dB
LHRP / TRP	57.25 %
Front/Back Ratio	3.28
PhiBW	300.3 deg
PhiBW Up	230.8 deg
PhiBW Down	69.5 deg
ThetaBW	59.9 deg
ThetaBW Up	20.6 deg
ThetaBW Down	39.3 deg
Boresight Phi	120 deg
Boresight Theta	180 deg
Maximum Power	4.85 dBm
Minimum Power	-11.84 dBm
Average Power	0.96 dBm
Max/Min Ratio	16.69 dB
Max/Avg Ratio	3.89 dB
Min/Avg Ratio	-12.80 dB
Best Single Value	4.15 dBm
Best Position	Phi = 90 deg; Theta = 165 deg; Pol = Hor

Application Note DN616

2.1.1 RP 868.000 tot

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.00	0.24	0.22	1.30	3.35	1.37	-6.12	-0.35	-1.55
15.00	0.46	0.45	1.22	3.30	0.63	-6.20	-0.13	-0.37
30.00	0.84	0.44	0.80	2.80	-0.09	-6.00	-0.11	-0.05
45.00	1.10	0.48	0.15	1.99	-1.93	-5.87	-0.42	0.07
60.00	1.54	0.13	-0.71	0.81	-3.89	-5.88	-1.17	-1.10
75.00	1.80	-0.16	-1.70	-0.78	-6.72	-5.58	-2.15	-2.57
90.00	2.16	-0.71	-2.19	-2.31	-10.11	-4.66	-2.94	-3.45
105.00	2.47	-0.60	-2.17	-4.47	-10.72	-3.30	-2.65	-2.41
120.00	2.70	-0.16	-1.32	-5.33	-7.63	-1.86	-1.58	-0.89
135.00	2.92	0.61	-0.10	-4.43	-5.15	-0.95	-0.87	0.52
150.00	3.28	1.34	0.98	-2.15	-3.51	-0.29	-0.38	1.34
165.00	3.78	2.44	2.06	-0.93	-1.96	-0.01	-0.63	1.74
180.00	3.93	3.18	2.69	0.15	-1.30	0.16	-1.33	1.39
195.00	3.96	3.91	3.04	0.65	-1.42	-0.22	-2.68	0.35
210.00	4.04	4.15	3.20	0.78	-1.88	-0.62	-4.46	-0.85
225.00	3.96	4.30	2.95	-0.24	-3.66	-1.42	-6.13	-2.42
240.00	3.77	4.12	2.78	-1.48	-5.56	-2.47	-7.24	-3.37
255.00	3.15	3.54	2.01	-3.25	-8.19	-4.48	-7.10	-4.43
270.00	2.84	2.81	1.49	-4.47	-6.85	-6.28	-5.19	-4.36
285.00	1.96	1.93	0.95	-3.53	-3.92	-7.49	-3.34	-4.28
300.00	1.57	1.21	0.78	-1.59	-1.53	-6.67	-2.02	-3.97
315.00	1.09	0.56	0.90	0.47	0.13	-5.86	-1.24	-3.50
330.00	0.74	0.22	1.20	1.79	1.15	-4.63	-0.87	-3.04
345.00	0.24	0.21	1.29	2.81	1.51	-5.19	-0.33	-2.51
360.00	0.06	0.12	1.39	3.22	1.45	-5.90	-0.43	-1.37

(continuation of the "RP_868.000_tot" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.00	0.31	4.08	3.62	2.08	1.14
15.00	0.33	4.05	3.39	2.36	0.80
30.00	-0.60	3.65	3.46	2.66	0.92
45.00	-2.32	2.89	3.28	2.99	1.52
60.00	-5.40	2.13	3.47	3.44	2.42
75.00	-9.57	0.88	3.53	3.87	3.28
90.00	-8.62	0.16	3.82	4.23	3.93
105.00	-3.88	0.10	4.06	4.38	4.53
120.00	-1.02	0.41	4.21	4.48	4.85
135.00	0.98	1.22	4.06	4.40	4.84
150.00	2.21	1.59	3.82	4.03	4.61
165.00	2.50	1.65	3.25	3.68	4.26
180.00	2.17	1.40	2.65	3.27	3.63
195.00	1.51	0.42	1.58	2.98	2.98
210.00	0.84	-1.28	0.44	2.66	2.81
225.00	-0.48	-4.06	-0.78	2.54	2.64
240.00	-1.42	-7.80	-2.03	2.55	2.63
255.00	-2.06	-11.84	-2.25	2.42	2.97
270.00	-2.38	-8.23	-1.31	2.55	3.13
285.00	-2.14	-3.54	-0.08	2.35	3.43
300.00	-1.66	-1.06	1.21	2.23	3.44
315.00	-1.03	1.16	2.18	2.23	3.36
330.00	-0.48	2.37	2.79	2.05	2.68
345.00	0.19	3.43	3.33	2.20	2.11
360.00	0.54	3.90	3.50	2.00	1.43

Application Note DN616

2.1.2 RP_868.000_hor

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-10.28	-15.73	-16.69	-8.17	-10.17	-15.77	-19.15	-11.64
15.0	-7.90	-10.68	-10.23	-5.91	-10.59	-12.32	-12.08	-7.86
30.0	-3.41	-5.39	-6.56	-4.61	-10.57	-9.58	-8.51	-5.84
45.0	-0.95	-2.95	-4.20	-3.96	-11.81	-7.70	-6.09	-4.31
60.0	0.63	-1.62	-3.38	-4.05	-14.80	-6.43	-4.56	-3.73
75.0	1.53	-0.95	-3.16	-4.40	-16.48	-5.76	-3.68	-3.46
90.0	1.86	-1.10	-3.16	-4.71	-18.68	-5.71	-3.54	-3.58
105.0	1.57	-1.78	-4.18	-5.86	-20.67	-5.93	-3.88	-3.63
120.0	0.51	-3.13	-5.16	-7.16	-19.27	-6.08	-4.46	-4.40
135.0	-1.35	-5.47	-7.98	-9.60	-23.05	-7.56	-5.10	-4.94
150.0	-3.88	-10.34	-11.52	-11.30	-20.17	-8.73	-6.13	-6.00
165.0	-8.48	-16.34	-15.63	-17.33	-18.65	-10.65	-8.07	-7.74
180.0	-13.97	-9.56	-10.45	-17.65	-17.25	-12.21	-10.35	-10.80
195.0	-8.27	-4.30	-5.60	-12.06	-17.82	-14.13	-16.45	-16.54
210.0	-3.36	-1.38	-2.59	-8.13	-16.80	-12.79	-17.74	-16.50
225.0	-1.00	0.58	-0.68	-6.03	-13.72	-10.42	-12.38	-10.65
240.0	0.92	1.88	0.69	-4.73	-11.47	-9.36	-8.98	-7.37
255.0	1.67	2.31	1.20	-4.38	-11.13	-9.35	-7.36	-6.18
270.0	2.30	2.32	1.31	-4.73	-10.11	-9.10	-6.47	-5.47
285.0	1.93	1.88	0.74	-5.99	-11.52	-9.70	-6.38	-5.72
300.0	1.29	0.95	-0.36	-8.50	-13.51	-10.83	-7.15	-6.75
315.0	-0.15	-0.87	-2.22	-13.22	-17.23	-12.33	-8.85	-8.84
330.0	-2.19	-3.52	-4.84	-20.59	-17.31	-14.45	-11.03	-12.05
345.0	-6.22	-7.92	-10.09	-13.17	-14.12	-17.41	-15.26	-15.66
360.0	-10.56	-13.65	-16.71	-8.93	-11.82	-16.87	-22.46	-13.25

(continuation of the "RP_868.000_hor" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	-11.54	-9.97	-5.01	-6.90	-19.78
15.0	-13.50	-6.69	-3.21	-3.88	-10.32
30.0	-14.35	-4.10	-0.59	-0.65	-3.72
45.0	-14.93	-2.47	1.17	1.44	-0.09
60.0	-13.93	-1.11	2.59	2.86	1.97
75.0	-14.57	-0.50	3.35	3.79	3.20
90.0	-15.64	-0.16	3.76	4.15	3.65
105.0	-15.64	-0.17	3.68	3.91	3.72
120.0	-17.37	-0.88	3.17	3.28	3.29
135.0	-15.56	-1.93	1.98	1.97	2.00
150.0	-14.57	-3.61	0.68	0.03	0.12
165.0	-14.57	-5.59	-1.60	-2.69	-3.01
180.0	-12.79	-7.56	-4.01	-5.89	-8.54
195.0	-10.46	-10.49	-6.12	-6.04	-14.98
210.0	-7.27	-13.24	-6.29	-3.15	-5.77
225.0	-5.52	-15.99	-4.62	-0.66	-1.22
240.0	-3.97	-14.58	-3.42	1.04	1.07
255.0	-2.86	-13.45	-2.46	1.96	2.53
270.0	-2.54	-13.19	-1.76	2.52	3.11
285.0	-2.71	-13.11	-1.56	2.15	3.23
300.0	-3.18	-14.67	-1.80	1.31	2.67
315.0	-4.05	-15.91	-2.57	-0.15	1.52
330.0	-5.53	-20.20	-4.03	-2.40	-1.01
345.0	-7.54	-14.47	-5.32	-5.30	-5.19
360.0	-10.47	-11.37	-5.15	-6.77	-13.24

Application Note DN616

2.1.3 RP_868.000_ver

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-0.17	0.11	1.23	3.04	1.06	-6.62	-0.41	-1.99
15.0	-0.23	0.10	0.90	2.74	0.29	-7.42	-0.42	-1.23
30.0	-1.20	-0.87	-0.08	1.93	-0.50	-8.51	-0.79	-1.38
45.0	-3.15	-2.14	-1.83	0.72	-2.40	-10.50	-1.79	-1.89
60.0	-5.72	-4.66	-4.09	-0.91	-4.25	-15.14	-3.84	-4.51
75.0	-10.50	-7.94	-7.15	-3.26	-7.20	-19.48	-7.41	-9.92
90.0	-9.66	-11.34	-9.21	-6.04	-10.76	-11.36	-11.86	-18.65
105.0	-4.78	-6.84	-6.48	-10.10	-11.18	-6.72	-8.72	-8.52
120.0	-1.32	-3.20	-3.64	-9.95	-7.94	-3.92	-4.73	-3.46
135.0	0.88	-0.62	-0.87	-6.00	-5.22	-2.02	-2.93	-0.94
150.0	2.35	1.03	0.73	-2.72	-3.61	-0.97	-1.72	0.45
165.0	3.51	2.39	1.98	-1.03	-2.05	-0.40	-1.49	1.22
180.0	3.86	2.94	2.47	0.08	-1.42	-0.10	-1.91	1.12
195.0	3.69	3.20	2.40	0.41	-1.52	-0.40	-2.87	0.26
210.0	3.17	2.72	1.87	0.18	-2.03	-0.89	-4.67	-0.97
225.0	2.29	1.90	0.49	-1.57	-4.11	-2.00	-7.31	-3.13
240.0	0.60	0.18	-1.40	-4.26	-6.85	-3.46	-12.07	-5.57
255.0	-2.26	-2.53	-5.66	-9.64	-11.26	-6.19	-19.49	-9.22
270.0	-6.47	-6.91	-12.31	-16.86	-9.62	-9.49	-11.10	-10.81
285.0	-18.78	-17.02	-12.18	-7.15	-4.75	-11.48	-6.32	-9.77
300.0	-10.54	-11.20	-5.59	-2.58	-1.81	-8.78	-3.61	-7.22
315.0	-4.97	-4.96	-2.01	0.28	0.05	-6.97	-2.06	-5.00
330.0	-2.36	-2.16	-0.05	1.77	1.09	-5.10	-1.32	-3.62
345.0	-0.87	-0.52	0.96	2.70	1.39	-5.45	-0.47	-2.73
360.0	-0.34	-0.06	1.33	2.95	1.24	-6.26	-0.46	-1.66


(continuation of the "RP_868.000_ver" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	0.02	3.91	2.98	1.49	1.11
15.0	0.14	3.66	2.32	1.19	0.45
30.0	-0.79	2.85	1.28	-0.07	-0.90
45.0	-2.57	1.39	-0.88	-2.24	-3.58
60.0	-6.05	-0.66	-3.89	-5.57	-7.63
75.0	-11.22	-4.79	-10.54	-13.36	-14.06
90.0	-9.59	-11.21	-15.17	-12.93	-8.07
105.0	-4.18	-12.03	-6.72	-5.51	-3.14
120.0	-1.12	-5.49	-2.53	-1.71	-0.37
135.0	0.88	-1.66	-0.13	0.73	1.65
150.0	2.12	0.02	0.93	1.83	2.71
165.0	2.42	0.74	1.53	2.55	3.36
180.0	2.03	0.81	1.60	2.71	3.36
195.0	1.22	0.06	0.77	2.39	2.91
210.0	0.11	-1.56	-0.59	1.34	2.16
225.0	-2.12	-4.35	-3.09	-0.28	0.34
240.0	-4.96	-8.83	-7.63	-2.79	-2.56
255.0	-9.78	-16.93	-15.61	-7.59	-7.21
270.0	-16.75	-9.90	-11.43	-18.88	-19.30
285.0	-11.19	-4.05	-5.47	-11.04	-10.24
300.0	-6.95	-1.26	-1.81	-4.97	-4.42
315.0	-4.03	1.08	0.41	-1.52	-1.24
330.0	-2.11	2.35	1.78	0.12	0.25
345.0	-0.61	3.36	2.69	1.35	1.22
360.0	0.18	3.77	2.86	1.39	1.28


Application Note DN616

2.1.4 Radiation Patterns


Theta = 0, Phi = 0



Theta = 180, Phi = 0




Theta = 90, Phi = 0




Application Note DN616


Theta = 90, Phi = 180



Theta = 90, Phi = 270



Theta = 90, Phi = 90



Application Note DN616

2.2 OTA Test Results for Frequency 2440.000 MHz

Total Radiated Power	-0.21 dBm
Peak EIRP	3.35 dBm
Directivity	3.56 dBi
Efficiency	-0.21 dB
Efficiency	95.35 %
Gain	3.35 dBi
NHPRP 45°	-1.92 dBm
NHPRP 45° / TRP	-1.71 dB
NHPRP 45° / TRP	67.38 %
NHPRP 30°	-3.72 dBm
NHPRP 30° / TRP	-3.51 dB
NHPRP 30° / TRP	44.54 %
NHPRP 22.5°	-4.98 dBm
NHPRP 22.5° / TRP	-4.77 dB
NHPRP 22.5° / TRP	33.35 %
UHRP	-3.25 dBm
UHRP / TRP	-3.04 dB
UHRP / TRP	49.62 %
LHRP	-3.18 dBm
LHRP / TRP	-2.98 dB
LHRP / TRP	50.38 %
Front/Back Ratio	1.39
PhiBW	91.9 deg
PhiBW Up	39.7 deg
PhiBW Down	52.2 deg
ThetaBW	119.4 deg
ThetaBW Up	102.8 deg
ThetaBW Down	16.6 deg
Boresight Phi	90 deg
Boresight Theta	45 deg
Maximum Power	3.35 dBm
Minimum Power	-7.53 dBm
Average Power	-0.03 dBm
Max/Min Ratio	10.88 dB
Max/Avg Ratio	3.38 dB
Min/Avg Ratio	-7.50 dB
Best Single Value	2.62 dBm
Best Position	Phi = 75 deg; Theta = 60 deg; Pol = Ver

Application Note DN616

2.2.1 RP 2440.000 tot

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.00	-1.88	-2.22	-2.25	0.08	0.51	-0.42	0.63	-0.08
15.00	-2.51	-2.68	-1.58	-0.25	1.29	-0.38	1.88	0.43
30.00	-2.29	-3.36	-2.70	0.19	0.07	0.09	1.22	-0.20
45.00	-2.06	-2.67	-1.29	0.50	-0.30	-0.43	-0.01	-0.76
60.00	-2.05	-2.29	-0.42	1.68	0.71	0.46	-0.91	0.09
75.00	-2.72	-1.85	0.52	2.71	2.85	1.71	0.69	1.36
90.00	-2.02	-2.45	0.68	3.35	1.80	2.75	1.70	1.69
105.00	-2.02	-3.29	0.64	2.34	0.94	2.95	0.36	0.78
120.00	-2.46	-3.14	-0.45	1.91	-1.37	0.31	-1.96	-1.80
135.00	-2.27	-4.83	-1.99	-0.49	-3.69	-3.88	-7.53	-5.71
150.00	-1.58	-4.33	-2.66	-1.46	-2.94	-5.57	-3.08	-4.71
165.00	-1.11	-2.22	-2.63	-0.85	-3.16	-2.47	-0.85	-3.52
180.00	-1.32	-1.86	-1.06	-0.06	-3.13	-3.99	-1.92	-2.95
195.00	-1.28	-1.05	0.48	0.29	-2.69	-7.42	-5.44	-3.01
210.00	-0.95	-0.76	0.95	0.67	-0.60	-5.91	-3.63	-4.66
225.00	-0.65	-0.09	2.21	0.18	0.51	-2.50	-2.21	-2.66
240.00	-0.42	0.62	1.62	0.25	0.63	-1.00	-1.51	-0.97
255.00	-0.02	0.64	2.06	-0.08	-0.43	-1.02	-1.55	-0.49
270.00	0.25	0.95	1.27	0.57	-0.76	-0.33	-0.66	-0.56
285.00	0.58	1.38	1.72	0.57	-1.43	-1.18	-0.69	-0.97
300.00	1.38	1.48	1.26	0.79	-1.87	-0.36	-0.36	-1.58
315.00	-0.44	0.87	0.98	0.89	-0.50	-0.85	-1.31	-1.43
330.00	-0.62	0.08	0.39	0.59	-0.62	-1.02	-2.50	-0.18
345.00	-0.82	-0.77	-0.58	0.60	0.02	-0.44	-2.15	-1.31
360.00	-1.42	-2.22	-0.96	0.01	0.01	-0.94	-0.96	-0.36

(continuation of the "RP_2440.000_tot" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.00	-0.40	-2.95	-0.50	-2.13	1.86
15.00	-0.58	-2.88	0.41	-1.28	1.30
30.00	0.29	-0.15	1.22	-0.84	1.79
45.00	0.98	1.93	1.91	-0.32	2.02
60.00	1.40	2.35	1.74	-0.54	2.61
75.00	1.29	2.34	1.29	-0.26	2.62
90.00	0.38	2.17	0.04	-0.64	2.55
105.00	-0.94	0.33	-1.06	-0.58	2.14
120.00	-2.82	-2.14	-1.96	-1.66	1.68
135.00	-1.34	-3.79	-1.64	-2.73	0.84
150.00	-0.44	-1.57	-1.46	-3.29	1.22
165.00	-0.77	0.28	-0.61	-1.73	1.47
180.00	-1.18	0.84	-0.52	0.73	1.41
195.00	-0.54	0.29	-0.35	1.24	2.10
210.00	0.44	1.32	0.60	1.05	2.04
225.00	0.25	1.93	0.79	0.81	2.03
240.00	-0.10	2.83	1.30	0.49	1.91
255.00	-0.34	1.80	1.90	0.33	2.06
270.00	-0.30	1.96	1.85	0.13	1.79
285.00	0.59	1.34	2.29	0.11	2.26
300.00	0.14	0.88	2.33	0.37	1.97
315.00	0.58	0.45	1.62	-0.12	2.06
330.00	-0.11	-0.70	0.60	-1.43	2.12
345.00	-0.49	-1.62	0.87	-1.39	2.39
360.00	-1.31	-3.40	-1.15	-2.19	1.62

Application Note DN616

2.2.2 RP 2440.000 hor

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-4.17	-3.69	-3.80	-3.36	-5.54	-9.21	-8.76	-9.01
15.0	-3.69	-4.81	-4.78	-4.63	-6.62	-9.75	-7.62	-8.22
30.0	-2.88	-5.11	-7.88	-7.30	-9.64	-11.51	-7.36	-7.79
45.0	-2.70	-4.70	-8.44	-9.25	-12.43	-13.48	-9.07	-7.73
60.0	-3.36	-4.39	-8.88	-8.06	-13.49	-12.91	-11.13	-6.56
75.0	-4.82	-3.73	-6.46	-4.94	-9.94	-11.75	-11.60	-4.83
90.0	-4.86	-3.61	-3.81	-2.87	-6.18	-11.23	-8.45	-5.10
105.0	-8.27	-4.19	-2.09	-0.86	-4.40	-8.02	-8.83	-4.61
120.0	-10.46	-5.10	-1.30	0.23	-3.67	-6.41	-9.51	-7.06
135.0	-11.25	-9.84	-2.72	-1.48	-4.79	-7.38	-13.06	-7.61
150.0	-8.26	-14.76	-6.58	-5.98	-9.77	-11.26	-11.40	-12.76
165.0	-4.66	-7.49	-13.28	-14.03	-15.55	-15.55	-10.93	-8.15
180.0	-3.32	-3.81	-4.95	-5.11	-9.67	-13.42	-11.71	-6.13
195.0	-1.94	-2.34	-1.56	-2.98	-5.54	-15.33	-11.83	-5.14
210.0	-1.53	-2.28	-1.10	-2.39	-3.58	-13.91	-11.98	-6.86
225.0	-2.13	-2.48	-1.36	-4.02	-3.24	-11.15	-11.56	-10.22
240.0	-3.28	-5.20	-4.73	-8.41	-6.60	-10.95	-11.34	-10.43
255.0	-5.01	-10.45	-8.02	-14.51	-10.19	-12.31	-9.99	-12.42
270.0	-7.05	-13.01	-14.44	-9.43	-14.25	-13.45	-11.15	-14.82
285.0	-10.45	-9.10	-9.93	-7.21	-10.36	-14.97	-10.90	-14.92
300.0	-13.32	-4.63	-5.98	-5.54	-12.27	-11.34	-11.50	-11.17
315.0	-10.24	-2.97	-3.76	-4.56	-8.85	-11.24	-12.09	-11.45
330.0	-7.54	-2.74	-2.37	-3.63	-6.68	-8.56	-13.79	-12.16
345.0	-5.57	-2.94	-2.42	-2.37	-5.49	-8.09	-11.02	-13.82
360.0	-3.63	-3.86	-3.37	-2.57	-5.32	-8.14	-10.53	-9.07

(continuation of the "RP_2440.000_hor" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	-10.75	-10.47	-7.27	-6.67	-1.99
15.0	-13.27	-15.55	-7.70	-5.09	-1.23
30.0	-12.15	-12.38	-4.19	-4.64	0.86
45.0	-9.18	-10.20	-2.50	-5.77	1.45
60.0	-6.95	-12.14	-1.25	-6.46	1.98
75.0	-6.59	-9.27	-1.07	-6.40	1.10
90.0	-5.25	-6.21	-1.79	-5.54	-0.09
105.0	-4.12	-4.37	-2.62	-4.51	-2.67
120.0	-3.58	-3.88	-4.89	-5.58	-6.95
135.0	-3.72	-7.47	-7.87	-7.90	-13.03
150.0	-7.64	-12.97	-9.21	-10.47	-7.17
165.0	-14.73	-7.31	-5.56	-7.19	-2.90
180.0	-7.57	-3.78	-1.95	-1.98	-0.98
195.0	-1.90	-1.36	-0.94	-0.40	0.23
210.0	-0.68	0.24	-0.38	-0.04	0.88
225.0	-2.03	-0.70	-1.81	0.35	1.13
240.0	-5.20	-1.95	-4.95	-0.86	0.84
255.0	-8.34	-5.00	-10.20	-2.16	0.50
270.0	-12.04	-7.68	-13.30	-5.28	-1.19
285.0	-9.63	-12.19	-7.90	-7.95	-1.92
300.0	-10.28	-14.62	-4.93	-13.26	-4.44
315.0	-9.18	-9.38	-3.93	-14.47	-5.67
330.0	-11.76	-7.82	-3.65	-11.03	-5.24
345.0	-9.15	-7.62	-4.58	-8.56	-5.05
360.0	-10.75	-10.38	-6.71	-7.19	-3.45

Application Note DN616

2.2.3 RP 2440.000_ver

Azimuth (deg)	Elevation 0 deg (dB)	Elevation 15 deg (dB)	Elevation 30 deg (dB)	Elevation 45 deg (dB)	Elevation 60 deg (dB)	Elevation 75 deg (dB)	Elevation 90 deg (dB)	Elevation 105 deg (dB)
0.0	-5.75	-7.66	-7.49	-2.54	-0.73	-1.04	0.10	-0.67
15.0	-8.75	-6.80	-4.40	-2.22	0.53	-0.91	1.36	-0.20
30.0	-11.28	-8.16	-4.27	-0.66	-0.42	-0.23	0.57	-1.04
45.0	-10.70	-6.94	-2.22	0.01	-0.57	-0.65	-0.59	-1.73
60.0	-7.88	-6.47	-1.09	1.19	0.54	0.26	-1.34	-0.97
75.0	-6.89	-6.41	-0.45	1.89	2.62	1.51	0.42	0.17
90.0	-5.21	-8.72	-1.24	2.17	1.05	2.57	1.25	0.66
105.0	-3.20	-10.55	-2.68	-0.49	-0.56	2.59	-0.20	-0.70
120.0	-3.21	-7.55	-7.94	-3.03	-5.24	-0.72	-2.80	-3.34
135.0	-2.85	-6.48	-10.07	-7.41	-10.19	-6.46	-8.96	-10.22
150.0	-2.64	-4.74	-4.92	-3.34	-3.94	-6.94	-3.77	-5.45
165.0	-3.65	-3.75	-3.02	-1.07	-3.41	-2.69	-1.30	-5.35
180.0	-5.67	-6.29	-3.35	-1.69	-4.22	-4.52	-2.40	-5.79
195.0	-9.78	-6.94	-3.79	-2.48	-5.88	-8.19	-6.58	-7.12
210.0	-9.97	-6.08	-3.29	-2.29	-3.63	-6.66	-4.32	-8.66
225.0	-6.06	-3.81	-0.30	-1.90	-1.87	-3.13	-2.75	-3.50
240.0	-3.58	-0.70	0.48	-0.39	-0.28	-1.47	-1.99	-1.49
255.0	-1.68	0.29	1.61	-0.24	-0.91	-1.36	-2.22	-0.78
270.0	-0.65	0.77	1.15	0.11	-0.96	-0.55	-1.07	-0.73
285.0	0.22	0.98	1.41	-0.22	-2.02	-1.36	-1.13	-1.15
300.0	1.23	0.26	0.35	-0.36	-2.28	-0.72	-0.71	-2.08
315.0	-0.93	-1.45	-0.80	-0.57	-1.19	-1.27	-1.69	-1.88
330.0	-1.61	-3.14	-2.89	-1.47	-1.86	-1.86	-2.83	-0.46
345.0	-2.59	-4.82	-5.20	-2.45	-1.41	-1.26	-2.76	-1.57
360.0	-5.41	-7.25	-4.68	-3.47	-1.49	-1.86	-1.47	-0.99


(continuation of the "RP_2440.000_ver" table from column 9 ...)

Azimuth (deg)	Elevation 120 deg (dB)	Elevation 135 deg (dB)	Elevation 150 deg (dB)	Elevation 165 deg (dB)	Elevation 180 deg (dB)
0.0	-0.82	-3.80	-1.53	-4.01	-0.45
15.0	-0.82	-3.13	-0.32	-3.62	-2.26
30.0	0.03	-0.42	-0.25	-3.19	-5.40
45.0	0.54	1.66	-0.05	-1.77	-7.05
60.0	0.71	2.19	-1.29	-1.83	-6.08
75.0	0.52	2.03	-2.48	-1.47	-2.66
90.0	-1.01	1.49	-4.61	-2.34	-0.86
105.0	-3.79	-1.46	-6.28	-2.82	0.40
120.0	-10.77	-6.96	-5.06	-3.91	1.04
135.0	-5.08	-6.23	-2.83	-4.30	0.66
150.0	-1.36	-1.90	-2.26	-4.21	0.54
165.0	-0.95	-0.55	-2.28	-3.19	-0.51
180.0	-2.32	-0.99	-6.03	-2.60	-2.31
195.0	-6.26	-4.74	-9.35	-3.77	-2.46
210.0	-6.00	-5.28	-6.33	-5.50	-4.29
225.0	-3.63	-1.50	-2.69	-9.16	-5.25
240.0	-1.70	1.07	0.12	-5.26	-4.73
255.0	-1.09	0.79	1.62	-3.28	-3.16
270.0	-0.61	1.46	1.72	-1.35	-1.25
285.0	0.15	1.14	1.86	-0.63	0.17
300.0	-0.28	0.76	1.43	0.18	0.85
315.0	0.09	-0.03	0.21	-0.28	1.26
330.0	-0.42	-1.64	-1.45	-1.94	1.23
345.0	-1.13	-2.88	-0.59	-2.32	1.52
360.0	-1.84	-4.37	-2.57	-3.84	0.00


Application Note DN616

2.2.4 Radiation Patterns


Theta = 0, Phi = 0



Theta = 180, Phi = 0




Theta = 90, Phi = 0




Application Note DN616


Theta = 90, Phi = 180



Theta = 90, Phi = 270



Theta = 90, Phi = 90



3 General Information

3.1 Document History

Revision	Date	Description/Changes
SWRA345	2010-08-12	Initial release.
SWRA345A	2010-10-20	Updated with DN024 Single Mode & Dual Band Mode Measurements

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DLP® Products	www.dlp.com	Communications and Telecom	www.ti.com/communications
DSP	dsp.ti.com	Computers and Peripherals	www.ti.com/computers
Clocks and Timers	www.ti.com/clocks	Consumer Electronics	www.ti.com/consumer-apps
Interface	interface.ti.com	Energy	www.ti.com/energy
Logic	logic.ti.com	Industrial	www.ti.com/industrial
Power Mgmt	power.ti.com	Medical	www.ti.com/medical
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
RFID	www.ti-rfid.com	Space, Avionics & Defense	www.ti.com/space-avionics-defense
RF/IF and ZigBee® Solutions	www.ti.com/lprf	Video and Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless-apps