



FCC TEST REPORT

FCC ID:2AJYRNM014605858

Report Number..... : ZKT-250116L1455E

Date of Test..... : Dec. 10, 2024 to Dec. 16, 2024

Date of issue..... : Feb. 11, 2025

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Nomad Goods, Inc.

Address : 1187 Coast Village Rd. #638, Santa Barbara, CA 93108, United States

Manufacturer's name : NuVolta Technologies (Hefei) Co., Ltd.

Address : Room 01, F5, Building B4, Phase 1, Zhongan Chuanggu Technology Park, No 900, West Wangjiang Road, High-tech Zone, Hefei, Anhui, PRC.

Test specification:

Standard..... : FCC CFR Title 47 Part 15 Subpart C

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No..... : TRF-EL-107_V0

Test Report Form(s) Originator..... : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : Stand One Max

Trademark : NOMAD

Model/Type reference..... : NM014605858

Model difference..... : /

Ratings..... : Input :12 V==2.5 A
iPhone charging port: 5 W/ 7.5 W/ 10 W/ 15W Max
AirPods charging port: 5 W
Apple Watch charging port: 5 W



Testing procedure and testing location:

Testing Laboratory.....: **Shenzhen ZKT Technology Co., Ltd.**

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: **Jim Liu**

Reviewer (name + signature).....: **Jackson Fang**

Approved (name + signature).....: **Lake Xie**



TABLE OF CONTENTS

1. VERSION	4
2. TEST SUMMARY	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 Test mode	7
3.3 Block Diagram of EUT Configuration	9
3.4 Test Conditions	9
3.5 Description Of Support Units (Conducted Mode)	9
3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. CONDUCTED EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 Test Result	14
5. RADIATED EMISSION MEASUREMENT	16
5.1 Radiated Emission Limits	16
5.2 Anechoic Chamber Test Setup Diagram	17
5.3 Test Procedure	18
5.4 DEVIATION FROM TEST STANDARD	18
5.5 Test Result	19
6. BANDWIDTH TEST	27
7. ANTENNA REQUIREMENT	30
8. TEST SETUP PHOTO	31
9. EUT CONSTRUCTIONAL DETAILS	31



1. VERSION

Report No.	Version	Description	Approved
ZKT-250116L1455E	Rev.01	Initial issue of report	Feb. 11, 2025



2. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	AC Conducted Emission Test	$\pm 1.38\text{dB}$
2	3m chamber Radiated spurious emission(9KHz-30MHz)	$U=4.5\text{dB}$
3	3m chamber Radiated spurious emission(30MHz-1GHz)	$U=4.8\text{dB}$
4	3m chamber Radiated spurious emission(1GHz-18GHz)	$U=4.9\text{dB}$
5	3m chamber Radiated spurious emission(18GHz-40GHz)	$U=5.0\text{dB}$
6	Conducted Adjacent channel power	$U=1.38\text{dB}$
7	Conducted output power uncertainty Above 1G	$U=1.576\text{dB}$
8	Conducted output power uncertainty below 1G	$U=1.28\text{dB}$
9	humidity uncertainty	$U=5.3\%$
10	Temperature uncertainty	$U=0.59^{\circ}\text{C}$



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Stand One Max
Test Model No.:	NM014605858
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	iPhone charging: 128-360 kHz AirPods charging: 110.1-205 kHz Apple Watch charging: 326.5 kHz-1.778 MHz
Modulation type:	MSK
Antenna Type:	Inductive loop coil Antenna
Antenna gain:	0dBi
Power supply:	Input :12 V==2.5 A iPhone charging port: 5 W/ 7.5 W/ 10 W/ 15W Max AirPods charging port: 5 W Apple Watch charging port: 5 W

3.2 Test mode

Test Modes:	
Mode 1	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status: $\leq$ 1%) + Apple Watch charging port(5 W)
Mode 2	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status:50%) + Apple Watch charging port(5 W)
Mode 3	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status: $\geq$ 98) + Apple Watch charging port(5 W)
Mode 4	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status: $\leq$ 1%) + Apple Watch charging port(5 W)
Mode 5	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status:50%) + Apple Watch charging port(5 W)
Mode 6	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status: $\geq$ 98) + Apple Watch charging port(5 W)
Mode 7	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status: $\leq$ 1%) + Apple Watch charging port(5 W)
Mode 8	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status:50%) + Apple Watch charging port(5 W)
Mode 9	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status: $\geq$ 98) + Apple Watch charging port(5 W)
Mode 10	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status: $\leq$ 1%) + Apple Watch charging port(5 W)
Mode 11	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status:50%) + Apple Watch charging port(5 W)
Mode 12	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status: $\geq$ 98) + Apple Watch charging port(5 W)
Mode 13	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status: $\leq$ 1%)
Mode 14	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status:50%)
Mode 15	AC Adapter + iPhone charging port(15W) + AirPods charging port(Battery Status: $\geq$ 98)




Mode 16	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status:≤1%)
Mode 17	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status:50%)
Mode 18	AC Adapter + iPhone charging port(10W) + AirPods charging port(Battery Status:≥98)
Mode 19	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status:≤1%)
Mode 20	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status:50%)
Mode 21	AC Adapter + iPhone charging port(7.5W) + AirPods charging port(Battery Status:≥98)
Mode 22	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status:≤1%)
Mode 23	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status:50%)
Mode 24	AC Adapter + iPhone charging port(5W) + AirPods charging port(Battery Status:≥98)
Mode 25	AC Adapter + iPhone charging port(15W) + Apple Watch charging port(5 W)
Mode 26	AC Adapter + iPhone charging port(10W) + Apple Watch charging port(5 W)
Mode 27	AC Adapter + iPhone charging port(7.5W) + Apple Watch charging port(5 W)
Mode 28	AC Adapter + iPhone charging port(5W) + Apple Watch charging port(5 W)
Mode 29	AC Adapter + iPhone charging port(15W)
Mode 30	AC Adapter + iPhone charging port(10W)
Mode 31	AC Adapter + iPhone charging port(7.5W)
Mode 32	AC Adapter + iPhone charging port(5W)
Mode 33	AC Adapter + AirPods charging port(Battery Status:≤1%)
Mode 34	AC Adapter + AirPods charging port(Battery Status:50%)
Mode 35	AC Adapter + AirPods charging port(Battery Status:≥98%)
Mode 36	AC Adapter + Apple Watch charging port(5 W)
Mode 37	Standby
Note: All modes were tested, only the worst-case was recorded in the report. Mode 1 is the worst mode.	




3.3 Block Diagram of EUT Configuration

Conducted Emission



Radiated Emission



3.4 Test Conditions

Temperature: 23~26℃

Relative Humidity: 54~63 %

3.5 Description Of Support Units (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Wireless charging power parameters	Note
E-1	Stand One Max	NOMAD	NM014605858	N/A	EUT
E-2	AC ADAPTER	Xiaomi	MDY-12-ED	N/A	AE
E-3	Wireless charging load	YBZ	EESON	5 W/ 7.5 W/ 10 W/ 15W	AE
E-4	AirPods	Apple	A2031	N/A	AE
E-5	Wireless charging load	YBZ	YBZ	2.5W/ 5 W	AE
E-6	Wireless charging load	HAN CAI ELECTRON	HC-RX	5 W	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation emissions& Radio Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Sep. 29, 2024	Sep. 28, 2025
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	00877	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Sep. 30, 2024	Sep. 29, 2025
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Sep. 30, 2024	Sep. 29, 2025
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Oct. 11, 2024	Oct. 10, 2025
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Sep. 29, 2024	Sep. 28, 2025
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Sep. 30, 2024	Sep. 29, 2025
11	Test Cable	N/A	R-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
12	Test Cable	N/A	R-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
13	Test Cable	N/A	R-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



Conducted emissions Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	RF-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	Test Cable	N/A	RF-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Test Cable	N/A	RF-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
6	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Sep. 29, 2024	Sep. 28, 2025
7	Signal Generator	Agilent	N5182A	N/A	A.01.87	Sep. 29, 2024	Sep. 28, 2025
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Van der Hoofden measuring head	Schwarzbeck Mess-elektronik	VDHH 9502	9502-039	N/A	Sep. 30, 2024	Sep. 29, 2025
10	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Sep. 30, 2024	Sep. 29, 2025
11	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
12	D.C. Power Supply	LongWei	TPR-6405 D	N/A	N/A	Sep. 29, 2024	Sep. 28, 2025
13	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\



4. CONDUCTED EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1544	31.58	9.89	41.47	65.76	-24.29	QP	P	
2	0.1544	16.44	9.89	26.33	55.76	-29.43	AVG	P	
3	0.3614	32.93	9.97	42.90	58.70	-15.80	QP	P	
4 *	0.3614	31.93	9.97	41.90	48.70	-6.80	AVG	P	
5	0.4694	21.30	10.00	31.30	56.52	-25.22	QP	P	
6	0.4694	5.51	10.00	15.51	46.52	-31.01	AVG	P	
7	0.4964	23.27	10.02	33.29	56.06	-22.77	QP	P	
8	0.4964	4.69	10.02	14.71	46.06	-31.35	AVG	P	
9	0.5730	20.82	10.03	30.85	56.00	-25.15	QP	P	
10	0.5730	3.56	10.03	13.59	46.00	-32.41	AVG	P	
11	1.5090	23.82	10.06	33.88	56.00	-22.12	QP	P	
12	1.5090	3.21	10.06	13.27	46.00	-32.73	AVG	P	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Mesurement Level = Reading level + Correct Factor



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1724	26.39	9.90	36.29	64.84	-28.55	QP	P	
2	0.1724	11.05	9.90	20.95	54.84	-33.89	AVG	P	
3	0.1860	25.31	9.90	35.21	64.21	-29.00	QP	P	
4	0.1860	9.44	9.90	19.34	54.21	-34.87	AVG	P	
5	0.3614	30.63	9.97	40.60	58.70	-18.10	QP	P	
6 *	0.3614	30.01	9.97	39.98	48.70	-8.72	AVG	P	
7	1.0814	17.84	10.06	27.90	56.00	-28.10	QP	P	
8	1.0814	16.88	10.06	26.94	46.00	-19.06	AVG	P	
9	1.5224	15.34	10.06	25.40	56.00	-30.60	QP	P	
10	1.5224	-0.51	10.06	9.55	46.00	-36.45	AVG	P	
11	3.2190	17.22	10.08	27.30	56.00	-28.70	QP	P	
12	3.2190	16.24	10.08	26.32	46.00	-19.68	AVG	P	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Mesurement Level = Reading level + Correct Factor



5. RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

5.1 Radiated Emission Limits

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value


Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value




5.2 Anechoic Chamber Test Setup Diagram

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



5.3 Test Procedure

Below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving loop antenna and in the center of a loop antenna, which was mounted on the top of a variable-height antenna tower.
- c. For each suspected emission, the EUT was arranged to its worst case, the height of interference-receiving loop antenna centre is 1 meter above the ground, and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- d. Both coaxial (loop plane perpendicular to the ground plane and to the measurement axis) and coplanar (loop plane perpendicular to the ground plane and coplanar with the measurement axis) polarizations of the antenna are set to make the measurement.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

30MHz-1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

5.4 DEVIATION FROM TEST STANDARD

No deviation



5.5 Test Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.127	62.48	0.16	62.64	105.60	-42.96	Peak
2	0.128	64.16	0.16	64.32	105.33	-41.01	Peak
3	0.327	62.70	0.79	63.49	97.31	-33.82	Peak
4	0.880	43.35	1.87	45.22	68.71	-23.49	QP
5	1.169	41.30	2.46	43.76	66.25	-22.49	QP
6 *	1.540	40.33	3.22	43.55	63.85	-20.30	QP




Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1






Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 29



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.128	67.66	0.16	67.82	105.33	-37.51	Peak
2	0.515	45.25	1.14	46.39	73.37	-26.98	QP
3	0.880	42.85	1.87	44.72	68.71	-23.99	QP
4 *	1.540	39.23	3.22	42.45	63.85	-21.40	QP
5	2.901	34.85	6.00	40.85	69.54	-28.69	QP
6	5.287	28.62	10.88	39.50	69.54	-30.04	QP




Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 33



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.127	62.98	0.16	63.14	105.60	-42.46	Peak
2	0.287	51.22	0.71	51.93	98.45	-46.52	Peak
3	0.524	45.58	1.14	46.72	73.22	-26.50	QP
4	0.880	42.85	1.87	44.72	68.71	-23.99	QP
5 *	1.480	39.86	3.09	42.95	64.20	-21.25	QP
6	2.901	34.35	6.00	40.35	69.54	-29.19	QP




Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 36



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.327	67.20	0.79	67.99	97.31	-29.32	Peak
2	0.931	42.75	1.97	44.72	68.23	-23.51	QP
3 *	1.540	40.73	3.22	43.95	63.85	-19.90	QP
4	2.719	36.39	5.63	42.02	69.54	-27.52	QP
5	6.168	26.93	12.66	39.59	69.54	-29.95	QP
6	10.199	44.04	-5.08	38.96	69.54	-30.58	QP



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 36



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	1.556	54.13	3.28	57.41	63.71	-6.30	QP
2	2.719	36.39	5.63	42.02	69.54	-27.52	QP
3	3.670	32.67	7.58	40.25	69.54	-29.29	QP
4	6.966	25.14	14.27	39.41	69.54	-30.13	QP
5	10.883	41.94	-3.88	38.06	69.54	-31.48	QP
6	16.594	31.81	6.18	37.99	69.54	-31.55	QP

Remarks:

Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Emission Level = Meter Reading - Factor


Margin = Emission Level- Limit.

The amplitude of emissions which are attenuated by more than 20db below the permissible value has no need to be reported.



30MHz-1GHz


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	159.980	33.17	-13.60	19.57	43.50	-23.93	QP
2 *	183.260	35.08	-12.27	22.81	43.50	-20.69	QP
3	231.760	31.72	-9.95	21.77	46.00	-24.23	QP
4	288.020	33.71	-8.49	25.22	46.00	-20.78	QP
5	384.050	30.72	-6.32	24.40	46.00	-21.60	QP
6	440.310	30.25	-5.23	25.02	46.00	-20.98	QP



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Modes:	Vertical



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



6. BANDWIDTH TEST

1. Set RBW = 1%-5%OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP






Temperature:	25.7 °C	Relative Humidity:	55%
Pressure:	101kPa		


	Frequency (KHz)	20dB bandwidth (KHz)	Result
iPhone charging coil	128.2	0.065	Pass
AirPods charging coil	127.8	0.029	Pass
Apple Watch charging coil	326.5	0.027	Pass

iPhone charging coil





AirPods charging coil



Apple Watch charging coil





7. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	
	The antenna is Coil Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details



8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****