

RF Exposure Evaluation

FCC ID: 2AGOFRC492A

Applicable Standard

According to FCC part 2.1093 and part 1.1307(b)(3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline

KDB447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.3 SAR-Based Exemption:

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in 1.1307(b)(3) (i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions

Accordingly, a RF source is considered an RF exempt device if its available maximum time averaged (matched conducted)power or its effective radiated power(ERP), whichever is greater, are below a specified threshold.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

Note: f is in GHz, d is the separation distance (cm)

Table 1-Example Power Thresholds(mw)

Frequency (MHz)	Distance(mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

TEST RESULT

☒ Passed

☐ Not Applicable

TRF No. FCC RF Exposure_R1

Add: West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail: info@gdkesign.cn Web: www.gdkesign.com

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power	ERP		Evaluation distance (cm)	Exemption Limit (mW)
				dBm	dBm	mw		
BLE_1M	2402	-0.67	-0.67±1	0.33	1.21	1.32	0.5	3

Note:

- The tune-up power was declared by the applicant
- $\text{dBi} = \text{dBd} + 2.15$, $\text{ERP} = \text{Max. Measured Tune up Power} + \text{dBd} = 0.33 + 0.88 = 1.21 \text{ dBm}$
- The maximum antenna gain is 3.03dBi. (Antenna gain provided by the applicant. Can affect the validity of results.)
- To maintain compliance with the RF exposure guidelines, place the equipment less than 0.5cm from nearby persons.

Result: Compliant

--THE END--