

## Modular Approval Request Letter

Date: 2021-08-17

FCC ID: T7V9028

Type of Equipment: Wi-Fi Dual Band 2.4/5 GHz and Bluetooth Module

Herewith we state that the requirements according to FCC Part 15.212 are met and the module qualifies for a single modular transmitter approval.

#	Requirement as per 47 CFR Part 15 Subpart C §15.212	Conditions met? (Y/N)	Realisation / Evidence in FORM 731 application filing
i	<b>RF shielding</b> The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	Y	The radio portion has his own shielding (see external photos).
ii	<b>Buffered modulation/data inputs</b> The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	Y	The function has been integrated in the chipset (see operational description)
iii	<b>Power supply regulation</b> The modular transmitter must have its own power supply regulation.	Y	The function has been integrated in the chipset (see operational description)
iv	<b>Antenna requirements</b> The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). Additional justification and details may be requested – please refer to KDB 996369	Y	The module comes with one permanently attached antenna. The spurious emission requirements are fulfilled (see attached test report).
v	<b>Stand-alone test configuration</b> The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	Y	The module has been tested in a stand-alone configuration (see test report/ test set-up photos)
vi	<b>Labelling</b> The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	Y	The module has its own label The FCC ID is shown in the User Manual. The instruction for labelling rules for the host device has been stated in the user manual
vii	<b>Compliance on specific rule or operating requirements</b> The modular transmitter must comply with any specific rules or	Y	The required FCC rules has been fulfilled and all instructions for

PANASONIC INDUSTRIAL DEVICES EUROPE GmbH  
Zeppelinstraße 19, 21337 Lüneburg

Telefon +49 (0) 4131 899-0  
Telefax +49 (0) 4131 899-120  
E-Mail: pideu@eu.panasonic.com  
www.pideu.panasonic.de

	operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.		maintaining compliance has been clearly stated in the user manual
viii	<b>RF Exposure</b> Radio frequency devices operating under the provisions of this part are subject to the radio frequency radiation exposure requirements specified in §§1.1307(b), 1.1310, 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of modular transmitters under this section must contain a statement confirming compliance with these requirements. The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Y	RF exposure requirements are fulfilled for mobile configuration. The installation of the module is restricted to mobile host devices what is clearly stated in the installation instruction of the user manual. For portable applications OEM integrators need SAR evaluation and an own FCC ID.



Olaf Knoth  
Safety Manager  
Panasonic Industrial Devices Europe GmbH  
Zeppelinstraße 19  
21337 Lueneburg  
Germany