

Product Specifications sheet



Specification No.	202406011002
Effective date	2024/6/11

Customer Name:	腾卓
Product Model	电感(inductance)
DZ Part No.	TX-DZ4005.3010-K6.8-L16（开单槽）
Customer item No	C01730-0137

【 ☒ New issue, ☐ version revision】

【 This specification includes contents and 7 pages in total 】 【 RoHS Compliant Parts 】

organize	Check	Approval
钟建立 Zhong jianli	/	马湘平 Ma xiangping

Guang Dong Top Wiser Electronic Technology Co., Ltd

Factory address:Address; 1F, 1231 Yingbin Avenue, Longmen County
, Huizhou City, Guangdong Province

Tel: 13147097490

【Within 30 days after the customer receives this acknowledgement, please return it with your signature and seal. If it is overdue, it will be deemed that the production will be carried out according to the standards of this acknowledgement】.

【customer approval】

Date:

Recognition status: ☐ full recognition ☐ conditional recognition ☐ refusal


Approval	Review	Recheck	Check

remark:

Product Specifications sheet

Customer Name:	腾卓	item	C01730-0137
DZ Part No.	TX-DZ4005.3010-K6.8-L16（开单槽）	Specification No.	202406011002
Issue/Revision History			
Version	Effective date	Change content / reason	Approval
01	2024/6/11	New specification release	钟建立Zhong Jianli
organize		check	approval
钟建立Zhong Jianli		/	马湘平 Ma XiangPing

Product Specifications sheet

Customer Name:	腾卓	Customer item No	C01730-0137			
DZ Part No	TX-DZ4005.3010-K6.8-L16（开单槽）	Specification No.	202406011002	Version	01	
◆、Overall dimensions 			(unit: mm)			
			A	40.0 ±1.5		
			B	20.5 ±1.5		
			C	16.0 ±2.0		
			D	2.0 ±0.3		
			E	1.0 ±0.2		
			F	5.3 ±1.0		
			G	37.5 ±1.5		
			(1)Wire diameter: 0.08 * 24P*2P enameled wire			
			(2)Number of windings: 10TS			
			(3)Whether the starting and ending lines cross: Yes			
			(4)The coil and magnetic sheet shall be pasted in the center			
			(5)Coil wrapped with 4mm high temperature adhesive tape			
			(6) Disc back 39.5 round white glue			
			(7) This disc is a custom 40*1.0 notched disc			
			(8) The lead on the right side of the figure should be within the notch range			
◆、Electrical characteristics::						
parameter	specification	Test conditions	Test instrument			
L0	6.8 ±10% μH	100KHz/1V	■TH1816B			
Q	>30 min	100KHz/1V	■TH1816B			
DCR	<95 mΩ	@ 25℃	■CH-502BC			
◆、Temperature class:						
Operating temperature	-40℃~ 125℃					
◆、list of materials:						
Item	Product Name	Material specification	Supplier	Remark		
1	Magnetic sheet	40*5.3*1.0T开单槽（Tape notch）		PC40		
2	Copper wire	0.08*24*2P		enameled wire		
3	High temperature adhesive tape	棕色4MM		ROHS		
4	tin	107H		ROHS		
5	Double-sided tape	39.5 Round double-sided white tape		ROHS		
6	glue	Yellow gum		ROHS		
				ROHS		
organize		check		approval		
钟建立 Zhong Jianli		/		马湘平Ma Xiangping		