

MEASUREMENT REPORT

FCC ID : 2BH7FGE400
Applicant : TP-Link Systems Inc.
Application Type : Certification
Product : BE6500 Dual-Band Wi-Fi 7 Gaming Router
Model No. : Archer GE400
Brand Name : tp-link
FCC Classification : Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s) : Part15 Subpart E (Section 15.407)
Received Date : January 10, 2025
Test Date : January 21 ~ February 24, 2025

Tested By : Owen Tsai
(Owen Tsai)
Reviewed By : Paddy Chen
(Paddy Chen)
Approved By : Chenz Ker
(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v02r01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2501TW0109-U3	1.0	Original Report	2025-03-29	

CONTENTS

Description	Page
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Equipment Description.....	8
2.2. Product Specification Subjective to this Report.....	8
2.3. Working Frequencies for this report	9
2.4. Description of Available Antennas.....	10
2.5. Test Mode	11
2.6. Configuration of Test System.....	12
2.7. Test System Details.....	13
2.8. Description of Test Software	13
2.9. Applied Standards	13
2.10. Duty Cycle	14
2.11. Test Configuration	17
2.12. EMI Suppression Device(s)/Modifications.....	17
2.13. Labeling Requirements.....	17
3. DESCRIPTION OF TEST	18
3.1. Evaluation Procedure	18
3.2. AC Line Conducted Emissions	18
3.3. Radiated Emissions.....	19
4. ANTENNA REQUIREMENTS.....	20
5. TEST EQUIPMENT CALIBRATION DATE.....	21
6. MEASUREMENT UNCERTAINTY.....	22
7. TEST RESULT	23
7.1. Summary	23
7.2. 26dB Bandwidth Measurement.....	24
7.2.1. Test Limit	24
7.2.2. Test Procedure used.....	24
7.2.3. Test Setting.....	24
7.2.4. Test Setup	24
7.2.5. Test Result.....	25
7.3. 6dB Bandwidth Measurement.....	46

7.3.1. Test Limit	46
7.3.2. Test Procedure used	46
7.3.3. Test Setting.....	46
7.3.4. Test Setup	46
7.3.5. TestResult.....	47
7.4. Output Power Measurement	54
7.4.1. Test Limit	54
7.4.2. Test Procedure Used	54
7.4.3. Test Setting.....	54
7.4.4. Test Setup	54
7.4.5. Test Result.....	55
7.5. Transmit Power Control	59
7.5.1. Test Limit	59
7.5.2. Test Procedure Used	59
7.5.3. Test Setting.....	59
7.5.4. Test Setup	59
7.5.5. Test Result.....	59
7.6. Power Spectral Density Measurement	60
7.6.1. Test Limit	60
7.6.2. Test Procedure Used	60
7.6.3. Test Setting.....	60
7.6.4. Test Setup	61
7.6.5. Test Result.....	62
7.7. Frequency Stability Measurement.....	135
7.7.1. Test Limit	135
7.7.2. Test Limit	135
7.7.3. Test Setup	136
7.7.4. Test Result.....	136
7.8. Radiated Spurious Emission Measurement	137
7.8.1. Test Limit	137
7.8.2. Test Procedure Used	137
7.8.3. Test Setting.....	137
7.8.4. Test Setup	139
7.8.5. Test Result.....	140
7.9. Radiated Restricted Band Edge Measurement	356
7.9.1. Test Limit	356
7.9.2. Test Procedure Used	357
7.9.3. Test Setting.....	357
7.9.4. Test Setup	358

7.9.5. Test Result.....	359
7.10. AC Conducted Emissions Measurement.....	551
7.10.1. Test Limit	551
7.10.2. Test Procedure	551
7.10.3. Test Setup	552
7.10.4. Test Result.....	553
8. CONCLUSION.....	555
Appendix A : Test Setup Photograph	556
Appendix B : EUT Photograph.....	556
Appendix C : Internal Photograph	556

General Information

Applicant	TP-Link Systems Inc.
Applicant Address	10 Mauchly, Irvine, CA 9261
Manufacturer	TP-Link Systems Inc.
Manufacturer Address	10 Mauchly, Irvine, CA 92618
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.407

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	BE6500 Dual-Band Wi-Fi 7 Gaming Router
Model No.:	Archer GE400
Brand Name:	tp-link
Wi-Fi Specification:	802.11a/b/g/n/ac/ax/be
EUT Identification No.:	#1-1 (Conducted) #1-2 (Radiated)
Accessory	
Adapter	BRAND: MASS POWER MODEL: NBS30D120250VU INPUT: 100 - 240V ~ 50/60Hz 0.8A. OUTPUT: DC 12.0V / 2.5A

2.2. Product Specification Subjective to this Report

Frequency Range:	For 802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80/be-EHT80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160/be-EHT160: 5250MHz, 5570MHz
Type of Modulation:	802.11a/n/ac: OFDM 802.11ax/be: OFDMA
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ac: up to 3466.7Mbps 802.11ax: up to 4804Mbps 802.11be: up to 5764Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80/be-EHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160/be-EHT160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250MHz	114	5570 MHz	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Number of spatial streams	Max Antenna Gain (dBi)	Beamforming Directional Gain(dBi)	CDD Directional Gain (dBi)	
						For Power	For PSD
Wi-Fi Antenna							
Dipole	2412 ~ 2462	2	1	6.33	7.63	4.65	7.63
	5150 ~ 5250	4	1	7.22	11.91	5.90	11.91
	5250 ~ 5350	4	1	7.87	12.76	6.77	12.76
	5470 ~ 5725	4	1	8.60	12.35	6.39	12.35
	5725 ~ 5895	4	1	8.42	11.90	6.22	11.90
Remark:							
1. The device supports CDD Mode and Beamforming mode, details refer to the table as below.							
2. CDD signals are correlated, the directional gain as follows, When N _{SS} =1, for power measurements: the max directional gain (each angle) = 10 log[(10 ^{G¹/10} + 10 ^{G²/10} + ... + 10 ^{G^N/10}) /N _{ANT}] For power spectral density (PSD) measurements: the max directional gain (each angle) = 10 log[(10 ^{G¹/20} + 10 ^{G²/20} + ... + 10 ^{G^N/20}) ² /N _{ANT}]							
3. Beamforming signals are correlated, the directional gain as follows, the max directional gain (each angle) = 10 log[(10 ^{G¹/20} + 10 ^{G²/20} + ... + 10 ^{G^N/20}) ² /N _{ANT}]							
4. The information as above is from the antenna report.							


Test Mode	Tx Paths	CDD Mode	Beamforming Mode
802.11b/g/n (DTS)	2	√	X
802.11ax/be (DTS)	2	√	√
802.11a/n (NII)	4	√	X
802.11ac/ax/be (NII)	4	√	√

2.5. Test Mode

CDD Mode
Mode 1: Transmit by 802.11a_Nss=1 (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20_Nss=1 (MCS0)
Mode 3: Transmit by 802.11ac-VHT40_Nss=1 (MCS0)
Mode 4: Transmit by 802.11ac-VHT80_Nss=1 (MCS0)
Mode 5: Transmit by 802.11ac-VHT160_Nss=1 (MCS0)
Mode 6: Transmit by 802.11ax-HE20_Nss=1 (MCS0)
Mode 7: Transmit by 802.11ax-HE40_Nss=1 (MCS0)
Mode 8: Transmit by 802.11ax-HE80_Nss=1 (MCS0)
Mode 9: Transmit by 802.11ax-HE160_Nss=1 (MCS0)
Mode 10: Transmit by 802.11be-EHT20_Nss=1 (MCS0)
Mode 11: Transmit by 802.11be-EHT40_Nss=1 (MCS0)
Mode 12: Transmit by 802.11be-EHT80_Nss=1 (MCS0)
Mode 13: Transmit by 802.11be-EHT160_Nss=1 (MCS0)
Remark: - For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - This device supports 4 Nss and the power level of 4 Nss is less than or equal to the power of 1 Nss. The worst case is Nss=1. - For beamforming operation, the manufacturer automatically reduces power based on a factor calculated as the difference between the beamforming directional gain and the CDD directional power gain. Thus, only the CDD mode was evaluated in this report. - EUT supports one configuration only in 802.11ax/be full RU mode. 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report. - As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.6. Configuration of Test System

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



2.7. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	UART Board	Arduino	CH340	N/A	N/A
2	Notebook PC	Lenovo	20Y7-006KTW	N/A	Non-shielded, 0.8m
3	USB Mouse	Logitech	M90	N/A	N/A

2.8. Description of Test Software

The test utility software used during testing was “accessMTool”, the version is ver REL_3_3_0_1.

Note: Final power setting please refer to operational description.

2.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01,
- KDB 662911 D01v02r01
- ANSI C63.10-2013


2.10. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz, 80MHz and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:


Test Mode	Duty Cycle
802.11a	94.91%
802.11ac-VHT20	98.47%
802.11ac-VHT40	96.57%
802.11ac-VHT80	93.55%
802.11ac-VHT160	89.08%
802.11ax-HE20	97.83%
802.11ax-HE40	95.47%
802.11ax-HE80	92.62%
802.11ax-HE160	88.87%
802.11be-EHT20	98.36%
802.11be-EHT 40	96.31%
802.11be-EHT 80	92.79%
802.11be-EHT 160	89.05%

Duty Cycle (T = Transmission Duration)


802.11a




802.11ac-VHT20




802.11ac-VHT40




802.11ac-VHT80




802.11ac-VHT160




802.11ax-HE20



802.11ax-HE40



802.11ax-HE80





2.11. Test Configuration

The device was tested per the guidance of KDB 789033 D02v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v02r01 were used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50 Ω /50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2025/4/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2025/3/5
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2025/6/14

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2025/5/7
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2025/11/5
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2025/5/20
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SE	MRTTWA00088	1 year	2025/5/14
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2025/3/26
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2025/3/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2025/3/5
Signal Analyzer	R&S	FSVA3044	MRTTWA00092	1 year	2025/6/20
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00034	1 year	2025/6/25
Cable	HUBERSUHNER	EMC105-NM-NM -3000	MRTTWE00035	1 year	2025/6/25
Temperature/Humidity Meter	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2025/9/24
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2025/8/12
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2025/3/12

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C} / \pm 3\%$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	$\geq 500\text{kHz}$		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	Refer to section 7.4		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	$\leq 24\text{ dBm}$		Pass	Section 7.5
15.407(a)(1)(ii), (2), (3), (12)	Peak Power Spectral Density	Refer to section 7.6		Pass	Section 7.6
15.407(g)	Frequency Stability	N/A		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Refer to Section 7.8	Radiated	Pass	Section 7.8 & 7.9
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- Output power test was verified over all data rates of each mode (data refers to operational description), and then choose the maximum power output (low data rate) for final test of each channel.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
- EUT supports one configuration only in 802.11ax full RU mode, i.e. 242 tone in 11ax-HE20, 484 tone in 11ax-HE40, 996 tone in 11ax-HE80 and 2 x 996 tone in 11ax-HE160.

7.2. 26dB Bandwidth Measurement

7.2.1. Test Limit

N/A

7.2.2. Test Procedure used


K DB 789033 D02v02r01- Section II)C.1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. $VBW \geq 3 \times RBW$.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4. Test Setup



7.2.5.Test Result

Product	BE6500 Dual-Band Wi-Fi 7 Gaming Router	Test Engineer	Peter
Test Site	SR6	Test Date	2025/2/12 ~ 2025/2/20

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 1					
802.11a	6Mbps	36	5180	22.750	16.797
802.11a	6Mbps	40	5200	21.730	16.780
802.11a	6Mbps	48	5240	21.540	16.794
802.11a	6Mbps	52	5260	22.620	16.840
802.11a	6Mbps	60	5300	21.520	16.766
802.11a	6Mbps	64	5320	22.610	16.813
802.11a	6Mbps	100	5500	21.330	16.777
802.11a	6Mbps	116	5580	24.210	16.883
802.11a	6Mbps	140	5700	21.030	16.667
802.11a	6Mbps	144	5720	21.530	16.814
802.11a	6Mbps	149	5745	21.350	16.792
802.11a	6Mbps	157	5785	21.210	16.761
802.11a	6Mbps	165	5825	21.750	16.820
802.11ac-VHT20	MCS0	36	5180	23.150	17.955
802.11ac-VHT20	MCS0	40	5200	25.900	17.958
802.11ac-VHT20	MCS0	48	5240	22.890	17.969
802.11ac-VHT20	MCS0	52	5260	22.190	17.952
802.11ac-VHT20	MCS0	60	5300	22.860	17.941
802.11ac-VHT20	MCS0	64	5320	24.160	17.951
802.11ac-VHT20	MCS0	100	5500	23.900	17.943
802.11ac-VHT20	MCS0	116	5580	22.210	17.950
802.11ac-VHT20	MCS0	140	5700	21.140	17.782
802.11ac-VHT20	MCS0	144	5720	21.880	17.906
802.11ac-VHT20	MCS0	149	5745	21.930	17.908
802.11ac-VHT20	MCS0	157	5785	21.690	17.906
802.11ac-VHT20	MCS0	165	5825	21.740	17.924


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 1					
802.11ac-VHT40	MCS0	38	5190	41.040	36.414
802.11ac-VHT40	MCS0	46	5230	41.500	36.416
802.11ac-VHT40	MCS0	54	5270	40.730	36.395
802.11ac-VHT40	MCS0	62	5310	45.400	36.459
802.11ac-VHT40	MCS0	102	5510	42.550	36.495
802.11ac-VHT40	MCS0	110	5550	42.950	36.365
802.11ac-VHT40	MCS0	134	5670	43.500	36.381
802.11ac-VHT40	MCS0	142	5710	45.460	36.468
802.11ac-VHT40	MCS0	151	5755	41.930	36.458
802.11ac-VHT40	MCS0	159	5795	44.410	36.437
802.11ac-VHT80	MCS0	42	5210	88.580	76.027
802.11ac-VHT80	MCS0	58	5290	85.340	75.904
802.11ac-VHT80	MCS0	106	5530	87.360	75.928
802.11ac-VHT80	MCS0	122	5610	81.090	75.909
802.11ac-VHT80	MCS0	138	5690	82.100	75.984
802.11ac-VHT80	MCS0	155	5775	82.070	75.910
802.11ac-VHT160	MCS0	50	5250	162.600	154.660
802.11ac-VHT160	MCS0	114	5570	163.400	154.890
802.11ax-HE20	MCS0	36	5180	27.620	19.093
802.11ax-HE20	MCS0	40	5200	27.420	19.026
802.11ax-HE20	MCS0	48	5240	25.450	19.054
802.11ax-HE20	MCS0	52	5260	22.260	19.090
802.11ax-HE20	MCS0	60	5300	21.520	19.072
802.11ax-HE20	MCS0	64	5320	21.950	19.097
802.11ax-HE20	MCS0	100	5500	25.000	19.093
802.11ax-HE20	MCS0	116	5580	24.280	19.120
802.11ax-HE20	MCS0	140	5700	21.370	19.038
802.11ax-HE20	MCS0	144	5720	22.220	19.052
802.11ax-HE20	MCS0	149	5745	22.970	19.079
802.11ax-HE20	MCS0	157	5785	25.270	19.103
802.11ax-HE20	MCS0	165	5825	21.770	19.153

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 1					
802.11ax-HE40	MCS0	38	5190	41.150	37.924
802.11ax-HE40	MCS0	46	5230	43.320	37.791
802.11ax-HE40	MCS0	54	5270	41.290	37.748
802.11ax-HE40	MCS0	62	5310	43.960	37.825
802.11ax-HE40	MCS0	102	5510	42.520	37.824
802.11ax-HE40	MCS0	110	5550	41.680	37.794
802.11ax-HE40	MCS0	134	5670	41.480	37.781
802.11ax-HE40	MCS0	142	5710	41.380	37.822
802.11ax-HE40	MCS0	151	5755	41.330	37.802
802.11ax-HE40	MCS0	159	5795	40.600	37.840
802.11ax-HE80	MCS0	42	5210	86.340	77.558
802.11ax-HE80	MCS0	58	5290	81.770	77.278
802.11ax-HE80	MCS0	106	5530	82.670	77.372
802.11ax-HE80	MCS0	122	5610	81.300	77.285
802.11ax-HE80	MCS0	138	5690	81.590	77.376
802.11ax-HE80	MCS0	155	5775	80.830	77.374
802.11ax-HE160	MCS0	50	5250	163.600	156.410
802.11ax-HE160	MCS0	114	5570	161.900	156.750
802.11be-EHT20	MCS0	36	5180	22.270	19.108
802.11be-EHT20	MCS0	40	5200	24.590	19.165
802.11be-EHT20	MCS0	48	5240	26.380	19.166
802.11be-EHT20	MCS0	52	5260	24.690	19.050
802.11be-EHT20	MCS0	60	5300	22.610	19.131
802.11be-EHT20	MCS0	64	5320	22.090	19.127
802.11be-EHT20	MCS0	100	5500	27.360	19.053
802.11be-EHT20	MCS0	116	5580	21.670	19.102
802.11be-EHT20	MCS0	140	5700	21.430	18.998
802.11be-EHT20	MCS0	144	5720	24.380	19.094
802.11be-EHT20	MCS0	149	5745	23.150	19.057
802.11be-EHT20	MCS0	157	5785	23.290	19.087
802.11be-EHT20	MCS0	165	5825	24.820	19.077


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 1					
802.11be-EHT40	MCS0	38	5190	49.630	37.858
802.11be-EHT40	MCS0	46	5230	48.580	37.932
802.11be-EHT40	MCS0	54	5270	42.260	37.804
802.11be-EHT40	MCS0	62	5310	42.920	37.790
802.11be-EHT40	MCS0	102	5510	42.080	37.869
802.11be-EHT40	MCS0	110	5550	41.220	37.819
802.11be-EHT40	MCS0	134	5670	40.790	37.796
802.11be-EHT40	MCS0	142	5710	42.550	37.834
802.11be-EHT40	MCS0	151	5755	44.850	37.767
802.11be-EHT40	MCS0	159	5795	41.940	37.882
802.11be-EHT80	MCS0	42	5210	82.910	77.374
802.11be-EHT80	MCS0	58	5290	83.820	77.249
802.11be-EHT80	MCS0	106	5530	84.730	77.417
802.11be-EHT80	MCS0	122	5610	82.190	77.303
802.11be-EHT80	MCS0	138	5690	81.650	77.480
802.11be-EHT80	MCS0	155	5775	83.540	77.453
802.11be-EHT160	MCS0	50	5250	162.400	156.480
802.11be-EHT160	MCS0	114	5570	162.200	156.100

802.11a 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 116 (5580MHz)






802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 116 (5580MHz)






802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)




Channel 110 (5550MHz)




Channel 134 (5670MHz)




Channel 142 (5710MHz)






802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth


Channel 42 (5210MHz)




Channel 58 (5290MHz)




Channel 106 (5530MHz)




Channel 122 (5610MHz)



Channel 138 (5690MHz)




Channel 155 (5775MHz)




802.11ac-VHT160 26dB Bandwidth & 99% Bandwidth

Channel 50 (5250MHz)




Channel 114 (5570MHz)




802.11ax-HE20 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 116 (5580MHz)






802.11ax-HE40 26dB Bandwidth & 99% Bandwidth


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)



Channel 110 (5550MHz)



Channel 134 (5670MHz)



Channel 142 (5710MHz)

