

TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	N48_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-19


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.48 dB	info only		
	Recv conversational gain 8N	20.48 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	6.1 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	2.07 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.76 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	N77_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-19


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.43 dB	info only		
	Recv conversational gain 8N	20.43 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	7.2 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.95 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.85 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	11b_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.25 dB	info only		
	Recv conversational gain 8N	20.25 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	9.8 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	2.12 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.89 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	11a_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.17 dB	info only		
	Recv conversational gain 8N	20.17 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	12.4 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	2.09 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.95 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	U-NII-2A_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.43 dB	info only		
	Recv conversational gain 8N	20.43 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	9.8 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.89 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.95 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	U-NII-2C_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.37 dB	info only		
	Recv conversational gain 8N	20.37 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	8.9 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.99 dB	Floating Limits	PASS	
	Recv resp DF 8N	2 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	U-NII-3_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.33 dB	info only		
	Recv conversational gain 8N	20.33 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	9.9 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	2.08 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.95 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	U-NII-4_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-12


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.33 dB	info only		
	Recv conversational gain 8N	20.33 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	6.5 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	2.03 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.87 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	U-NII-5_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-23


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.34 dB	info only		
	Recv conversational gain 8N	20.34 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	11.6 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.82 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.5 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	L66_Ant.B_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.66 dB	info only		
	Recv conversational gain 2N	18.66 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.17 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.99 dB	Floating Limits	PASS	
	Recv resp DF 2N	1.96 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	L66_Ant.B_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.39 dB	info only		
	Recv conversational gain 2N	19.39 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.34 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.74 dB	Floating Limits	PASS	
	Recv resp DF 2N	2 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	L41_PC2_Ant.B_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-17

Receive Volume Control Performance


TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.7 dB	info only		
	Recv conversational gain 2N	18.7 dB	6.00	PASS	

Receive Distortion and Noise Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	6.59 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.


2N - Receive Signal-To-Distortion & Noise Ratio vs Frequency




Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.88 dB	Floating Limits	PASS	
	Recv resp DF 2N	1.72 dB	Floating Limits	PASS	

Receive Response FF 2N



Receive Response DF 2N



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	L41_PC2_Ant.B_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.58 dB	info only		
	Recv conversational gain 2N	19.58 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	8.12 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.77 dB	Floating Limits	PASS	
	Recv resp DF 2N	2 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	N12_Ant.D_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-18

Receive Volume Control Performance


TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.79 dB	info only		
	Recv conversational gain 2N	18.79 dB	6.00	PASS	

Receive Distortion and Noise Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.65 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.


2N - Receive Signal-To-Distortion & Noise Ratio vs Frequency




Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.96 dB	Floating Limits	PASS	
	Recv resp DF 2N	1.9 dB	Floating Limits	PASS	

Receive Response FF 2N



Receive Response DF 2N



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	N12_Ant.D_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-18


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.97 dB	info only		
	Recv conversational gain 2N	19.97 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.56 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	2.14 dB	Floating Limits	PASS	
	Recv resp DF 2N	2.4 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	N41_PC2_Ant.E_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-18


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.7 dB	info only		
	Recv conversational gain 2N	18.7 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	8.84 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	2.17 dB	Floating Limits	PASS	
	Recv resp DF 2N	2.05 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	N41_PC2_Ant.E_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-18


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.82 dB	info only		
	Recv conversational gain 2N	19.82 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	4.83 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.93 dB	Floating Limits	PASS	
	Recv resp DF 2N	2.1 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	11b_MIMO_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.71 dB	info only		
	Recv conversational gain 2N	18.71 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.35 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.9 dB	Floating Limits	PASS	
	Recv resp DF 2N	1.94 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	11b_MIMO_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.6 dB	info only		
	Recv conversational gain 2N	19.6 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	7.16 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.84 dB	Floating Limits	PASS	
	Recv resp DF 2N	2.1 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	11a_MIMO_EVS-NB24.4_2N
Bandwidth	Narrowband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	88.74 dB	info only		
	Recv conversational gain 2N	18.74 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	8.57 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.83 dB	Floating Limits	PASS	
	Recv resp DF 2N	1.99 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 2N

Device Under Test:	11a_MIMO_EVS-WB24.4_2N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 2N	89.67 dB	info only		
	Recv conversational gain 2N	19.67 dB	6.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 2N	5.35 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 2N	1.9 dB	Floating Limits	PASS	
	Recv resp DF 2N	2 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	L66_Ant.B_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	89.66 dB	info only		
	Recv conversational gain 8N	19.66 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	8 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.95 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.85 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	L66_Ant.B_EVS-WB24.4_8N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.49 dB	info only		
	Recv conversational gain 8N	20.49 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	5.2 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.36 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.6 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	L41_PC2_Ant.B_EVS-NB24.4_8N
Bandwidth	Narrowband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	89.72 dB	info only		
	Recv conversational gain 8N	19.72 dB	18.00	PASS	

Receive Distortion and Noise Performance



TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	10.5 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.98 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.87 dB	Floating Limits	PASS	



TIA-5050 Receive Volume Control Measurements - 8N

Device Under Test:	L41_PC2_Ant.B_EVS-WB24.4_8N
Bandwidth	Wideband
Test Date:	2024-04-17


Receive Volume Control Performance

TIA-5050	Test	Measured	Limits	Result	Reference
Clause 5.1	Recv output level dB SPL 8N	90.53 dB	info only		
	Recv conversational gain 8N	20.53 dB	18.00	PASS	

Receive Distortion and Noise Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.2	Recv PN-SDNR 8N	10.6 dB	Absolute Limits	PASS	

Note: SDNR includes noise and distortion products.



Receive Acoustic Frequency Response Performance

TIA-5050	Test	Margin	Limits	Result	Reference
Clause 5.3	Recv resp FF 8N	1.56 dB	Floating Limits	PASS	
	Recv resp DF 8N	1.8 dB	Floating Limits	PASS	

