

FCC ID : 2ACHBN5

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm², If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 40cm between the equipment and a person's body.

11.2 Measurement Result

WIFI2.4G and radio stations can transmit at the same time, BT and radio stations can transmit at the same time; WIFI2.4G and Bluetooth cannot transmit at the same time,

BT

Antenna gain: 1.0 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	0.44	-1 to 1	1	1.26	0.0001	1
	2441	1.20	0 to 2	2	1.26	0.0001	1
	2480	1.94	0 to 2	2	1.26	0.0001	1
pi/4-DQPSK	2402	2.60	1 to 3	3	1.26	0.0001	1
	2441	3.33	2 to 4	4	1.26	0.0002	1
	2480	4.03	3 to 5	5	1.26	0.0002	1
8DPSK	2402	2.99	1 to 3	3	1.26	0.0001	1
	2441	3.75	2 to 4	4	1.26	0.0002	1
	2480	4.45	3 to 5	5	1.26	0.0002	1

BLE

Antenna gain: 1.0 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	0.37	-1 to 1	1	1.26	0.0001	1
	2440	-0.08	-2 to 0	0	1.26	0.0001	1
	2480	-0.80	-2 to 0	0	1.26	0.0001	1

Wifi 2.4G

Antenna gain: 1.0 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	2412	14.23	13 to 15	15	1.26	0.0020	1
	2437	14.39	13 to 15	15	1.26	0.0020	1
	2462	15.30	14 to 16	16	1.26	0.0025	1
802.11g	2412	14.12	13 to 15	15	1.26	0.0020	1
	2437	14.38	13 to 15	15	1.26	0.0020	1
	2462	15.30	14 to 16	16	1.26	0.0025	1
802.11n (HT20)	2412	14.04	13 to 15	15	1.26	0.0020	1
	2437	14.24	13 to 15	15	1.26	0.0020	1
	2462	15.16	14 to 16	16	1.26	0.0025	1
802.11n (HT40)	2422	14.37	13 to 15	15	1.26	0.0020	1
	2437	14.39	13 to 15	15	1.26	0.0020	1
	2452	14.77	13 to 15	15	1.26	0.0020	1

UHF

Antenna gain: 4.0 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GMSK	469.9750	31.84	30 to 32	32	2.51	0.1979	0.31

CONCLUSION of simultaneous transmitter

Both of the module 1 and module 2 can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1 + CPD2/LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is $0.1979 / 1.00 + 0.0025 / 1.00 = 0.2004$,
which is less than “0.31”,

This confirmed that the device comply with FCC 1.1310 MPE limit.

