

FCC Test Report

Report No.: AGC02931240602FE01

FCC ID		2BLTR-QUADBAND
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Mobile Radio
BRAND NAME	:	ТҮТЕСН
MODEL NAME	:	TH-9800 Pro, TH-9800 Plus
APPLICANT	:	Quanzhou RadioBoss Technology Co.,Ltd
DATE OF ISSUE	:	Oct. 14, 2024
STANDARD(S)	:	FCC Part 15 Subpart B
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 14, 2024	Valid	Initial Release



Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Auxiliary Surrounding Description	5
2.2 Test Methodology	5
2.3 Description of Test Modes	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Used	9
4. Summary of Test Results	
5. Radiated Emission Measurements	11
5.1 Provisions Applicable	11
5.2 Measurement Setup	
5.3 Measurement Procedure	
5.4 Measurement Resul	
6. Conducted Emission Measurements	
6.1 Provisions Applicable	21
6.2 Measurement Setup	21
6.3 Measurement Procedure	
6.4 Measurement Result	
7. Antenna Conducted Power for Receivers	
7.1 Provisions Applicable	
7.2 Measurement Setup	
7.3 Measurement Procedure	
7.4 Measurement Result	
8. Scanning Receivers and Frequency Converters Used with Scanning Receivers	
8.1 Provisions Applicable	
8.2 Measurement Setup	
8.3 Measurement Procedure	
8.4 Measurement Result	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



1. General Information

Quanzhou RadioBoss Technology Co.,Ltd
No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian
Quanzhou RadioBoss Technology Co.,Ltd
No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian
Quanzhou RadioBoss Technology Co.,Ltd
No.8, Chuangzao Road, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian
Mobile Radio
ТҮТЕСН
TH-9800 Pro
TH-9800 Plus
Only the model name is different
Jun. 13, 2024
Jun. 25, 2024~Oct. 14, 2024
No any deviation from the test method
Normal
Pass
AGCTR-ER-FCC-CSR-V1.0

Note: The test results of this report relate only to the tested sample identified in this report.

Bibo zhang Prepared By Bibo Zhang Oct. 14, 2024 (Project Engineer) **Reviewed By** Calvin Liu

Calvin Liu (Reviewer)

Oct. 14, 2024

Approved By

Max Zha

Max Zhang (Authorized Officer)

Oct. 14, 2024



2. Product Information

2.1 Product Technical Description

Housing Type	Plastic and metal
Receive Frequency Range	AM:108-136MHz FM:26-33MHz/47-54MHz/136-180MHz/320-512MHz/750-950MHz (Scanning Receiver)
Highest Operating Frequency	⊠Greater than 108MHz ⊠Less than 108MHz
Equipment Type	Table-Top
Hardware Version	V1.6.2
Software Version	V1.0
Power Supply	DC 13.8V from DC power supply

I/O Port Information (Applicable Not Applicable)

I/O Port of EUT				
I/O Port Type	Q'TY	Cable	Tested with	
Antenna Port	1	N/A	1	
Hand Microphone	1	0.6m Unshielded	1	

2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

Equipment	Manufacturer	Model Name	Specification	Data Cable	Power Cable
Bluetooth Speaker	SONY	SRS-XB01	DC5V/0.5A,AUX in, micro B	N/A	N/A
50ohm load	/	A-01	SMA interface(Max 5W)	N/A	N/A

☑ Test Accessories Come From The Manufacturer

Equipment	Manufacturer	Model Name	Specification	Data Cable	Power Cable
Charger	N/A	N/A	N/A	N/A	0.6m Unshielded
Power Line	N/A	N/A	N/A	N/A	1.5m unshielded
Hand Microphone	N/A	N/A	N/A	N/A	N/A



2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.3 Description of Test Modes

No.	Test Mode	Remark
1	Scanning mode	Worst
2	Scanning stopped/Receiving at low channel of 108 MHz to 136 MHz	
3	Scanning stopped/Receiving at middle channel of 108 MHz to 136 MHz	
4	Scanning stopped/Receiving at high channel of 108 MHz to 136 MHz	
5	Scanning stopped/Receiving at low channel of 26 MHz to 33 MHz	
6	Scanning stopped/Receiving at middle channel of 26 MHz to 33 MHz	
7	Scanning stopped/Receiving at high channel of 26 MHz to 33 MHz	
8	Scanning stopped/Receiving at low channel of 47 MHz to 54 MHz	
9	Scanning stopped/Receiving at middle channel of 47 MHz to 54 MHz	
10	Scanning stopped/Receiving at high channel of 47 MHz to 54 MHz	
11	Scanning stopped/Receiving at low channel of 136 MHz to 180 MHz	
12	Scanning stopped/Receiving at middle channel of 136 MHz to 180 MHz	
13	Scanning stopped/Receiving at high channel of 136 MHz to 180 MHz	
14	Scanning stopped/Receiving at low channel of 320 MHz to 512 MHz	
15	Scanning stopped/Receiving at middle channel of 320 MHz to 512 MHz	
16	Scanning stopped/Receiving at high channel of 320 MHz to 512 MHz	
17	Scanning stopped/Receiving at low channel of 750 MHz to 950 MHz	
18	Scanning stopped/Receiving at middle channel of 750 MHz to 950 MHz	
19	Scanning stopped/Receiving at high channel of 750 MHz to 950 MHz	

Note: Only the result of the worst case was recorded in the report.



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$



3.5 List of Equipment Used

• Ra	Radiated Emission									
Used	Equipment No.	Test Equipment	Manufacturer	Model No. Serial N		Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)			
\square	AGC-EM-E046	EMI Test Receiver	ver R&S ESC		10096	2024-02-01	2025-01-31			
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23			
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10			
\square	AGC-EM-E029	Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30			
\square	AGC-EM-E096	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23			
	AGC-EM-S003	Test Software	FARA	V.RA-03A	N/A	N/A	N/A			
\square	AGC-EM-S004	Test Software	Tonscend	4.0.0.0	N/A	N/A	N/A			
\boxtimes	AGC-EM-A007	30dB Attenuator	N/A	58-30-33	N/A	2023-06-01	2025-05-31			

 Test Software 	è
-----------------------------------	---

• res	Test Software										
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information						
\boxtimes	AGC-EM-S004	04 RE Test System Tonscend		TS ⁺ Ver2.1(JS32-RE)	4.0.0.0						
	AGC-EM-S003	C-EM-S003 RE Test System		EZ-EMC	V.RA-03A						
\boxtimes	AGC-EM-S011 RSE Test System Tonscend		Tonscend	TS⁺ Ver2.1(JS36-RSE)	4.0.0.0						
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71						



4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	N/A
3	§15.111	Antenna Conducted Power for Receivers	/	Pass
4	§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	/	Pass




5. Radiated Emission Measurements

5.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value	
30MHz-88MHz	40.00	50.00	Quasi-peak	
88MHz-216MHz	43.50	53.50	Quasi-peak	
216MHz-960MHz	46.00	56.00	Quasi-peak	
960MHz-1GHz	54.00	64.00	Quasi-peak	
Above 1GHz	54.00	60.00	Average	
	74.00	80.00	Peak	

5.2 Measurement Setup



Radiated Emission Measurements Test Setup for 30MHz to 1GHz



Radiated Emission Measurements Test Setup for above 1GHz



5.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.


EMI Test Receiver Setup:

During the radiated emission test, the EMI test receiver was set with the following configurations:


Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above T GHz	1MHz	10 Hz	/	Ave.



5.4 Measurement Result









		Radi	ated Emissi	ion 150kHz	-30MHz Test	Result		
Test Mode	Mode 1				Polarity	:	Ho	orizontal
122.0	dBuV/m							
-							Lin Ma	nit: <u> </u>
62								
	whenter	MMmmmm	Mundan Marina Series	hter man and the second se	orthurston and the second	5	ur all and a second state	Second and the second and
2.0 0.15	j0	0.5		(MHz)	5			30.000
	No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
	1	0.3537	13.75	25.33	39.08	96.61	-57.53	peak
	2	0.5020	13.64	25.40	39.04	73.59	-34.55	peak
	3 *	1.0597	9.48	25.18	34.66	67.10	-32.44	peak
	4	3.4355	9.15	23.94	33.09	69.54	-36.45	peak
	5	7.5258	9.94	23.47	33.41	69.54	-36.13	peak
	6	18.8204	7.50	24.14	31.64	69.54	-37.90	peak



		Radi	ated Emiss	ion 150kHz	-30MHz Test	t Result		
Test Mode	Mode	1			Polarity	:	Ve	rtical
122.0	dBu∀/m							
	MMMANNAN		Martin and Martin	Monte and a state of a			4 rd UM/YV-work	gin:
2.0 0.15	50	0.5		(MHz)	5			30.000
_	No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
_		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
_	1	0.3558	14.43	25.33	39.76	96.57	-56.81	peak
_	2 *	0.5701	14.04	25.38	39.42	72.48	-33.06	peak
_	3	0.8483	8.99	25.28	34.27	69.03	-34.76	peak
_	4	2.1326	9.34	24.72	34.06	69.54	-35.48	peak
-	5	5.8050	9.49	23.69	33.18	69.54	-36.36	peak
_	6	23.6361	7.07	24.17	31.24	69.54	-38.30	peak



		Rad	diated Emis	ssion 30MHz-	1GHz Test Re	sult		
Test Mode	Мос	de 1	Polarity:		Vertical			
130				FCC Part 1	15B		· · · · · · · · · · · · · · · · · · ·	
120 110 100 90 80 70 70 60 50 40 30 20 10 0 -10	*1							
30M - Final Data	QP Limit QP Detector	— Vertical PK	100M	Frequency	[Hz]			16
	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1 3	33.88	35.56	12.12	40.00	4.44	100	190	Vertica
2 6	67.83	31.90	15.36	40.00	8.10	100	180	Vertica
3 1	00.81	38.33	17.03	43.50	5.17	100	100	Vertica
4 1	34.76	31.07	15.79	43.50	12.43	100	260	Vertica
5 1	59.01	27.88	17.75	43.50	15.62	100	150	Vertica
6 8	351.59	36.13	29.74	46.00	9.87	100	120	Vertica




		R	adiated Emi	ssion 30MHz	-1GHz Test Re	esult			
Test M	Mode Mode 1				Polarity:		Horizontal		
	130			FCC Part 15	iB				
Level(dBµV/m)	120 110 100 90 80 70 60 50 40 30 20 10 0 -10 30M		100M	* ⁵	⁶	un halde luche veren			
Final [Tata List	imit — Horizontal PK etector		Frequency[ŀ	łz]				
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	33.88	34.44	12.12	40.00	5.56	100	160	Horizontal	
2	49.4	28.09	14.92	40.00	11.91	100	170	Horizontal	
3	100.81	34.13	17.03	43.50	9.37	100	90	Horizontal	
4	110.51	33.54	16.50	43.50	9.96	100	220	Horizontal	
5	134.76	30.35	15.79	43.50	13.15	100	160	Horizontal	
6	233.7	31.37	14.84	46.00	14.63	100	140	Horizontal	



			Ra	diated Em	ission Above	1GHz Test Re	sult		
Test N	lode	Мос	de 1			Polarity:		Vertical	
		PK Limit AV Detec			FCC PART 1	3G	4G	5 5 5 5 5 5 5 5 5 5	6G
Final	Data List								
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1316.06	632	33.26	-17.83	74.00	40.74	100	30	Vertical
2	1748.14	196	36.36	-15.49	74.00	37.64	100	210	Vertical
3	2604.32	209	37.67	-12.15	74.00	36.33	100	130	Vertical
4	3420.48	341	39.78	-10.85	74.00	34.22	100	30	Vertical
5	4317.66	635	41.11	-8.64	74.00	32.89	100	330	Vertical
6	5590.91	182	44.09	-6.61	74.00	29.91	100	110	Vertical





5461.8924

43.93

Note:

6

1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Measurement.

-6.95

2. The "Factor" value can be calculated automatically by software of measurement system.

74.00

30.07

100

30

Horizontal



6. Conducted Emission Measurements

6.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.107: For Class B Limits:

Frequency	Maximum RF Line Voltage		
	Q.P. (dBµV)	Average (dBµV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

For Class A Limits:

Frequency	Maximum RF Line Voltage		
	Q.P. (dBµV)	Average (dBµV)	
150kHz~500kHz	79	66	
500kHz~30MHz	73	60	

6.2 Measurement Setup





6.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipment received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test data of the worst case condition (Mode 1) was reported on the following Data page.

6.4 Measurement Result

Note: Not applicable.



7. Antenna Conducted Power for Receivers

7.1 Provisions Applicable

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz	
Limit	2.0 nW (-57 dBm)	

7.2 Measurement Setup

	Spectrum analyzer	
	EUT	
Restored in the second	Non-Conducted Table	

7.3 Measurement Procedure


- 1. The receiver antenna terminal connected to a spectrum analyzer.
- 2. Receiver set as follow:

Frequency range	RBW (kHz)	VBW (kHz)
9 kHz ~ 150 kHz	1	3
150 kHz ~ 30 MHz	10	30
30 MHz ~ 1000 MHz	100	300
1000 MHz ~ 3000 MHz	1000	3000

3. The test data of the worst case condition (mode 1) was reported on the following Data page.




7.4 Measurement Result



Test Graphs of Antenna Conducted Power for Receivers








8. Scanning Receivers and Frequency Converters Used with Scanning Receivers

8.1 Provisions Applicable

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

8.2 Measurement Setup



8.3 Measurement Procedure

- 1) Connected the EUT as shown in the above block diagram.
- 2) Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
- 3) Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
- 4) Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB. This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
- 5) Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
- 6) Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5) and its frequency to the frequency points in the cellular band.
- 7) Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
- 8) Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
- 9) If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
- 10) Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.



8.4 Measurement Result

Scanning Frequency Band (MHz)	Test Frequency of Cellular Band (MHz)	Spurious Value of Cellular Frequency (dBm)	Reference Sensitivity (dBm)	Measurement Result (dB)	Limit (dB)
108-136	824.5/836.0/848.5	>-46	-107	<-61	<-38
108-136	869.1/881.5/893.5	>-46	-107	<-61	<-38
136-180	824.5/836.0/848.5	>-47	-107	<-60	<-38
136-180	869.1/881.5/893.5	>-47	-107	<-60	<-38
320-512	824.5/836.0/848.5	>-46	-107	<-61	<-38
320-512	869.1/881.5/893.5	>-46	-107	<-61	<-38
750-950	824.5/836.0/848.5	>-45	-107	<-62	<-38
750-950	869.1/881.5/893.5	>-45	-107	<-62	<-38

Note:

- 2. Reference Sensitivity is the recorded value when the signal-to-noise ratio is 12dB.
- 3. Measurement Result = Reference Sensitivity- Spurious Value.

^{1.} Measurement Result = Rejection Ratio



Report No.: AGC02931240602FE01 Page 28 of 28

Appendix I: Photographs of Test Setup Refer to the Report No.: AGC02931240602AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC02931240602AP03

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.