

RF Exposure Requirements

Product Description: Bluetooth speaker

Model No.: HY-01, C-93B, C-317, C-330, C-335, C-336, C-342, C-345, C-347, 38-1D-009, V44

FCC ID: 2AJMUHY-01

According to the KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

Bluetooth(EDR)

Conducted Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
-0.86	0.82	5	2.402	0.25	3

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]: 0.82/5 \cdot \sqrt{2.402} = 0.25$

The exclusion thresholds is less than 3, therefore, the RF exposure evaluation is not required.