

# RF TEST REPORT



Report No.: 15070690-FCC-R1

Supersede Report No.: N/A

Applicant	PAX Technology Limited	
Product Name	Wireless POS Terminal Base	
Model No.	B210	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	August 22 to October 12, 2015	
Issue Date	October 12, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070690-FCC-R1
Page	3 of 56

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	8
6.1 ANTENNA REQUIREMENT .....	8
6.2 CHANNEL SEPARATION .....	9
6.3 20DB BANDWIDTH .....	13
6.4 PEAK OUTPUT POWER .....	17
6.5 NUMBER OF HOPPING CHANNEL .....	21
6.6 TIME OF OCCUPANCY (DWEIL TIME) .....	23
6.7 BAND EDGE .....	27
6.8 AC POWER LINE CONDUCTED EMISSIONS .....	35
6.9 RADIATED SPURIOUS EMISSIONS .....	41
ANNEX A. TEST INSTRUMENT .....	46
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....	47
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....	51
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	55
ANNEX E. DECLARATION OF SIMILARITY .....	56

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070690-FCC-R1	NONE	Original	October 12, 2015

## 2. Customer information

Applicant Name	PAX Technology Limited
Applicant Add	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong
Manufacturer	PAX Computer Technology (Shenzhen) Co., Ltd.
Manufacturer Add	4/F No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen,Guangdong, P.R.C.

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

## 4. Equipment under Test (EUT) Information

Description of EUT:	Wireless POS Terminal Base
Main Model:	B210
Serial Model:	N/A
Date EUT received:	August 21, 2015
Test Date(s):	August 22 to October 12, 2015
Equipment Category :	DSS
Antenna Gain:	Bluetooth/BLE: 1.5dBi
Type of Modulation:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	Bluetooth& BLE: 2402-2480 MHz
Max. Output Power:	8.670dBm
Number of Channels:	Bluetooth: 79CH BLE: 40CH
Port:	Power Port, Lan Port, USB Port, RS232 Port, Line Port
Input Power:	Rating: 9.0V, 1.0A
Trade Name :	PAX
FCC ID:	V5PB210

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Antenna must be permanently attached to the unit.

Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth/BLE, the gain is 1.5dBi for Bluetooth/BLE.

**The antenna meets up with the ANTENNA REQUIREMENT.**


**Result:** Compliance.



## 6.2 Channel Separation

Temperature	21°C
Relative Humidity	55%
Atmospheric Pressure	1015mbar
Test date :	September 17, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer settings:</u>            The EUT must have its hopping function enabled            Span = wide enough to capture the peaks of two adjacent channels            Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span            Video (or Average) Bandwidth (VBW) ≥ RBW            Sweep = auto            Detector function = peak            Trace = max hold            Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

### Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.692	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.685	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.957	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.893	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.901	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.890	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.893	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.887	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.887	Pass
	Adjacency Channel	2479			

## Test Plots

### Channel Separation measurement result



GFSK - Low Channel



GFSK - Middle Channel



GFSK - High Channel



$\pi/4$  DPSK - Low Channel



$\pi/4$  DQPSK - Middle Channel



$\pi/4$  DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

### 6.3 20dB Bandwidth

Temperature	21°C
Relative Humidity	55%
Atmospheric Pressure	1015mbar
Test date :	September 17, 2015
Tested By :	Winnie Zhang

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer settings:</u>            Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel            RBW <math>\geq</math> 1% of the 20 dB bandwidth            VBW <math>\geq</math> RBW            Sweep = auto            Detector function = peak            Trace = max hold.</p> <p>The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the</p>		

Test Report	15070690-FCC-R1
Page	14 of 56

	20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

#### Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.038	0.9213
	Mid	2441	1.027	0.9061
	High	2480	0.957	0.8873
$\pi/4$ DQPSK	Low	2402	1.340	1.2101
	Mid	2441	1.351	1.2069
	High	2480	1.335	1.1987
8-DPSK	Low	2402	1.340	1.2175
	Mid	2441	1.330	1.2111
	High	2480	1.331	1.2041

## Test Plots

### 20dB Bandwidth measurement result



GFSK - Low Channel




GFSK - Middle Channel



GFSK - High Channel




$\pi/4$  DPSK - Low Channel



$\pi/4$  DQPSK - Middle Channel




$\pi/4$  DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel



8DPSK - High Channel




## 6.4 Peak Output Power

Temperature	21°C
Relative Humidity	55%
Atmospheric Pressure	1015mbar
Test date :	September 17, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $<50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <p>Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</p> <p>RBW <math>&gt;</math> the 20 dB bandwidth of the emission being measured</p> <p>VBW <math>\geq</math> RBW</p> <p>Sweep = auto</p> <p>Detector function = peak</p> <p>Trace = max hold</p>
----------------	---

Test Report	15070690-FCC-R1
Page	18 of 56

	<p>Allow the trace to stabilize.</p> <p>Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


#### Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	8.009	125	Pass
		Mid	2441	7.519	125	Pass
		High	2480	6.335	1000	Pass
	$\pi/4$ DQPSK	Low	2402	8.044	125	Pass
		Mid	2441	7.537	125	Pass
		High	2480	6.359	125	Pass
	8-DPSK	Low	2402	<b>8.670</b>	125	Pass
		Mid	2441	8.172	125	Pass
		High	2480	7.073	125	Pass


## Test Plots

### Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

## 6.5 Number of Hopping Channel

Temperature	21°C
Relative Humidity	55%
Atmospheric Pressure	1015mbar
Test date :	September 17, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer settings:</u>          The EUT must have its hopping function enabled.          Span = the frequency band of operation          RBW ≥ 1% of the span          VBW ≥ RBW          Sweep = auto          Detector function = peak          Trace = max hold          Allow trace to fully stabilize.          It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes                      ☐ N/A  
 Test Plot ☒ Yes (See below)                      ☐ N/A

## Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

## Test Plots


### Number of Hopping Channels measurement result



## 6.6 Time of Occupancy (Dwell Time)

Temperature	21°C
Relative Humidity	55%
Atmospheric Pressure	1015mbar
Test date :	September 17, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer</u>            Span = zero span, centered on a hopping channel            RBW = 1 MHz            VBW ≥ RBW            Sweep = as necessary to capture the entire dwell time per hopping channel            Detector function = peak            Trace = max hold            use the marker-delta function to determine the dwell time</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes                      ☐ N/A


Test Plot    ☒ Yes (See below)                      ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.895	308.800	400	Pass
		Mid	2.880	307.200	400	Pass
		High	2.880	307.200	400	Pass
	$\pi$ / 4 DQPSK	Low	2.895	308.800	400	Pass
		Mid	2.880	307.200	400	Pass
		High	2.880	307.200	400	Pass
	8-DPSK	Low	2.895	308.800	400	Pass
		Mid	2.895	308.800	400	Pass
		High	2.880	307.200	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						



## Test Plots


### Dwell Time measurement result




GFSK - Low CH 2402



GFSK - Mid CH 2441



GFDK - High CH 2480




$\pi/4$  DQPSK - Low CH 2402



$\pi/4$  DQPSK - Mid CH 2441




$\pi/4$  DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

## 6.7 Band Edge

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1009mbar
Test date :	October 09, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ol style="list-style-type: none"> <li>1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the</li> </ol>
----------------	--

Test Report	15070690-FCC-R1
Page	28 of 56


	<p>instrument is operated in its linear range.</p> <p>3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:</p> <p>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</p> <p>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</p> <p>5. Repeat above procedures until all measured frequencies were complete.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A

## Test Plots


### GFSK Mode:






GFSK-Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




GFSK-Left Side-AV


Note: (no need if PK value less than the AV limit)

GFSK-Right Side-AV


$\pi/4$  DQPSK Mode:



$\pi/4$  DQPSK-Hopping Left Side-PK  
Note: F1 is frequency 2400MHz




$\pi/4$  DQPSK-Hopping Right Side-PK  
Note: F1 is frequency 2483.5MHz



$\pi/4$  DQPSK-Hopping Left-AV


Note: (no need if PK value less than the AV limit)

$\pi/4$  DQPSK-Hopping Right-AV




Date: 9.OCT.2015 13:46:36

$\pi/4$  DQPSK-Left Side-PK  
Note: F1 is frequency 2400MHz



Date: 9.OCT.2015 14:12:23

$\pi/4$  DQPSK-Right Side-PK  
Note: F1 is frequency 2483.5MHz



Date: 9.OCT.2015 13:42:47


$\pi/4$  DQPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)


$\pi/4$  DQPSK-Right Side-AV




### 8-DPSK Mode:



8DPSK-Hopping Left Side-PK  
Note: F1 is frequency 2400MHz





8DPSK-Hopping Right Side-PK  
Note: F1 is frequency 2483.5MHz



8DPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)

8DPSK-Hopping Right-AV




8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Note: (no need if PK value less than the AV limit)

8DPSK-Left Side-AV


8DPSK-Right Side-AV

## 6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	September 26, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>		
		Frequency ranges (MHz)		Limit (dBμV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
Procedure	<p>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</p> <p>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</p> <p>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial</p>


Test Report	15070690-FCC-R1
Page	36 of 56

	<p>cable.</p> <p>All other supporting equipment were powered separately from another main supply.</p> <p>The EUT was switched on and allowed to warm up to its normal operating condition.</p> <p>A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</p> <p>High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</p> <p>Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

**Test Mode:** Bluetooth Mode




**Test Data**

**Phase Line Plot at 120Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1540	34.08	QP	10.03	44.11	65.78	-21.67
2	L1	0.1540	6.31	AVG	10.03	16.34	55.78	-39.44
3	L1	0.1851	28.84	QP	10.03	38.87	64.25	-25.38
4	L1	0.1851	3.35	AVG	10.03	13.38	54.25	-40.87
5	L1	0.2163	25.54	QP	10.03	35.57	62.96	-27.39
6	L1	0.2163	14.52	AVG	10.03	24.55	52.96	-28.41
7	L1	0.3489	32.77	QP	10.03	42.80	58.99	-16.19
8	L1	0.3489	25.58	AVG	10.03	35.61	48.99	-13.38
9	L1	0.5361	23.68	QP	10.03	33.71	56.00	-22.29
10	L1	0.5361	9.88	AVG	10.03	19.91	46.00	-26.09
11	L1	23.1279	21.61	QP	10.36	31.97	60.00	-28.03
12	L1	23.1279	17.48	AVG	10.36	27.84	50.00	-22.16

**Test Mode:** Bluetooth Mode




**Test Data**

**Phase Neutral Plot at 120Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1659	32.30	QP	10.02	42.32	65.16	-22.84
2	N	0.1659	6.77	AVG	10.02	16.79	55.16	-38.37
3	N	0.2046	26.30	QP	10.02	36.32	63.42	-27.10
4	N	0.2046	4.82	AVG	10.02	14.84	53.42	-38.58
5	N	0.2436	23.01	QP	10.02	33.03	61.97	-28.94
6	N	0.2436	11.16	AVG	10.02	21.18	51.97	-30.79
7	N	0.3489	35.26	QP	10.02	45.28	58.99	-13.71
8	N	0.3489	28.61	AVG	10.02	38.63	48.99	-10.36
9	N	0.5361	17.92	QP	10.02	27.94	56.00	-28.06
10	N	0.5361	7.30	AVG	10.02	17.32	46.00	-28.68
11	N	13.3428	18.99	QP	10.18	29.17	60.00	-30.83
12	N	13.3428	9.34	AVG	10.18	19.52	50.00	-30.48

**Test Mode:** Bluetooth Mode




*Test Data*

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1617	17.29	QP	10.03	27.32	65.38	-38.06
2	L1	0.1617	1.53	AVG	10.03	11.56	55.38	-43.82
3	L1	0.2046	17.88	QP	10.03	27.91	63.42	-35.51
4	L1	0.2046	3.56	AVG	10.03	13.59	53.42	-39.83
5	L1	0.2748	29.45	QP	10.03	39.48	60.97	-21.49
6	L1	0.2748	21.87	AVG	10.03	31.90	50.97	-19.07
7	L1	0.3489	34.51	QP	10.03	44.54	58.99	-14.45
8	L1	0.3489	27.65	AVG	10.03	37.68	48.99	-11.31
9	L1	0.5322	15.48	QP	10.03	25.51	56.00	-30.49
10	L1	0.5322	4.53	AVG	10.03	14.56	46.00	-31.44
11	L1	13.7601	19.07	QP	10.21	29.28	60.00	-30.72
12	L1	13.7601	9.78	AVG	10.21	19.99	50.00	-30.01

**Test Mode:** Bluetooth Mode



### Test Data

#### Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2748	30.13	QP	10.02	40.15	60.97	-20.82
2	N	0.2748	22.33	AVG	10.02	32.35	50.97	-18.62
3	N	0.3489	35.48	QP	10.02	45.50	58.99	-13.49
4	N	0.3489	28.44	AVG	10.02	38.46	48.99	-10.53
5	N	0.5478	22.75	QP	10.02	32.77	56.00	-23.23
6	N	0.5478	10.80	AVG	10.02	20.82	46.00	-25.18
7	N	0.7389	18.58	QP	10.02	28.60	56.00	-27.40
8	N	0.7389	7.53	AVG	10.02	17.55	46.00	-28.45
9	N	1.4214	16.68	QP	10.03	26.71	56.00	-29.29
10	N	1.4214	6.22	AVG	10.03	16.25	46.00	-29.75
11	N	12.7539	21.44	QP	10.17	31.61	60.00	-28.39
12	N	12.7539	8.54	AVG	10.17	18.71	50.00	-31.29



## 6.9 Radiated Spurious Emissions

Temperature	23°C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	September 26, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges												
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> <li>The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> <li>Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> </ol> </li> </ol>
-----------	---

Test Report	15070690-FCC-R1
Page	42 of 56


	<p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

**Test Mode:** Bluetooth Mode

**Below 1GHz**




**Test Data**

**Horizontal Polarity Plot @3m**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	175.0368	45.56	peak	-9.49	36.07	43.50	-7.43	100	212
2	H	191.7450	45.18	peak	-9.14	36.04	43.50	-7.46	100	175
3	H	219.8449	44.79	peak	-8.92	35.87	46.00	-10.13	100	220
4	H	276.1236	46.03	peak	-7.99	38.04	46.00	-7.96	100	182
5	H	295.1469	46.05	peak	-7.12	38.93	46.00	-7.07	100	186
6	H	432.5457	38.21	peak	-3.50	34.71	46.00	-11.29	100	265

### Below 1GHz



### Test Data

#### Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	50.0566	45.76	peak	-13.19	32.57	40.00	-7.43	100	0
2	V	63.3132	46.96	peak	-14.09	32.87	40.00	-7.13	100	139
3	V	177.5092	41.71	peak	-9.69	32.02	43.50	-11.48	100	166
4	V	223.7334	43.46	peak	-8.95	34.51	46.00	-11.49	100	139
5	V	291.0360	42.87	peak	-7.31	35.56	46.00	-10.44	100	233
6	V	406.0880	36.07	peak	-4.16	31.91	46.00	-14.09	100	166

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.95	AV	V	33.83	6.86	31.72	47.92	54	-6.08
4804	38.12	AV	H	33.83	6.86	31.72	47.09	54	-6.91
4804	47.59	PK	V	33.83	6.86	31.72	56.56	74	-17.44
4804	47.16	PK	H	33.83	6.86	31.72	56.13	74	-17.87

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.88	AV	V	33.86	6.82	31.82	47.74	54	-6.26
4882	38.21	AV	H	33.86	6.82	31.82	47.07	54	-6.93
4882	47.46	PK	V	33.86	6.82	31.82	56.32	74	-17.68
4882	47.08	PK	H	33.86	6.82	31.82	55.94	74	-18.06

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.91	AV	V	33.9	6.76	31.92	47.65	54	-6.35
4960	38.15	AV	H	33.9	6.76	31.92	46.89	54	-7.11
4960	47.58	PK	V	33.9	6.76	31.92	56.32	74	-17.68
4960	47.12	PK	H	33.9	6.76	31.92	55.86	74	-18.14

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>



## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo



EUT - Front View




EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View




EUT - Right View




Port View




**Annex B.ii. Photograph: EUT Internal Photo**




Cover Off - Top View




Small board - Front View




Small board - Rear View



Mainboard - Front View



Mainboard - Rear View




BT/BLE - Antenna View




**Annex B.iii. Photograph: Test Setup Photo**




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz


## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


#### Block Configuration Diagram for AC Line Conducted Emissions



**Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .**



**Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .**



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
Lenovo	Lenovo Laptop	E40	N/A	N/A

Test Report	15070690-FCC-R1
Page	55 of 56

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	15070690-FCC-R1
Page	56 of 56

## Annex E. DECLARATION OF SIMILARITY

N/A