



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel: +86-755-27521059 Fax: +86-755-27521011 Http://www.sz-ctc.com.cn

RF Exposure Evaluation

FCC ID: 2ASWHNC7

According to KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

EUT Specification

EUT	Wireless Earbuds
Model/Type reference:	NC7
Listed Model(s):	/
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GHz ☐ BLE: 2.402GHz ~ 2.480GHz ☐ WLAN: 2.412GHz ~ 2.462GHz ☐ Others
Device category	☒ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☐ fixed (>20cm separation) ☐ Others
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	-1.25dBi

Limit

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$

Where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>

**Measurement Result:**

Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up Tolerance (dBm)	Max. Tune up Power (dBm)	Result	Limit
GFSK	2402	0.27	1±1	2	0.368	3.0
	2441	1.18	1±1	2	0.371	3.0
	2480	1.51	2±1	3	0.471	3.0
$\pi/4$ -DQPSK	2402	0.25	1±1	2	0.368	3.0
	2441	1.16	1±1	2	0.371	3.0
	2480	1.51	2±1	3	0.471	3.0
8-DPSK	2402	0.32	1±1	2	0.368	3.0
	2441	1.11	1±1	2	0.371	3.0
	2480	1.51	2±1	3	0.471	3.0

Note: For a more detailed features description, please refer to the RF Test Report.

*****THE END*****