



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdksign.cn Website: www.gdksign.com

RF Exposure Evaluation

FCC ID: 2A094-H5

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ Passed

☐ Not Applicable

BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance Power (dBm)	Max. Tune up tolerance Power (dBm)	Max. Tune up tolerance Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	0.71	0.71±1	1.71	1.483	0.46	3.00	Pass
	2440	0.62	0.62±1	1.62	1.452	0.45		
	2480	0.23	0.23±1	1.23	1.327	0.42		
GFSK_2M	2402	0.66	0.66±1	1.66	1.466	0.45		
	2440	0.60	0.60±1	1.60	1.445	0.45		
	2480	0.13	0.13±1	1.13	1.297	0.41		

Note:

-The exposure safety distance is less than 5mm.



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

NFC

Antenna Gain=0dBi(Numeric 1.0), $\pi=3.14$

Frequency	Max. Measured Power (dBm)	Max. Tune up tolerance Power	Max. Tune up tolerance Power	Calculati ng data	Limit	Results
MHz	dBm	(dBm)	(mW)	0.001466	3.00	Pass
13.56	-13.01	-13.01 $\pm$ 1	0.0629			

According to the follow transmitter output power (P_t) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

According to the formula described above:

$$E_{max} = \underline{82.40} \text{dBuV/m} = 0.01318 \text{V/m}, d=3\text{m}, g_t=1.0$$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.01318 \times 3)^2 / (30 \times 1.0) = \underline{0.000052\text{W}} = \underline{0.052\text{mW}} = -13.01 \text{dBm}$$

Note:

- Only the worst case recorded.
- The 2.4G BLE and NFC can transmit simultaneously and
 $MPE \text{ Ratio (BLE+NFC)} = 0.46/3 + 0.001466/3 = 0.1538 < 3$

and it satisfy the RF exposure requirements for simultaneous transmission that the sum of the MPE
radios < 3

*****THE END*****