

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

Letter of acceptance

Customer name: TOUMEI

Customer model: X5 projector

Customer number:

Specification description:

Built-in Antenna: 2.4G&5.8G-WiFi/3dBi/50ohm/FPC 43.40*12.00mm/
RF1.13mm/Grey coaxial line/L=270mm+Ipex1

Confirm signature and seal					
Company confirmation			Customer confirmation		
Sample	Examine	Permission	Verify	Examine	Permission
Tianpin Intelligent iot Technology (Shenzhen) Co., LTD					
Date	2022-11-23		Date	2022- -	

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

2. Document preparation/revision/repeal of the resume


[illegible]

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

3. Catalogue

1. Cover.....	1
2. Documentpreparation/revision/repealoftheresume.....	2
3. Catalogue	3
4. Product drawing	4
5. Passive performance test parameters.....	5
6. Electrical performance test report.....	7
7. Reliability test report.....	8
8. Packing specification.....	10


4. Product drawing



Tianpin Intelligent iot Technology (Shenzhen) Co., LTD


5.Passive performance test parameters

S11



Fre(GHz)	2.4	2.5	5.15	5.85
ReeturnLoss	-13.30	-13.69	-24.30	-16.55
VSWR	1.55	1.47	1.13	1.35

Efficiency, gain, direction chart




Frequency ID	1	3	5	7	9	11	12	14	16	18	20	22	24	26
Frequency (MHz)	2400.0	2420.0	2440.0	2460.0	2480.0	2500.0	5150.0	5250.0	5350.0	5450.0	5550.0	5650.0	5750.0	5850.0
Efficiency (dBi)	-2.60	-2.61	-3.08	-3.39	-3.03	-2.61	-4.71	-4.91	-3.51	-3.51	-4.15	-4.60	-4.46	-4.21
Gain (dBi)	2.70	2.75	2.63	2.54	2.65	3.39	2.86	2.48	4.01	4.09	3.53	3.30	3.28	3.18
Efficiency (%)	54.95	54.81	49.21	45.78	49.77	54.86	33.80	32.28	44.58	44.59	38.50	34.67	35.81	37.97
Directivity (dB)	5.30	5.36	5.70	5.94	5.68	6.00	7.57	7.39	7.52	7.60	7.67	7.90	7.74	7.38
Peak Gain Position (Theta)	96.00	110.00	98.00	96.00	101.00	108.00	99.00	68.00	96.00	71.00	70.00	69.00	70.00	99.00
Peak Gain Position (Phi)	71.00	62.00	70.00	72.00	69.00	65.00	64.00	91.00	74.00	87.00	89.00	87.00	84.00	63.00
Efficiency ThetaPol (%)	44.13	43.69	39.28	37.66	40.31	44.84	30.68	28.07	40.36	40.98	34.90	30.84	32.28	34.08
Efficiency PhiPol (%)	10.82	11.12	9.93	8.11	9.46	10.02	3.12	4.20	4.23	3.61	3.60	3.83	3.53	3.90
Upper Hem. Efficiency (%)	31.68	30.27	26.30	25.46	28.01	29.56	20.11	17.97	25.14	25.47	22.73	20.81	21.25	22.10
Lower Hem. Efficiency (%)	23.27	24.54	22.92	20.32	21.76	25.31	13.69	14.31	19.44	19.12	15.76	13.86	14.56	15.88

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

Contact person: Jianguo Wang Phone: +8613424341872

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD



Tianpin Intelligent iot Technology (Shenzhen) Co., LTD
 Contact person: Jianguo Wang Phone: +8613424341872

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

6. Electrical performance test report

Electrical parameter		
Frequency range		2.4-2.5GHz /5.15-5.85GHz
Input impedance		50 á
VSWR		<2.0
Gain	2.4GHz	3 dBi
	5.8GHz	3 dBi
Polarization mode		Cross polarization
Radiation direction		Omnidirectional
Type		Ipex1
Mechanical parameter		
Line length		270mm
Maintenance power		/
Coaxial cable		1.13mm gray
Salt spray test		
Environmental parameter		
Operating temperature		-40~85 Ě

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

Contact person: Jianguo Wang Phone: +8613424341872

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

7. Reliability test report

7.1. Constant temperature and humidity test

Trials/pilot projects	Constant temperature and humidity test	Inspection number
Product/specification	2.4G&5.8G-FPC RF1.13mm,L: 270mm, Ipex1	Number of tests: 5PCS
Date of submission: 2022-11-9		Completion Date: 2022-11-10
Test/inspection equipment: 1. Programmable constant temperature and humidity test chamber 2. 8753ES Network Analyzer		
Test/inspection conditions: 1. Constant temperature -40℃ 12H 2. +65℃~70%RH 12H Total 24 hours		
Test Result		
Judging criteria: 1, the metal surface is not cracked wrinkles, separation, etc.; Non-metallic parts should not discolor, crack, deformation, degumming and other bad. 2. Electrical test meets standard requirements; VSWR test passed		
Test/inspection decision: ●PASS ●FAIL ●Not Application		
Test: Examine:		

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

7.2.High and low temperature cold and heat shock

Trials/pilot projects	High and low temperature cold and heat shock	Inspection number
Product/specification	2.4G&5.8G-FPC RF1.13mm,L: 270mm, Ipex1	Number of tests: 5PCS
Date of submission: 2022-11-9		Completion Date: 2022-11-10
Test/inspection equipment: 1. High and low temperature alternating humidity and heat 2.8753ES Network Analyzer		
Test/inspection conditions: -40Ñ (2H)---interval 80Ñ (2H),6 cycles, 24 hours in total		
Test Result		
Judging criteria: 3, the metal surface coating should not flake, crack wrinkles, separation, etc.; Non-metallic parts should not discolor, crack, deformation, degumming and other bad; 4, electrical test in line with standards; VSWR test passed.		
Test/inspection decision: ●PASS ●FAIL ●Not Application		
Test Examine:		

Tianpin Intelligent iot Technology (Shenzhen) Co., LTD

8. Packing specification

Product Part number:													
Specification description: Built-in Antenna: 2.4G&5.8G-WiFi/3dBi/50ohm/FPC 43.40*12.00mm/ RF1.13mm/Grey coaxial line/L=270mm+Ipexl													
1.Label requirements													
Inner label length 45 wide 70						Outer label length 45 wide 70							
demander						demander							
supplier		Tianpin Intelligent iot Technology (Shenzhen) Co., LTD				supplier		Tianpin Intelligent iot Technology (Shenzhen) Co., LTD					
Customer order number						Customer order number							
Part number						Part number							
Material code						Material code							
Name specification			inspector					Name specification			inspector		
Quantity/ unit			Producti on date					Quantity/ unit			Producti on date		
Remark								Remark					
2. Packing requirements													
Inner packaging													
Product													
50PCS													
5000PCS													
Outer packaging													
Note:													