

# **FCC Test Report**

Report No.: AGC13372240901FE01

FCC ID 2ASNS-C2

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Two Way Radio

**BRAND NAME** : RETEVIS

MODEL NAME : C2

**APPLICANT**: Shenzhen Retevis Technology Co., Ltd.

**DATE OF ISSUE** : Oct. 25, 2024

**STANDARD(S)** : FCC Part 15 Subpart B

**REPORT VERSION**: V1.0


Attestation of Global Chicago (Shenzhen) Co., Ltd



Page 2 of 26

# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 25, 2024	Valid	Initial Release





# **Table of Contents**

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Auxiliary Surrounding Description	5
2.2 Test Methodology	6
2.3 Description of Test Modes	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Used	9
4. Summary of Test Results	10
5. Radiated Emission Measurements	11
5.1 Provisions Applicable	11
5.2 Measurement Setup	11
5.3 Measurement Procedure	12
5.4 Measurement Result	13
6. Conducted Emission Measurements	17
6.1 Provisions Applicable	17
6.2 Measurement Setup	17
6.3 Measurement Procedure	18
6.4 Measurement Result	19
7. Antenna Conducted Power for Receivers	21
7.1 Provisions Applicable	21
7.2 Measurement Setup	21
7.3 Measurement Procedure	21
7.4 Measurement Result	22
8. Scanning Receivers and Frequency Converters Used with Scanning Receivers	24
8.1 Provisions Applicable	24
8.2 Measurement Setup	24
8.3 Measurement Procedure	24
8.4 Measurement Result	25
Appendix I: Photographs of Test Setup	26
Appendix II: Photographs of Test EUT	26



Report No.: AGC13372240901FE01 Page 4 of 26

# 1. General Information

Applicant	Shenzhen Retevis Technology Co., Ltd.	
Address	Room 700, 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China	
Manufacturer	Shenzhen Retevis Technology Co., Ltd.	
Address	Room 700, 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road,Jihua Street, Longgang District, Shenzhen,China	
Factory	N/A	
Address	N/A	
Product Designation	Two Way Radio	
Brand Name	RETEVIS	
Test Model	C2	
Date of receipt of test item	Sep. 14, 2024	
Date of Test	Sep. 14, 2024~Oct. 25, 2024	
Deviation from Standard	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Test Report Form No	AGCTR-ER-FCC-CSR-V1.0	

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Mang	
	Bibo Zhang (Project Engineer)	Oct. 25, 2024
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Oct. 25, 2024
Approved By	Max Zhang	
_	Max Zhang (Authorized Officer)	Oct. 25, 2024



Page 5 of 26

### 2. Product Information

# 2.1 Product Technical Description

Housing Type	Plastic and metal
Receive Frequency Range	64-108MHz, 400-480MHz (Scanning Receiver)
Highest Operating Frequency	⊠Greater than 108MHz □Less than 108MHz
Equipment Type	Table-Top
Hardware Version	C2 V1.7
Software Version	C2 version V2.1
Power Supply	DC 7.4V 2000mAh by battery of DC 8.4V 0.5A

# I/O Port Information (⊠Applicable □Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Antenna Port	1	N/A	1
Earphone Port	1	1.2m unshielded	1

# 2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Speaker	GPO	PR200	N/A	
2	Adapter	Huawei	HW-200440C00	Input(AC):100V-240V 50/60Hz 2.4A Output(DC):USB-C(5V/3A)	1.0m unshielded

# 

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	BL2	Retevis	DC 7.4V 2000mAh	N/A
2	Lanyard	N/A	N/A	N/A	0.5m unshielded
3	Back Clip	N/A	N/A	N/A	



Page 6 of 26

# 2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

# 2.3 Description of Test Modes

No.	Test Mode	Remark
1	Scanning mode	Worst
2	Scanning stopped/Receiving at low channel of 64 MHz to 108 MHz	
3	Scanning stopped/Receiving at middle channel of 64 MHz to 108 MHz	
4	Scanning stopped/Receiving at high channel of 64 MHz to 108 MHz	
5	Scanning stopped/Receiving at low channel of 400 MHz to 480 MHz	
6	Scanning stopped/Receiving at middle channel of 400 MHz to 480 MHz	
7	Scanning stopped/Receiving at high channel of 400 MHz to 480 MHz	

### Note:

- 1. Only the result of the worst case was recorded in the report.
- 2. The device is scanning and receiving. Bluetooth is in idle receiving state. It has been considered synchron ously



Page 7 of 26

# 3. Test Environment

# 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

# A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

# FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

# IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 26

### 3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

### 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$



Report No.: AGC13372240901FE01 Page 9 of 26

3.5 List of Equipment Used

•	Radiated Emission									
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)			
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31			
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23			
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27			
	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10			
$\boxtimes$	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023-01-05	2025-01-04			
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2025-03-22			
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23			

•	AC Power Line Conducted Emission									
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)			
$\boxtimes$	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27			
$\boxtimes$	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08			
$\boxtimes$	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27			

• Tes	Test Software									
Used	Equipment No. Test Equipment Manu		Manufacturer	Model No.	Version Information					
$\boxtimes$	AGC-EM-S004	RE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS32-RE)	4.0.0.0					
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A					
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71					



Page 10 of 26

# 4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	Pass
3	§15.111	Antenna Conducted Power for Receivers	/	Pass
4	§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	/	Pass




### 5. Radiated Emission Measurements

# 5.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
Above IGHZ	74.00	80.00	Peak

# 5.2 Measurement Setup



# Radiated Emission Measurements Test Setup for 30MHz to 1GHz



### Radiated Emission Measurements Test Setup for above 1GHz



Page 12 of 26

### **5.3 Measurement Procedure**

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.

### **EMI Test Receiver Setup:**


During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.




Report No.: AGC13372240901FE01 Page 13 of 26

5.4 Measurement Result




Final	Final Data List_Peak									
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity		
1	31.94	27.73	12.70	40.00	12.27	100	300	Vertical		
2	58.13	26.09	17.38	40.00	13.91	100	259	Vertical		
3	149.31	26.60	17.08	43.50	16.90	100	300	Vertical		
4	461.65	31.50	24.36	46.00	14.50	100	180	Vertical		
5	619.76	35.66	25.90	46.00	10.34	100	50	Vertical		
6	895.24	39.04	30.07	46.00	6.96	100	300	Vertical		

**RESULT: PASS** 








### Final Data List\_Peak Limit Freq. Level Factor Margin Height Angle NO. Polarity [MHz] [dBµV/m] [dBµV/m] [cm] [dB] [dB] 68.8 31.81 15.04 40.00 8.19 100 260 Horizontal 1 2 33.71 13.46 6.29 100 310 Horizontal 87.23 40.00 36.12 3 111.48 16.41 43.50 7.38 100 250 Horizontal 17.19 4 150.28 34.88 43.50 8.62 100 270 Horizontal 5 184.23 34.98 11.71 43.50 8.52 100 150 Horizontal 6 845.77 35.96 29.51 46.00 10.04 100 340 Horizontal


# **RESULT: PASS**



Horizontal

Horizontal





### Final Data List Peak Freq. Level Factor Limit Margin Height Angle NO. **Polarity** [MHz] [dBµV/m] [dB] [dBµV/m] [dB] [cm] [°] 1130.026005 1 34.40 -18.13 74.00 39.60 100 310 Horizontal 2 1721.144229 36.54 -15.71 74.00 37.46 100 260 Horizontal 3 2415.283057 40.35 -12.40 74.00 33.65 100 170 Horizontal 2871.374275 39.78 -12.03 74.00 34.22 100 180 Horizontal 4

74.00

74.00

32.58

30.93

100

100

110

70

-8.25

-6.88

# **RESULT: PASS**

4411.682337

5497.89958


5

6


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

41.42

43.07







### Final Data List Peak

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1096.019204	32.80	-18.19	74.00	41.20	100	70	Vertical
2	1610.122024	35.78	-16.63	74.00	38.22	100	60	Vertical
3	2088.217644	38.39	-13.20	74.00	35.61	100	210	Vertical
4	2735.347069	39.22	-12.10	74.00	34.78	100	320	Vertical
5	3908.581716	39.37	-10.09	74.00	34.63	100	170	Vertical
6	5166.833367	42.09	-7.47	74.00	31.91	100	360	Vertical

# **RESULT: PASS**

### Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain, Margin= Limit-Measurement.
- 2. The "Factor" value can be calculated automatically by software of measurement system.



Page 17 of 26

# 6. Conducted Emission Measurements

# 6.1 Provisions Applicable

FCC CFR Title 47 Part 15 Subpart B Section 15.107:


For Class B Limits:

Fraguenay	Maximum RF Line Voltage				
Frequency	Q.P. (dBμV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

### For Class A Limits:

Fraguency	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	79	66			
500kHz~30MHz	73	60			

### 6.2 Measurement Setup





Report No.: AGC13372240901FE01 Page 18 of 26

### **6.3 Measurement Procedure**

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipment received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test data of the worst case condition (Mode 1) was reported on the following Data page.



### 6.4 Measurement Result

	Ac Power Line Conducted Emission Test						
est Mode	Mode 1			LIS	N Line	Hot Sid	de
L	evel [dBµV]						
80	[ <u>:</u>		·i				
70	<del>    </del>		·				
60 50						1 1	
40		<del></del>	<del> </del> 		<del> </del>	         +	
30					╬╌╌╬╌╬╌╬	- † -	 
20		-++		Chain in the second of		National Control	
10							
-10		- +	·	i	-iiiii	- <del>i -i</del>	i
-10	150k 300k 400k	600k 800k 1		M 3M 4 ency [Hz]	4M 5M 6M 8N	M 10M 20	M 30M
	+MES agc_fin		rieque	incy [HZ]			
	Times agc_IIII						
МТ	EASUREMENT	RESULT	: "agc	fin"			
20	24/9/23 11:						
	Frequency MHz				Margin dB	Detector	Line
	MIL	dBµV	dB	dΒμV	uБ		
	0.594000	19.70	6.2	56	36.3	QP	L1
	1.390000	21.40	6.2	56	34.6		L1
	16.578000	26.60	6.9	60	33.4		L1
	19.198000 25.522000	17.00 27.10	7.0	60	43.0		L1
	28.118000	23.00	8.0 8.2	60 60	32.9 37.0	QP QP	L1 L1
	20.110000	23.00	0.2	00	37.0	Χı	D.I.
				c: o"			
ME	EASUREMENT	RESULT	: "agc_	I1n2"			
20	24/9/23 11:						
	Frequency					Detector	Line
	MHz	dΒμV	dB	dΒμV	dB		
	1.274000	18.00	6.2	46	28.0	AV	L1
	1.2/4000	10.00	0.2	40	20.0	AV	111
	14.046000	19.60	6.8	50	30.4	AV	L1

# **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.  $Further\ enquiry\ of\ validity\ or\ verification\ of\ the\ test\ report\ should\ be\ addressed\ to\ AGC\ by\ agc 01@agccert.com.$ 

6.9

7.6

8.0

8.2

50

50

50

50

ΑV

ΑV

ΑV

ΑV

L1

L1

L1

L1

31.9

29.8

28.5

34.7

16.562000

22.962000

25.518000

28.118000


18.10

20.20

21.50

15.30





### **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.2

50

32.1

ΑV

Ν

28.022000

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

17.90



Page 21 of 26


# 7. Antenna Conducted Power for Receivers

# 7.1 Provisions Applicable

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz
Limit	2.0 nW (-57 dBm )

### 7.2 Measurement Setup




### 7.3 Measurement Procedure

1. The receiver antenna terminal connected to a spectrum analyzer.

2. Receiver set as follow:


Frequency range	RBW (kHz)	VBW (kHz)	
9 kHz ~ 150 kHz	1	3	
150 kHz ~ 30 MHz	10	30	
30 MHz ~ 1000 MHz	100	300	
1000 MHz ~ 3000 MHz	1000	3000	

3. The test data of the worst case condition (mode 1) was reported on the following Data page.






### 7.4 Measurement Result







# **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




Page 24 of 26

# 8. Scanning Receivers and Frequency Converters Used with Scanning Receivers

# 8.1 Provisions Applicable

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

### 8.2 Measurement Setup



### 8.3 Measurement Procedure

- 1) Connected the EUT as shown in the above block diagram.
- Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
- 3) Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
- 4) Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB. This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
- 5) Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
- 6) Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5) and its frequency to the frequency points in the cellular band.
- 7) Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
- 8) Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
- 9) If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
- 10) Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.



Page 25 of 26

### 8.4 Measurement Result

Scanning Frequency Band (MHz)	Test Frequency of Cellular Band (MHz)	Spurious Value of Cellular Frequency (dBm)	Reference Sensitivity (dBm)	Measurement Result (dB)	Limit (dB)
400-480	824.5/836.0/848.5	>-47	-107	<-60	<-38
400-480	869.1/881.5/893.5	>-47	-107	<-60	<-38

### Note:

- 1. Measurement Result = Rejection Ratio
- 2. Reference Sensitivity is the recorded value when the signal-to-noise ratio is 12dB.
- 3. Measurement Result = Reference Sensitivity- Spurious Value.



Page 26 of 26

**Appendix I: Photographs of Test Setup** 

Refer to the Report No.: AGC13372240901AP03

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC13372240901AP02

----End of Report----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.