

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Pendant
<b>Model Number</b>	BH-SKY2-PP0-CBK001-2
<b>FCC ID</b>	2BAZK-SKY2PP1
<b>Antenna Gain</b>	2.2dBi
<b>Operation Frequency</b>	2412 MHz to 2462 MHz
<b>Modulation</b>	802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM)
<b>Power Supply</b>	AC120V/60Hz
<b>Max. output power</b>	IEEE 802.11b: 15.61 dBm IEEE 802.11g: 14.65 dBm IEEE 802.11n HT20: 14.15 dBm IEEE 802.11n HT40: 14.29 dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

**Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm=20cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Measurement Result

Antenna gain: 2.2dBi

Mode	Channe l Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	2412	15.57	16±1	17	1.66	0.016551	1
	2437	15.61	16±1	17	1.66	0.016551	1
	2462	15.34	16±1	17	1.66	0.016551	1
802.11g	2412	14.65	15±1	16	1.66	0.013147	1
	2437	14.51	15±1	16	1.66	0.013147	1
	2462	14.34	14±1	15	1.66	0.010443	1
802.11n HT20	2412	14.15	14±1	15	1.66	0.010443	1
	2437	13.96	14±1	15	1.66	0.010443	1
	2462	13.8	14±1	15	1.66	0.010443	1
802.11n HT40	2422	14.29	14±1	15	1.66	0.010443	1
	2437	14.16	14±1	15	1.66	0.010443	1
	2452	14.14	14±1	15	1.66	0.010443	1

Signature:

