




FCC RADIO TEST REPORT

FCC ID : 2AFZZRC04
Equipment : Xiaomi WiFi Range Extender AC1200
Brand Name : xiaomi
Model Name : RC04
Applicant : Xiaomi Communications Co., Ltd
#019, 9th Floor, Building 6, 33 Xi'erqi Middle
Road, Haidian District, Beijing, China, 100085
Manufacturer : Xiaomi Communications Co., Ltd
#019, 9th Floor, Building 6, 33 Xi'erqi Middle
Road, Haidian District, Beijing, China, 100085
Standard : FCC Part 15 Subpart E §15.407

The product was received on Apr. 24, 2024 and testing was performed from May 06, 2024 to May 30, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 Test Result	14
3.1 26dB & 99% Occupied Bandwidth Measurement	14
3.2 Maximum Conducted Output Power Measurement	15
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement.....	19
3.5 AC Conducted Emission Measurement.....	24
3.6 Antenna Requirements.....	26
4 List of Measuring Equipment.....	27
5 Measurement Uncertainty	28
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR441123B	01	Initial issue of report	Jun. 27, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	0.53 dB under the limit at 11160.00 MHz
3.5	15.207	AC Conducted Emission	Pass	2.82 dB under the limit at 0.48 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Peter Liao

Report Producer: Wilda Wei



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Wi-Fi 2.4GHz 802.11b/g/n and Wi-Fi 5GHz 802.11a/n/ac.		
Antenna Type WLAN: <Ant. 1>: External Antenna <Ant. 2>: External Antenna		
Antenna information		
5150 MHz ~ 5250 MHz	Peak Gain (dBi)	Ant. 1: 3.85 Ant. 2: 4.05
5250 MHz ~ 5350 MHz	Peak Gain (dBi)	Ant. 1: 3.87 Ant. 2: 4.40
5470 MHz ~ 5725 MHz	Peak Gain (dBi)	Ant. 1: 3.72 Ant. 2: 3.93

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.1.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1 / 20} + 10^{G_2 / 20} + \dots + 10^{G_N / 20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 1 (dBi)	Ant 2 (dBi)	(dBi)	(dBi)	(dB)	(dB)
Band I	3.85	4.05	4.05	6.96	0.00	0.96
Band II	3.87	4.40	4.40	7.15	0.00	1.15
Band III	3.72	3.93	3.93	6.84	0.00	0.84

Calculation example:

If a device has two antenna, $G_{ANT1} = 3.85$ dBi; $G_{ANT2} = 4.05$ dBi

Directional gain of power measurement = $\max(3.85, 4.05) + 0 = 4.05$ dBi

Directional gain of PSD derived from formula which is

$10 \times \log \{ [10^{(3.85 \text{ dBi} / 20)} + 10^{(4.05 \text{ dBi} / 20)}]^2 / 2 \}$

= 6.96 dBi

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010 TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH23-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210		
Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5250-5350 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290		
Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5470-5725 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710		

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80.



2.2 Test Mode

The power for 802.11ac mode is smaller than 802.11n mode, so all other conducted and radiated test is covered by 802.11n mode.

The device supports single transmission only in 802.11a mode, and single and multiple transmission in 802.11n and ac modes.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is chosen as main test configuration.

The final test modes include the worst data rates for each modulation shown in the table below.

Single Mode

Modulation	Data Rate
802.11a	6 Mbps

MIMO Mode

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : Lan Link + WLAN (5GHz) Link

<Ant. 1>

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140
Straddle		-	-	144

<Ant. 2>

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140
Straddle		-	-	144

MIMO <Ant. 1+2>


Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140
Straddle		-	-	144

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102
M	Middle	-	-	110
H	High	46	62	134
Straddle		-	-	142

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106
M	Middle	42	58	-
H	High	-	-	122
Straddle		-	-	138

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility “QA(MT7663) 0.0.2.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For the 5.15–5.25 GHz bands:

■ For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For the 5.25–5.725 GHz bands:

■ The maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures


The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For the 5.15–5.25 GHz bands:

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1.0 MHz band.

For the 5.25–5.725 GHz bands:

The maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points; the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Sep. 12, 2023	May 07, 2024~ May 29, 2024	Sep. 11, 2024	Radiation (03CH23-HY)
Bilog Antenna with 6dB pad	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	62028 & 003	N/A	Oct. 15, 2023	May 07, 2024~ May 29, 2024	Oct. 14, 2024	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421582	N/A	Jul. 15, 2023	May 07, 2024~ May 29, 2024	Jul. 14, 2024	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18E N	1GHz~18GHz	Jul. 12, 2023	May 07, 2024~ May 29, 2024	Jul. 11, 2024	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA9170	1223	18GHz~40GHz	Jul. 10, 2023	May 07, 2024~ May 29, 2024	Jul. 09, 2024	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	N/A	Sep. 28, 2023	May 07, 2024~ May 29, 2024	Sep. 27, 2024	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060871	18-40GHz	Sep. 06, 2023	May 07, 2024~ May 29, 2024	Sep. 05, 2024	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	N/A	Aug. 17, 2023	May 07, 2024~ May 29, 2024	Aug. 16, 2024	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303B	TP211542	N/A	Oct. 30, 2023	May 07, 2024~ May 29, 2024	Oct. 29, 2024	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 07, 2024~ May 29, 2024	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 07, 2024~ May 29, 2024	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 07, 2024~ May 29, 2024	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019 122	RK-002348	N/A	N/A	May 07, 2024~ May 29, 2024	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	May 07, 2024~ May 29, 2024	Mar. 05, 2025	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	N/A	Nov. 27, 2023	May 07, 2024~ May 29, 2024	Nov. 26, 2024	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/23111 9/231122	N/A	Nov. 27, 2023	May 07, 2024~ May 29, 2024	Nov. 26, 2024	Radiation (03CH23-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	May 06, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 06, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 20, 2023	May 06, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	May 06, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	May 06, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	May 06, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	May 06, 2024	Sep. 19, 2024	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	May 24, 2024~ May 30, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 36 (NO:35)	10MHz~6GHz	Aug. 23, 2023	May 24, 2024~ May 30, 2024	Aug. 22, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Jan. 24, 2024	May 24, 2024~ May 30, 2024	Jan. 23, 2025	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44 dB
--	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
--	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
--	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
--	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.30 dB
--	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Wei Shun	Temperature:	21~25	°C
Test Date:	2024/5/24~2024/5/30	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

U-NII-1 single antenna											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth EIRP Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	36	5180	16.86	16.77	20.29	20.30	22.27	22.25	-
11a	6Mbps	1	44	5220	17.04	16.85	23.91	20.46	22.32	22.27	
11a	6Mbps	1	48	5240	17.25	16.81	27.57	20.58	22.37	22.26	

U-NII-1 MIMO												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth EIRP Limit (dBm)			Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	36	5180	17.72	17.60	20.50	20.42	22.45		-	
HT20	MCS0	2	44	5220	17.78	17.66	20.56	20.39	22.47			
HT20	MCS0	2	48	5240	17.79	17.65	20.66	20.38	22.47			
HT40	MCS0	2	38	5190	36.03	36.34	41.25	41.42	23.01			
HT40	MCS0	2	46	5230	37.23	36.51	47.55	42.03	23.01			
VHT80	MCS0	2	42	5210	75.44	75.21	81.41	80.83	23.01			

TEST RESULTS DATA**Average Power Table**

FCC U-NII-1 single antenna													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	36	5180	18.40	18.10	-	30.00	30.00	3.85	4.05	-	Pass
11a	6Mbps	1	44	5220	19.60	18.20		30.00	30.00	3.85	4.05		Pass
11a	6Mbps	1	48	5240	19.90	18.20		30.00	30.00	3.85	4.05		Pass

FCC U-NII-1 MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	36	5180	16.60	16.90	19.76	30.00		4.05		-	Pass
HT20	MCS0	2	44	5220	16.90	17.20	20.06	30.00		4.05			Pass
HT20	MCS0	2	48	5240	16.40	16.80	19.61	30.00		4.05			Pass
HT40	MCS0	2	38	5190	13.70	14.00	16.86	30.00		4.05			Pass
HT40	MCS0	2	46	5230	18.20	17.80	21.01	30.00		4.05			Pass
VHT20	MCS0	2	36	5180	16.50	16.80	19.66	30.00		4.05			Pass
VHT20	MCS0	2	44	5220	16.80	17.10	19.96	30.00		4.05			Pass
VHT20	MCS0	2	48	5240	16.30	16.70	19.51	30.00		4.05			Pass
VHT40	MCS0	2	38	5190	13.60	13.90	16.76	30.00		4.05			Pass
VHT40	MCS0	2	46	5230	18.10	17.70	20.91	30.00		4.05			Pass
VHT80	MCS0	2	42	5210	10.90	11.20	14.06	30.00		4.05			Pass

TEST RESULTS DATA
Power Spectral Density

FCC U-NII-1 single antenna															
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	36	5180	0.20	0.19	8.76	8.15	-	17.00	17.00	3.85	4.05	-	Pass
11a	6Mbps	1	44	5220	0.20	0.19	9.38	8.08		17.00	17.00	3.85	4.05		Pass
11a	6Mbps	1	48	5240	0.20	0.19	10.06	8.35		17.00	17.00	3.85	4.05		Pass

FCC U-NII-1 MIMO														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	36	5180	0.19	0.17	-		9.54	16.04	6.96	-		Pass
HT20	MCS0	2	44	5220	0.19	0.17			9.61	16.04	6.96			Pass
HT20	MCS0	2	48	5240	0.19	0.17			9.28	16.04	6.96			Pass
HT40	MCS0	2	38	5190	0.09	0.09			4.23	16.04	6.96			Pass
HT40	MCS0	2	46	5230	0.09	0.09			8.89	16.04	6.96			Pass
VHT80	MCS0	2	42	5210	0.09	0.09			-1.95	16.04	6.96			Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2A single antenna															
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	52	5260	17.66	16.90	29.98	20.40	23.47	23.28	29.47	29.28	23.98	23.98	-
11a	6Mbps	1	60	5300	17.20	16.83	27.38	20.56	23.36	23.26	29.36	29.26	23.98	23.98	
11a	6Mbps	1	64	5320	16.83	16.79	20.50	20.33	23.26	23.25	29.26	29.25	23.98	23.98	

U-NII-2A MIMO															
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	52	5260	17.72	17.65	20.62	20.44	23.47		29.47		23.98	-	
HT20	MCS0	2	60	5300	17.81	17.64	20.58	20.57	23.46		29.46		23.98		
HT20	MCS0	2	64	5320	17.78	17.64	20.61	20.48	23.47		29.47		23.98		
HT40	MCS0	2	54	5270	36.09	36.39	42.37	41.94	23.98		30.00		23.98		
HT40	MCS0	2	62	5310	36.96	36.18	42.30	41.25	23.98		30.00		23.98		
VHT80	MCS0	2	58	5290	75.69	75.23	81.12	80.96	23.98		30.00		23.98		

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	52	5260	20.60	18.50	-	23.98	23.98	3.87	4.40	30	Pass
11a	6Mbps	1	60	5300	20.10	18.40		23.98	23.98	3.87	4.40	30	Pass
11a	6Mbps	1	64	5320	17.90	18.10		23.98	23.98	3.87	4.40	30	Pass

FCC U-NII-2A MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	52	5260	16.50	16.90	19.71	23.98		4.40		30	Pass
HT20	MCS0	2	60	5300	16.60	17.10	19.87	23.98		4.40		30	Pass
HT20	MCS0	2	64	5320	16.60	17.00	19.81	23.98		4.40		30	Pass
HT40	MCS0	2	54	5270	18.50	18.80	21.66	23.98		4.40		30	Pass
HT40	MCS0	2	62	5310	16.00	16.50	19.27	23.98		4.40		30	Pass
VHT20	MCS0	2	52	5260	16.40	16.80	19.61	23.98		4.40		30	Pass
VHT20	MCS0	2	60	5300	16.50	17.00	19.77	23.98		4.40		30	Pass
VHT20	MCS0	2	64	5320	16.50	16.90	19.71	23.98		4.40		30	Pass
VHT40	MCS0	2	54	5270	18.40	18.70	21.56	23.98		4.40		30	Pass
VHT40	MCS0	2	62	5310	15.90	16.40	19.17	23.98		4.40		30	Pass
VHT80	MCS0	2	58	5290	10.40	10.70	13.56	23.98		4.40		30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2A single antenna														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	52	5260	0.20	0.19	10.70	8.59		11.00	11.00	3.87	4.40	Pass
11a	6Mbps	1	60	5300	0.20	0.19	10.05	8.09	-	11.00	11.00	3.87	4.40	Pass
11a	6Mbps	1	64	5320	0.20	0.19	8.15	8.03		11.00	11.00	3.87	4.40	Pass

U-NII-2A MIMO														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	52	5260	0.19	0.17	-		9.79	9.85		7.15		Pass
HT20	MCS0	2	60	5300	0.19	0.17			9.37	9.85		7.15		Pass
HT20	MCS0	2	64	5320	0.19	0.17			9.68	9.85		7.15		Pass
HT40	MCS0	2	54	5270	0.09	0.09			9.03	9.85		7.15		Pass
HT40	MCS0	2	62	5310	0.09	0.09			5.74	9.85		7.15		Pass
VHT80	MCS0	2	58	5290	0.09	0.09			-2.89	9.85		7.15		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2C single antenna																
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
11a	6Mbps	1	100	5500	16.78	16.95	20.14	20.45	23.25	23.29	29.25	29.29	23.98	23.98	----	----
11a	6Mbps	1	116	5580	16.98	16.97	23.04	20.49	23.30	23.30	29.30	29.30	23.98	23.98	----	----
11a	6Mbps	1	140	5700	16.77	16.80	20.36	20.37	23.24	23.25	29.24	29.25	23.98	23.98	----	----

U-NII-2C MIMO																
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
HT20	MCS0	2	100	5500	17.74	17.66	20.75	20.33	23.47		29.47		23.98		----	----
HT20	MCS0	2	116	5580	17.77	17.66	20.59	20.56	23.47		29.47		23.98		----	----
HT20	MCS0	2	140	5700	17.80	17.61	20.58	20.34	23.46		29.46		23.98		----	----
HT40	MCS0	2	102	5510	36.07	36.26	41.55	41.25	23.98		30.00		23.98		----	----
HT40	MCS0	2	110	5550	36.54	36.24	41.84	41.52	23.98		30.00		23.98		----	----
HT40	MCS0	2	134	5670	36.19	36.28	41.46	41.62	23.98		30.00		23.98		----	----
VHT80	MCS0	2	106	5530	75.98	75.27	82.02	81.28	23.98		30.00		23.98		----	----
VHT80	MCS0	2	122	5610	75.49	75.61	82.66	81.41	23.98		30.00		23.98		----	----

U-NII-2C straddle channel single antenna																
Mod.	Data Rate	N _{Tx}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
11a	6Mbps	1	144	5720	14.08	13.41	21.30	15.08	22.49	22.27	28.49	28.27	23.98	22.78	2.525	2.525
6dB Bandwidth Limit ≥ 500kHz															Pass	

U-NII-2C straddle channel MIMO																
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
HT20	MCS0	2	144	5720	13.88	13.90	15.37	15.18	22.42		28.42		22.81		3.075	2.49
VHT40	MCS0	2	142	5710	33.44	33.28	47.11	35.91	23.98		30.00		23.98		2.505	1.218
VHT80	MCS0	2	138	5690	73.02	72.68	108.38	91.77	23.98		30.00		23.98		2.52	2.488
6dB Bandwidth Limit ≥ 500kHz															Pass	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	100	5500	18.80	16.50	-	23.98	23.98	3.72	3.93	30	Pass
11a	6Mbps	1	116	5580	19.40	14.70		23.98	23.98	3.72	3.93	30	Pass
11a	6Mbps	1	140	5700	15.50	14.80		23.98	23.98	3.72	3.93	30	Pass

FCC U-NII-2C MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	100	5500	17.70	16.70	20.24	23.98		3.93		30	Pass
HT20	MCS0	2	116	5580	17.60	16.60	20.14	23.98		3.93		30	Pass
HT20	MCS0	2	140	5700	14.10	13.70	16.91	23.98		3.93		30	Pass
HT40	MCS0	2	102	5510	16.20	15.20	18.74	23.98		3.93		30	Pass
HT40	MCS0	2	110	5550	16.40	15.40	18.94	23.98		3.93		30	Pass
HT40	MCS0	2	134	5670	16.00	15.40	18.72	23.98		3.93		30	Pass
VHT20	MCS0	2	100	5500	17.60	16.60	20.14	23.98		3.93		30	Pass
VHT20	MCS0	2	116	5580	17.50	16.50	20.04	23.98		3.93		30	Pass
VHT20	MCS0	2	140	5700	14.00	13.60	16.81	23.98		3.93		30	Pass
VHT40	MCS0	2	102	5510	16.10	15.10	18.64	23.98		3.93		30	Pass
VHT40	MCS0	2	110	5550	16.30	15.30	18.84	23.98		3.93		30	Pass
VHT40	MCS0	2	134	5670	15.90	15.30	18.62	23.98		3.93		30	Pass
VHT80	MCS0	2	106	5530	11.10	9.60	13.42	23.98		3.93		30	Pass
VHT80	MCS0	2	122	5610	17.20	16.20	19.74	23.98		3.93		30	Pass

FCC U-NII-2C straddle channel single antenna													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	144	5720	18.90	14.40	-	23.98	22.78	3.72	3.93	30	Pass

FCC U-NII-2C straddle channel MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
HT20	MCS0	2	144	5720	16.00	16.00	19.01	22.81		3.93		30	Pass
HT40	MCS0	2	142	5710	16.90	16.80	19.86	23.98		3.93		30	Pass
VHT20	MCS0	2	144	5720	15.90	15.90	18.91	23.98		3.93		30	Pass
VHT40	MCS0	2	142	5710	16.80	16.70	19.76	23.98		3.93		30	Pass
VHT80	MCS0	2	138	5690	18.50	18.10	21.31	23.98		3.93		30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2C single antenna														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	100	5500	0.20	0.19	9.05	6.35	-	11.00	11.00	3.72	3.93	Pass
11a	6Mbps	1	116	5580	0.20	0.19	9.57	4.53		11.00	11.00	3.72	3.93	Pass
11a	6Mbps	1	140	5700	0.20	0.19	5.64	5.21		11.00	11.00	3.72	3.93	Pass

U-NII-2C MIMO														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	100	5500	0.19	0.17	-		10.05	10.16	6.84	-		Pass
HT20	MCS0	2	116	5580	0.19	0.17			9.99	10.16	6.84			Pass
HT20	MCS0	2	140	5700	0.19	0.17			6.85	10.16	6.84			Pass
HT40	MCS0	2	102	5510	0.09	0.09			6.23	10.16	6.84			Pass
HT40	MCS0	2	110	5550	0.09	0.09			5.74	10.16	6.84			Pass
HT40	MCS0	2	134	5670	0.09	0.09			5.98	10.16	6.84			Pass
VHT80	MCS0	2	106	5530	0.09	0.09			-3.53	10.16	6.84			Pass
VHT80	MCS0	2	122	5610	0.09	0.09			3.47	10.16	6.84			Pass


U-NII-2C straddle channel single antenna														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	144	5720	0.20	0.19	9.15	4.61	-	11.00	11.00	3.72	3.93	Pass

U-NII-2C straddle channel MIMO														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	144	5720	0.19	0.17	-		8.99	10.16	6.84	-		Pass
HT40	MCS0	2	142	5710	0.09	0.09			6.96	10.16	6.84			Pass
VHT80	MCS0	2	138	5690	0.09	0.09			5.62	10.16	6.84			Pass

**Test Result of 26dB & 99% Occupied Bandwidth**

<Ant. 1>


<802.11a>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

MIMO <Ant. 1+2>


<802.11n HT20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11n HT40>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT80>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



Test Result of Power Spectral Density


<Ant1>

<802.11a>



<Ant2>


<802.11a>






MIMO <Ant. 1+2>

<802.11n HT20>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11n HT40>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11ac VHT80>



Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	23.7~25.6℃
		Relative Humidity :	43.6~51.8%

EUT Information

Report NO : 441123
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163230	---	30.31	55.30	24.99	L1	OFF	19.9
0.163230	40.95	---	65.30	24.35	L1	OFF	19.9
0.286440	---	16.55	50.63	34.08	L1	OFF	19.9
0.286440	26.89	---	60.63	33.74	L1	OFF	19.9
0.321000	---	22.26	49.68	27.42	L1	OFF	19.9
0.321000	32.37	---	59.68	27.31	L1	OFF	19.9
0.362400	---	18.32	48.67	30.35	L1	OFF	19.9
0.362400	30.40	---	58.67	28.27	L1	OFF	19.9
0.483000	---	35.09	46.29	11.20	L1	OFF	19.9
0.483000	42.59	---	56.29	13.70	L1	OFF	19.9
0.492450	---	18.85	46.13	27.28	L1	OFF	19.9
0.492450	31.04	---	56.13	25.09	L1	OFF	19.9
0.777750	---	15.94	46.00	30.06	L1	OFF	19.9
0.777750	22.17	---	56.00	33.83	L1	OFF	19.9
23.128620	---	28.63	50.00	21.37	L1	OFF	20.1
23.128620	32.70	---	60.00	27.30	L1	OFF	20.1

EUT Information

Report NO : 441123
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163500	---	28.47	55.28	26.81	N	OFF	19.9
0.163500	40.23	---	65.28	25.05	N	OFF	19.9
0.201750	---	19.60	53.54	33.94	N	OFF	19.9
0.201750	34.69	---	63.54	28.85	N	OFF	19.9
0.484440	---	43.44	46.26	2.82	N	OFF	19.9
0.484440	45.30	---	56.26	10.96	N	OFF	19.9
0.532500	---	19.17	46.00	26.83	N	OFF	19.9
0.532500	30.30	---	56.00	25.70	N	OFF	19.9
0.935250	---	16.98	46.00	29.02	N	OFF	19.9
0.935250	29.38	---	56.00	26.62	N	OFF	19.9
23.128260	---	28.18	50.00	21.82	N	OFF	20.2
23.128260	32.86	---	60.00	27.14	N	OFF	20.2

**Appendix C. Radiated Spurious Emission Test Data**

Test Engineer :	Leo Li and Lucifer Jiang	Relative Humidity :	51~57%
		Temperature :	21.7~22.5 °C

Note symbol

-L	Low channel location
-R	High channel location



C1. Radiated Spurious Emission Test Modes

<Ant. 1>

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	U-NII-1	5.15-5.25	1	802.11a	36	5180	6Mbps	-	-
Mode 2	U-NII-1	5.15-5.25	1	802.11a	44	5220	6Mbps	-	-
Mode 3	U-NII-1	5.15-5.25	1	802.11a	48	5240	6Mbps	-	-
Mode 4	U-NII-2A	5.25-5.35	1	802.11a	52	5260	6Mbps	-	-
Mode 5	U-NII-2A	5.25-5.35	1	802.11a	60	5300	6Mbps	-	-
Mode 6	U-NII-2A	5.25-5.35	1	802.11a	64	5320	6Mbps	-	-
Mode 7	U-NII-2C	5.47-5.725	1	802.11a	100	5500	6Mbps	-	-
Mode 8	U-NII-2C	5.47-5.725	1	802.11a	116	5580	6Mbps	-	-
Mode 9	U-NII-2C	5.47-5.725	1	802.11a	140	5700	6Mbps	-	-
Mode 10	U-NII-2C	Straddle Channel	1	802.11a	144	5720	6Mbps	-	-

<Ant. 2>

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 11	U-NII-1	5.15-5.25	2	802.11a	36	5180	6Mbps	-	-
Mode 12	U-NII-1	5.15-5.25	2	802.11a	44	5220	6Mbps	-	-
Mode 13	U-NII-1	5.15-5.25	2	802.11a	48	5240	6Mbps	-	-
Mode 14	U-NII-2A	5.25-5.35	2	802.11a	52	5260	6Mbps	-	-
Mode 15	U-NII-2A	5.25-5.35	2	802.11a	60	5300	6Mbps	-	-
Mode 16	U-NII-2A	5.25-5.35	2	802.11a	64	5320	6Mbps	-	-
Mode 17	U-NII-2C	5.47-5.725	2	802.11a	100	5500	6Mbps	-	-
Mode 18	U-NII-2C	5.47-5.725	2	802.11a	116	5580	6Mbps	-	-
Mode 19	U-NII-2C	5.47-5.725	2	802.11a	140	5700	6Mbps	-	-
Mode 20	U-NII-2C	Straddle Channel	2	802.11a	144	5720	6Mbps	-	-
Mode 21	U-NII-2C	5.47-5.725	2	802.11a	116	5580	6Mbps	-	LF
Mode 22	U-NII-2C	5.47-5.725	2	802.11a	116	5580	6Mbps	-	SHF

**<Ant. 1+2>**

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 23	U-NII-1	5.15-5.25	1+2	802.11n HT20	36	5180	MCS0	-	-
Mode 24	U-NII-1	5.15-5.25	1+2	802.11n HT20	44	5220	MCS0	-	-
Mode 25	U-NII-1	5.15-5.25	1+2	802.11n HT20	48	5240	MCS0	-	-
Mode 26	U-NII-1	5.15-5.25	1+2	802.11n HT40	38	5190	MCS0	-	-
Mode 27	U-NII-1	5.15-5.25	1+2	802.11n HT40	46	5230	MCS0	-	-
Mode 28	U-NII-1	5.15-5.25	1+2	802.11ac VHT80	42	5210	MCS0	-	-
Mode 29	U-NII-2A	5.25-5.35	1+2	802.11n HT20	52	5260	MCS0	-	-
Mode 30	U-NII-2A	5.25-5.35	1+2	802.11n HT20	60	5300	MCS0	-	-
Mode 31	U-NII-2A	5.25-5.35	1+2	802.11n HT20	64	5320	MCS0	-	-
Mode 32	U-NII-2A	5.25-5.35	1+2	802.11n HT40	54	5270	MCS0	-	-
Mode 33	U-NII-2A	5.25-5.35	1+2	802.11n HT40	62	5310	MCS0	-	-
Mode 34	U-NII-2A	5.25-5.35	1+2	802.11ac VHT80	58	5290	MCS0	-	-
Mode 35	U-NII-2C	5.47-5.725	1+2	802.11n HT20	100	5500	MCS0	-	-
Mode 36	U-NII-2C	5.47-5.725	1+2	802.11n HT20	116	5580	MCS0	-	-
Mode 37	U-NII-2C	5.47-5.725	1+2	802.11n HT20	140	5700	MCS0	-	-
Mode 38	U-NII-2C	Straddle Channel	1+2	802.11n HT20	144	5720	MCS0	-	-
Mode 39	U-NII-2C	5.47-5.725	1+2	802.11n HT40	102	5510	MCS0	-	-
Mode 40	U-NII-2C	5.47-5.725	1+2	802.11n HT40	110	5550	MCS0	-	-
Mode 41	U-NII-2C	5.47-5.725	1+2	802.11n HT40	134	5670	MCS0	-	-
Mode 42	U-NII-2C	Straddle Channel	1+2	802.11n HT40	142	5710	MCS0	-	-
Mode 43	U-NII-2C	5.47-5.725	1+2	802.11ac VHT80	106	5530	MCS0	-	-
Mode 44	U-NII-2C	5.47-5.725	1+2	802.11ac VHT80	122	5610	MCS0	-	-
Mode 45	U-NII-2C	Straddle Channel	1+2	802.11ac VHT80	138	5690	MCS0	-	-
Mode 46	U-NII-2C	5.47-5.725	1+2	802.11n HT20	116	5580	MCS0	-	LF
Mode 47	U-NII-2C	5.47-5.725	1+2	802.11n HT20	116	5580	MCS0	-	SHF

C2. Summary of each worse mode

<Ant. 1>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	802.11a	36	5149.94	53.30	54.00	-0.70	V	Avg.	Pass	-	Band Edge
	802.11a	36	15540.00	50.17	54.00	-3.83	V	Avg.	Pass	-	Harmonic
2	802.11a	44	5138.60	46.26	54.00	-7.74	V	Avg.	Pass	-	Band Edge
	802.11a	44	15660.00	53.24	54.00	-0.76	V	Avg.	Pass	-	Harmonic
3	802.11a	48	5081.84	45.45	54.00	-8.55	V	Avg.	Pass	-	Band Edge
	802.11a	48	15720.00	52.80	54.00	-1.20	V	Avg.	Pass	-	Harmonic
4	802.11a	52	5102.96	45.51	54.00	-8.49	V	Avg.	Pass	-	Band Edge
	802.11a	52	15780.00	53.10	54.00	-0.90	H	Avg.	Pass	-	Harmonic
5	802.11a	60	5378.88	47.55	54.00	-6.45	V	Avg.	Pass	-	Band Edge
	802.11a	60	15900.00	52.73	54.00	-1.27	V	Avg.	Pass	-	Harmonic
6	802.11a	64	5350.38	53.30	54.00	-0.70	V	Avg.	Pass	-	Band Edge
	802.11a	64	15960.00	49.34	54.00	-4.66	V	Avg.	Pass	-	Harmonic
7	802.11a	100	5467.30	66.14	68.20	-2.06	V	Peak	Pass	-	Band Edge
	802.11a	100	16500.00	50.92	54.00	-3.08	H	Avg.	Pass	-	Harmonic
8	802.11a	116	5454.65	44.30	54.00	-9.70	V	Avg.	Pass	-	Band Edge
	802.11a	116	11160.00	53.09	54.00	-0.91	V	Avg.	Pass	-	Harmonic
9	802.11a	140	5726.52	66.72	68.20	-1.48	V	Peak	Pass	-	Band Edge
	802.11a	140	11400.00	45.23	54.00	-8.77	V	Avg.	Pass	-	Harmonic
10	802.11a	144	5454.52	42.34	54.00	-11.66	V	Avg.	Pass	-	Band Edge
	802.11a	144	17160.00	67.21	68.20	-0.99	V	Peak	Pass	-	Harmonic



<Ant. 2>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
11	802.11a	36	5149.94	53.26	54.00	-0.74	V	Avg.	Pass	-	Band Edge
	802.11a	36	15540.00	50.34	54.00	-3.66	V	Avg.	Pass	-	Harmonic
12	802.11a	44	5142.12	47.60	54.00	-6.40	V	Avg.	Pass	-	Band Edge
	802.11a	44	15660.00	52.93	54.00	-1.07	V	Avg.	Pass	-	Harmonic
13	802.11a	48	5146.16	45.34	54.00	-8.66	V	Avg.	Pass	-	Band Edge
	802.11a	48	15720.00	53.08	54.00	-0.92	V	Avg.	Pass	-	Harmonic
14	802.11a	52	5098.28	45.35	54.00	-8.65	V	Avg.	Pass	-	Band Edge
	802.11a	52	15780.00	52.79	54.00	-1.21	V	Avg.	Pass	-	Harmonic
15	802.11a	60	5376.32	46.96	54.00	-7.04	V	Avg.	Pass	-	Band Edge
	802.11a	60	15900.00	52.87	54.00	-1.13	V	Avg.	Pass	-	Harmonic
16	802.11a	64	5350.24	48.15	54.00	-5.85	V	Avg.	Pass	-	Band Edge
	802.11a	64	15960.00	53.31	54.00	-0.69	V	Avg.	Pass	-	Harmonic
17	802.11a	100	5468.50	62.11	68.20	-6.09	V	Peak	Pass	-	Band Edge
	802.11a	100	16500.00	67.50	68.20	-0.70	H	Peak	Pass	-	Harmonic
18	802.11a	116	5421.53	44.89	54.00	-9.11	V	Avg.	Pass	-	Band Edge
	802.11a	116	11160.00	53.36	54.00	-0.64	H	Avg.	Pass	-	Harmonic
19	802.11a	140	5725.48	65.59	68.20	-2.61	V	Peak	Pass	-	Band Edge
	802.11a	140	11400.00	53.13	54.00	-0.87	V	Avg.	Pass	-	Harmonic
20	802.11a	144	5440.09	42.44	54.00	-11.56	V	Avg.	Pass	-	Band Edge
	802.11a	144	11440.00	53.14	54.00	-0.86	V	Avg.	Pass	-	Harmonic
21	WLAN Tx LF	116	716.76	39.24	46.00	-6.76	V	Peak	Pass	-	LF
22	WLAN Tx SHF	116	38504.00	48.04	68.20	-20.16	V	Peak	Pass	-	SHF

**<Ant. 1+2>**





Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
23	802.11n HT20	36	5149.94	49.70	54.00	-4.30	V	Avg.	Pass	-	Band Edge
	802.11n HT20	36	15540.00	52.90	54.00	-1.10	V	Avg.	Pass	-	Harmonic
24	802.11n HT20	44	5139.04	49.55	54.00	-4.45	V	Avg.	Pass	-	Band Edge
	802.11n HT20	44	15660.00	53.30	54.00	-0.70	V	Avg.	Pass	-	Harmonic
25	802.11n HT20	48	5081.12	45.93	54.00	-8.07	V	Avg.	Pass	-	Band Edge
	802.11n HT20	48	15720.00	52.70	54.00	-1.30	V	Avg.	Pass	-	Harmonic
26	802.11n HT40	38	5149.34	53.24	54.00	-0.76	V	Avg.	Pass	-	Band Edge
	802.11n HT40	38	15570.00	46.68	54.00	-7.32	V	Avg.	Pass	-	Harmonic
27	802.11n HT40	46	5149.04	52.54	54.00	-1.46	V	Avg.	Pass	-	Band Edge
	802.11n HT40	46	15690.00	53.17	54.00	-0.83	V	Avg.	Pass	-	Harmonic
28	802.11ac VHT80	42	5149.94	53.24	54.00	-0.76	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	42	15630.00	45.80	54.00	-8.20	V	Avg.	Pass	-	Harmonic
29	802.11n HT20	52	5354.20	45.86	54.00	-8.14	V	Avg.	Pass	-	Band Edge
	802.11n HT20	52	15780.00	52.71	54.00	-1.29	H	Avg.	Pass	-	Harmonic
30	802.11n HT20	60	5378.88	50.35	54.00	-3.65	V	Avg.	Pass	-	Band Edge
	802.11n HT20	60	15900.00	52.78	54.00	-1.22	V	Avg.	Pass	-	Harmonic
31	802.11n HT20	64	5363.26	52.10	54.00	-1.90	V	Avg.	Pass	-	Band Edge
	802.11n HT20	64	15960.00	53.35	54.00	-0.65	V	Avg.	Pass	-	Harmonic
32	802.11n HT40	54	5351.89	52.15	54.00	-1.85	V	Avg.	Pass	-	Band Edge
	802.11n HT40	54	15810.00	53.09	54.00	-0.91	V	Avg.	Pass	-	Harmonic
33	802.11n HT40	62	5350.80	53.10	54.00	-0.90	V	Avg.	Pass	-	Band Edge
	802.11n HT40	62	15930.00	45.96	54.00	-8.04	V	Avg.	Pass	-	Harmonic
34	802.11ac VHT80	58	5354.60	52.98	54.00	-1.02	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	58	15870.00	46.70	54.00	-7.30	V	Avg.	Pass	-	Harmonic
35	802.11n HT20	100	5452.60	52.64	54.00	-1.36	V	Avg.	Pass	-	Band Edge
	802.11n HT20	100	11000.00	53.31	54.00	-0.69	H	Avg.	Pass	-	Harmonic
36	802.11n HT20	116	5415.78	47.03	54.00	-6.97	V	Avg.	Pass	-	Band Edge
	802.11n HT20	116	11160.00	53.47	54.00	-0.53	V	Avg.	Pass	-	Harmonic
37	802.11n HT20	140	5726.26	67.03	68.20	-1.17	V	Peak	Pass	-	Band Edge
	802.11n HT20	140	11400.00	52.27	54.00	-1.73	V	Avg.	Pass	-	Harmonic



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
38	802.11n HT20	144	5459.59	42.54	54.00	-11.46	V	Avg.	Pass	-	Band Edge
	802.11n HT20	144	11440.00	53.38	54.00	-0.62	V	Avg.	Pass	-	Harmonic
39	802.11n HT40	102	5459.60	52.13	54.00	-1.87	V	Avg.	Pass	-	Band Edge
	802.11n HT40	102	11020.00	50.39	54.00	-3.61	H	Avg.	Pass	-	Harmonic
40	802.11n HT40	110	5459.80	48.44	54.00	-5.56	V	Avg.	Pass	-	Band Edge
	802.11n HT40	110	11100.00	53.33	54.00	-0.67	H	Avg.	Pass	-	Harmonic
41	802.11n HT40	134	5725.96	67.06	68.20	-1.14	V	Peak	Pass	-	Band Edge
	802.11n HT40	134	11340.00	52.26	54.00	-1.74	H	Avg.	Pass	-	Harmonic
42	802.11n HT40	142	5442.43	43.52	54.00	-10.48	V	Avg.	Pass	-	Band Edge
	802.11n HT40	142	11420.00	53.04	54.00	-0.96	V	Avg.	Pass	-	Harmonic
43	802.11ac VHT80	106	5438.56	52.43	54.00	-1.57	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	106	11060.00	48.52	54.00	-5.48	H	Avg.	Pass	-	Harmonic
44	802.11ac VHT80	122	5456.08	52.36	54.00	-1.64	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	122	11220.00	53.07	54.00	-0.93	H	Avg.	Pass	-	Harmonic
45	802.11ac VHT80	138	5458.81	46.90	54.00	-7.10	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	138	11380.00	53.36	54.00	-0.64	V	Avg.	Pass	-	Harmonic
46	WLAN Tx LF	116	958.29	33.59	46.00	-12.41	V	Peak	Pass	-	LF
47	WLAN Tx SHF	116	39371.85	46.62	74.00	-27.38	H	Peak	Pass	-	SHF





<Ant. 1>

Mode	1																																																																																	
	Band Edge																																																																																	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz																																																																																	
ANT	1																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	 Site : 83CH3-HY Condition: PEAK_BE_74 3e DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5149.84</td><td>55.23</td><td>74.00</td><td>-18.77</td><td>42.40</td><td>32.60</td><td>18.44</td><td>33.21</td><td>4.00</td><td>360 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5149.84	55.23	74.00	-18.77	42.40	32.60	18.44	33.21	4.00	360 PEAK	 Site : 83CH3-HY Condition: PEAK(UNI) 3e DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5180.00</td><td>56.61</td><td>70.00</td><td>-13.39</td><td>54.81</td><td>32.60</td><td>18.43</td><td>33.25</td><td>4.02</td><td>360 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5180.00	56.61	70.00	-13.39	54.81	32.60	18.43	33.25	4.02	360 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																									
1 5149.84	55.23	74.00	-18.77	42.40	32.60	18.44	33.21	4.00	360 PEAK																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																									
1 5180.00	56.61	70.00	-13.39	54.81	32.60	18.43	33.25	4.02	360 PEAK																																																																									
Avg	 Site : 83CH3-HY Condition: AVG_BE_54 3e DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:9.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5149.84</td><td>44.80</td><td>54.00</td><td>-9.12</td><td>31.05</td><td>32.60</td><td>18.44</td><td>33.21</td><td>4.00</td><td>360 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5149.84	44.80	54.00	-9.12	31.05	32.60	18.44	33.21	4.00	360 AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3e DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:9.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5180.00</td><td>52.93</td><td>70.00</td><td>-17.07</td><td>79.14</td><td>32.60</td><td>18.43</td><td>33.26</td><td>4.02</td><td>360 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5180.00	52.93	70.00	-17.07	79.14	32.60	18.43	33.26	4.02	360 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																									
1 5149.84	44.80	54.00	-9.12	31.05	32.60	18.44	33.21	4.00	360 AVERAGE																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																									
1 5180.00	52.93	70.00	-17.07	79.14	32.60	18.43	33.26	4.02	360 AVERAGE																																																																									





Mode	1																																																																																									
	Band Edge																																																																																									
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical	Fundamental																																																																																								
Peak	Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5149.84</td><td>65.81</td><td>74.00</td><td>-8.19</td><td>51.80</td><td>32.68</td><td>18.44</td><td>33.21</td><td>4.00</td><td>230</td><td>284</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5149.84	65.81	74.00	-8.19	51.80	32.68	18.44	33.21	4.00	230	284	PEAK	Site : 83CH3-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5180.00</td><td>112.84</td><td>-----</td><td>-----</td><td>90.24</td><td>32.68</td><td>18.43</td><td>33.25</td><td>4.02</td><td>230</td><td>284</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5180.00	112.84	-----	-----	90.24	32.68	18.43	33.25	4.02	230	284	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																
1	5149.84	65.81	74.00	-8.19	51.80	32.68	18.44	33.21	4.00	230	284	PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																
1	5180.00	112.84	-----	-----	90.24	32.68	18.43	33.25	4.02	230	284	PEAK																																																																														
Avg	Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5149.84</td><td>53.30</td><td>54.00</td><td>-0.70</td><td>39.47</td><td>32.68</td><td>18.44</td><td>33.21</td><td>4.00</td><td>230</td><td>284</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5149.84	53.30	54.00	-0.70	39.47	32.68	18.44	33.21	4.00	230	284	AVERAGE	Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5180.00</td><td>105.13</td><td>-----</td><td>-----</td><td>91.34</td><td>32.68</td><td>18.43</td><td>33.26</td><td>4.02</td><td>230</td><td>284</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5180.00	105.13	-----	-----	91.34	32.68	18.43	33.26	4.02	230	284	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																
1	5149.84	53.30	54.00	-0.70	39.47	32.68	18.44	33.21	4.00	230	284	AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																
1	5180.00	105.13	-----	-----	91.34	32.68	18.43	33.26	4.02	230	284	AVERAGE																																																																														



Mode	1																																																																																																																																							
	Harmonic																																																																																																																																							
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz																																																																																																																																							
ANT	1																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																						
Peak Avg	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_238712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 18368.00</td><td>49.96</td><td>68.28</td><td>-18.24</td><td>34.32</td><td>37.46</td><td>14.76</td><td>38.71</td><td>2.13</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 15548.00</td><td>58.92</td><td>74.00</td><td>-15.08</td><td>42.18</td><td>48.44</td><td>18.18</td><td>44.49</td><td>2.77</td><td>183</td><td>193</td><td>PEAK</td></tr><tr><td>3 15548.00</td><td>49.32</td><td>54.00</td><td>-4.68</td><td>32.58</td><td>48.44</td><td>18.18</td><td>44.49</td><td>2.77</td><td>183</td><td>193</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1 18368.00	49.96	68.28	-18.24	34.32	37.46	14.76	38.71	2.13	--	--	PEAK	2 15548.00	58.92	74.00	-15.08	42.18	48.44	18.18	44.49	2.77	183	193	PEAK	3 15548.00	49.32	54.00	-4.68	32.58	48.44	18.18	44.49	2.77	183	193	AVERAGE	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_238712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 18368.00</td><td>52.26</td><td>68.28</td><td>-15.94</td><td>36.62</td><td>37.46</td><td>14.76</td><td>38.71</td><td>2.13</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 15548.00</td><td>59.48</td><td>74.00</td><td>-14.52</td><td>42.66</td><td>48.44</td><td>18.18</td><td>44.49</td><td>2.77</td><td>217</td><td>387</td><td>PEAK</td></tr><tr><td>3 15548.00</td><td>58.17</td><td>54.00</td><td>-3.83</td><td>33.35</td><td>48.44</td><td>18.18</td><td>44.49</td><td>2.77</td><td>217</td><td>387</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1 18368.00	52.26	68.28	-15.94	36.62	37.46	14.76	38.71	2.13	--	--	PEAK	2 15548.00	59.48	74.00	-14.52	42.66	48.44	18.18	44.49	2.77	217	387	PEAK	3 15548.00	58.17	54.00	-3.83	33.35	48.44	18.18	44.49	2.77	217	387	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1 18368.00	49.96	68.28	-18.24	34.32	37.46	14.76	38.71	2.13	--	--	PEAK																																																																																																																													
2 15548.00	58.92	74.00	-15.08	42.18	48.44	18.18	44.49	2.77	183	193	PEAK																																																																																																																													
3 15548.00	49.32	54.00	-4.68	32.58	48.44	18.18	44.49	2.77	183	193	AVERAGE																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1 18368.00	52.26	68.28	-15.94	36.62	37.46	14.76	38.71	2.13	--	--	PEAK																																																																																																																													
2 15548.00	59.48	74.00	-14.52	42.66	48.44	18.18	44.49	2.77	217	387	PEAK																																																																																																																													
3 15548.00	58.17	54.00	-3.83	33.35	48.44	18.18	44.49	2.77	217	387	AVERAGE																																																																																																																													





Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 HORIZONTAL	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 VERTICAL







Mode	2																																																																																							
	Band Edge - L																																																																																							
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz																																																																																							
ANT	1																																																																																							
Pol.	Horizontal	Fundamental																																																																																						
Peak	Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5005.32</td><td>52.99</td><td>74.00</td><td>-21.01</td><td>18.94</td><td>32.70</td><td>18.46</td><td>32.98</td><td>3.87</td><td>400</td><td>53 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5005.32	52.99	74.00	-21.01	18.94	32.70	18.46	32.98	3.87	400	53 PEAK	Site : 83CH3-HY Condition: PEAK(UH1) 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5220.00</td><td>94.82</td><td>-----</td><td>-----</td><td>88.99</td><td>32.60</td><td>18.50</td><td>33.31</td><td>4.04</td><td>400</td><td>53 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5220.00	94.82	-----	-----	88.99	32.60	18.50	33.31	4.04	400	53 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																														
1	5005.32	52.99	74.00	-21.01	18.94	32.70	18.46	32.98	3.87	400	53 PEAK																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																														
1	5220.00	94.82	-----	-----	88.99	32.60	18.50	33.31	4.04	400	53 PEAK																																																																													
Avg	Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5045.90</td><td>43.44</td><td>54.00</td><td>-10.56</td><td>29.43</td><td>32.70</td><td>18.45</td><td>33.05</td><td>3.91</td><td>400</td><td>53 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5045.90	43.44	54.00	-10.56	29.43	32.70	18.45	33.05	3.91	400	53 AVERAGE	Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5220.00</td><td>88.48</td><td>-----</td><td>-----</td><td>74.63</td><td>32.60</td><td>18.52</td><td>33.32</td><td>4.05</td><td>400</td><td>53 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5220.00	88.48	-----	-----	74.63	32.60	18.52	33.32	4.05	400	53 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																														
1	5045.90	43.44	54.00	-10.56	29.43	32.70	18.45	33.05	3.91	400	53 AVERAGE																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																		
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																														
1	5220.00	88.48	-----	-----	74.63	32.60	18.52	33.32	4.05	400	53 AVERAGE																																																																													





Mode	2																																												
	Band Edge - R																																												
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz																																												
ANT	1																																												
Pol.	Horizontal	Fundamental																																											
Peak	 Site : 80CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5442.48</td><td>51.49</td><td>74.00</td><td>-22.51</td><td>37.17</td><td>32.67</td><td>11.20</td><td>33.65</td><td>4.10</td><td>400</td><td>53 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBV/m	dBV/m	dB	dBV/m	dB	dB	dB	cm	deg	1	5442.48	51.49	74.00	-22.51	37.17	32.67	11.20	33.65	4.10	400	53 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																				
	MHz	dBV/m	dBV/m	dB	dBV/m	dB	dB	dB	cm	deg																																			
1	5442.48	51.49	74.00	-22.51	37.17	32.67	11.20	33.65	4.10	400	53 PEAK																																		
Avg	 Site : 80CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1800.000kHz VBW:0.750kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5440.56</td><td>42.16</td><td>54.00</td><td>-11.84</td><td>27.05</td><td>32.66</td><td>11.20</td><td>33.65</td><td>4.10</td><td>400</td><td>53 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBV/m	dBV/m	dB	dBV/m	dB	dB	dB	cm	deg	1	5440.56	42.16	54.00	-11.84	27.05	32.66	11.20	33.65	4.10	400	53 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																				
	MHz	dBV/m	dBV/m	dB	dBV/m	dB	dB	dB	cm	deg																																			
1	5440.56	42.16	54.00	-11.84	27.05	32.66	11.20	33.65	4.10	400	53 AVERAGE																																		





		2																																																																																										
Mode	Band Edge - L																																																																																											
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz																																																																																											
ANT	1																																																																																											
Pol.	Vertical						Fundamental																																																																																					
Peak																																																																																												
	Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5135.96</td><td>55.22</td><td>74.00</td><td>-18.78</td><td>43.35</td><td>32.63</td><td>18.44</td><td>33.19</td><td>3.99</td><td>200</td><td>351 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1	5135.96	55.22	74.00	-18.78	43.35	32.63	18.44	33.19	3.99	200	351 PEAK	Site : 83CH3-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5220.00</td><td>113.38</td><td>-----</td><td>-----</td><td>99.45</td><td>32.68</td><td>18.52</td><td>33.32</td><td>4.85</td><td>200</td><td>351 PEAK</td></tr></tbody></table>					Limit	Read	Ant	Cable	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1	5220.00	113.38	-----	-----	99.45	32.68	18.52	33.32	4.85	200
Limit	Read	Ant	Cable	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	5135.96	55.22	74.00	-18.78	43.35	32.63	18.44	33.19	3.99	200	351 PEAK																																																																																	
Limit	Read	Ant	Cable	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	5220.00	113.38	-----	-----	99.45	32.68	18.52	33.32	4.85	200	351 PEAK																																																																																	
Avg																																																																																												
	Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5138.68</td><td>46.26</td><td>54.00</td><td>-7.74</td><td>32.48</td><td>32.62</td><td>18.44</td><td>33.19</td><td>3.99</td><td>200</td><td>351 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1	5138.68	46.26	54.00	-7.74	32.48	32.62	18.44	33.19	3.99	200	351 AVERAGE	Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5220.00</td><td>187.38</td><td>-----</td><td>-----</td><td>93.45</td><td>32.68</td><td>18.52</td><td>33.32</td><td>4.85</td><td>200</td><td>351 AVERAGE</td></tr></tbody></table>					Limit	Read	Ant	Cable	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1	5220.00	187.38	-----	-----	93.45	32.68	18.52	33.32	4.85	200
Limit	Read	Ant	Cable	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	5138.68	46.26	54.00	-7.74	32.48	32.62	18.44	33.19	3.99	200	351 AVERAGE																																																																																	
Limit	Read	Ant	Cable	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																																																																		
1	5220.00	187.38	-----	-----	93.45	32.68	18.52	33.32	4.85	200	351 AVERAGE																																																																																	





Mode	2																																												
	Band Edge - R																																												
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz																																												
ANT	1																																												
Pol.	Vertical	Fundamental																																											
Peak	 Site : 80CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:3000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5307.04</td><td>53.24</td><td>74.00</td><td>-20.76</td><td>39.00</td><td>32.50</td><td>11.14</td><td>33.57</td><td>4.09</td><td>200</td><td>351</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5307.04	53.24	74.00	-20.76	39.00	32.50	11.14	33.57	4.09	200	351	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																				
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																				
1	5307.04	53.24	74.00	-20.76	39.00	32.50	11.14	33.57	4.09	200	351	PEAK																																	
Avg	 Site : 80CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:3000.000kHz VBW:8.750kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5308.56</td><td>44.63</td><td>54.00</td><td>-9.37</td><td>38.40</td><td>32.50</td><td>11.12</td><td>33.56</td><td>4.09</td><td>200</td><td>351</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5308.56	44.63	54.00	-9.37	38.40	32.50	11.12	33.56	4.09	200	351	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																				
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																				
1	5308.56	44.63	54.00	-9.37	38.40	32.50	11.12	33.56	4.09	200	351	AVERAGE																																	







Mode	2																																																																																																																									
	Harmonic																																																																																																																									
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_238712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 10440.00</td><td>55.36</td><td>60.20</td><td>-12.04</td><td>40.87</td><td>37.14</td><td>14.81</td><td>30.00</td><td>2.14</td><td>-- -- Peak</td></tr><tr><td>2 15660.00</td><td>59.74</td><td>74.00</td><td>-14.26</td><td>43.12</td><td>40.34</td><td>18.14</td><td>44.66</td><td>2.00</td><td>100 215 PEAK</td></tr><tr><td>3 15660.00</td><td>49.96</td><td>54.00</td><td>-4.04</td><td>33.34</td><td>40.34</td><td>18.14</td><td>44.66</td><td>2.00</td><td>100 215 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 10440.00	55.36	60.20	-12.04	40.87	37.14	14.81	30.00	2.14	-- -- Peak	2 15660.00	59.74	74.00	-14.26	43.12	40.34	18.14	44.66	2.00	100 215 PEAK	3 15660.00	49.96	54.00	-4.04	33.34	40.34	18.14	44.66	2.00	100 215 AVERAGE	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_238712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 10440.00</td><td>57.24</td><td>60.20</td><td>-10.96</td><td>41.95</td><td>37.14</td><td>14.81</td><td>30.00</td><td>2.14</td><td>-- -- Peak</td></tr><tr><td>2 15660.00</td><td>63.30</td><td>74.00</td><td>-10.70</td><td>46.68</td><td>40.34</td><td>18.14</td><td>44.66</td><td>2.00</td><td>200 300 PEAK</td></tr><tr><td>3 15660.00</td><td>53.24</td><td>54.00</td><td>-0.76</td><td>36.62</td><td>40.34</td><td>18.14</td><td>44.66</td><td>2.00</td><td>200 300 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 10440.00	57.24	60.20	-10.96	41.95	37.14	14.81	30.00	2.14	-- -- Peak	2 15660.00	63.30	74.00	-10.70	46.68	40.34	18.14	44.66	2.00	200 300 PEAK	3 15660.00	53.24	54.00	-0.76	36.62	40.34	18.14	44.66	2.00	200 300 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																																	
1 10440.00	55.36	60.20	-12.04	40.87	37.14	14.81	30.00	2.14	-- -- Peak																																																																																																																	
2 15660.00	59.74	74.00	-14.26	43.12	40.34	18.14	44.66	2.00	100 215 PEAK																																																																																																																	
3 15660.00	49.96	54.00	-4.04	33.34	40.34	18.14	44.66	2.00	100 215 AVERAGE																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																																	
1 10440.00	57.24	60.20	-10.96	41.95	37.14	14.81	30.00	2.14	-- -- Peak																																																																																																																	
2 15660.00	63.30	74.00	-10.70	46.68	40.34	18.14	44.66	2.00	200 300 PEAK																																																																																																																	
3 15660.00	53.24	54.00	-0.76	36.62	40.34	18.14	44.66	2.00	200 300 AVERAGE																																																																																																																	





Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 HORIZONTAL	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 VERTICAL







		3																																																																								
Mode	Band Edge - L																																																																									
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz																																																																									
ANT	1																																																																									
Pol.	Horizontal	Fundamental																																																																								
Peak	 Site : 83CH03-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5126.96</td><td>52.91</td><td>74.00</td><td>-21.09</td><td>39.81</td><td>32.65</td><td>18.44</td><td>33.17</td><td>3.98</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5126.96	52.91	74.00	-21.09	39.81	32.65	18.44	33.17	3.98	 Site : 83CH03-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5248.00</td><td>54.18</td><td>-----</td><td>-----</td><td>88.38</td><td>32.68</td><td>18.57</td><td>33.34</td><td>4.05</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5248.00	54.18	-----	-----	88.38	32.68	18.57	33.34	4.05
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																		
1 5126.96	52.91	74.00	-21.09	39.81	32.65	18.44	33.17	3.98																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																		
1 5248.00	54.18	-----	-----	88.38	32.68	18.57	33.34	4.05																																																																		
Avg	 Site : 83CH03-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5050.00</td><td>43.44</td><td>54.00</td><td>-10.56</td><td>29.44</td><td>32.70</td><td>18.45</td><td>33.06</td><td>3.91</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5050.00	43.44	54.00	-10.56	29.44	32.70	18.45	33.06	3.91	 Site : 83CH03-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5248.00</td><td>87.61</td><td>-----</td><td>-----</td><td>73.73</td><td>32.68</td><td>18.57</td><td>33.34</td><td>4.05</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5248.00	87.61	-----	-----	73.73	32.68	18.57	33.34	4.05
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																		
1 5050.00	43.44	54.00	-10.56	29.44	32.70	18.45	33.06	3.91																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																		
1 5248.00	87.61	-----	-----	73.73	32.68	18.57	33.34	4.05																																																																		





Mode	3																																												
	Band Edge - R																																												
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz																																												
ANT	1																																												
Pol.	Horizontal	Fundamental																																											
Peak	 Site : 80CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5416.20</td><td>58.78</td><td>74.00</td><td>-23.22</td><td>36.54</td><td>32.57</td><td>11.19</td><td>33.62</td><td>4.18</td><td>300</td><td>182 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	cm	deg	1	5416.20	58.78	74.00	-23.22	36.54	32.57	11.19	33.62	4.18	300	182 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																				
	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	cm	deg																																			
1	5416.20	58.78	74.00	-23.22	36.54	32.57	11.19	33.62	4.18	300	182 PEAK																																		
Avg	 Site : 80CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5416.76</td><td>42.33</td><td>54.00</td><td>-11.77</td><td>27.92</td><td>32.66</td><td>11.20</td><td>33.65</td><td>4.18</td><td>300</td><td>182 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	cm	deg	1	5416.76	42.33	54.00	-11.77	27.92	32.66	11.20	33.65	4.18	300	182 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																				
	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	cm	deg																																			
1	5416.76	42.33	54.00	-11.77	27.92	32.66	11.20	33.65	4.18	300	182 AVERAGE																																		





Mode	3																																																																																									
	Band Edge - L																																																																																									
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical	Fundamental																																																																																								
Peak	 Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5081.36</td><td>54.87</td><td>74.00</td><td>-19.93</td><td>48.00</td><td>32.70</td><td>18.45</td><td>33.10</td><td>3.94</td><td>200</td><td>129</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5081.36	54.87	74.00	-19.93	48.00	32.70	18.45	33.10	3.94	200	129	PEAK	 Site : 83CH3-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5248.00</td><td>114.22</td><td>-----</td><td>-----</td><td>100.33</td><td>32.60</td><td>10.59</td><td>33.35</td><td>4.05</td><td>200</td><td>129</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5248.00	114.22	-----	-----	100.33	32.60	10.59	33.35	4.05	200	129	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	5081.36	54.87	74.00	-19.93	48.00	32.70	18.45	33.10	3.94	200	129	PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	5248.00	114.22	-----	-----	100.33	32.60	10.59	33.35	4.05	200	129	PEAK																																																																														
Avg	 Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5081.04</td><td>45.45</td><td>54.00</td><td>-8.55</td><td>31.46</td><td>32.70</td><td>18.45</td><td>33.10</td><td>3.94</td><td>200</td><td>129</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5081.04	45.45	54.00	-8.55	31.46	32.70	18.45	33.10	3.94	200	129	AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5248.00</td><td>107.03</td><td>-----</td><td>-----</td><td>93.94</td><td>32.60</td><td>10.59</td><td>33.35</td><td>4.05</td><td>200</td><td>129</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5248.00	107.03	-----	-----	93.94	32.60	10.59	33.35	4.05	200	129	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	5081.04	45.45	54.00	-8.55	31.46	32.70	18.45	33.10	3.94	200	129	AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	5248.00	107.03	-----	-----	93.94	32.60	10.59	33.35	4.05	200	129	AVERAGE																																																																														





Mode	3																																									
	Band Edge - R																																									
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz																																									
ANT	1																																									
Pol.	Vertical	Fundamental																																								
Peak	 Site : 89CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SUT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5485.00</td><td>55.18</td><td>74.00</td><td>-18.82</td><td>40.90</td><td>32.52</td><td>11.19</td><td>33.60</td><td>4.09 200 129 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm deg	1	5485.00	55.18	74.00	-18.82	40.90	32.52	11.19	33.60	4.09 200 129 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																	
MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm deg																																	
1	5485.00	55.18	74.00	-18.82	40.90	32.52	11.19	33.60	4.09 200 129 PEAK																																	
Avg	 Site : 89CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1800.000kHz VBW:0.750kHz SUT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5399.28</td><td>44.77</td><td>54.00</td><td>-9.23</td><td>30.50</td><td>32.50</td><td>11.19</td><td>33.59</td><td>4.09 200 129 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm deg	1	5399.28	44.77	54.00	-9.23	30.50	32.50	11.19	33.59	4.09 200 129 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																	
MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm deg																																	
1	5399.28	44.77	54.00	-9.23	30.50	32.50	11.19	33.59	4.09 200 129 AVERAGE																																	



Mode	3																																																																																																																																													
	Harmonic																																																																																																																																													
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz																																																																																																																																													
ANT	1																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																												
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>10400.00</td><td>58.92</td><td>68.20</td><td>-9.28</td><td>43.69</td><td>37.10</td><td>14.83</td><td>38.84</td><td>2.14</td><td>200</td><td>131</td><td>PEAK</td></tr><tr><td>2</td><td>15720.00</td><td>59.85</td><td>74.00</td><td>-14.15</td><td>43.01</td><td>40.62</td><td>18.16</td><td>44.75</td><td>2.81</td><td>100</td><td>215</td><td>PEAK</td></tr><tr><td>3</td><td>15720.00</td><td>50.44</td><td>54.00</td><td>-3.56</td><td>33.60</td><td>40.62</td><td>18.16</td><td>44.75</td><td>2.81</td><td>100</td><td>215</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	10400.00	58.92	68.20	-9.28	43.69	37.10	14.83	38.84	2.14	200	131	PEAK	2	15720.00	59.85	74.00	-14.15	43.01	40.62	18.16	44.75	2.81	100	215	PEAK	3	15720.00	50.44	54.00	-3.56	33.60	40.62	18.16	44.75	2.81	100	215	AVERAGE	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>10400.00</td><td>59.04</td><td>68.20</td><td>-8.36</td><td>44.61</td><td>37.10</td><td>14.83</td><td>38.84</td><td>2.14</td><td>300</td><td>22</td><td>PEAK</td></tr><tr><td>2</td><td>15720.00</td><td>61.64</td><td>74.00</td><td>-12.36</td><td>44.80</td><td>40.62</td><td>18.16</td><td>44.75</td><td>2.81</td><td>200</td><td>308</td><td>PEAK</td></tr><tr><td>3</td><td>15720.00</td><td>52.80</td><td>54.00</td><td>-1.20</td><td>35.96</td><td>40.62</td><td>18.16</td><td>44.75</td><td>2.81</td><td>200</td><td>308</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	10400.00	59.04	68.20	-8.36	44.61	37.10	14.83	38.84	2.14	300	22	PEAK	2	15720.00	61.64	74.00	-12.36	44.80	40.62	18.16	44.75	2.81	200	308	PEAK	3	15720.00	52.80	54.00	-1.20	35.96	40.62	18.16	44.75	2.81	200	308	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																				
1	10400.00	58.92	68.20	-9.28	43.69	37.10	14.83	38.84	2.14	200	131	PEAK																																																																																																																																		
2	15720.00	59.85	74.00	-14.15	43.01	40.62	18.16	44.75	2.81	100	215	PEAK																																																																																																																																		
3	15720.00	50.44	54.00	-3.56	33.60	40.62	18.16	44.75	2.81	100	215	AVERAGE																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																				
1	10400.00	59.04	68.20	-8.36	44.61	37.10	14.83	38.84	2.14	300	22	PEAK																																																																																																																																		
2	15720.00	61.64	74.00	-12.36	44.80	40.62	18.16	44.75	2.81	200	308	PEAK																																																																																																																																		
3	15720.00	52.80	54.00	-1.20	35.96	40.62	18.16	44.75	2.81	200	308	AVERAGE																																																																																																																																		





Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 VERTICAL







Mode	4																																																																																																													
	Band Edge - L																																																																																																													
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz																																																																																																													
ANT	1																																																																																																													
Pol.	Horizontal	Fundamental																																																																																																												
Peak	Site : 83CH03-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5099.58</td><td>52.75</td><td>74.00</td><td>-21.25</td><td>38.78</td><td>32.70</td><td>18.45</td><td>33.13</td><td>3.95</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>200</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>215 PEAK</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5099.58	52.75	74.00	-21.25	38.78	32.70	18.45	33.13	3.95									200									215 PEAK	Site : 83CH03-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5268.00</td><td>58.22</td><td>-----</td><td>-----</td><td>84.31</td><td>32.58</td><td>18.66</td><td>33.38</td><td>4.85</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>200</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>215 PEAK</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5268.00	58.22	-----	-----	84.31	32.58	18.66	33.38	4.85									200									215 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																																																						
1 5099.58	52.75	74.00	-21.25	38.78	32.70	18.45	33.13	3.95																																																																																																						
								200																																																																																																						
								215 PEAK																																																																																																						
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																																																						
1 5268.00	58.22	-----	-----	84.31	32.58	18.66	33.38	4.85																																																																																																						
								200																																																																																																						
								215 PEAK																																																																																																						
Avg	Site : 83CH03-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5064.48</td><td>43.47</td><td>54.00</td><td>-10.53</td><td>29.48</td><td>32.70</td><td>18.45</td><td>33.88</td><td>3.92</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>200</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>215 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5064.48	43.47	54.00	-10.53	29.48	32.70	18.45	33.88	3.92									200									215 AVERAGE	Site : 83CH03-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5268.00</td><td>91.45</td><td>-----</td><td>-----</td><td>77.54</td><td>32.58</td><td>18.66</td><td>33.38</td><td>4.85</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>200</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>215 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5268.00	91.45	-----	-----	77.54	32.58	18.66	33.38	4.85									200									215 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																																																						
1 5064.48	43.47	54.00	-10.53	29.48	32.70	18.45	33.88	3.92																																																																																																						
								200																																																																																																						
								215 AVERAGE																																																																																																						
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																																																						
1 5268.00	91.45	-----	-----	77.54	32.58	18.66	33.38	4.85																																																																																																						
								200																																																																																																						
								215 AVERAGE																																																																																																						





Mode	4																																													
	Band Edge - R																																													
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz																																													
ANT	1																																													
Pol.	Horizontal	Fundamental																																												
Peak	 Site : 89CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SUT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5421.48</td><td>51.85</td><td>74.00</td><td>-22.15</td><td>37.59</td><td>32.59</td><td>11.19</td><td>33.62</td><td>4.10</td><td>200</td><td>215 PEAK</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	Remark	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg		1	5421.48	51.85	74.00	-22.15	37.59	32.59	11.19	33.62	4.10	200	215 PEAK	Blank
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	Remark																																			
MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg																																				
1	5421.48	51.85	74.00	-22.15	37.59	32.59	11.19	33.62	4.10	200	215 PEAK																																			
Avg	 Site : 89CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SUT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5457.00</td><td>42.24</td><td>54.00</td><td>-11.76</td><td>27.89</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11</td><td>200</td><td>215 AVERAGE</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	Remark	MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg		1	5457.00	42.24	54.00	-11.76	27.89	32.71	11.20	33.67	4.11	200	215 AVERAGE	Blank
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	Remark																																			
MHz	dBV/m	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg																																				
1	5457.00	42.24	54.00	-11.76	27.89	32.71	11.20	33.67	4.11	200	215 AVERAGE																																			





Mode	4																																																																																	
	Band Edge - L																																																																																	
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz																																																																																	
ANT	1																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	 Site : 83CH3-HY Condition: PEAK_BE_74 3m DRM18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5106.00</td><td>54.43</td><td>74.00</td><td>-19.57</td><td>40.48</td><td>32.69</td><td>10.44</td><td>33.14</td><td>3.96 173 147 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor						MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5106.00	54.43	74.00	-19.57	40.48	32.69	10.44	33.14	3.96 173 147 PEAK	 Site : 83CH3-HY Condition: PEAK(UNI) 3m DRM18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5268.00</td><td>115.57</td><td>-----</td><td>-----</td><td>180.66</td><td>32.58</td><td>10.66</td><td>33.38</td><td>4.05 173 147 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor						MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5268.00	115.57	-----	-----	180.66	32.58	10.66	33.38	4.05 173 147 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																																																									
1	5106.00	54.43	74.00	-19.57	40.48	32.69	10.44	33.14	3.96 173 147 PEAK																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																																																									
1	5268.00	115.57	-----	-----	180.66	32.58	10.66	33.38	4.05 173 147 PEAK																																																																									
Avg	 Site : 83CH3-HY Condition: AVG_BE_54 3m DRM18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5102.90</td><td>45.51</td><td>54.00</td><td>-8.49</td><td>35.56</td><td>32.69</td><td>10.44</td><td>33.14</td><td>3.96 173 147 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor						MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5102.90	45.51	54.00	-8.49	35.56	32.69	10.44	33.14	3.96 173 147 AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3m DRM18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5268.00</td><td>189.01</td><td>-----</td><td>-----</td><td>95.18</td><td>32.58</td><td>10.66</td><td>33.38</td><td>4.05 173 147 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor						MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5268.00	189.01	-----	-----	95.18	32.58	10.66	33.38	4.05 173 147 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																																																									
1	5102.90	45.51	54.00	-8.49	35.56	32.69	10.44	33.14	3.96 173 147 AVERAGE																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																																																									
1	5268.00	189.01	-----	-----	95.18	32.58	10.66	33.38	4.05 173 147 AVERAGE																																																																									





Mode	4																																												
	Band Edge - R																																												
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz																																												
ANT	1																																												
Pol.	Vertical	Fundamental																																											
Peak	 Site : 89CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5422.68</td><td>53.77</td><td>74.00</td><td>-20.23</td><td>39.55</td><td>32.55</td><td>11.19</td><td>33.61</td><td>4.09</td><td>173</td><td>147 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg	1	5422.68	53.77	74.00	-20.23	39.55	32.55	11.19	33.61	4.09	173	147 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																				
	MHz	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg																																			
1	5422.68	53.77	74.00	-20.23	39.55	32.55	11.19	33.61	4.09	173	147 PEAK																																		
Avg	 Site : 89CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dB</th><th>dBV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5429.00</td><td>45.82</td><td>54.00</td><td>-8.90</td><td>38.77</td><td>32.50</td><td>11.19</td><td>33.62</td><td>4.10</td><td>173</td><td>147 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg	1	5429.00	45.82	54.00	-8.90	38.77	32.50	11.19	33.62	4.10	173	147 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																				
	MHz	dBV/m	dB	dBV/m	dB/m	dB	dB	dB	cm	deg																																			
1	5429.00	45.82	54.00	-8.90	38.77	32.50	11.19	33.62	4.10	173	147 AVERAGE																																		





Mode	4																																																																																																																																											
	Harmonic																																																																																																																																											
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz																																																																																																																																											
ANT	1																																																																																																																																											
Pol.	Horizontal	Vertical																																																																																																																																										
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>10520.00</td><td>55.00</td><td>68.20</td><td>-12.40</td><td>40.50</td><td>37.18</td><td>14.86</td><td>38.88</td><td>2.14</td><td>400</td><td>95</td><td>PEAK</td></tr><tr><td>2</td><td>15780.00</td><td>60.91</td><td>74.00</td><td>-13.09</td><td>43.99</td><td>40.74</td><td>18.19</td><td>44.83</td><td>2.82</td><td>100</td><td>216</td><td>PEAK</td></tr><tr><td>3</td><td>15780.00</td><td>53.10</td><td>54.00</td><td>-0.90</td><td>36.18</td><td>40.74</td><td>18.19</td><td>44.83</td><td>2.82</td><td>100</td><td>216</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	10520.00	55.00	68.20	-12.40	40.50	37.18	14.86	38.88	2.14	400	95	PEAK	2	15780.00	60.91	74.00	-13.09	43.99	40.74	18.19	44.83	2.82	100	216	PEAK	3	15780.00	53.10	54.00	-0.90	36.18	40.74	18.19	44.83	2.82	100	216	AVERAGE	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>10520.00</td><td>59.28</td><td>68.20</td><td>-8.92</td><td>43.98</td><td>37.18</td><td>14.86</td><td>38.88</td><td>2.14</td><td>400</td><td>15</td><td>PEAK</td></tr><tr><td>2</td><td>15780.00</td><td>61.57</td><td>74.00</td><td>-12.43</td><td>44.65</td><td>40.74</td><td>18.19</td><td>44.83</td><td>2.82</td><td>200</td><td>311</td><td>PEAK</td></tr><tr><td>3</td><td>15780.00</td><td>52.10</td><td>54.00</td><td>-1.90</td><td>35.18</td><td>40.74</td><td>18.19</td><td>44.83</td><td>2.82</td><td>200</td><td>311</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	10520.00	59.28	68.20	-8.92	43.98	37.18	14.86	38.88	2.14	400	15	PEAK	2	15780.00	61.57	74.00	-12.43	44.65	40.74	18.19	44.83	2.82	200	311	PEAK	3	15780.00	52.10	54.00	-1.90	35.18	40.74	18.19	44.83	2.82	200	311	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																																																																			
1	10520.00	55.00	68.20	-12.40	40.50	37.18	14.86	38.88	2.14	400	95	PEAK																																																																																																																																
2	15780.00	60.91	74.00	-13.09	43.99	40.74	18.19	44.83	2.82	100	216	PEAK																																																																																																																																
3	15780.00	53.10	54.00	-0.90	36.18	40.74	18.19	44.83	2.82	100	216	AVERAGE																																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																			
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																																																																			
1	10520.00	59.28	68.20	-8.92	43.98	37.18	14.86	38.88	2.14	400	15	PEAK																																																																																																																																
2	15780.00	61.57	74.00	-12.43	44.65	40.74	18.19	44.83	2.82	200	311	PEAK																																																																																																																																
3	15780.00	52.10	54.00	-1.90	35.18	40.74	18.19	44.83	2.82	200	311	AVERAGE																																																																																																																																







Mode	4	
	Harmonic	
	U-NII-2A_5.25-5.35_802.11a_CH52_5260MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 VERTICAL





Mode	5																																																																																	
	Band Edge - L																																																																																	
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz																																																																																	
ANT	1																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Site : 83CH03-HY Condition: PEAK_BE_74 3m DRM18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>84.72</td><td>74.00</td><td>-11.00</td><td>38.96</td><td>32.70</td><td>18.45</td><td>33.06</td><td>3.92 200 284 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg	1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 PEAK	Site : 83CH03-HY Condition: PEAK_UNI1 3m DRM18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>84.72</td><td>74.00</td><td>-11.00</td><td>38.96</td><td>32.70</td><td>18.45</td><td>33.06</td><td>3.92 200 284 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg	1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																												
	MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg																																																																									
1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 PEAK																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																												
	MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg																																																																									
1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 PEAK																																																																									
Avg	Site : 83CH03-HY Condition: AVG_BE_54 3m DRM18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>84.72</td><td>74.00</td><td>-11.00</td><td>38.96</td><td>32.70</td><td>18.45</td><td>33.06</td><td>3.92 200 284 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg	1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 AVERAGE	Site : 83CH03-HY Condition: AVG_UNI 3m DRM18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>84.72</td><td>74.00</td><td>-11.00</td><td>38.96</td><td>32.70</td><td>18.45</td><td>33.06</td><td>3.92 200 284 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg	1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																												
	MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg																																																																									
1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 AVERAGE																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																												
	MHz	dBV/m	dBV/m	dB	dB	dB	dB	dB	cm deg																																																																									
1	5300.00	84.72	74.00	-11.00	38.96	32.70	18.45	33.06	3.92 200 284 AVERAGE																																																																									

Mode	5																																																	
	Band Edge - R																																																	
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz																																																	
ANT	1																																																	
Pol.	Horizontal					Fundamental																																												
Peak	 Site : 80CH03-HY Condition: PEAK_BE_74 3m DRH18-E LE2CHSA18EN 230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5439.36</td><td>51.50</td><td>74.00</td><td>-22.50</td><td>37.19</td><td>32.66</td><td>11.20</td><td>33.65</td><td>4.10 200 284 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1	5439.36	51.50	74.00	-22.50	37.19	32.66	11.20	33.65	4.10 200 284 PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																									
1	5439.36	51.50	74.00	-22.50	37.19	32.66	11.20	33.65	4.10 200 284 PEAK																																									
Avg	 Site : 80CH03-HY Condition: AVG_BE_54 3m DRH18-E LE2CHSA18EN 230712 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5458.24</td><td>42.19</td><td>54.00</td><td>-11.81</td><td>27.84</td><td>32.72</td><td>11.20</td><td>33.68</td><td>4.11 200 284 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1	5458.24	42.19	54.00	-11.81	27.84	32.72	11.20	33.68	4.11 200 284 AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																									
1	5458.24	42.19	54.00	-11.81	27.84	32.72	11.20	33.68	4.11 200 284 AVERAGE																																									





Mode	5																																																																																									
	Band Edge - L																																																																																									
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical	Fundamental																																																																																								
Peak	 Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>53.52</td><td>74.00</td><td>-20.48</td><td>39.66</td><td>32.62</td><td>10.44</td><td>33.19</td><td>3.99</td><td>109</td><td>342</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5300.00	53.52	74.00	-20.48	39.66	32.62	10.44	33.19	3.99	109	342	PEAK	 Site : 83CH3-HY Condition: PEAK(FUN1) 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>114.74</td><td>-----</td><td>-----</td><td>100.81</td><td>32.51</td><td>10.79</td><td>33.43</td><td>4.06</td><td>109</td><td>342</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5300.00	114.74	-----	-----	100.81	32.51	10.79	33.43	4.06	109	342	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																	
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																
1	5300.00	53.52	74.00	-20.48	39.66	32.62	10.44	33.19	3.99	109	342	PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																	
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																
1	5300.00	114.74	-----	-----	100.81	32.51	10.79	33.43	4.06	109	342	PEAK																																																																														
Avg	 Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>44.73</td><td>54.00</td><td>-9.27</td><td>30.00</td><td>32.62</td><td>10.44</td><td>33.20</td><td>3.99</td><td>109</td><td>342</td><td>AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5300.00	44.73	54.00	-9.27	30.00	32.62	10.44	33.20	3.99	109	342	AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5300.00</td><td>100.82</td><td>-----</td><td>-----</td><td>94.87</td><td>32.50</td><td>10.82</td><td>33.44</td><td>4.07</td><td>109</td><td>342</td><td>AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5300.00	100.82	-----	-----	94.87	32.50	10.82	33.44	4.07	109	342	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																	
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																
1	5300.00	44.73	54.00	-9.27	30.00	32.62	10.44	33.20	3.99	109	342	AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																	
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																
1	5300.00	100.82	-----	-----	94.87	32.50	10.82	33.44	4.07	109	342	AVERAGE																																																																														





Mode	5																																													
	Band Edge - R																																													
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz																																													
ANT	1																																													
Pol.	Vertical	Fundamental																																												
Peak	 Site : 80CH23-HY Condition: PEAK_BE_74 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5358.56</td><td>64.58</td><td>74.00</td><td>-9.58</td><td>58.42</td><td>32.58</td><td>11.83</td><td>33.53</td><td>4.88</td><td>189</td><td>342</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5358.56	64.58	74.00	-9.58	58.42	32.58	11.83	33.53	4.88	189	342	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	5358.56	64.58	74.00	-9.58	58.42	32.58	11.83	33.53	4.88	189	342	PEAK																																		
Avg	 Site : 80CH23-HY Condition: AVG_BE_54 3m DR18-E_LEXORSA18EN_230712 VERTICAL : RBW:1000.000kHz VBW:8.750kHz SUT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5370.88</td><td>47.55</td><td>54.00</td><td>-6.45</td><td>33.42</td><td>32.58</td><td>11.11</td><td>33.56</td><td>4.88</td><td>189</td><td>342</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5370.88	47.55	54.00	-6.45	33.42	32.58	11.11	33.56	4.88	189	342	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	5370.88	47.55	54.00	-6.45	33.42	32.58	11.11	33.56	4.88	189	342	AVERAGE																																		



Mode	5																																																																																																																																													
	Harmonic																																																																																																																																													
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz																																																																																																																																													
ANT	1																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																												
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1 10600.00</td><td>55.68</td><td>74.00</td><td>-18.32</td><td>40.19</td><td>37.40</td><td>14.91</td><td>38.97</td><td>2.15</td><td>200</td></tr><tr><td>2 10600.00</td><td>46.58</td><td>54.00</td><td>-7.42</td><td>31.09</td><td>37.40</td><td>14.91</td><td>38.97</td><td>2.15</td><td>200</td></tr><tr><td>3 15900.00</td><td>58.08</td><td>74.00</td><td>-15.92</td><td>41.42</td><td>40.60</td><td>18.23</td><td>45.01</td><td>2.84</td><td>100</td></tr><tr><td>4 15900.00</td><td>50.75</td><td>54.00</td><td>-3.25</td><td>34.09</td><td>40.60</td><td>18.23</td><td>45.01</td><td>2.84</td><td>100</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 10600.00	55.68	74.00	-18.32	40.19	37.40	14.91	38.97	2.15	200	2 10600.00	46.58	54.00	-7.42	31.09	37.40	14.91	38.97	2.15	200	3 15900.00	58.08	74.00	-15.92	41.42	40.60	18.23	45.01	2.84	100	4 15900.00	50.75	54.00	-3.25	34.09	40.60	18.23	45.01	2.84	100	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1 10600.00</td><td>58.43</td><td>74.00</td><td>-15.57</td><td>42.94</td><td>37.40</td><td>14.91</td><td>38.97</td><td>2.15</td><td>200</td></tr><tr><td>2 10600.00</td><td>49.50</td><td>54.00</td><td>-4.50</td><td>34.01</td><td>37.40</td><td>14.91</td><td>38.97</td><td>2.15</td><td>200</td></tr><tr><td>3 15900.00</td><td>62.03</td><td>74.00</td><td>-11.97</td><td>45.37</td><td>40.60</td><td>18.23</td><td>45.01</td><td>2.84</td><td>289</td></tr><tr><td>4 15900.00</td><td>52.73</td><td>54.00</td><td>-1.27</td><td>36.07</td><td>40.60</td><td>18.23</td><td>45.01</td><td>2.84</td><td>289</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 10600.00	58.43	74.00	-15.57	42.94	37.40	14.91	38.97	2.15	200	2 10600.00	49.50	54.00	-4.50	34.01	37.40	14.91	38.97	2.15	200	3 15900.00	62.03	74.00	-11.97	45.37	40.60	18.23	45.01	2.84	289	4 15900.00	52.73	54.00	-1.27	36.07	40.60	18.23	45.01	2.84	289
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																																					
1 10600.00	55.68	74.00	-18.32	40.19	37.40	14.91	38.97	2.15	200																																																																																																																																					
2 10600.00	46.58	54.00	-7.42	31.09	37.40	14.91	38.97	2.15	200																																																																																																																																					
3 15900.00	58.08	74.00	-15.92	41.42	40.60	18.23	45.01	2.84	100																																																																																																																																					
4 15900.00	50.75	54.00	-3.25	34.09	40.60	18.23	45.01	2.84	100																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																																					
1 10600.00	58.43	74.00	-15.57	42.94	37.40	14.91	38.97	2.15	200																																																																																																																																					
2 10600.00	49.50	54.00	-4.50	34.01	37.40	14.91	38.97	2.15	200																																																																																																																																					
3 15900.00	62.03	74.00	-11.97	45.37	40.60	18.23	45.01	2.84	289																																																																																																																																					
4 15900.00	52.73	54.00	-1.27	36.07	40.60	18.23	45.01	2.84	289																																																																																																																																					



Mode	5	
	Harmonic	
	U-NII-2A_5.25-5.35_802.11a_CH60_5300MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 VERTICAL





Mode	6																																																																																
	Band Edge																																																																																
	U-NII-2A_5.25-5.35_802.11a_CH64_5320MHz																																																																																
ANT	1																																																																																
Pol.	Horizontal	Fundamental																																																																															
Peak	Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5352.06</td><td>51.42</td><td>74.00</td><td>-22.58</td><td>37.35</td><td>32.58</td><td>11.01</td><td>33.51</td><td>4.00</td><td>195 327 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5352.06	51.42	74.00	-22.58	37.35	32.58	11.01	33.51	4.00	195 327 PEAK	Site : 83CH3-HY Condition: PEAK(FUN1) 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5328.00</td><td>97.12</td><td>-----</td><td>83.13</td><td>32.58</td><td>10.89</td><td>33.47</td><td>4.07</td><td>195 327 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5328.00	97.12	-----	83.13	32.58	10.89	33.47	4.07	195 327 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																											
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																								
1 5352.06	51.42	74.00	-22.58	37.35	32.58	11.01	33.51	4.00	195 327 PEAK																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																											
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																								
1 5328.00	97.12	-----	83.13	32.58	10.89	33.47	4.07	195 327 PEAK																																																																									
Avg	Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5358.18</td><td>43.74</td><td>54.00</td><td>-10.26</td><td>29.67</td><td>32.58</td><td>11.00</td><td>33.51</td><td>4.00</td><td>195 327 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5358.18	43.74	54.00	-10.26	29.67	32.58	11.00	33.51	4.00	195 327 AVERAGE	Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5328.00</td><td>90.61</td><td>-----</td><td>76.62</td><td>32.58</td><td>10.89</td><td>33.47</td><td>4.07</td><td>195 327 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 5328.00	90.61	-----	76.62	32.58	10.89	33.47	4.07	195 327 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																											
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																								
1 5358.18	43.74	54.00	-10.26	29.67	32.58	11.00	33.51	4.00	195 327 AVERAGE																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																											
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																								
1 5328.00	90.61	-----	76.62	32.58	10.89	33.47	4.07	195 327 AVERAGE																																																																									



	6																																																																																											
Mode	Band Edge																																																																																											
	U-NII-2A_5.25-5.35_802.11a_CH64_5320MHz																																																																																											
ANT	1																																																																																											
Pol.	Vertical	Fundamental																																																																																										
Peak	Site : 83CH3-HY Condition: PEAK_BE_74 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5358.24</td><td>62.88</td><td>74.00</td><td>-11.20</td><td>48.73</td><td>32.58</td><td>11.00</td><td>33.51</td><td>4.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>285 342 PEAK</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5358.24	62.88	74.00	-11.20	48.73	32.58	11.00	33.51	4.00									285 342 PEAK	Site : 83CH3-HY Condition: PEAK(UNI) 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5320.00</td><td>112.00</td><td>-----</td><td>-----</td><td>90.89</td><td>32.58</td><td>10.89</td><td>33.47</td><td>4.07</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>285 342 PEAK</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5320.00	112.00	-----	-----	90.89	32.58	10.89	33.47	4.07									285 342 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																																				
1 5358.24	62.88	74.00	-11.20	48.73	32.58	11.00	33.51	4.00																																																																																				
								285 342 PEAK																																																																																				
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																																				
1 5320.00	112.00	-----	-----	90.89	32.58	10.89	33.47	4.07																																																																																				
								285 342 PEAK																																																																																				
Avg	Site : 83CH3-HY Condition: AVG_BE_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5358.30</td><td>53.30</td><td>54.00</td><td>-0.70</td><td>39.23</td><td>32.58</td><td>11.00</td><td>33.51</td><td>4.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>285 342 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5358.30	53.30	54.00	-0.70	39.23	32.58	11.00	33.51	4.00									285 342 AVERAGE	Site : 83CH3-HY Condition: AVG_54 3m DR18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5320.00</td><td>105.70</td><td>-----</td><td>-----</td><td>92.79</td><td>32.58</td><td>10.89</td><td>33.47</td><td>4.07</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>285 342 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	1 5320.00	105.70	-----	-----	92.79	32.58	10.89	33.47	4.07									285 342 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																																				
1 5358.30	53.30	54.00	-0.70	39.23	32.58	11.00	33.51	4.00																																																																																				
								285 342 AVERAGE																																																																																				
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																				
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm																																																																																				
1 5320.00	105.70	-----	-----	92.79	32.58	10.89	33.47	4.07																																																																																				
								285 342 AVERAGE																																																																																				



Mode	6	
	Harmonic	
	U-NII-2A_5.25-5.35_802.11a_CH64_5320MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 HORIZONTAL	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 VERTICAL





	7																																																																																																			
Mode	Band Edge																																																																																																			
	U-NII-2C_5.47-5.725_802.11a_CH100_5500MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal	Fundamental																																																																																																		
Peak	Site : 83CH3-HY Condition: PEAK_BE(UNI1)_83 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>Hz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5456.65</td><td>52.57</td><td>74.00</td><td>-21.43</td><td>30.22</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11</td><td>100</td><td>35 PEAK</td></tr><tr><td>2</td><td>5469.78</td><td>54.22</td><td>68.28</td><td>-13.98</td><td>39.86</td><td>32.74</td><td>11.20</td><td>33.69</td><td>4.11</td><td>100</td><td>35 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5456.65	52.57	74.00	-21.43	30.22	32.71	11.20	33.67	4.11	100	35 PEAK	2	5469.78	54.22	68.28	-13.98	39.86	32.74	11.20	33.69	4.11	100	35 PEAK	Site : 83CH3-HY Condition: PEAK(UNI1)_3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>Hz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5500.00</td><td>100.55</td><td>-----</td><td>-----</td><td>86.17</td><td>32.88</td><td>11.20</td><td>33.74</td><td>4.12</td><td>100</td><td>35 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5500.00	100.55	-----	-----	86.17	32.88	11.20	33.74	4.12	100	35 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																														
	Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																										
1	5456.65	52.57	74.00	-21.43	30.22	32.71	11.20	33.67	4.11	100	35 PEAK																																																																																									
2	5469.78	54.22	68.28	-13.98	39.86	32.74	11.20	33.69	4.11	100	35 PEAK																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																														
	Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																										
1	5500.00	100.55	-----	-----	86.17	32.88	11.20	33.74	4.12	100	35 PEAK																																																																																									
Avg	Site : 83CH3-HY Condition: AVG_BE(UNI1)_83 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>Hz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5459.35</td><td>42.95</td><td>54.00</td><td>-11.05</td><td>28.68</td><td>32.72</td><td>11.20</td><td>33.68</td><td>4.11</td><td>100</td><td>35 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5459.35	42.95	54.00	-11.05	28.68	32.72	11.20	33.68	4.11	100	35 AVERAGE	Site : 83CH3-HY Condition: AVG_54 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>Hz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5500.00</td><td>93.94</td><td>-----</td><td>-----</td><td>79.56</td><td>32.88</td><td>11.20</td><td>33.74</td><td>4.12</td><td>100</td><td>35 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5500.00	93.94	-----	-----	79.56	32.88	11.20	33.74	4.12	100	35 AVERAGE												
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																														
	Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																										
1	5459.35	42.95	54.00	-11.05	28.68	32.72	11.20	33.68	4.11	100	35 AVERAGE																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																														
	Hz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																										
1	5500.00	93.94	-----	-----	79.56	32.88	11.20	33.74	4.12	100	35 AVERAGE																																																																																									





Mode	7																																																																																																		
	Band Edge																																																																																																		
	U-NII-2C_5.47-5.725_802.11a_CH100_5500MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Vertical	Fundamental																																																																																																	
Peak	Site : 83CH3-HY Condition: PEAK_BE(UNII)_B3 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5455.75</td><td>61.26</td><td>74.00</td><td>-12.74</td><td>46.91</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11</td><td>200</td><td>129</td><td>PEAK</td></tr><tr><td>2</td><td>5467.38</td><td>66.14</td><td>68.28</td><td>-2.06</td><td>51.79</td><td>32.73</td><td>11.20</td><td>33.69</td><td>4.11</td><td>200</td><td>129</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5455.75	61.26	74.00	-12.74	46.91	32.71	11.20	33.67	4.11	200	129	PEAK	2	5467.38	66.14	68.28	-2.06	51.79	32.73	11.20	33.69	4.11	200	129	PEAK	Site : 83CH3-HY Condition: PEAK(UNII) 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5500.00</td><td>114.59</td><td>-----</td><td>-----</td><td>100.21</td><td>32.80</td><td>11.20</td><td>33.74</td><td>4.12</td><td>200</td><td>129</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5500.00	114.59	-----	-----	100.21	32.80	11.20	33.74	4.12	200	129	PEAK
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																									
1	5455.75	61.26	74.00	-12.74	46.91	32.71	11.20	33.67	4.11	200	129	PEAK																																																																																							
2	5467.38	66.14	68.28	-2.06	51.79	32.73	11.20	33.69	4.11	200	129	PEAK																																																																																							
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																									
1	5500.00	114.59	-----	-----	100.21	32.80	11.20	33.74	4.12	200	129	PEAK																																																																																							
Avg	Site : 83CH3-HY Condition: AVG_BE(UNII)_B3 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5459.95</td><td>58.51</td><td>54.00</td><td>-3.49</td><td>36.16</td><td>32.72</td><td>11.20</td><td>33.68</td><td>4.11</td><td>200</td><td>129</td><td>AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5459.95	58.51	54.00	-3.49	36.16	32.72	11.20	33.68	4.11	200	129	AVERAGE	Site : 83CH3-HY Condition: AVG_54 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5500.00</td><td>187.15</td><td>-----</td><td>-----</td><td>92.77</td><td>32.80</td><td>11.20</td><td>33.74</td><td>4.12</td><td>200</td><td>129</td><td>AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5500.00	187.15	-----	-----	92.77	32.80	11.20	33.74	4.12	200	129	AVERAGE													
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																									
1	5459.95	58.51	54.00	-3.49	36.16	32.72	11.20	33.68	4.11	200	129	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																									
1	5500.00	187.15	-----	-----	92.77	32.80	11.20	33.74	4.12	200	129	AVERAGE																																																																																							







Mode	7																																																																																																																																																																							
	Harmonic																																																																																																																																																																							
	U-NII-2C_5.47-5.725_802.11a_CH100_5500MHz																																																																																																																																																																							
ANT	1																																																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																																																						
Peak Avg	 Site : 83CH23-HY Condition: PEAK(UNII) 3m DRX18-E_LE2C05A180N_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11000.00</td><td>58.37</td><td>74.00</td><td>-15.63</td><td>42.73</td><td>37.70</td><td>15.16</td><td>39.39</td><td>2.17</td><td>244</td><td>126</td><td>PEAK</td></tr><tr><td>2</td><td>11000.00</td><td>48.53</td><td>54.00</td><td>-5.47</td><td>32.89</td><td>37.70</td><td>15.16</td><td>39.39</td><td>2.17</td><td>244</td><td>126</td><td>AVERAGE</td></tr><tr><td>3</td><td>16500.00</td><td>63.90</td><td>68.20</td><td>-4.30</td><td>47.44</td><td>40.60</td><td>18.56</td><td>45.75</td><td>3.05</td><td>400</td><td>50</td><td>Peak</td></tr><tr><td>4</td><td>16500.00</td><td>50.92</td><td>54.00</td><td>-3.08</td><td>34.46</td><td>40.60</td><td>18.56</td><td>45.75</td><td>3.05</td><td>400</td><td>50</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11000.00	58.37	74.00	-15.63	42.73	37.70	15.16	39.39	2.17	244	126	PEAK	2	11000.00	48.53	54.00	-5.47	32.89	37.70	15.16	39.39	2.17	244	126	AVERAGE	3	16500.00	63.90	68.20	-4.30	47.44	40.60	18.56	45.75	3.05	400	50	Peak	4	16500.00	50.92	54.00	-3.08	34.46	40.60	18.56	45.75	3.05	400	50	Average	 Site : 83CH23-HY Condition: PEAK(UNII) 3m DRX18-E_LE2C05A180N_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11000.00</td><td>59.57</td><td>74.00</td><td>-14.43</td><td>43.93</td><td>37.70</td><td>15.16</td><td>39.39</td><td>2.17</td><td>181</td><td>246</td><td>PEAK</td></tr><tr><td>2</td><td>11000.00</td><td>49.97</td><td>54.00</td><td>-4.03</td><td>34.33</td><td>37.70</td><td>15.16</td><td>39.39</td><td>2.17</td><td>181</td><td>246</td><td>AVERAGE</td></tr><tr><td>3</td><td>16500.00</td><td>56.52</td><td>68.20</td><td>-11.68</td><td>40.06</td><td>40.60</td><td>18.56</td><td>45.75</td><td>3.05</td><td>400</td><td>322</td><td>PEAK</td></tr><tr><td>4</td><td>16500.00</td><td>44.83</td><td>54.00</td><td>-9.17</td><td>28.37</td><td>40.60</td><td>18.56</td><td>45.75</td><td>3.05</td><td>400</td><td>322</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11000.00	59.57	74.00	-14.43	43.93	37.70	15.16	39.39	2.17	181	246	PEAK	2	11000.00	49.97	54.00	-4.03	34.33	37.70	15.16	39.39	2.17	181	246	AVERAGE	3	16500.00	56.52	68.20	-11.68	40.06	40.60	18.56	45.75	3.05	400	322	PEAK	4	16500.00	44.83	54.00	-9.17	28.37	40.60	18.56	45.75	3.05	400	322	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																														
1	11000.00	58.37	74.00	-15.63	42.73	37.70	15.16	39.39	2.17	244	126	PEAK																																																																																																																																																												
2	11000.00	48.53	54.00	-5.47	32.89	37.70	15.16	39.39	2.17	244	126	AVERAGE																																																																																																																																																												
3	16500.00	63.90	68.20	-4.30	47.44	40.60	18.56	45.75	3.05	400	50	Peak																																																																																																																																																												
4	16500.00	50.92	54.00	-3.08	34.46	40.60	18.56	45.75	3.05	400	50	Average																																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																														
1	11000.00	59.57	74.00	-14.43	43.93	37.70	15.16	39.39	2.17	181	246	PEAK																																																																																																																																																												
2	11000.00	49.97	54.00	-4.03	34.33	37.70	15.16	39.39	2.17	181	246	AVERAGE																																																																																																																																																												
3	16500.00	56.52	68.20	-11.68	40.06	40.60	18.56	45.75	3.05	400	322	PEAK																																																																																																																																																												
4	16500.00	44.83	54.00	-9.17	28.37	40.60	18.56	45.75	3.05	400	322	Average																																																																																																																																																												



Mode	7	
	Harmonic	
	U-NII-2C_5.47-5.725_802.11a_CH100_5500MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 HORIZONTAL	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 VERTICAL



Mode	8																																																																																											
	Band Edge - L																																																																																											
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz																																																																																											
ANT	1																																																																																											
Pol.	Horizontal	Fundamental																																																																																										
Peak	 Site : 83CH3-HY Condition: PEAK_BE(UNI1)_83 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5387.72</td><td>51.52</td><td>74.00</td><td>-22.48</td><td>37.36</td><td>32.58</td><td>11.14</td><td>33.57</td><td>4.89</td><td>122 76 PEAK</td></tr><tr><td>2 5485.88</td><td>58.68</td><td>68.28</td><td>-17.52</td><td>36.33</td><td>32.73</td><td>11.20</td><td>33.69</td><td>4.11</td><td>122 76 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5387.72	51.52	74.00	-22.48	37.36	32.58	11.14	33.57	4.89	122 76 PEAK	2 5485.88	58.68	68.28	-17.52	36.33	32.73	11.20	33.69	4.11	122 76 PEAK	 Site : 83CH3-HY Condition: PEAK(UNI1)_3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5588.88</td><td>59.55</td><td>-----</td><td>-----</td><td>84.91</td><td>33.86</td><td>11.22</td><td>33.79</td><td>4.15</td><td>122 76 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5588.88	59.55	-----	-----	84.91	33.86	11.22	33.79	4.15	122 76 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																			
1 5387.72	51.52	74.00	-22.48	37.36	32.58	11.14	33.57	4.89	122 76 PEAK																																																																																			
2 5485.88	58.68	68.28	-17.52	36.33	32.73	11.20	33.69	4.11	122 76 PEAK																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																			
1 5588.88	59.55	-----	-----	84.91	33.86	11.22	33.79	4.15	122 76 PEAK																																																																																			
Avg	 Site : 83CH3-HY Condition: AVG_BE(UNI1)_83 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5436.82</td><td>42.27</td><td>54.00</td><td>-11.73</td><td>27.97</td><td>32.64</td><td>11.20</td><td>33.64</td><td>4.18</td><td>122 76 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5436.82	42.27	54.00	-11.73	27.97	32.64	11.20	33.64	4.18	122 76 AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3e DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5588.88</td><td>93.41</td><td>-----</td><td>-----</td><td>78.76</td><td>33.87</td><td>11.22</td><td>33.79</td><td>4.15</td><td>122 76 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5588.88	93.41	-----	-----	78.76	33.87	11.22	33.79	4.15	122 76 AVERAGE										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																			
1 5436.82	42.27	54.00	-11.73	27.97	32.64	11.20	33.64	4.18	122 76 AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																			
1 5588.88	93.41	-----	-----	78.76	33.87	11.22	33.79	4.15	122 76 AVERAGE																																																																																			



Mode	8																																									
	Band Edge - R																																									
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz																																									
ANT	1																																									
Pol.	Horizontal	Fundamental																																								
Peak	Site : 83CH23-HY Condition: PEAK_BE(U-NII_83) 3m DRMS-E_LE2C05418EN_230712 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5732.63</td><td>52.91</td><td>68.28</td><td>-15.29</td><td>37.76</td><td>33.83</td><td>11.01</td><td>33.88</td><td>4.19</td><td>122</td><td>76 PEAK</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg	1 5732.63	52.91	68.28	-15.29	37.76	33.83	11.01	33.88	4.19	122	76 PEAK	Blank
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																	
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	dB	cm	deg																																
1 5732.63	52.91	68.28	-15.29	37.76	33.83	11.01	33.88	4.19	122	76 PEAK																																





Mode	8																																																																																																												
	Band Edge - L																																																																																																												
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz																																																																																																												
ANT	1																																																																																																												
Pol.	Vertical						Fundamental																																																																																																						
Peak	Site : 83CH3-HY Condition: PEAK_BE(UNII)_83 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5427.85</td><td>53.95</td><td>74.00</td><td>-20.05</td><td>39.60</td><td>32.61</td><td>11.19</td><td>33.63</td><td>4.10</td><td>300</td><td>342</td><td>PEAK</td></tr><tr><td>2</td><td>5463.39</td><td>53.11</td><td>68.20</td><td>-15.09</td><td>38.75</td><td>32.73</td><td>11.20</td><td>33.68</td><td>4.11</td><td>300</td><td>342</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5427.85	53.95	74.00	-20.05	39.60	32.61	11.19	33.63	4.10	300	342	PEAK	2	5463.39	53.11	68.20	-15.09	38.75	32.73	11.20	33.68	4.11	300	342	PEAK	Site : 83CH3-HY Condition: PEAK(UNII) 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5580.00</td><td>114.75</td><td>-----</td><td>-----</td><td>100.10</td><td>33.07</td><td>11.22</td><td>33.79</td><td>4.15</td><td>300</td><td>342</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5580.00	114.75	-----	-----	100.10	33.07	11.22	33.79	4.15	300	342	PEAK
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																			
1	5427.85	53.95	74.00	-20.05	39.60	32.61	11.19	33.63	4.10	300	342	PEAK																																																																																																	
2	5463.39	53.11	68.20	-15.09	38.75	32.73	11.20	33.68	4.11	300	342	PEAK																																																																																																	
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																			
1	5580.00	114.75	-----	-----	100.10	33.07	11.22	33.79	4.15	300	342	PEAK																																																																																																	
Avg	Site : 83CH3-HY Condition: AVG_BE(UNII)_83 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5454.65</td><td>44.30</td><td>54.00</td><td>-9.70</td><td>29.95</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11</td><td>300</td><td>342</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5454.65	44.30	54.00	-9.70	29.95	32.71	11.20	33.67	4.11	300	342	AVERAGE	Site : 83CH3-HY Condition: AVG_54 3e DRH18-E_LE2CR5A18EN_238712 VERTICAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5580.00</td><td>107.59</td><td>-----</td><td>-----</td><td>92.94</td><td>33.07</td><td>11.22</td><td>33.79</td><td>4.15</td><td>300</td><td>342</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5580.00	107.59	-----	-----	92.94	33.07	11.22	33.79	4.15	300	342	AVERAGE													
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																			
1	5454.65	44.30	54.00	-9.70	29.95	32.71	11.20	33.67	4.11	300	342	AVERAGE																																																																																																	
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																			
1	5580.00	107.59	-----	-----	92.94	33.07	11.22	33.79	4.15	300	342	AVERAGE																																																																																																	





Mode	8																																												
	Band Edge - R																																												
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz																																												
ANT	1																																												
Pol.	Vertical	Fundamental																																											
Peak	Site : 83CH23-HY Condition: PEAK_BE(U-NII)_B3 3m DRMSB-E_LE2C05418EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5736.80</td><td>55.55</td><td>68.20</td><td>-12.65</td><td>40.38</td><td>33.85</td><td>11.01</td><td>33.88</td><td>4.19</td><td>300</td><td>342</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg	1	5736.80	55.55	68.20	-12.65	40.38	33.85	11.01	33.88	4.19	300	342	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																				
	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	cm	deg																																				
1	5736.80	55.55	68.20	-12.65	40.38	33.85	11.01	33.88	4.19	300	342	PEAK																																	






Mode	8																																																																																																																																													
	Harmonic																																																																																																																																													
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz																																																																																																																																													
ANT	1																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																												
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11160.00</td><td>58.76</td><td>74.00</td><td>-15.24</td><td>42.70</td><td>38.04</td><td>15.31</td><td>39.47</td><td>2.18</td><td>200</td><td>240</td><td>PEAK</td></tr><tr><td>2</td><td>11160.00</td><td>50.63</td><td>54.00</td><td>-3.37</td><td>34.57</td><td>38.04</td><td>15.31</td><td>39.47</td><td>2.18</td><td>200</td><td>240</td><td>AVERAGE</td></tr><tr><td>3</td><td>16740.00</td><td>59.14</td><td>68.20</td><td>-9.06</td><td>42.72</td><td>40.38</td><td>18.69</td><td>45.79</td><td>3.14</td><td>176</td><td>217</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11160.00	58.76	74.00	-15.24	42.70	38.04	15.31	39.47	2.18	200	240	PEAK	2	11160.00	50.63	54.00	-3.37	34.57	38.04	15.31	39.47	2.18	200	240	AVERAGE	3	16740.00	59.14	68.20	-9.06	42.72	40.38	18.69	45.79	3.14	176	217	PEAK	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_230712 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11160.00</td><td>62.76</td><td>74.00</td><td>-11.24</td><td>46.70</td><td>38.04</td><td>15.31</td><td>39.47</td><td>2.18</td><td>299</td><td>254</td><td>PEAK</td></tr><tr><td>2</td><td>11160.00</td><td>53.09</td><td>54.00</td><td>-0.91</td><td>37.03</td><td>38.04</td><td>15.31</td><td>39.47</td><td>2.18</td><td>299</td><td>254</td><td>AVERAGE</td></tr><tr><td>3</td><td>16740.00</td><td>60.40</td><td>68.20</td><td>-7.80</td><td>43.98</td><td>40.38</td><td>18.69</td><td>45.79</td><td>3.14</td><td>200</td><td>354</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11160.00	62.76	74.00	-11.24	46.70	38.04	15.31	39.47	2.18	299	254	PEAK	2	11160.00	53.09	54.00	-0.91	37.03	38.04	15.31	39.47	2.18	299	254	AVERAGE	3	16740.00	60.40	68.20	-7.80	43.98	40.38	18.69	45.79	3.14	200	354	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																				
1	11160.00	58.76	74.00	-15.24	42.70	38.04	15.31	39.47	2.18	200	240	PEAK																																																																																																																																		
2	11160.00	50.63	54.00	-3.37	34.57	38.04	15.31	39.47	2.18	200	240	AVERAGE																																																																																																																																		
3	16740.00	59.14	68.20	-9.06	42.72	40.38	18.69	45.79	3.14	176	217	PEAK																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																				
1	11160.00	62.76	74.00	-11.24	46.70	38.04	15.31	39.47	2.18	299	254	PEAK																																																																																																																																		
2	11160.00	53.09	54.00	-0.91	37.03	38.04	15.31	39.47	2.18	299	254	AVERAGE																																																																																																																																		
3	16740.00	60.40	68.20	-7.80	43.98	40.38	18.69	45.79	3.14	200	354	PEAK																																																																																																																																		






Mode	8	
	Harmonic	
	U-NII-2C_5.47-5.725_802.11a_CH116_5580MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EH_230712 VERTICAL





Mode	9																																																																																	
	Band Edge																																																																																	
	U-NII-2C_5.47-5.725_802.11a_CH140_5700MHz																																																																																	
ANT	1																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	 Site : 83CH03-HY Condition: PEAK_BE(UNII)_B3 3m DRMS-E_LE2C85A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5726.15</td><td>105.0</td><td>68.26</td><td>-18.97</td><td>42.89</td><td>33.81</td><td>11.82</td><td>33.88</td><td>4.19</td><td>100 79 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 PEAK	 Site : 83CH03-HY Condition: PEAK(UNII) 3m DRMS-E_LE2C85A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5726.15</td><td>105.0</td><td>68.26</td><td>-18.97</td><td>42.89</td><td>33.81</td><td>11.82</td><td>33.88</td><td>4.19</td><td>100 79 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																									
MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																									
1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 PEAK																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																									
MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																									
1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 PEAK																																																																									
Avg	Blank	 Site : 83CH03-HY Condition: AVG_54 3m DRMS-E_LE2C85A18EN_238712 HORIZONTAL : RBW:1000.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5726.15</td><td>105.0</td><td>68.26</td><td>-18.97</td><td>42.89</td><td>33.81</td><td>11.82</td><td>33.88</td><td>4.19</td><td>100 79 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark	MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg	1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 AVERAGE																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																									
MHz	dBV/m	dBV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																									
1 5726.15	105.0	68.26	-18.97	42.89	33.81	11.82	33.88	4.19	100 79 AVERAGE																																																																									





Mode	9																																																																									
	Band Edge																																																																									
	U-NII-2C_5.47-5.725_802.11a_CH140_5700MHz																																																																									
ANT	1																																																																									
Pol.	Vertical	Fundamental																																																																								
Peak	 Site : 83CH3-HY Condition: PEAK_BE(UNII)_B3 3m DRMS-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5726.52</td><td>66.72</td><td>68.28</td><td>-1.48</td><td>51.58</td><td>33.81</td><td>11.82</td><td>33.88</td><td>4.19</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5726.52	66.72	68.28	-1.48	51.58	33.81	11.82	33.88	4.19	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRMS-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5700.00</td><td>111.89</td><td>-----</td><td>-----</td><td>96.89</td><td>33.72</td><td>11.86</td><td>33.86</td><td>4.18</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5700.00	111.89	-----	-----	96.89	33.72	11.86	33.86	4.18
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																		
1 5726.52	66.72	68.28	-1.48	51.58	33.81	11.82	33.88	4.19																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																		
1 5700.00	111.89	-----	-----	96.89	33.72	11.86	33.86	4.18																																																																		
Avg	Blank	 Site : 83CH3-HY Condition: AVG_54 3m DRMS-E_LE2CR5A18EN_238712 VERTICAL : RBW:1000.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 5700.00</td><td>185.58</td><td>-----</td><td>-----</td><td>98.42</td><td>33.69</td><td>11.87</td><td>33.86</td><td>4.18</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1 5700.00	185.58	-----	-----	98.42	33.69	11.87	33.86	4.18																																				
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																		
1 5700.00	185.58	-----	-----	98.42	33.69	11.87	33.86	4.18																																																																		







Mode	9																																																																																																																									
	Harmonic																																																																																																																									
	U-NII-2C_5.47-5.725_802.11a_CH140_5700MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C085418EN_238712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11400.00</td><td>53.75</td><td>74.00</td><td>-20.25</td><td>37.00</td><td>30.60</td><td>15.54</td><td>39.50</td><td>2.19</td><td>181 22 PEAK</td></tr><tr><td>2 11400.00</td><td>44.68</td><td>54.00</td><td>-9.32</td><td>27.93</td><td>30.60</td><td>15.54</td><td>39.50</td><td>2.19</td><td>181 22 AVERAGE</td></tr><tr><td>3 17100.00</td><td>54.44</td><td>68.20</td><td>-13.76</td><td>38.13</td><td>40.10</td><td>18.90</td><td>45.97</td><td>3.28</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 11400.00	53.75	74.00	-20.25	37.00	30.60	15.54	39.50	2.19	181 22 PEAK	2 11400.00	44.68	54.00	-9.32	27.93	30.60	15.54	39.50	2.19	181 22 AVERAGE	3 17100.00	54.44	68.20	-13.76	38.13	40.10	18.90	45.97	3.28	-- -- PEAK	 Site : 83CH3-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C085418EN_238712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11400.00</td><td>55.18</td><td>74.00</td><td>-18.82</td><td>38.43</td><td>30.60</td><td>15.54</td><td>39.50</td><td>2.19</td><td>236 256 PEAK</td></tr><tr><td>2 11400.00</td><td>45.13</td><td>54.00</td><td>-8.77</td><td>28.48</td><td>30.60</td><td>15.54</td><td>39.50</td><td>2.19</td><td>236 256 AVERAGE</td></tr><tr><td>3 17100.00</td><td>55.55</td><td>68.20</td><td>-12.65</td><td>39.24</td><td>40.10</td><td>18.90</td><td>45.97</td><td>3.28</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1 11400.00	55.18	74.00	-18.82	38.43	30.60	15.54	39.50	2.19	236 256 PEAK	2 11400.00	45.13	54.00	-8.77	28.48	30.60	15.54	39.50	2.19	236 256 AVERAGE	3 17100.00	55.55	68.20	-12.65	39.24	40.10	18.90	45.97	3.28	-- -- PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																	
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																																	
1 11400.00	53.75	74.00	-20.25	37.00	30.60	15.54	39.50	2.19	181 22 PEAK																																																																																																																	
2 11400.00	44.68	54.00	-9.32	27.93	30.60	15.54	39.50	2.19	181 22 AVERAGE																																																																																																																	
3 17100.00	54.44	68.20	-13.76	38.13	40.10	18.90	45.97	3.28	-- -- PEAK																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																	
MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																																																																																																	
1 11400.00	55.18	74.00	-18.82	38.43	30.60	15.54	39.50	2.19	236 256 PEAK																																																																																																																	
2 11400.00	45.13	54.00	-8.77	28.48	30.60	15.54	39.50	2.19	236 256 AVERAGE																																																																																																																	
3 17100.00	55.55	68.20	-12.65	39.24	40.10	18.90	45.97	3.28	-- -- PEAK																																																																																																																	




Mode	9	
	Harmonic	
	U-NII-2C_5.47-5.725_802.11a_CH140_5700MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 HORIZONTAL	 Site : 88CH23-HY Condition: AVG_54 3m DRH18-E_LE20HS410EN_238712 VERTICAL



Mode	10																																																																																		
	Band Edge - L																																																																																		
	U-NII-2C_Straddle Channel_802.11a_CH144_5720MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal	Fundamental																																																																																	
Peak	 Site : 83CH3-HY Condition: STRADDLES U-NII-1&2A 3m DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5456.47</td><td>51.71</td><td>74.00</td><td>-22.29</td><td>37.36</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11 100 83 PEAK</td></tr><tr><td>2 5467.78</td><td>51.27</td><td>68.28</td><td>-16.93</td><td>36.91</td><td>32.74</td><td>11.20</td><td>33.69</td><td>4.11 100 83 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1 5456.47	51.71	74.00	-22.29	37.36	32.71	11.20	33.67	4.11 100 83 PEAK	2 5467.78	51.27	68.28	-16.93	36.91	32.74	11.20	33.69	4.11 100 83 PEAK	 Site : 83CH3-HY Condition: PEAK(U-NII) 3m DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:3000.000kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5728.00</td><td>182.12</td><td>-----</td><td>87.81</td><td>33.76</td><td>11.84</td><td>33.87</td><td>4.18</td><td>100 83 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1 5728.00	182.12	-----	87.81	33.76	11.84	33.87	4.18	100 83 PEAK
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																											
1 5456.47	51.71	74.00	-22.29	37.36	32.71	11.20	33.67	4.11 100 83 PEAK																																																																											
2 5467.78	51.27	68.28	-16.93	36.91	32.74	11.20	33.69	4.11 100 83 PEAK																																																																											
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																											
1 5728.00	182.12	-----	87.81	33.76	11.84	33.87	4.18	100 83 PEAK																																																																											
Avg	 Site : 83CH3-HY Condition: U-NII-1&2A AVERAGE 3m DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5455.69</td><td>42.84</td><td>54.00</td><td>-11.96</td><td>27.69</td><td>32.71</td><td>11.20</td><td>33.67</td><td>4.11 100 83 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1 5455.69	42.84	54.00	-11.96	27.69	32.71	11.20	33.67	4.11 100 83 AVERAGE	 Site : 83CH3-HY Condition: AVG_54 3m DRH18-E_LE2CR5A18EN_238712 HORIZONTAL : RBW:1800.000kHz VBW:8.750kHz SdF:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 5728.00</td><td>96.82</td><td>-----</td><td>88.89</td><td>33.79</td><td>11.83</td><td>33.87</td><td>4.18</td><td>100 83 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1 5728.00	96.82	-----	88.89	33.79	11.83	33.87	4.18	100 83 AVERAGE									
		Limit	Read	Ant	Cable	Aux	APos	TPos																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																											
1 5455.69	42.84	54.00	-11.96	27.69	32.71	11.20	33.67	4.11 100 83 AVERAGE																																																																											
	Limit	Read	Ant	Cable	Aux	APos	TPos																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																											
1 5728.00	96.82	-----	88.89	33.79	11.83	33.87	4.18	100 83 AVERAGE																																																																											



Mode	10																																												
	Band Edge - R																																												
	U-NII-2C_Straddle Channel_802.11a_CH144_5720MHz																																												
ANT	1																																												
Pol.	Horizontal	Fundamental																																											
Peak	 Site : 83CH23-HY Condition: STRADDLES U-NII-1A2A 3m DRH10-E LE2CR5A18EN_238712 HORIZONTAL : RBW:3000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBV/m</th><th>dBV/m</th><th>dB</th><th>dBV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5948.00</td><td>53.51</td><td>68.28</td><td>-14.69</td><td>37.95</td><td>34.00</td><td>11.47</td><td>34.01</td><td>4.18</td><td>100</td><td>83 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg	1	5948.00	53.51	68.28	-14.69	37.95	34.00	11.47	34.01	4.18	100	83 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																				
	MHz	dBV/m	dBV/m	dB	dBV	dB/m	dB	dB	cm	deg																																			
1	5948.00	53.51	68.28	-14.69	37.95	34.00	11.47	34.01	4.18	100	83 PEAK																																		