



TEST REPORT

APPLICANT : Thundercomm Technology Co., Ltd

PRODUCT NAME : TurboX C450 SOM

MODEL NAME : TurboX C450

BRAND NAME : TurboX

FCC ID : 2AOHHTURBOXC450

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2020-10-28

TEST DATE : 2020-11-07 to 2021-03-12

ISSUE DATE : 2021-05-08

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Modulation Type and Data Rate of EUT	4
1.4. The Channel Number and Frequency	5
1.5. Test Standards and Results	6
1.6. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna Requirement	8
2.2. Duty Cycle of Test Signal	9
2.3. Maximum Peak and Average Conducted Output Power	13
2.4. Bandwidth	16
2.5. Conducted Spurious Emissions and Band Edge	25
2.6. Power Spectral Density (PSD)	38
2.7. Conducted Emission	47
2.8. Restricted Frequency Bands	51
2.9. Radiated Emission	64
Annex A Test Uncertainty	80
Annex B Testing Laboratory Information	81

Change History		
Version	Date	Reason for change
1.0	2021-05-08	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Thundercomm Technology Co., Ltd
Applicant Address:	Building 4, No. 99, Data Valley Middle Road, Xiantao District, Yubei District, Chongqing, China
Manufacturer:	Thundercomm Technology Co., Ltd
Manufacturer Address:	Building 4, No. 99, Data Valley Middle Road, Xiantao District, Yubei District, Chongqing, China

1.2. Equipment Under Test (EUT) Description

Product Name:	TurboX C450 SOM
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	TURBOX-C450_SOM
Software Version:	2020.10.22
Modulation Technology:	DSSS, OFDM
Modulation Type:	Refer to section1.3
Operating Frequency Range:	802.11b/g/ n (HT20): 2412MHz–2462MHz 802.11n (HT40): 2422MHz–2452MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	3dBi

Note 1: The EUT will not sell with antenna.

Note 2: We use the dedicated software to control the EUT continuous transmission.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation technology	Modulation Type	Data Rate (Mbps) Note1
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n (HT20))	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11n (HT40))	BPSK	13.5
	QPSK	27/40.5
	16QAM	54/81/108
	64QAM	121.5/135

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

1.4. The Channel Number and Frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n (HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		
Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11n (HT40)	3	2422	8	2447
	4	2427	9	2452
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Mar 12, 2021	Liu Bo	PASS	No deviation
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Mar 12, 2021	Liu Bo	PASS	No deviation
4	15.247(a)	Bandwidth	Mar 12, 2021	Liu Bo	PASS	No deviation
5	15.247(d)	Conducted Spurious Emission and Band Edge	Mar 12, 2021	Liu Bo	PASS	No deviation
6	15.247(e)	Power Spectral Density (PSD)	Mar 12, 2021	Liu Bo	PASS	No deviation
7	15.207	Conducted Emission	Nov 07, 2020	Huang Zhiye	PASS	No deviation
8	15.247(d)	Restricted Frequency Bands	Mar 11&12, 2021	Lin Jiayong	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Mar 10, 2021	Lin Jiayong	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting



in the test equipments. The ref offset 11.5dB contains two parts that cable loss 1.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.




2.2.3. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
802.11b	97.88	0.09
802.11g	87.22	0.59
802.11n (HT20)	86.73	0.62
802.11n (HT40)	76.05	1.19


B. Test Plot:




(Channel 1, 802.11b)



(Channel 1, 802.11g)



(Channel 1, 802.11n (HT20))



(Channel 3, 802.11n (HT40))

2.3. Maximum Peak and Average Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.



2.3.3.Test Result

Maximum Peak Conducted Output Power

802.11b Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.67	0.037	30	1	PASS
6	2437	15.36	0.034			PASS
11	2462	15.01	0.032			PASS

802.11g Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	20.48	0.112	30	1	PASS
6	2437	20.65	0.116			PASS
11	2462	20.01	0.100			PASS

802.11n (HT20) Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	20.24	0.106	30	1	PASS
6	2437	20.25	0.106			PASS
11	2462	20.01	0.100			PASS

802.11n (HT40) Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	20.08	0.102	30	1	PASS
6	2437	19.78	0.095			PASS
9	2452	19.59	0.091			PASS

**Maximum Average Conducted Output Power****802.11b Mode**

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	12.77	0.09	12.86	0.019	30	1	PASS
6	2437	12.51		12.60	0.018			PASS
11	2462	12.18		12.27	0.017			PASS

802.11g Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	10.62	0.59	11.21	0.013	30	1	PASS
6	2437	10.30		10.89	0.012			PASS
11	2462	10.01		10.60	0.011			PASS

802.11n (HT20) Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	10.59	0.62	11.21	0.013	30	1	PASS
6	2437	10.44		11.06	0.013			PASS
11	2462	10.05		10.67	0.012			PASS

802.11n (HT40) Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
3	2422	10.63	1.19	11.82	0.015	30	1	PASS
6	2437	10.44		11.63	0.015			PASS
9	2452	10.30		11.49	0.014			PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.4.3. Test Procedure

KDB 558074 Section 8.2 was used in order to prove compliance.



2.4.4. Test Result

802.11b Mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.092	≥500	PASS
6	2437	9.023	≥500	PASS
11	2462	8.566	≥500	PASS

B. Test Plot:



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)




802.11g Mode


A.Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	16.42	≥500	PASS
6	2437	16.37	≥500	PASS
11	2462	16.45	≥500	PASS

B.Test Plot:



(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)




802.11n (HT20) Mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	17.59	≥500	PASS
6	2437	17.59	≥500	PASS
11	2462	17.59	≥500	PASS

B.Test Plot:



(Channel 1, 802.11n (HT20))



(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))



(Channel 6, 802.11n (HT40))



(Channel 9, 802.11n (HT40))


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.5.4.Test Result

802.11b Mode


A.Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.80	-4.07	-24.07	PASS
6	2437	-43.78	-5.04	-25.04	PASS
11	2462	-43.01	-2.68	-22.68	PASS


B.Test Plot:




(30MHz to 25GHz, Channel 1, 802.11b)




(Band Edge, Channel 1, 802.11b)



(30MHz to 25GHz, Channel 6, 802.11b)




(30MHz to 25GHz, Channel 11, 802.11b)



(Band Edge, Channel 11, 802.11b)

**802.11g Mode****A.Test Verdict:**


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.02	-12.38	-32.38	PASS
6	2437	-42.87	-11.97	-31.97	PASS
11	2462	-43.63	-10.72	-30.72	PASS

B.Test Plot:


(30MHz to 25GHz, Channel 1, 802.11g)




(Band Edge, Channel 1, 802.11g)



(30MHz to 25GHz, Channel 6, 802.11g)



(30MHz to 25GHz, Channel 11, 802.11g)



(Band Edge, Channel 11, 802.11g)




802.11n (HT20) Mode

A.Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.53	-13.16	-33.16	PASS
6	2437	-43.58	-12.74	-32.74	PASS
11	2462	-42.89	-12.27	-32.27	PASS


B.Test Plot:




(30MHz to 25GHz, Channel 1, 802.11n (HT20))



(Band Edge, Channel 1, 802.11n (HT20))



(30MHz to 25GHz, Channel 6, 802.11n (HT20))



(30MHz to 25GHz, Channel 11, 802.11n (HT20))



(Band Edge, Channel 11, 802.11n (HT20))




802.11n (HT40) Mode

A.Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-43.34	-16.31	-36.31	PASS
6	2437	-42.42	-16.21	-36.21	PASS
9	2452	-41.07	-16.10	-36.10	PASS


B.Test Plot:




(30MHz to 25GHz, Channel 3, 802.11n (HT40))



(Band Edge, Channel 3, 802.11n (HT40))



(30MHz to 25GHz, Channel 6, 802.11n (HT40))



(30MHz to 25GHz, Channel 9, 802.11n (HT40))



(Band Edge, Channel 11, 802.11n (HT40))


2.6. Power Spectral Density (PSD)

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.6.3. Test Procedure

KDB 558074 Section 8.4 was used in order to prove compliance.



2.6.4. Test Result

802.11b Mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-18.25	8	PASS
6	2437	-17.66	8	PASS
11	2462	-16.68	8	PASS

B. Test Plot:



(Channel 1, 802.11b)



(Channel 6, 802.11b)




(Channel 11, 802.11b)

**802.11g Mode****A.Test Verdict:**

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-23.75	8	PASS
6	2437	-22.44	8	PASS
11	2462	-21.46	8	PASS

B.Test Plot:

(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)




802.11n (HT20) Mode


A.Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-23.33	8	PASS
6	2437	-22.91	8	PASS
11	2462	-23.28	8	PASS


B.Test Plot:



(Channel 1, 802.11n (HT20))



(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))



A.Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-24.46	8	PASS
6	2437	-27.55	8	PASS
9	2452	-25.96	8	PASS

Agilent Spectrum Analyzer - Swept SA

RF 50.0 AC SENSE:PULSE SOURCE OFF ALIGN: AUTO 03:38:22 PM Mar 12, 2021

Ref Level 10.00 dBm

PNO: Fast IF Gain: Low Trig: Free Run Atten: 10 dB

Avg Type: Log-Pwr Avg Hold: 3/10

TRACE 1 TYPE N HANDED DET N 0 10 0 1 N

Ref Offset 11.5 dB Ref 10.00 dBm

Mkr1 2.432 62 GHz -24.460 dBm

10 dB/div Log

Center 2.42200 GHz Span 60.0 MHz

#Res BW 3.0 kHz #VBW 10 kHz Sweep 6.326 s (1001 pts)

Amplitude

Ref Level 10.00 dBm


Attenuation [10 dB]

Scale/Div 10 dB


Scale Type Log Lin

More 1 of 2

(Channel 3, 802.11n (HT40))



(Channel 6, 802.11n (HT40))



(Channel 9, 802.11n (HT40))

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+ camera + display + adapter + WIFI TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B.Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.3028	35.24	26.63	60.17	50.17	Line	PASS
2	0.4697	39.50	29.06	56.52	46.52		PASS
3	0.5505	35.65	26.83	56.00	46.00		PASS
4	0.6808	35.77	27.72	56.00	46.00		PASS
5	0.9012	33.32	24.64	56.00	46.00		PASS
6	1.1263	34.23	25.85	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2807	35.63	26.60	60.80	50.80	Neutral	PASS
2	0.3751	34.85	25.14	58.39	48.39		PASS
3	0.4738	37.70	27.45	56.45	46.45		PASS
4	0.9204	35.27	25.79	56.00	46.00		PASS
5	1.0271	37.16	27.04	56.00	46.00		PASS
6	1.2830	33.71	24.80	56.00	46.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.8.3.Test Procedure

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

2.8.4.Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


802.11b Mode

A.Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2388.93	PK	24.51	6.74	27.20	58.45	74	PASS
1	2390.00	AV	12.22	6.74	27.20	46.16	54	PASS
11	2484.83	PK	26.11	6.74	27.20	60.05	74	PASS
11	2483.50	AV	12.69	6.74	27.20	46.63	54	PASS




B.Test Plot:



(PEAK, Channel 1, 802.11b)



(AVERAGE, Channel 1, 802.11b)



(PEAK, Channel 11, 802.11b)



(AVERAGE, Channel 11, 802.11b)




802.11g Mode

A.Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2390.00	PK	26.33	6.74	27.20	60.27	74	PASS
1	2390.00	AV	12.86	6.74	27.20	46.80	54	PASS
11	2483.95	PK	29.68	6.74	27.20	63.62	74	PASS
11	2483.50	AV	15.08	6.74	27.20	49.02	54	PASS

B.Test Plot:



(PEAK, Channel 1, 802.11g)



(AVERAGE, Channel 1, 802.11g)



(PEAK, Channel 11, 802.11g)



(AVERAGE, Channel 11, 802.11g)




802.11n (HT20) Mode


A.Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2389.73	PK	25.74	6.74	27.20	59.68	74	PASS
1	2390.00	AV	13.15	6.74	27.20	47.09	54	PASS
11	2483.95	PK	31.42	6.74	27.20	65.36	74	PASS
11	2483.50	AV	15.32	6.74	27.20	49.26	54	PASS


B.Test Plot:




(PEAK, Channel 1, 802.11n (HT20))



(AVERAGE, Channel 1, 802.11n (HT20))



(PEAK, Channel 11, 802.11n (HT20))



(AVERAGE, Channel 11, 802.11n (HT20))




802.11n (HT40) Mode

A.Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2388.70	PK	26.15	6.74	27.20	60.09	74	PASS
3	2390.00	AV	12.93	6.74	27.20	46.87	54	PASS
9	2483.50	PK	31.59	6.74	27.20	65.53	74	PASS
9	2483.50	AV	15.95	6.74	27.20	49.89	54	PASS

B.Test Plot:




(PEAK, Channel 3, 802.11n (HT40))



(AVERAGE, Channel 3, 802.11n (HT40))



(PEAK, Channel 9, 802.11n (HT40))



(AVERAGE, Channel 9, 802.11n (HT40))

2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.9.2.Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.




802.11b Mode

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
46.490	28.48	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
98.870	26.41	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2219.733	45.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3912.080	44.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8969.440	47.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12514.520	48.31	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.400	29.64	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
351.070	27.50	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2372.800	46.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4503.440	45.83	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5753.920	48.46	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12551.480	47.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.550	30.34	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
440.310	27.70	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2496.533	45.92	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4161.560	44.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5870.960	48.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8405.800	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
46.490	27.87	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
594.540	30.95	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2188.267	46.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4484.960	45.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8439.680	47.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12157.240	47.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
45.520	28.91	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
437.400	27.78	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2462.933	48.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3902.840	44.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8408.880	47.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11867.720	46.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
50.370	28.18	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
448.070	28.97	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2371.733	45.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3773.480	43.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5747.760	47.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12526.840	47.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11g Mode**

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
41.640	28.13	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
683.780	30.91	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2453.333	46.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4497.280	46.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5750.840	48.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12292.760	47.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.580	28.47	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
575.140	29.44	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2405.867	47.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4481.880	45.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9055.680	46.46	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12539.160	47.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
55.220	26.58	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
570.290	29.58	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2322.667	46.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4497.280	45.78	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5747.760	47.22	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12141.840	48.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.550	28.85	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
679.900	29.93	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2362.133	46.25	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3240.640	43.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5624.560	47.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12874.880	47.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
41.640	30.27	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
573.200	29.76	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1982.933	47.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4272.440	44.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8978.680	47.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12292.760	48.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
41.640	28.94	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
556.710	28.90	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2453.867	46.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3819.680	44.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8473.560	46.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13663.360	46.31	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




802.11n (HT20) Mode

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
47.460	28.19	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
603.270	29.71	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2194.667	45.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4497.280	45.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5655.360	47.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12536.080	47.45	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.610	29.26	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
667.290	30.40	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2493.867	45.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4392.560	45.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8445.840	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12539.160	47.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
40.670	29.51	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
446.130	28.03	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2220.267	49.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5744.680	49.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9024.880	47.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10786.640	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.610	29.64	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
557.680	29.92	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2220.267	49.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3702.640	45.41	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5747.760	47.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11732.200	47.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.430	27.67	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
573.200	29.96	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2417.600	47.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5741.600	48.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8461.240	48.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12536.080	48.49	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.580	29.88	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
575.140	30.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2389.333	46.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5744.680	50.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8396.560	46.95	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12893.360	47.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11n (HT40) Mode**

Plot for Channel 3



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.550	27.96	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
551.860	28.46	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2219.733	48.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4136.920	45.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5741.600	47.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12616.160	47.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.430	28.57	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
577.080	29.81	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2220.267	46.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3363.840	43.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5738.520	47.95	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11051.520	47.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.400	28.05	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
577.080	30.39	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2219.733	46.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5744.680	48.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8482.800	47.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11140.840	47.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.700	28.32	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
555.740	29.54	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2281.067	45.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4715.960	46.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5741.600	47.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10999.160	47.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 9



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.580	28.75	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
573.200	30.36	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2220.267	48.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4484.960	45.91	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5741.600	49.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12603.840	47.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.700	29.91	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
351.070	29.39	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2417.600	46.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3841.240	44.57	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5744.680	49.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12194.200	48.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Attenuator 1	(N/A.)	10dB	Resent	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2020.04.01	2021.03.31
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2020.04.01	2021.03.31
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2020.03.26	2021.03.25
LISN	812744	NSLK 8127	Schwarzbeck	2020.03.26	2021.03.25
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2020.07.24	2021.07.23
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
Adapter	J5164200005	AK933JH	OPPO	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Townsend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2020.07.21	2021.07.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2019.02.14	2022.02.13
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2022.07.25
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2019.07.26	2022.07.25
Coaxial cable (N male) (9kHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L32 03	Tonscend	2020.07.21	2021.07.20
18-26.5GHz pre-Amplifier	46732	S10M100L38 02	Tonscend	2020.07.21	2021.07.20
26-40GHz pre-Amplifier	56774	S40M400L40 02	Tonscend	2020.07.21	2021.07.20
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2020.07.21	2021.07.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

_____ END OF REPORT _____