

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant:	Flarm Technology AG
Address of applicant:	Hinterbergstrasse 15, 6330 Cham, Zug, Switzerland
Manufacturer:	Flarm Technology AG
Address of manufacturer:	Hinterbergstrasse 15, 6330 Cham, Zug, Switzerland

General Description of EUT:

Product Name:	Atom UAV OEM
Trade Name:	/
Model No.:	FLATMUAOW
Adding Model(s):	FLATMUAWW
Rated Voltage:	DC5V-28V
FCC ID:	2AXJM-FLATMUAOW
Equipment Type:	Fixed

Technical Characteristics of EUT:

Frequency Range:	902.6-927.4MHz
RF Output Power:	9.56dBm (Conducted)
Modulation:	GFSK
Quantity of Channels:	63
Channel Separation:	400kHz
Type of Antenna:	External Antenna
Antenna Gain:	1dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For SRD(915MHz):

Maximum Tune-Up output power: 10(dBm)

Maximum peak output power at antenna input terminal: 10.00(mW)

Prediction distance: >20(cm)

Prediction frequency: 902.6 (MHz)

Antenna gain: 1 (dBi)

Directional gain (numeric gain): 1.26

The worst case is power density at prediction frequency at 20cm: 0.0025 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 0.6017 (mw/cm²)

For Wi-Fi & Bluetooth Internet of Things Module (FCC ID: 2AC7Z-ESPWROOM32UE):

Wi-Fi:

The worst case is power density at prediction frequency at 20cm: 0.0959 (mw/cm²)

Bluetooth:

The worst case is power density at prediction frequency at 20cm: 0.0021 (mw/cm²)

Mode for Simultaneous Multi-band Transmission

SRD(915MHz)+ Wi-Fi

The worst case is power density at prediction frequency at 20cm: 0.0025/0.6017 +0.0959/1=0.1001<1

SRD(915MHz)+ Bluetooth

The worst case is power density at prediction frequency at 20cm: 0.0025/0.6017 +0.0021/1=0.0063<1

Result: Pass