

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



MEASUREMENT REPORT LTE

Applicant Name: LG Electronics USA, Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States**

Date of Testing: 2/11 - 3/5/2019**Test Site/Location:** PCTEST Lab. Columbia, MD, USA **Test Report Serial No.:** 1M1902110024-03-R1.ZNF

FCC ID: ZNFX220TB

APPLICANT: LG Electronics USA, Inc.

Application Type: Certification LM-X220TB Model:

Additional Model(s): LMX220TB, X220TB, LM-X220MB, LMX220MB, X220MB

EUT Type: Portable Handset

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)


FCC Rule Part(s): 22, 24, & 27

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01 **Test Procedure(s):**

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1902110024-03-R1.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1902110024-03.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 1 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 1 01 162



TABLE OF CONTENTS

1.0	INTF	RODUCTION	5
	1.1	Scope	5
	1.2	PCTEST Test Location	5
	1.3	Test Facility / Accreditations	5
2.0	PRC	DUCT INFORMATION	6
	2.1	Equipment Description	6
	2.2	Device Capabilities	6
	2.3	Test Configuration	6
	2.4	EMI Suppression Device(s)/Modifications	6
3.0	DES	CRIPTION OF TESTS	7
	3.1	Measurement Procedure	7
	3.2	Block A Frequency Range	7
	3.3	Cellular - Base Frequency Blocks	7
	3.4	Cellular - Mobile Frequency Blocks	7
	3.5	PCS - Base Frequency Blocks	8
	3.6	PCS - Mobile Frequency Blocks	ε
	3.7	AWS - Base Frequency Blocks	8
	3.8	AWS - Mobile Frequency Blocks	g
	3.9	Radiated Power and Radiated Spurious Emissions	g
4.0	MEA	SUREMENT UNCERTAINTY	10
5.0	TES	T EQUIPMENT CALIBRATION DATA	11
6.0	SAM	IPLE CALCULATIONS	12
7.0	TES	T RESULTS	13
	7.1	Summary	13
	7.2	Occupied Bandwidth	15
	7.3	Spurious and Harmonic Emissions at Antenna Terminal	41
	7.4	Band Edge Emissions at Antenna Terminal	67
	7.5	Peak-Average Ratio	125
	7.6	Radiated Power (ERP/EIRP)	132
	7.7	Radiated Spurious Emissions Measurements	139
	7.8	Frequency Stability / Temperature Variation	151
8.0	CON	ICLUSION	162

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 2 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 2 01 102





MEASUREMENT REPORT



FCC Part 22, 24, & 27

			El	RP	EI	RP		
Mode	FCC Rule Part	Tx Frequency (MHz)	Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	Emission Designator	Modulation
LTE Band 71	27	665.5 - 695.5	0.091	19.60			4M53G7D	QPSK
LTE Band 71	27	665.5 - 695.5	0.062	17.90			4M53W7D	16QAM
LTE Band 71	27	668 - 693	0.074	18.70			9M01G7D	QPSK
LTE Band 71	27	668 - 693	0.054	17.31			8M98W7D	16QAM
LTE Band 71	27	670.5 - 690.5	0.084	19.27			13M4G7D	QPSK
LTE Band 71	27	670.5 - 690.5	0.069	18.40			13M5W7D	16QAM
LTE Band 71	27	673 - 688	0.081	19.08			17M9G7D	QPSK
LTE Band 71	27	673 - 688	0.057	17.53			17M9W7D	16QAM
LTE Band 12	27	699.7 - 715.3	0.076	18.80	0.124	20.95	1M10G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.058	17.65	0.095	19.80	1M11W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.087	19.37	0.142	21.52	2M72G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.069	18.37	0.113	20.52	2M71W7D	16QAM
LTE Band 12	27	701.5 - 713.5	0.088	19.47	0.145	21.62	4M52G7D	QPSK
LTE Band 12	27	701.5 - 713.5	0.068	18.35	0.112	20.50	4M51W7D	16QAM
LTE Band 12	27	704 - 711	0.089	19.50	0.146	21.65	9M00G7D	QPSK
LTE Band 12	27	704 - 711	0.063	18.02	0.104	20.17	9M01W7D	16QAM
LTE Band 26/5	22H	824.7 - 848.3	0.096	19.82	0.157	21.97	1M10G7D	QPSK
LTE Band 26/5	22H	824.7 - 848.3	0.084	19.22	0.137	21.37	1M09W7D	16QAM
LTE Band 26/5	22H	825.5 - 847.5	0.106	20.27	0.175	22.42	2M70G7D	QPSK
LTE Band 26/5	22H	825.5 - 847.5	0.092	19.62	0.150	21.77	2M70W7D	16QAM
LTE Band 26/5	22H	826.5 - 846.5	0.118	20.73	0.194	22.88	4M54G7D	QPSK
LTE Band 26/5	22H	826.5 - 846.5	0.076	18.84	0.125	20.99	4M52W7D	16QAM
LTE Band 26/5	22H	829 - 844	0.133	21.25	0.219	23.40	9M00G7D	QPSK
LTE Band 26/5	22H	829 - 844	0.094	19.74	0.154	21.89	8M98W7D	16QAM
LTE Band 26/5	22H	831.5 - 841.5	0.132	21.21	0.217	23.36	13M5G7D	QPSK
LTE Band 26/5	22H	831.5 - 841.5	0.102	20.09	0.167	22.24	13M5W7D	16QAM

EUT Overview (<1 GHz)

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 2 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 3 of 162



			EI	RP		
Mode	FCC Rule Part	Tx Frequency (MHz)	Max. Power (W)	Max. Power (dBm)	Emission Designator	Modulation
LTE Band 66/4	27	1710.7 - 1779.3	0.183	22.62	1M10G7D	QPSK
LTE Band 66/4	27	1710.7 - 1779.3	0.154	21.88	1M11W7D	16QAM
LTE Band 66/4	27	1711.5 - 1778.5	0.203	23.08	2M70G7D	QPSK
LTE Band 66/4	27	1711.5 - 1778.5	0.158	21.98	2M70W7D	16QAM
LTE Band 66/4	27	1712.5 - 1777.5	0.250	23.98	4M54G7D	QPSK
LTE Band 66/4	27	1712.5 - 1777.5	0.162	22.08	4M52W7D	16QAM
LTE Band 66/4	27	1715 - 1775	0.280	24.47	9M00G7D	QPSK
LTE Band 66/4	27	1715 - 1775	0.245	23.88	9M06W7D	16QAM
LTE Band 66/4	27	1717.5 - 1772.5	0.239	23.78	13M4G7D	QPSK
LTE Band 66/4	27	1717.5 - 1772.5	0.177	22.48	13M4W7D	16QAM
LTE Band 66/4	27	1720 - 1770	0.205	23.12	17M9G7D	QPSK
LTE Band 66/4	27	1720 - 1770	0.138	21.41	18M0W7D	16QAM
LTE Band 25/2	24E	1850.7 - 1914.3	0.185	22.67	1M10G7D	QPSK
LTE Band 25/2	24E	1850.7 - 1914.3	0.136	21.33	1M10W7D	16QAM
LTE Band 25/2	24E	1851.5 - 1913.5	0.209	23.21	2M71G7D	QPSK
LTE Band 25/2	24E	1851.5 - 1913.5	0.164	22.14	2M71W7D	16QAM
LTE Band 25/2	24E	1852.5 - 1912.5	0.239	23.78	4M52G7D	QPSK
LTE Band 25/2	24E	1852.5 - 1912.5	0.148	21.70	4M54W7D	16QAM
LTE Band 25/2	24E	1855 - 1910	0.316	25.00	9M01G7D	QPSK
LTE Band 25/2	24E	1855 - 1910	0.187	22.72	9M02W7D	16QAM
LTE Band 25/2	24E	1857.5 - 1907.5	0.244	23.88	13M5G7D	QPSK
LTE Band 25/2	24E	1857.5 - 1907.5	0.190	22.79	13M4W7D	16QAM
LTE Band 25/2	24E	1860 - 1905	0.237	23.74	17M9G7D	QPSK
LTE Band 25/2	24E	1860 - 1905	0.158	21.98	17M9W7D	16QAM

EUT Overview (Mid Bands)

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 4 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 4 of 162



1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo F of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 5 of 162



2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFX220TB**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

Test Device Serial No.: 00765, 00781

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, LE)

LTE Band 26 (814.7 – 849 MHz) overlaps the entire frequency range of LTE Band 5 (824 – 849 MHz). Therefore, test data provided in this report covers Band 5 and the portion of Band 26 subject to Part 22.

LTE Band 66 (1710 - 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz). Therefore, test data provided in this report covers Band 4 as well as Band 66.

LTE Band 25 (1850 - 1915 MHz) overlaps the entire frequency range of LTE Band 2 (1850 - 1910 MHz). Therefore, test data provided in this report covers Band 2 as well as Band 25.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFX220TB	PETEST*	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 6 of 162
1M1902110024-03-R1.ZNF	2/11 - 3/5/2019	Portable Handset	Page 6 of 162



DESCRIPTION OF TESTS 3.0

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM - Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 **Block A Frequency Range**

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz; Block B: 704-710 MHz and 734-740 MHz; and Block C: 710-716 MHz and 740-746 MHz.

3.3 Cellular - Base Frequency Blocks



BLOCK 1: 869 - 880 MHz (A* Low + A) BLOCK 3: 890 - 891.5 MHz (A* High) BLOCK 2: 880 - 890 MHz (B) BLOCK 4: 891.5 - 894 MHz (B*)

3.4 **Cellular - Mobile Frequency Blocks**




BLOCK 1: 824 - 835 MHz (A* Low + A) BLOCK 3: 845 - 846.5 MHz (A* High) BLOCK 2: 835 - 845 MHz (B) BLOCK 4: 846.5 - 849 MHz (B*)


FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 7 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 7 of 162




3.5 **PCS - Base Frequency Blocks**



3.6 **PCS - Mobile Frequency Blocks**



3.7 **AWS - Base Frequency Blocks**




BLOCK 1: 2110 - 2120 MHz (A) BLOCK 4: 2135 - 2140 MHz (D) BLOCK 2: 2120 - 2130 MHz (B) BLOCK 5: 2140 - 2145 MHz (E) BLOCK 3: 2130 - 2135 MHz (C) BLOCK 6: 2145 - 2155 MHz (F)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 8 of 162
1M1902110024-03-R1 7NF	2/11 – 3/5/2019	Portable Handset		Page 6 01 162



3.8 AWS - Mobile Frequency Blocks



BLOCK 1: 1710 – 1720 MHz (A) BLOCK 4: 1735 – 1740 MHz (D) BLOCK 2: 1720 – 1730 MHz (B) BLOCK 5: 1740 – 1745 MHz (E) BLOCK 3: 1730 – 1735 MHz (C) BLOCK 6: 1745 – 1755 MHz (F)

3.9 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_{g \, [dBm]}$ – cable loss [dB].

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10 $log_{10}(Power_{[Watts]})$.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 0 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 9 of 162



4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (±dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 10 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 10 01 162



5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	8/23/2018	Annual	8/23/2019	LTx3
Agilent	N9030A	PXA Signal Analyzer (44GHz)	5/25/2018	Annual	5/25/2019	MY52350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2017	Biennial	10/10/2019	121034
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/9/2018	Biennial	8/9/2020	135427
Espec	ESX-2CA	Environmental Chamber	3/28/2018	Annual	3/28/2019	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/28/2018	Biennial	3/28/2020	128337
Mini Circuits	TVA-11-422	RF Power Amp		N/A		QA1317001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11401010036
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator		N/A		11208010032
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	8/17/2018	Biennial	8/17/2020	101072
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	9/19/2018	Annual	9/19/2019	100040
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/21/2018	Annual	5/21/2019	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	8/9/2018	Annual	8/9/2019	100348
Rohde & Schwarz	CMW500	Radio Communication Tester	11/14/2018	Annual	11/14/2019	100976
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/18/2018	Annual	6/18/2019	102134
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

Table 5-1. Test Equipment

Notes:

- 1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- 2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 11 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 11 of 162



SAMPLE CALCULATIONS 6.0

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHzG = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission - LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm -(-24.80).

FCC ID: ZNFX220TB	PETEST* ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	.G	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 12 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset		Fage 12 01 162



TEST RESULTS 7.0

7.1 **Summary**

Company Name: LG Electronics USA, Inc.

FCC ID: ZNFX220TB

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

Mode(s): <u>LTE</u>

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A		D PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(g) 27.53(h)	Out of Band Emissions	> 43 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of- band emissions			Section 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB	CONDUCTED		Section 7.5
2.1046	Transmitter Conducted Output Power	N/A			See RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)			Section 7.8

Table 7-1. Summary of Conducted Test Results

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 13 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 13 01 102



FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
22.913(a)(5)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 26/5)	< 7 Watts max. ERP		PASS	Section 7.6
27.50(c)(10)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 71, 12)	< 3 Watts max. ERP			Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power (Band 25/2)	< 2 Watts max. EIRP	RADIATED		Section 7.6
27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 66/4)	< 1 Watts max. EIRP			Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(g) 27.53(h)	Undesirable Emissions	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions			Section 7.7

Table 7-2. Summary of Radiated Test Results

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 5.1.

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 14 of 162
1M1902110024-03-R1.ZNF	2/11 - 3/5/2019	Portable Handset	Page 14 of 162



7.2 **Occupied Bandwidth**

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 - Section 4.2

Test Settings

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW \geq 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within
 - 1 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 15 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 15 01 102



Band 71



Plot 7-1. Occupied Bandwidth Plot (Band 71 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-2. Occupied Bandwidth Plot (Band 71 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 16 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 10 01 102






Plot 7-3. Occupied Bandwidth Plot (Band 71 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-4. Occupied Bandwidth Plot (Band 71 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 17 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 17 01 102





Plot 7-5. Occupied Bandwidth Plot (Band 71 - 15.0MHz QPSK - Full RB Configuration)



Plot 7-6. Occupied Bandwidth Plot (Band 71 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 18 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 18 01 162





Plot 7-7. Occupied Bandwidth Plot (Band 71 - 20.0MHz QPSK - Full RB Configuration)



Plot 7-8. Occupied Bandwidth Plot (Band 71 - 20.0MHz 16-QAM - Full RB Configuration)


FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 10 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 19 of 162



Band 12




Plot 7-9. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-10. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 20 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 20 01 102





Plot 7-11. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-12. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 21 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 21 of 162





Plot 7-13. Occupied Bandwidth Plot (Band 12 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (Band 12 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 22 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 22 01 102





Plot 7-15. Occupied Bandwidth Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-16. Occupied Bandwidth Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 23 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 23 01 102



Band 26/5



Plot 7-17. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-18. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 24 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 24 of 162





Plot 7-19. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-20. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 25 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 25 01 102





Plot 7-21. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-22. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 26 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 20 01 102





Plot 7-23. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-24. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 27 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 27 of 162





Plot 7-25. Occupied Bandwidth Plot (Band 26 - 15.0MHz QPSK - Full RB Configuration)



Plot 7-26. Occupied Bandwidth Plot (Band 26 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 29 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 28 of 162



Band 66/4



Plot 7-27. Occupied Bandwidth Plot (Band 66/4 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-28. Occupied Bandwidth Plot (Band 66/4 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 29 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 29 01 102





Plot 7-29. Occupied Bandwidth Plot (Band 66/4 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-30. Occupied Bandwidth Plot (Band 66/4 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 30 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 30 01 162





Plot 7-31. Occupied Bandwidth Plot (Band 66/4 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-32. Occupied Bandwidth Plot (Band 66/4 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 21 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 31 of 162





Plot 7-33. Occupied Bandwidth Plot (Band 66/4 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-34. Occupied Bandwidth Plot (Band 66/4 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 32 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 32 01 102





Plot 7-35. Occupied Bandwidth Plot (Band 66/4 - 15.0MHz QPSK - Full RB Configuration)



Plot 7-36. Occupied Bandwidth Plot (Band 66/4 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 33 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 33 01 102





Plot 7-37. Occupied Bandwidth Plot (Band 66/4 - 20.0MHz QPSK - Full RB Configuration)



Plot 7-38. Occupied Bandwidth Plot (Band 66/4 - 20.0MHz 16-QAM - Full RB Configuration)


FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 24 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 34 of 162



Band 25/2



Plot 7-39. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-40. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 35 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 33 01 102





Plot 7-41. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-42. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 26 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 36 of 162





Plot 7-43. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-44. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 27 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 37 of 162





Plot 7-45. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-46. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 38 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 36 01 162





Plot 7-47. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz QPSK - Full RB Configuration)



Plot 7-48. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 39 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 39 01 102





Plot 7-49. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz QPSK - Full RB Configuration)



Plot 7-50. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz 16-QAM - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 40 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 40 of 162



7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is 43 + 10 $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 - Section 6.0

Test Settings

- 1. Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
- Detector = RMS
- 3. Trace mode = trace average
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 41 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 41 01 102



Band 71




Plot 7-51. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-52. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 42 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 42 of 162






Plot 7-53. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-54. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 43 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	rage 43 01 162






Plot 7-55. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-56. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 44 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 44 01 102





Plot 7-57. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-58. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 45 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 45 01 102






Plot 7-59. Conducted Spurious Plot (Band 71 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 46 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 46 01 162



Band 12




Plot 7-60. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-61. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 47 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 47 01 102






Plot 7-62. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-63. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 49 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 48 of 162






Plot 7-64. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-65. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 49 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 49 01 162





Plot 7-66. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-67. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	ENGINESRING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 50 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 50 of 162






Plot 7-68. Conducted Spurious Plot (Band 12 - 5.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 51 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 51 of 162



Band 26/5



Plot 7-69. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-70. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 52 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 52 of 162






Plot 7-71. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-72. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 53 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 55 01 162





Plot 7-73. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-74. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	PETEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 54 of 462
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 54 of 162





Plot 7-75. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-76. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo EE of 160
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 55 of 162






Plot 7-77. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-78. Conducted Spurious Plot (Band 26 - 15.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo F6 of 160
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 56 of 162





Plot 7-79. Conducted Spurious Plot (Band 26 - 15.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-80. Conducted Spurious Plot (Band 26 - 15.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)


FCC ID: ZNFX220TB	ENGINESRING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 57 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 57 of 162



Band 66/4



Plot 7-81. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-82. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 59 of 160
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 58 of 162






Plot 7-83. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-84. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 50 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 59 of 162






Plot 7-85. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-86. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 60 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 60 of 162






Plot 7-87. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-88. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 61 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 61 of 162






Plot 7-89. Conducted Spurious Plot (Band 66/4 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 62 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Fage 62 01 162



Band 25/2



Plot 7-90. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-91. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 63 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	rage 03 01 102





Plot 7-92. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-93. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 64 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 04 01 102





Plot 7-94. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-95. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 65 of 160
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 65 of 162





Plot 7-96. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-97. Conducted Spurious Plot (Band 25/2 - 20.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 66 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 66 of 162



Band Edge Emissions at Antenna Terminal 7.4

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{IWatts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 - Section 6.0

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW > 1% of the emission bandwidth
- 4. $VBW > 3 \times RBW$
- 5. Detector = RMS
- 6. Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 67 of 160
1M1902110024-03-R1.ZNF	2/11 - 3/5/2019	Portable Handset	Page 67 of 162



Test Notes


Per 22.917(b), 24.238(a), and 27.53(h), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.


FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 68 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	rage to til 162



Band 71



Plot 7-98. Lower Band Edge Plot (Band 71 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-99. Lower Extended Band Edge Plot (Band 71 - 5.0MHz QPSK - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 69 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	rage 09 01 102





Plot 7-100. Upper Band Edge Plot (Band 71 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-101. Upper Extended Band Edge Plot (Band 71 - 5.0MHz QPSK - Full RB Configuration)

FCC ID: ZNFX220TB	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 70 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 70 of 162





Plot 7-102. Lower Band Edge Plot (Band 71 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-103. Lower Extended Band Edge Plot (Band 71 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: ZNFX220TB	ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 71 of 162
1M1902110024-03-R1.ZNF	2/11 – 3/5/2019	Portable Handset	Page 71 of 162