

FCC 47 CFR MPE REPORT

TCL Entertainment Solutions Limited

2.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer

Model Number: TS8212

Additional Model: TS8212,TS822 , TDS8212,FS8212,OS8212,
TS8212K ,TDS8212K,Alto 8*, ***8212(* can be any alphanumeric character
including blank for marketing differences)

FCC ID: 2ARUDTS8212

Prepared for:	TCL Entertainment Solutions Limited
	7/F, building 22E, 22 science park east avenue Hong Kong science park,
	SHATIN, N.T. ,Hong Kong China.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2106012
Date of Test:	May. 17-31, 2021
Date of Report:	Jun. 02, 2021



Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
GFSK	2402	5.21	3.319	5±2	3.32	2.15
	2441	5.31	3.396	5±2	3.32	2.15
	2480	5.56	3.597	5±2	3.32	2.15
8-DPSK	2402	5.92	3.908	5±2	3.32	2.15
	2441	5.92	3.908	5±2	3.32	2.15
	2480	6.20	4.169	6±2	3.32	2.15
2.4G Wireless	2405	9.28	8.472	9±2	1.85	1.53
	2450	8.96	7.870	8±2	1.85	1.53
	2477	8.57	7.194	8±2	1.85	1.53

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
Bluetooth Antenna						
GFSK	7	3.32	2.15	0.00214	1	Complies
8-DPSK	8	3.32	2.15	0.00270	1	Complies
2.4G Wireless Antenna						
2.4G Wireless	11	1.85	1.53	0.00383	1	Complies

Power Density (S) (mW/cm ²) Bluetooth	Power Density (S) (mW/cm ²) 2.4G Wireless	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
0.00270	0.00383	0.00653	1	Complies

End of Test Report