

## 6.1 Conducted Output Power

### §2.1046

This device was tested under all R.C.s and S.O.s and the worst case is reported with EvDO FTAP with "All Up" power control bits.

### SAR Measurement Conditions for CDMA2000

The following procedures were followed according to FCC "SAR Measurement Procedures for 3G Devices", June 2006.

### Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices", June 2006.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 6-2 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 6-3 was applied.
5. FCHs were configured at full rate for maximum SAR with "All Up" power control bits.

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4



**Table 6-2**  
Parameters for Max. Power for RC1

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

**Table 6-3**  
Parameters for Max. Power for RC3

Band	Channel	SO55	TDSO SO32	1x EvDO Rev. 0	1x EvDO Rev. 0
		RC3/3	RC3/3	(FTAP)	(RTAP)
Cellular	1013	24.91	24.83	25.03	24.98
	384	24.84	24.91	25.08	25.01
	777	24.53	24.50	25.02	24.96
PCS	25	25.11	25.09	25.12	25.09
	600	24.54	24.31	25.16	25.02
	1175	24.38	24.27	24.98	24.93

**Table 6-4**  
Maximum Power Output Table for CF-19

FCC ID: ACJ9TGCF-192		FCC Pt. 22/24 CDMA (EvDO) MEASUREMENT REPORT		Reviewed by: Quality Manager
Test Report S/N: 0608220697	Test Dates: September 29 - October 3, 2006	EUT Type: Toughbook Model: CF-19		Page 12 of 28