



# MEASUREMENT REPORT

## FCC PART 22&24 Portable Handset

---

**FCC ID:** HD5-EDA50211

**APPLICANT:** Honeywell International Inc  
Honeywell Sensing & Productivity Solutions

**Application Type:** Certification

**Product:** Mobile Computer

**Model No.:** EDA50-211

**Brand Name:** Honeywell

**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part(s):** Part2, Part22 Subpart H, Part24 Subpart E

**Test Procedure(s):** ANSI/TIA-603-D-2010, KDB 971168 D01v02r02

**Test Date:** May 04 ~ June 02, 2017

Reviewed By : Jame Yuan  
( Jame Yuan )

Approved By : Marlin Chen  
( Marlin Chen )



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
1704RSU05707	Rev. 01	Initial report	06-20-2017	Invalid
1704RSU05707	Rev. 02	Revised some description	06-22-2017	Valid

## CONTENTS

Description	Page
<b>§2.1033 General Information .....</b>	<b>5</b>
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION .....</b>	<b>7</b>
2.1. Equipment Description.....	7
2.2. Product Specification Subjective to this Report.....	7
2.3. Device Capabilities .....	8
2.4. Test Configuration .....	8
2.5. EMI Suppression Device(s)/Modifications.....	8
<b>3. DESCRIPTION OF TEST .....</b>	<b>9</b>
3.1. Evaluation Procedure .....	9
3.2. Cellular - Base Frequency Blocks .....	9
3.3. Cellular - Mobile Frequency Blocks.....	9
3.4. PCS - Base Frequency Blocks.....	9
3.5. PCS - Mobile Frequency Blocks .....	10
3.6. Occupied Bandwidth.....	10
3.7. Spurious and Harmonic Emissions at Antenna Terminal.....	10
3.8. Radiated Power and Radiated Spurious Emissions .....	11
3.9. Peak-Average Ratio.....	12
3.10. Frequency Stability / Temperature Variation .....	12
<b>4. TEST EQUIPMENT CALIBRATION DATE .....</b>	<b>13</b>
<b>5. SAMPLE CALCULATIONS .....</b>	<b>14</b>
<b>6. MEASUREMENT UNCERTAINTY .....</b>	<b>15</b>
<b>7. TEST RESULT .....</b>	<b>16</b>
7.1. Summary .....	16
7.2. Occupied Bandwidth .....	17
7.2.1. Test Limit .....	17
7.2.2. Test Procedure used.....	17
7.2.3. Test Setting.....	17
7.2.4. Test Setup.....	17
7.2.5. Test Result.....	18

7.3.	Spurious and Harmonic Emissions at Antenna Terminal.....	25
7.3.1.	Test Limit .....	25
7.3.2.	Test Procedure Used .....	25
7.3.3.	Test Setting.....	25
7.3.4.	Test Setup.....	25
7.3.5.	Test Result.....	26
7.4.	Conducted & Radiated Power and Radiated Spurious Emissions.....	33
7.4.1.	Test Limit .....	33
7.4.2.	Test Procedure Used .....	33
7.4.3.	Test Setting.....	33
7.4.4.	Test Setup.....	35
7.4.5.	Test Result.....	36
7.5.	Peak-Average Ratio.....	46
7.5.1.	Test Limit .....	46
7.5.2.	Test Procedure .....	46
7.5.3.	Test Setup.....	46
7.5.4.	Test Result.....	47
7.6.	Frequency Stability Under Temperature & Voltage Variations.....	50
7.6.1.	Test Limit .....	50
7.6.2.	Test Procedure .....	50
7.6.3.	Test Setup.....	50
7.6.4.	Test Result.....	51
<b>8.</b>	<b>CONCLUSION.....</b>	<b>57</b>

## §2.1033 General Information

<b>Applicant:</b>	Honeywell International Inc Honeywell Sensing and Productivity Solutions
<b>Applicant Address:</b>	9680 Old Bailes Rd. Fort Mill, SC 29707 United States
<b>Manufacturer:</b>	Honeywell International Inc Honeywell Sensing and Productivity Solutions
<b>Manufacturer Address:</b>	9680 Old Bailes Rd. Fort Mill, SC 29707 United States
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
<b>MRT Registration No.:</b>	809388
<b>FCC Rule Part(s):</b>	Part 22 Subpart H, Part 24 Subpart E
<b>Model No.:</b>	EDA50-211
<b>FCC ID:</b>	HD5-EDA50211
<b>Test Device Serial No.:</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)

## Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



# 1. INTRODUCTION

## 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name:	Mobile Computer
Model No.:	EDA50-211
Brand Name:	Honeywell
Hardware Version:	V2.0
Software Version:	205.01.00.0006.eng
IMEI:	356074080038511
Wi-Fi Specification:	802.11a/b/g/n
Bluetooth Specification:	v4.0 dual mode
GSM Operation Band (s):	E-GSM 850 / DCS 1900
WCDMA Operation Band (s):	Band II / V
LTE Operation Band (s):	FDD Band 2/4/7
NFC:	13.56MHz
GPS:	1575.42MHz
<b>Components</b>	
Adapter	Model No.: ADS-12B-06 05010E Input Power: 100 - 240V ~ 50/60Hz, Max. 0.3A Output Power: 5VDC 2.0A

### 2.2. Product Specification Subjective to this Report

T <sub>x</sub> Frequency Range	GSM850: 824.2 ~ 848.8MHz, PCS1900: 1850.2 ~ 1909.8MHz WCDMA Band II: 826.4 ~ 846.6MHz WCDMA Band V: 1852.4 ~ 1907.6MHz
R <sub>x</sub> Frequency Range	GSM850: 869.2 ~ 893.8MHz, PCS1900: 1930.2 ~ 1989.8MHz WCDMA Band II: 1932.4 ~ 1987.6MHz WCDMA Band V: 826.4 ~ 846.6MHz
Antenna Type	FPC Antenna
Antenna Gain	GSM850 / WCDMA Band V: 1.9dBi PCS1900 / WCDMA Band II: 0.6dBi
Type of Modulation	GSM / GPRS: GMSK EDGE: 8PSK WCDMA: QPSK

Note: For other features of this EUT, test report will be issued separately.

### **2.3. Device Capabilities**

This device contains the following capabilities:

2.4GHz WLAN (DTS), 5GHz WLAN (UNII), Bluetooth (v4.0 dual mode), NFC, GSM 850/1900 WCDMA Band II/V, LTE FDD Band 2/4/7

### **2.4. Test Configuration**

The **Mobile Computer FCC ID: HD5-EDA50211** was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01v02r02. See section 3.0 of this report for a description of the radiated and antenna port conducted emissions tests.

### **2.5. EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added and no modifications were made during testing.



### 3. DESCRIPTION OF TEST


#### 3.1. Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM - Communications Equipment - Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **Mobile Computer FCC ID: HD5-EDA50211**

Deviation from measurement procedure.....None


#### 3.2. Cellular - Base Frequency Blocks

##### §22.905




#### 3.3. Cellular - Mobile Frequency Blocks

##### §22.905




#### 3.4. PCS - Base Frequency Blocks

##### §24.229



### 3.5. PCS - Mobile Frequency Blocks

#### §24.229



### 3.6. Occupied Bandwidth

#### §2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers' "occupied bandwidth" measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

### 3.7. Spurious and Harmonic Emissions at Antenna Terminal

#### §2.1051 §22.917(a) §24.238(a)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

### 3.8. Radiated Power and Radiated Spurious Emissions

#### §2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurement and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 80cm high PVC support structure is placed on top of the turntable.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

The calculated  $P_d$  levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of  $43 + 10 \cdot \log_{10}(\text{Power [Watts]})$  specified in 22.917(a) and 24.238(a).

### 3.9. Peak-Average Ratio

#### §24.232(d)

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

For pulsed signals, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power. For continuous signals, the trigger is set to “free run” in the CCDF measurement mode.

### 3.10. Frequency Stability / Temperature Variation

#### §2.1055 §22.355 §22.863 §22.905 §24.229 §24.235

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 24, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### 4. TEST EQUIPMENT CALIBRATION DATE

##### Radiated Emissions - AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9038A	MRTSUE06125	1 year	2017/08/19
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2017/06/21
Radio Communication Tester	R&S	CMU 200	MRTSUE06009	1 year	2017/11/10
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2018/02/14
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2018/04/15
Loop Antenna	Schwarzbeck	FMZB1519	MRTSUE06025	1 year	2017/11/21
TRILOG Antenna	Schwarzbeck	VULB9168	MRTSUE06172	1 year	2017/11/19
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06171	1 year	2017/11/19
Broadband Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06024	1 year	2017/12/30
Digital Thermometer & Hygrometer	Minggao	N/A	MRTSUE06170	1 year	2017/12/14
Anechoic Chamber	RIKEN	Chamber-AC2	MRTSUE06213	1 year	2017/05/10

##### Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2018/04/25
Radio Communication Tester	R&S	CMU 200	MRTSUE06009	1 year	2017/11/10
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2018/02/14
DC Power Supply	GWINSTEK	DPS-3303C	MRTSUE06064	N/A	N/A
Programmable Temperature & Humidity Chamber	BAOYT	BYH-1500L	MRTSUE06051	1 year	2017/12/06
Temperature/Humidity Meter	Yuhuaze	HTC-2	MRTSUE06180	1 year	2017/12/20

Software	Version	Function
e3	V8.3.5	EMI Test Software

## 5. SAMPLE CALCULATIONS

### **GSM Emission Designator**

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### **EDGE Emission Designator**

Emission Designator = 250KG7W

GSM BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

### **WCDMA Emission Designator**

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### **Spurious Radiated Emission**

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0dBm.

The gain of the substituted antenna is 8.1dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40MHz. So 6.1 dB is added to the signal generator reading of -30.9dBm yielding -24.80dBm. The fundamental EIRP was 25.50dBm so this harmonic was  $25.50\text{dBm} - (-24.80) = 50.3\text{dBc}$ .

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

AC Conducted Emission Measurement - SR2
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement - AC2
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB

## 7. TEST RESULT

### 7.1. Summary

**Company Name:** Honeywell International Inc  
Honeywell Sensing & Productivity Solutions  
**FCC ID:** HD5-EDA50211  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**Mode(s):** GSM / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied bandwidth	N/A	Conducted	Pass	Section 7.2
2.1051 22.917(a) 24.238(a)	Band Edge / Conducted Spurious Emissions	> 43 + log10 (P[Watts]) at Band Edge and for all out-of-band emissions		Pass	Section 7.3
24.232(d)	Peak-Average Ratio	< 13 dB		Pass	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		Pass	RF Exposure Report
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	Radiated	Pass	Section 7.4
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		Pass	Section 7.4
2.1053 22.917(a) 24.238(a)	Undesirable Emissions	> 43 + log10 (P[Watts]) for all out-of-band emissions		Pass	Section 7.4
2.1055 22.355 24.235	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24)		Pass	Section 7.6

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 4.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.



## 7.2. Occupied Bandwidth

### 7.2.1. Test Limit

N/A


### 7.2.2. Test Procedure used

KDB 971168 D01v02r02 - Section 4.1 & ANSI/TIA-603-D-2010

### 7.2.3. Test Setting

1. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.  
The span range for the spectrum analyzer shall be between two and five times the anticipated OBW. RBW = approximately 1% of the emission bandwidth.
2. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
3. Set the detection mode to peak, and the trace mode to max hold.
4. Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.


### 7.2.4. Test Setup



### 7.2.5. Test Result


Product	Mobile Computer	Temperature	25°C
Test Engineer	Polly Zong	Relative Humidity	52%
Test Site	TR3	Test Date	2017/05/23

Test Mode	Channel No.	Frequency (MHz)	99% Occupied Bandwidth (kHz)	-26dB Occupied Bandwidth (kHz)	Result
GSM850	128	824.2	245.6	315.6	Pass
	189	836.4	243.3	316.8	Pass
	251	848.8	245.0	315.3	Pass
PCS1900	512	1850.2	247.7	316.4	Pass
	661	1880.0	246.3	314.9	Pass
	810	1909.8	247.0	313.0	Pass
EDGE850	128	824.2	245.6	317.3	Pass
	189	836.4	246.6	315.5	Pass
	251	848.8	244.3	318.5	Pass
EDGE1900	512	1850.2	245.8	315.8	Pass
	661	1880.0	245.3	312.7	Pass
	810	1909.8	244.7	316.9	Pass
WCDMA Band II	9262	1852.4	4177.7	4644.0	Pass
	9400	1880.0	4180.7	4648.0	Pass
	9538	1907.6	4179.3	4656.0	Pass
WCDMA Band V	4132	826.4	4162.1	4636.0	Pass
	4182	836.4	4161.8	4616.0	Pass
	4233	846.6	4158.8	4624.0	Pass




## PCS1900 Occupied Bandwidth


### Channel 512 (1850.2MHz)



### Channel 661 (1880.0MHz)




### Channel 810 (1909.8MHz)




## EDGE850 Occupied Bandwidth


### Channel 128 (824.2MHz)



### Channel 189 (836.4MHz)




### Channel 251 (848.8MHz)




# EDGE1900 Occupied Bandwidth


## Channel 512 (1850.2MHz)



## Channel 661 (1880.0MHz)




## Channel 810 (1909.8MHz)




# WCDMA Band II Occupied Bandwidth


## Channel 9262 (1852.4MHz)



## Channel 9400 (1880.0MHz)




## Channel 9538 (1907.6MHz)






# WCDMA Band V Occupied Bandwidth


## Channel 4132 (826.4MHz)



## Channel 4182 (836.4MHz)



## Channel 4233 (846.6MHz)





### 7.3. Spurious and Harmonic Emissions at Antenna Terminal

#### 7.3.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

#### 7.3.2. Test Procedure Used

KDB 971168 D01v02r02 - Section 6.0 & ANSI/TIA-603-D-2010

#### 7.3.3. Test Setting

In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

#### 7.3.4. Test Setup

