

UR800

User Manual



Car Diagnostic Tool



Trademarks

iCarzone, UR800 is trademarks of iCarzone Technology Inc., registered in the United States and other countries. All other marks are trademarks or registered trademarks of their respective holders.

Copyright Information

No part of this manual may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without the prior written permission of iCarzone.

Disclaimer of Warranties and Limitation of Liabilities

All information, specifications and illustrations in this manual are based on the latest information available at the time of printing.

iCarzone reserves the right to make changes at any time without notice. While information of this manual has been carefully checked for accuracy, no guarantee is given for the completeness and correctness of the contents, including but not limited to the product specifications, functions, and illustrations.

iCarzone will not be liable for any direct, special, incidental, indirect damages or any economic consequential damages (including the loss of profits).



Before operating or maintaining this unit, please read this manual carefully, paying extra attention to the safety warnings and precautions.

For Services and Support



Http://www.icarzone.net



Support@icarzone.us

For technical assistance in all other markets, please contact your local selling agent.

Safety Information

ı

For your own safety and the safety of others, and to prevent damage to the device and vehicles upon which it is used, it is important that the safety instructions presented throughout this manual be read and understood by all persons operating or coming into contact with the device.

There are various procedures, techniques, tools, and parts for servicing vehicles, as well as in the skill of the person doing the work. Because of the vast number of test applications and variations in the products that can be tested with this equipment. we cannot possibly anticipate or provide advice or safety messages to cover every circumstance. It is the automotive technician's responsibility to be knowledgeable of the system being tested. It is crucial to use proper service methods and test procedures. It is essential to perform tests in an appropriate and acceptable manner that does not endanger your safety, the safety of others in the work area, the device being used, or the vehicle being tested.

Before using the device, always refer to and follow the safety messages and applicable test procedures provided by the manufacturer of the vehicle or equipment being tested. Use the device only as described in this manual. Read, understand, and follow all safety messages and instructions in this manual.

Safety Messages

Safety messages are provided to help prevent personal injury and equipment damage. All safety messages are introduced by a signal word indicating the hazard level.

A DANGER

Indicates an imminently hazardous situation which, if not avoided. will result in death or serious injury to the operator or to bystanders.

A WARNING

Indicates a potentially hazardous situation which, if not avoided. could result in death or serious injury to the operator or to bystanders.

Safety Instructions

The safety messages herein cover situations iCarzone is aware of. iCarzone cannot know, evaluate or advise you as to all of the possible hazards. You must be certain that any condition or service procedure encountered does not jeopardize your personal safety.

DANGER

When an engine is operating, keep the service area WELL VENTILATED or attach a building exhaust removal system to the engine exhaust system. Engines produce carbon monoxide, an odorless, poisonous gas that causes slower reaction time and can lead to serious personal injury or loss of life.

SAFETY WARNINGS

- Always perform automotive testing in a safe environment.
- Wear safety eye protection that meets ANSI standards.
- Keep clothing, hair, hands, tools, test equipment, etc. away from all moving or hot engine parts.
- Operate the vehicle in a well ventilated work area, for exhaust gases are poisonous.
- Put the transmission in PARK (for automatic transmission) or NEUTRAL (for manual transmission) and make sure the parking brake is engaged.
- Put blocks in front of the drive wheels and never leave the vehicle unattended while testing.
- Be extra cautious when working around the ignition coil, distributor cap, ignition wires and spark plugs. These components create hazardous voltages when the engine is running.
- Keep a fire extinguisher suitable for gasoline, chemical, and electrical fires nearby.
- Do not connect or disconnect any test equipment while the ignition is on or the engine is running.
- Keep the test equipment dry, clean, free from oil, water or grease. Use a mild detergent on a clean cloth to clean the outside of the equipment as necessary.
- Do not drive the vehicle and operate the test equipment at the same time. Any distraction may cause an accident.
- Refer to the service manual for the vehicle being serviced and adhere to all diagnostic procedures and precautions. Failure to do so may result in personal injury or damage to the test

equipment.

- To avoid damaging the test equipment or generating false data, make sure the vehicle battery is fully charged and the connection to the vehicle DLC is clean and secure.
- Do not place the test equipment on the distributor of the vehicle. Strong electro-magnetic interference can damage the equipment.
- Please ensure that the distance between the device and the human body is at least 20cm, otherwise personal injury may be caused.

Contents

1		nis Manual	
	1.1 Cor	nventions	
	1.1.1	Bold Text	1
	1.1.2	Notes and Important Messages	1
	1.1.3	Hyperlink	1
	1.1.4	Illustrations	
	1.1.5	Operation	2
2	General	Introduction	2
		800 Display Tablet	3
	2.1.1	Functional Description	3
	2.1.2	Power Sources	3
	2.1.3		4
	2.2 Acc	cessory Kit	5
	2.2.1		5
	2.2.2		6
3	Getting	started	7
		wering Up	7
	3.1.1		8
	3.1.2		9
		wering Down	10
	3.2.1	Reboot System	
4	Diagnos	stics	10
		ting Started	
	4.1.1	Vehicle Menu Layout	10
		nicle Identification	12
	4.2.1		12
	4.2.2	Vehicle select	14
		vigation	15
	4.3.1		15
	4.3.2		15
	4.3.3	Making Selections	16
		gnosis mode	16
	4.4.1		16
	4.4.2		18
	4.4.3	Service	18
	4.5 Dia	gnostic operation	18
		neric OBDII Operations	
	4.6.1		
	4.6.2		25
_	4.7 Exi	ting Diagnostics	26
5	Service	Operations	27
	5.1 Oil	Reset (OIL) Service	28

5.3 Steering Angle Sensor (SAS) Service	29 30 32 32 33 33 33 34
5.4 Electronic Throttle Control (ETC) Service	29 30 32 32 33 33 33 34 34
5.6 Battery Management System (BMS) Service	31 32 32 33 33 33 34 34
5.6 Battery Management System (BMS) Service	31 32 32 33 33 33 34 34
5.7 ABS Bleeding (BLD) Service	32 32 33 33 33 34 34
5.8 Injector Coding (INJ) Service	32 33 33 33 34 34
5.10 Air Suspension	33 33 33 34 34
5.10 Air Suspension	33 33 33 34 34
5.11 Air conditioner service	33 33 34 34 34
5.13 Gearbox Reset	33 34 34 34
5.14 Air Filter	34 34 34
5.15 Fuel Pump activation function	34 34
5.16 Engine Idle	34
5.16 Engine Idle	34
5.17 Body stability	24
	ა4
5.18 Door	
5.19 Seat	
5.20 Engine Control Module	35
5.21 Air Bag	35
5.22 Odometer	
5.23 Cylinder	35
5.24 ECM Correction	35
5.25 Immobilizer	
5.26 Exhaust Gas Recirculation	35
5.27 TPMS Programming	36
5.28 AdBlue	
5.29 Clutch	36
5.30 Water Pump	36
5.31 Crankshaft	
5.32 Gas Particulator Filter	36
5.33 High Voltage Battery	36
5.34 Cruise Control System	36
5.35 Language Setting	36
5.36 NOx Sensor	37
5.37 Rain Sensor	
5.38 Stop And Start	37
5.39 Turbocharger	37
5.40 Head-Up Display	37
5.41 Radar/Camera	
5.42 Vehicle Setup	37
5.43 Cylinder Shutoff Test	37
5.44 Cylinder Misfire Check	
5.45 Speed Limit Assist	37

	5.46	Control Unit Reset	
	5.47	Oxygen Sensor	
	5.48	Seat Belt	
	5.49	Miscellaneous	38
6	Upg	rade	38
7	Vehi	icle History	40
8	Use	r Data	41
	8.1	Image Files	41
	8.2	Play Back	41
	8.3	User Manual	44
	8.4	Fault Code	44
	8.5	Report	45
	8.6	Data Link Connector (DLC) Location	45
9	Sett	ing	45
	9.1	Unit	
	9.2	Language	45
	9.3	Data log	45
	9.4	WIFI	
	9.5	Data & Time	46
	9.6	Brightness	46
	9.7	Screen Sleep	
	9.8	Vehicle Sorted By	46
	9.9	Restore Default Úser Profiles	46
	9.10	Restore Factory Settings	46
	9.11	Screenshot Switch	
	9.12	Privacy Policy	47
10) Un	install	47
11	Su	pport	47
	11.1	Data Log	
12	2 Ab	out	48
13	8 Ma	intenance and Service	48
	13.1	Maintenance Instructions	48
	13.2	Troubleshooting Checklist	49
	13.3		
	13.4	Service Procedures	
	13	3.4.1 Technical Support	51
	13	3.4.2 Repair Service	
	13	3.4.3 Other Services	51
14	Co	mpliance Information	
15		rranty	
	15.1	Limited One Year Warranty	53
		•	



Using this Manual

This manual contains device usage instructions.

Some illustrations shown in this manual may contain modules and optional equipment that are not included in your system.

Conventions

The following conventions are used.

1.1.1 **Bold Text**

Bold text is used to highlight selectable items such as buttons and menu options.

Example:

Tap OK.

1.1.2 Notes and Important Messages

Notes

A **NOTE** provides helpful information such as additional explanations, tips, and comments.

Example:



NOTE

New batteries reach full capacity after approximately 3 to 5 charging and discharging cycles.

Important

IMPORTANT indicates a situation which, if not avoided, may result in damage to the tablet or vehicle.

Example:



IMPORTANT

Keep the cable away from heat, oil, sharp edges and moving parts. Replace damaged cables immediately.

Hyperlink 1.1.3

Hyperlinks, or links, that take you to other related articles, procedures, and illustrations are available in electronic documents.





Blue italic text indicates a selectable hyperlink and blue underlined text indicates a website link or an email address link.

1.1.4 Illustrations

Illustrations used in this manual are samples, the actual testing screen may vary for each vehicle being tested. Observe the menu titles and on-screen instructions to make correct option selection.

1.1.5 Operation

Welcome to using the scan tool of iCarzone, you should do something before using the scan tool.

- At first, please check production list such as scan tool and accessories already when you open the package, read the user's manual and connect the OBDII cable to scan tool.
- Don't open the scan tool in a rainy environment or in the absence of training. Don't soak the scan tool as the keypad and port are not waterproof, also no solvents such as alcohol are allowed to clean the keypad or display.
- Make sure the ignition is ON when you connected the scan tool already.



For vehicles manufactured by different vendors, it is possible that it has different diagnostic menus. For details, please follow the instructions on the screen to proceed. Some functions need to be used under the guidance of professional technicians.

2 General Introduction

When it comes to ultra-portability, UR800 is your perfect companion. Installed with a fast quad-core processor, UR800 offers maximum convenience and swift diagnosis. The intuitive user screen makes using the device effortless through a 5-inch LCD touchscreen that displays at 854 x 480 quality. Together with the ability to quickly read and clear DTCs for all available modules of the majority of the makes and models on the market, UR800 provides you with superior special functions, including OIL (Oil Reset Service), EPB (Electronic Parking Brake), SAS (Steering Angle Sensor), BMS (Battery Management System), DPF (Diesel



Particulate Filter), BLD (ABS Bleeding), ETC (Electronic Throttle Control) and INJ (Injector Coding).

This manual describes the construction and operation of the device and how it works to deliver diagnostic solutions.

2.1 UR800 Display Tablet

2.1.1 Functional Description




Figure 2-1 Display Tablet Front View

1. 5.0" LCD Capacitive Touchscreen.




Figure 2-2 UR800 Display Tablet Top View

- 2. USB Port.
- 3. DB15-Pin Port connects the main cable.
- Lock/Power Button long press button to turn tablet off and on. Quick press button to lock screen.

2.1.2 Power Sources





The Display Tablet can receive power from any of the following sources:

- Internal Battery Pack
- Vehicle Power
- External Power Supply

Internal Battery Pack

The Display Tablet can be powered with the internal rechargeable battery, which if fully charged can provide sufficient power for about 2.5 hours of continuous operation.

Vehicle Power

When the Display Tablet is connected to the test vehicle via the main cable, the Display Tablet automatically receives power from the vehicle.

External Power Supply

The Display Tablet can be powered from a wall socket using the USB cable and USB external power adapter. The external power supply also charges the internal battery pack.

2.1.3 Technical Specifications

Table 2-1 Specifications

Item	Description	
Recommended Use	Indoor	
Operating System	Android	
Processor	Quad Core 1.3 GHz	
Memory	32GB	
Display	5-inch LCD capacitive touchscreen with 854x480 resolution	
Connectivity	• USB 2.0 • Wi-Fi (2.4GHz) • OBDII	



Body Color	Black	
Power and Battery	OBD DLC Voltage Range:9-18V 3.7V/2000mAh lithium-polymer battery Charges via 5V DC power supply	
Tested Battery Life	Around 2.5 hours of continuous use	
Battery Charging Input	5V / 2A	
Power Consumption	500mA (LCD on with default brightness, Wi-Fi on) @3.7 V	
Operating Temp.	0 to 50°C (32 to 122°F)	
Storage Temp.	-20 to 70°C (-4 to 158°F)	
Operating Humidity	5% - 95% non-condensing	
Dimensions (W x H x D)	190mm X 117mm X 29.3mm (7.48inch X 4.61inch X 1.16inch)	
Net Weight	≈320g	
Supported Automotive Protocols	ISO9141-2, ISO14230-2,ISO15765, K/L-Line, Flashing Code, SAE-J1850 VPW, SAE-J1850 PWM, ISO11898 (Highspeed, Middlespeed, Lowspeed and Singlewire CAN), SAE J2610,GM UART,UART Echo Byte Protocol, Honda Diag-H Protocol, TP2.0, TP1.6	

2.2 Accessory Kit

2.2.1 Main Cable

The Main Cable connects the Display Tablet to the vehicle's data link connector (DLC).









Figure 2-4 Main Cable

2.2.2 Other Accessories



O NOTE:



Before connecting the main cable to your vehicle, please connect the cable to the unit first and tighten the screws.

3 Getting started

Ensure the tablet is sufficiently charged or is connected to the external power supply (see *Power Sources* on section 2.1.2).

NOTE

The images and illustrations depicted in this manual may differ from the actual ones.

3.1 Powering Up

Long press the power/lock button on the top right corner of the tablet to power on the device. The system will start and display the UR800 main menu.



Figure 3-1 Sample UR800 Job Menu

- 1. Application Buttons
- 2. Navigation Buttons
- 3. Status Icons



The tablet screen is locked by default upon startup. It is recommended to lock the screen when not in use to protect the information in the system and conserve the power.

Almost all operations on the tablet can be controlled through



the touch screen. The touch screen navigation is menu driven, which allows you to quickly locate the test procedure, or data that you need, through a series of choices and questions. Detailed descriptions of the menu structures are found in the chapters for each application.

3.1.1 Application Buttons

The tablet below briefly describes each of the applications in the UR800 system.

Table 3-1 Applications

Button	Name	Description
@	Diagnostics	Accesses diagnostic functions menu. See Diagnostics Operations on chapter 4.
	Service	Accesses special functions menu. See Service Operations on chapter 5.
(①	Upgrade	Checks for the latest update available for the UR800 system, and performs updates. See Upgrade Operations on chapter 6.
	Vehicle History	Records the vehicle's historical diagnostic data, allowing the user to quickly access the diagnostic next time. See Vehicle history Operations on chapter 7.
2	User Data	Accesses the organization system for saved data files. See User Data Operations on chapter 8.



(\$)	Settings	Accesses UR800 system settings menu and general tablet menu. See Settings Operations on chapter 9.
	Uninstall	Manage the application and database installed on the UR800 tablet. See Uninstall Operations on chapter 10.
9	Support	Feedback and get on-line service from iCarzone with the UR800 tablet. See Support Operations on chapter 11.
	About	Accesses UR800 system information about the machine. See About Operations on chapter 12.

3.1.2 Locator and Navigation Buttons

Operations of the Navigation buttons at the bottom of the screen are described in the table below:

Table 3-2 Locator and Navigation Buttons

Button	Name	Description
s s	Locator	Indicates the location of the screen. Swipe the screen left or right to view the previous or next screen.
Ð	Back	Returns to the previous screen.
(6)	UR800 Home	Returns to UR800 System's Home screen.





Recent Apps	Displays a list of applications that are currently in use. Tap an app icon to launch. To remove an app, swipe it to the left or right.
-------------	--

3.2 Powering Down

All vehicle communications must be terminated before shutting down the Display Tablet. Forcing a shutdown while the tablet is communicating may lead to ECM problems on some vehicles. Please exit the Diagnostics application before shutting off the tablet

To power down the display tablet

- 1. Long press the Lock/Power Button.
- Tap Power off option, the tablet will turn off in a few seconds.

3.2.1 Reboot System

In case of system crash, long press the Lock/Power button and tap Reboot option to restart the system.

4 Diagnostics

The Diagnostics application can access the electronic control unit (ECU) of various vehicle control systems, such as engine, transmission, anti-lock brake system (ABS), airbag system (SRS) and more.

4.1 Getting Started

The Diagnostics operations require connecting the UR800 to the test vehicle's DLC using the main cable.

4.1.1 Vehicle Menu Layout

When the tablet is properly connected to the vehicle, the platform is ready to start vehicle diagnosis. Tap on the Diagnostics application button on the UR800 Job Menu, the Vehicle Menu then displays.





Figure 4-1 Sample Vehicle Menu

- 1. Top Toolbar Buttons
- 2. Manufacturer Buttons


Top Toolbar Buttons

The operations of the toolbar buttons at the top of the screen are listed and described in the table below:

Table 4-1 Top Toolbar Buttons

Button	Name	Description
U	Back	Returns to the UR800 Job Menu.
All	All	Displays a menu of vehicle manufacturers.
History	History	Displays stored test vehicle history records.
USA	USA	Displays the USA vehicle menu.
EU	Europe	Displays the European vehicle menu.
Asia	Asia	Displays the Asian vehicle menu.
۵,	Search	Searches for a specific vehicle





Manufacturer Buttons

The vehicle manufacturer buttons display the vehicle brands currently compatible with the tool. After establishing communication with the vehicle. Tap the desired manufacturer button to start a diagnostic session.

4.2 Vehicle Identification

The UR800 diagnostic system supports two methods for Vehicle Identification.

- 1. Auto identify or VIN identify
- Vehicle select

4.2.1 Auto Identify

The UR800 diagnostic system features the latest VIN-based Auto VIN Scan function to identify vehicles with just one touch, enabling the technician to quickly identify the vehicle, scan all the diagnosable ECUs on the vehicle and perform diagnostics on the selected system.

The "VIN identify" can automatically parse the car model, eliminating the cumbersome program manually input by the user.

The device diagnostic system has the latest automatic identification function based on the vehicle identification number. It stores all the diagnosable electronic control units of Scan on the vehicle and performs the diagnosis on the selected system. Perform automatic VIN recognition. For some vehicles that do not support the automatic vehicle identification number scanning function, the diagnostic tool allows you to manually enter the vehicle identification number. Recognize the VIN first. If the VIN cannot be recognized, you need to enter it manually.

Automatic VIN identification

- To perform VIN Identify
 - Tap the **Diagnostics** application button from the UR800 Job Menu. The Vehicle Menu displays.
 - Select vehicle brand. Tap the "Auto Identify", Wait for the vehicle to communicate.





Figure 4-2 Sample VIN Identification Screen

 Once the test vehicle is successfully identified, the screen will show the Vehicle information: include VIN, model code, brand etc., then tap OK to enter the diagnosis.




Figure 4-3 Sample Vehicle information Screen

Manual VIN Input

For some vehicles that not supporting the Auto VIN Scan function, the UR800 diagnostic system allows you to enter the vehicle VIN manually.

> To perform Manual VIN Input

1. Tap the **Diagnostics** application button from the UR800





- Job Menu. The Vehicle Menu displays.
- Select vehicle brand. If some vehicles do not support automatic VIN code recognition, you need to enter the VIN code manually.
- 3. Tap the input box and enter the correct VIN.



Figure 4-4 Sample VIN input Screen

- 4. Tap OK. The vehicle will be identified and the Vehicle Diagnostics screen will display.
- 5. Tap Cancel to exit Manual Input.

4.2.2 Vehicle select

In some cases, when the user selects the vehicle brand without performing an automatic vehicle identification number scan, the system can provide vehicle selection to enter the vehicle diagnosis system.

> To perform Vehicle Select

- Tap the Diagnostics application button from the UR800 Job Menu. The Vehicle Menu displays.
- 2. Tap the vehicle brand of the test vehicle.
- Tap the "Vehicle Select" option to make a series of selections according to the on-screen prompts, select the correct vehicle model, model year, etc.,
- Select step by step according to the screen prompts, and finally enter the list of diagnosis modes.



4.3 Navigation

This section describes how to operate the Diagnostics screen and select test options.

4.3.1 Diagnostics Screen Layout




Figure 4-5 Sample Diagnosis mode Screen

The diagnostic screens typically include two sections.

- 1. Status Information Bar
- 2. Main Section

Status Information Bar

The Status Information Bar at the top of the Main Section displays the following items:

- 1) Back button Returns to the UR800 Job Menu.
- Menu Title displays the menu heading of the Main Section.
- 3) Voltage Icon displays the vehicle's voltage status.

Main Section

The main section displays the diagnostic mode of the vehicle, depending on the vehicle type; or it may vary depending on the operation stage, displaying vehicle identification selection, main menu, test data, messages, instructions and other diagnostic information.

4.3.2 Screen Messages





Screen messages appear when additional input is needed before proceeding. There are three main types of on-screen messages: Confirmation, Warning, and Error.

Confirmation Messages

This type of messages usually displays as an "Information" screen that informs you when you are about to perform an action that cannot be reversed or when an action has been initiated and your confirmation is needed to continue.

When a user-response is not required to continue, the message displays briefly.

Warning Messages

This type of messages displays a warning that a selected action may result in an irreversible change or loss of data. The typical example of this is the "Erase Codes" message.

Error Messages

Error messages display when a system or procedural error has occurred. Examples of possible errors include a disconnection or communication interruption.

4.3.3 Making Selections

The Diagnostics application is a menu driven program that presents a series of choices. As a selection is made, the next menu in the series displays. Each selection narrows the focus and leads to the desired test. Tap the screen to make menu selections.

4.4 Diagnosis mode

The Diagnostics application enables a data link to the electronic control system of the test vehicle for vehicle diagnosis. The application performs functional tests, retrieves vehicle diagnostic information such as trouble and event codes and live data for various vehicle control systems, such as engine, transmission, and ABS.

The scan tool provides three diagnostic modes for users to choose: Auto Scan, Control Unit and Service as shown in the figure below.

4.4.1 Auto Scan

The Auto Scan function performs a comprehensive scanning of the ECUs in the vehicle's system to locate and retrieve DTCs.



Enter Auto Scan, the system will scan your vehicle's system for you. At the same time, the fault information of each unit is detected to show the list and fault status.




Figure 4-6 Sample Auto Scan Screen

Left side – Show vehicle control unit system name.

Right side – Show vehicle control unit status.

- Fault | (2): Indicates that the fault code is detected; 2 represents the number of faults detected.
- Pass: Indicates that the vehicle is equipped with this system and has no fault code.
- Fitted: Indicates that the vehicle is equipped with this system.
- Not Fitted: Indicates that it is detected that the vehicle is not equipped with this system.
- Unknown: Indicates that it is detected that it is unknown whether the vehicle is equipped with this system.
- Scanning: Indicates that the device is scanning the vehicle system.

[Quick Erase] – Press this button to quickly clear the fault code.

 $[\mbox{Pause}]$ / $[\mbox{Continue}]$ – $\mbox{Press this button to pause or continue scanning.}$

[Report] – Press this button to view the fault reports generated during diagnosis.





[Back Button] – Returns to the previous screen or exits Auto Scan.

4.4.2 Control Unit

This option allows you to manually locate the desired control system. According to the menu driven program, the user manually selects the specified control unit that he wants to detect, skips the whole vehicle scanning, and directly carries out the diagnosis of the specified system.

4.4.3 Service

The vehicle diagnostic tool provides an entry from the diagnostic mode to the service function. You can easily select the service function from the diagnosis mode, without returning to the service menu for selection. For different vehicle models, the service functions are different. Select this option to perform service function and calibrating different systems, such as reset oil service lamp, EPB service, SAS service, Doors, windows and seat calibration learning and so on.

4.5 Diagnostic operation

This option allows you to manually locate a required control system for testing through a series of choices. Follow the menu driven procedures and make proper selection each time; the program will guide you to the diagnostic function menu after selections are made.




Figure 4-7 Sample Diagnostic Operation Screen



The Function Menu options vary slightly for different vehicles. The function menu may include:

- Module Information Read full electronic system module information, such as VIN, part number, version, supplier, production date of ECU.
- Read fault code Read full electronic system module fault code, show state and description of fault code.
- Clear fault Memory Erase full electronic system module fault code and diagnostic related freeze frame information.
- 4. **View data** Read full electronic system module live data by text value or waveform.
- Actuation Test This function provides access to vehicle specific subsystem tests and component tests.

> To perform a diagnostic function

- 1. Establish communication with the test vehicle.
- 2. Select "Diagnostic" icon.
- 3. Select Vehicle Manufacturer.
- 4. Select "Vehicle Select" and select vehicle model, model year, etc. according to the on-screen prompts.
- Select the diagnosis mode and guide the selection through the menu of any diagnosis mode to locate the required test system.
- 6. Select the test to be performed on the function list.

Module Information

This function retrieves and displays the specific information for the tested control unit, including unit type, version numbers and other specifications. Also you can save these data by press save button. The sample Module Information screen displays as below:

Read Fault Codes

This function retrieves and displays the DTCs from the vehicle's control system. The Read Codes screen varies for each vehicle being tested. On some vehicles, freeze frame data can also be retrieved for viewing. The sample Read Codes screen displays as below:

Functional Button

• Save – tap this icon to save the information related to the





fault code

- Back tap it to return to the previous screen or exit the function.
- tap this icon to view the information of the freeze frame.

Clear Fault Codes

After reading the retrieved codes from the vehicle and certain repairs have been carried out, you can erase the codes from the vehicle using this function. Before performing this function, make sure the vehicle's ignition key is in the ON (RUN) position with the engine off.

To erase codes

- Select the [Clear fault code] on the "function menu"
- At this time, a warning message will appear on the screen, indicating that the fault code and frozen data information will be cleared.
 - Select [OK] to continue. After the operation is successful, an complete information will be displayed on the screen.
 - b) Select [Cancel] to exit.
- Re-enter the [Read fault code] function to retrieve the fault code to ensure the successful code clearing operation.

View Data

When this function is selected, the screen displays the data list for the selected module. The items available for any control module vary from one vehicle to another. The parameters display in the order that they are transmitted by the ECM, so expect variation between vehicles.

Select any module manually, and you will enter the specific data flow list. Gesture scrolling allows you to quickly move through the data list. Simply swipe the screen up or down to locate the data you want. The figure below shows a typical Live Data screen:





Figure 4-8 Sample View Data Screen

Main Section

- Name Column displays the parameter names.
 - a) Check Box tap the check box on the left side of the parameter name to make item selection. Tap the check box again to de-select the item.
 - b) Data icon –tap the data icon on the far right to open the submenu that provides various choices for data display mode.
- Value Column displays the values of the parameter items.
- Unit Column displays the unit for the parameters.
 To change the unit mode, return to the "Settings" button and select the desired mode.

Display Mode

There are four types of display modes available for data viewing, allowing you to view various types of parameters in the most suitable way.

Tapping the drop-down button on the right side of the parameter name to open a sub menu. There are four buttons to configure the data display mode, and a Help button for access to additional information.

Each parameter item displays the selected mode independently.

1) Analog Gauge Mode – displays the parameters in form



of an analog meter graph.

 Text Mode – this is the default mode that displays the parameters in texts and displays in list format.



Reading of status parameters, such as a switch reading, which are mostly in word form, such as ON, OFF, ACTIVE, and ABORT, can only be displayed in Text Mode. Whereas reading of value parameters, such as a sensor reading, can be displayed in text mode and other graph modes.

- Waveform Graph Mode displays the parameters in waveform graphs. When this mode is applied, you can use two fingers to zoom in or out.
- Digital Gauge Mode displays the parameters in form of a digital gauge graph.

2. Functional Buttons

The operations of available functional buttons on Live Data screen are described below:

- Back returns to previous screen or exits the function.
- Search –search for parameter names to view data
- Record starts recording the retrieved live data; the recorded data is then stored as a video clip in the Data Manager application for future reviews.
- Freeze frame displays the retrieved data in freeze frame mode.
 - Previous Frame moves to the previous frame in the freeze frame data.
 - Next Frame moves to the next frame in the freeze frame data.
- Clear Data clears all previously retrieved parameter values at a selected point.
- To Top moves a selected data item to the top of the list.
- Graph Merge tap this button to merge selected data graphs (for Waveform Graph Mode only). This function is useful when making a comparisons between parameters.





This mode supports up to 4 "graphics merge" parameters.

To cancel Graph Merge mode, tap the \otimes button in the upper right corner.

 Show – tap this option to switch between the two options; one displays the selected parameter items, the other displays all the available items.

Actuation Test

The "Actuation Test" function accesses vehicle specific subsystem tests and performs component tests. The available test functions vary according to the manufacturer, year and model, and the menu will only show the available test options.

When performing the actuation test, the tester inputs the command to the ECU to drive the actuator. This test can monitor the operation of the actuator by reading the ECU data of the engine. For example, by repeatedly switching the two working states of the solenoid valve, relay and switch, it can determine whether the system or components are working normally, and execute the command of the switch on the door or window.

- Left / Right turn signals
 - Through the left / right turn signal action test item, you can control the left and right turn signal flashing to test whether the turn signal works normally.
- Window regulator front / rear left / right: down / up Through the window regulator action test item, you can control the whole vehicle window up and down to test whether the window up and down works normally.
- Windshield wiper motor (V) stage 1 / 2

Through the action test item of windshield wiper motor, the wiper can be controlled to work at $1\,/\,2$ gear to test whether the wiper motor works normally

4.6 Generic OBDII Operations

A fast-access option for OBDII/EOBD vehicle diagnosis is available on the Vehicle Menu screen. This option presents a quick way to check for DTCs. isolate the cause of an illuminated



malfunction indicator lamp (MIL), check monitor status prior to emissions certification testing, verify repairs, and perform a number of other services that are emissions-related.

4.6.1 General Procedure

To access the OBDII/EOBD diagnostics functions

- Tap the **Diagnostics** application button from the UR800 Job Menu. The Vehicle Menu displays.
- 2. Tap the **EOBD** button. The device will automatically establish communication with the vehicle, as shown in the figure below:
- Select a specific protocol under the **Protocol** option. 3. Wait for the OBDII Diagnostic Menu to display.




Figure 4-9 Sample OBDII Diagnostic Menu



Tapping (i) button beside the function name to display additional function information.

Select a function option to continue.

- Read Codes
- Erase Codes
- I/M Readiness
- Live Data
- Freeze Frame



- Vehicle Information
- O2 Monitor Test
- On-Board Monitor
- Evap System(mode\$8)



Some functions are supported only on certain vehicle manufacturers.

4.6.2 Function Descriptions

This section describes the various functions of each diagnostic option:

Read Codes

When this function is selected, the screen displays all the Stored, Pending and Permanent Codes. You can save the fault code information of the current page through the save button in the lower right corner.

Stored codes are the current emission related DTCs from the ECM of the vehicle. OBDII/EOBD Codes have a priority according to their emission severity, with higher priority codes overwriting lower priority codes. The priority of the code determines the illumination of the MIL and the codes erase procedure. Manufacturers rank codes differently, so expect to see differences between makes

Erase Codes

This option is used to clear all emission related diagnostic data such as, DTCs, freeze frame data and manufacturer specific enhanced data from the vehicle's ECM.


A confirmation screen displays when the clear codes option is selected to prevent accidental loss of data. Select "Yes" on the confirmation screen to continue or No to exit.

I/M Readiness

This function is used to check the readiness of the monitoring system. It is an excellent function to use prior to having a vehicle inspected for compliance to a state emissions program. Selecting I/M Readiness opens a submenu with two choices:

 Since Codes Cleared – displays the status of monitors since the last time the codes are erased.





Live Data

This function displays the real time PID data from ECU. Displayed data includes analog inputs and outputs, digital inputs and outputs, and system status information broadcast on the vehicle data stream.

Live data can be displayed in various modes, see **View Data** on section 4.5 for detailed information.

Freeze Frame

In most cases the stored frame is the last DTC that occurred. Certain DTCs, which have a greater impact on vehicle emission, have a higher priority. In these cases, the top prioritized DTC is the one for which the freeze frame records are retained. Freeze frame data includes a "snapshot" of critical parameter values at the time the DTC is set.

Vehicle Information

The option displays the vehicle identification number (VIN), the calibration identification (CID), and the calibration verification number (CVN), and other information of the test vehicle.

O2 Monitor Test

This option allows you access and show the Oxygen Monitor Sensor value, which indicates the car emission status.

On-Board Monitor

This option allows you to view the results of On-Board Monitor tests. The tests are useful after servicing or after erasing a vehicle's control module memory.

Evap System

This item is used to issue the EVAP system test command.

4.7 Exiting Diagnostics

The Diagnostics application remains open as long as there is active communication with the vehicle. You must exit the diagnostics operation to stop all communications with the vehicle before closing the Diagnostics application.



Damage to the vehicle electronic control module (ECM) may occur



if communication is disrupted. Make sure all connections, such as diagnostic cable, USB cable and wireless connections, are properly connected at all times during testing. Exit all tests before disconnecting the test connection or powering down the tool.

> To exit the Diagnostics application

- From an active diagnostic screen, tap the Back or ESC functional button to exit a diagnostic session step-by-step.
- From the Vehicle Menu screen, tap the Back button on the top toolbar; or tap the Back button on the navigation bar at the bottom of the screen.
- Or tap the **Home** button on the diagnostics toolbar to exit the application directly and return to the UR800 Job Menu.

Once the Diagnostics application is no longer communicating with the vehicle, it is safe to open other UR800 applications, or exit the UR800 Diagnostic System and return to the Android System's Home screen.

5 Service Operations

The Service section is specially designed to provide you with quick access to the vehicle systems for various scheduled service and maintenance performances. The typical service operation screen is a series of menu driven executive commands. By following the on-screen instructions to select appropriate execution options, enter correct values or data, and perform necessary actions, the system will guide you through the complete performance for various service operations.

This product contains a variety of service functions. After entering each special function, the screen will display the Vehicle Manufacturer, you need to make a step-by-step selection according to your test vehicle.



Figure 5-1 Sample Service Function List

5.1 Oil Reset (OIL) Service

This function allows you to perform reset for the Engine Oil Life system, which calculates an optimal oil life change interval depending on the vehicle driving conditions and climate. The Oil Life Reminder must be reset every time the oil is changed, so the system can calculate when the next oil change is required. Different vehicles may have different methods to do the oil maintenance, generally, oil change is required whenever oil lamp is on and the recommended maintenance period is reached. The Oil Reset function can reset the maintenance period and distance and turn off the lamp when you really change the oil.

NOTE

All required work must be carried out before the service indicators are reset. Failure to do so may result in incorrect service values and cause DTCs to be stored by the relevant control module.

5.2 Electronic Parking Brake (EPB) Service

This function has a multitude of usages to maintain the electronic braking system safely and effectively. The applications include deactivating and activating the brake control system, assisting with brake fluid control, opening and closing brake pads, and setting brakes after disc or pad replacement.

Electronic Parking Brake (EPB) system maintenance,



deactivates and reactivates the EPB system for replacement and initialization.

5.3 Steering Angle Sensor (SAS) Service

SAS: Steering Angle Sensor (SAS) calibration, calibrates the steering wheel to straight ahead, or recalibrates SAS while steering part replacement.

Calibration must be completed after the following operations:

- Steering wheel replacement
- Steering angle sensor replacement
- Any maintenance involving opening the connector hub from the steering angle sensor to the column
- Any maintenance or repair work on the steering linkage, steering gear or other related mechanism
- Wheel alignment or wheel track adjustment
- Accident repairs where damage to the steering angle sensor or assembly, or any part of the steering system may have occurred.

NOTE

- iCarzone accepts no responsibility for any accident or injury arising from servicing the SAS system. When interpreting DTCs retrieved from the vehicle, always follow the manufacturer's recommendation for repair.
- All software screens shown in this manual are examples, actual test screens may vary for each vehicle being tested. Observe the menu titles and on-screen instructions to make correct option selections.
- 3) Before starting the procedure, make sure the vehicle has an ESC button. Look for the button on dash.

Steering Column Calibration

If the steering column or instrument cluster is replaced or the instrument cluster software is updated, a body system steering column calibration is required.

5.4 Electronic Throttle Control (ETC)



Service

FΝ

Electronic Throttle Control system (ETC), relearns the throttle value control value while clear or replace the throttle value.

5.5 Diesel Particulate Filter (DPF) Service

The DPF function allows you to carry out numerous functions to the Diesel Particulate Filter system. The tool will manage DPF regeneration, DPF component replacement teach-in and DPF teach-in after replacing the engine control unit.

The ECM monitors driving style and selects a suitable time to employ regeneration. Cars driven primarily at idling speed and low load will attempt to regenerate earlier than cars driven with higher loads and at higher speed. For regeneration to occur, a prolonged high exhaust temperature must be obtained.

In the event that the vehicle has been driven in such a way that regeneration is not possible, a diagnostic trouble code will be registered, DPF light and "Check Engine" indicator will display. A service regeneration can be performed using this tool.

Before carrying out a forced DPF regeneration, check the following items:

- The fuel light is not on.
- No DPF-relevant faults are stored in system.
- The vehicle has the correct spec engine oil.
- The oil for diesel is not contaminated.

IMPORTANT

Before diagnosing a vehicle and attempting to perform an emergency regeneration, it is important to obtain a full diagnostic log and read out relevant measured value blocks.

NOTE

- The DPF will not regenerate if the engine management light is on, or there is a faulty EGR valve.
- The ECU must be re-adapted when replacing the DPF and adding the fuel additive eolys.
- 3) If the vehicle needs to be driven in order to perform a DPF

30



service, ALWAYS have a second person help you. One person should drive the vehicle while the other person observes the screen on the Tool. Trying to drive and observe the Scan Tool at the same time is dangerous, and could cause a serious traffic accident.

5.6 Battery Management System (BMS) Service

The BMS (Battery Management System) allows the scan tool to evaluate the battery charge state, monitor the close-circuit current, register the battery replacement, and activate the rest state of the vehicle.

NOTE

- 1) This function is not supported by all vehicles.
- The sub functions and actual test screens of the BMS may vary by vehicle. Please follow the on-screen instructions to make the correct selection.

The vehicle may use either a sealed lead-acid battery or an AGM (Absorbed Glass Mat) battery. Lead acid battery contains liquid sulphuric acid and can spill when overturned. AGM battery (known as VRLA battery, valve regulated lead acid) also contains sulphuric acid, but the acid is contained in glass mats between terminal plates.

It is recommended that the replacement aftermarket battery have the same specifications, such as capacity and type, as the battery in the vehicle. If the original battery is replaced with a different type of battery (e.g. a lead-acid battery is replaced with an AGM battery) or a battery with a different capacity (mAh), the vehicle may require reprogramming the new battery type in addition to performing the battery reset. Consult the vehicle manual for additional vehicle-specific information.

Register Battery Replacement

This option allows displaying the mileage reading of last battery replacement, registering the battery replacement after replacing a new battery and informing the power management system that a new battery has been fitted to the vehicle.

If the battery change is not registered, the power management system will not function properly, which may not provide the battery





FΝ

with enough charging power to operate the car and limit the functions of individual electrical equipment.

ABS Bleeding (BLD) Service

When the ABS contains air, or the ABS computer / ABS pump / brake master cylinder / brake cylinder/ brake fluid is replaced, the ABS bleeding function must be performed to bleed the brake system to restore ABS brake sensitivity.

Injector Coding (INJ) Service 5.8

When individual injectors are renewed, the injector control module requires the new configuration values for the injector to perform correctly. Write injector actual code or rewrite code in the ECU to the injector code of the corresponding cylinder so as to more accurately control or correct cylinder injection quantity. After the ECU or injector is replaced, injector code of each cylinder must be confirmed or re-coded so that the cylinder can better identify injectors to accurately control fuel injection.

If the vehicle has replaced the fuel injector, in order to ensure the normal operation of the fuel injector, you need to carry out this operation to replace the fuel injector code.

Tire Pressure Monitor System (TPMS) service

The TPMS service function include displaying sensor IDs from the vehicle's ECU, inputting TPMS sensor replacement IDs and testing sensors.

Select tire pressure sensor replacement (Front right wheel sensor) as an example.

NOTE

- 1) This function will require the sensor ID be inputted on the screen.
- 2) The sensor IDs can be read directly from the sensor or by using a sensor activation tool that can read the ID.
- Once the IDs have been entered, the vehicle may have to be 3) driven at a certain speed for a certain time to complete procedure. Follow the instructions displays.

Select tire pressure sensor replacement (Front right wheel



sensor) as an example.

Tire pressure sensor replacement:

During this application the wheel unit 8-bits identifications will need to be entered using the screens provided. The sensor identifications can be accessed by reading directly from the wheel unit or by using the identification reading tool. On completion, a specific road test will be required followed by the tire pressure monitor system confirmation application.

NOTE

The vehicle must remain stationary for at least 15 minutes with the ignition off, this will place the sensors into sleep mode. The vehicle must be driven for at least 15 minutes at a speed higher than 20 kph to ensure the module has learned the sensor identifications and positions.

For other services, please follow the on-screen instructions to operate. On completion of the drive cycle, carry out the tire pressure monitor system test application.

5.10 Air Suspension

Air Suspension: After maintenance, replacement and other operations of the suspension height sensor are performed in all aspects, this function needs to be executed for suspension learning and calibration.

5.11 Air conditioner service

After the refrigerant, blower pump, etc. in the air conditioner are replaced, the air conditioning system may not work normally. At this time, this function is needed to activate the air conditioner for a period of time to match the replaced refrigerant, blower pump and other automotive components.

5.12 Head Lamp reset

Head Lamp is about the headlamp maintenance, nd other related operations (including AFS setting), and then perform this function for calibration.

If the vehicle has a headlamp replacement, the calibration of the headlamp leveling height sensor needs to be performed.

5.13 Gearbox Reset



After the gearbox is disassembled or repaired, it will cause shift delay or shock problems. At this time, this function needs to be executed to make the gearbox automatically compensate according to the driving conditions in order to achieve a more comfortable and more ideal shift quality.

5.14 Air Filter

The engine is a very precise machine part, and even the smallest impurities will cause the wear of the engine. Therefore, the air must be filtered by the air cleaner before entering the cylinder. Therefore, the disassembly, maintenance or replacement of the air filter will cause some particulate impurities in the air to enter the car parts. At this time, the air filter learning and matching functions need to be performed to make the air filter work normally.

5.15 Fuel Pump activation function

After the fuel pump is disassembled, repaired or replaced, it may cause the fuel pump to be unable to continuously provide fuel to the fuel injection nozzle. At this time, the function needs to be executed to activate the replaced fuel pump so that the car can start to inject fuel normally and make the engine achieve the ideal Running status.

5.16 Engine Idle

This correction can be executed when the idle speed fault is resolved. Adjust the engine speed of the car at idle speed.

5.17 Body stability

Learning and calibration after replacing the body stability control unit and other related components, such as: lateral acceleration sensor for active roll stabilization system, BAS brake assist system, ESP electronic stability program, calibration of yaw rate / lateral and longitudinal acceleration sensors, pedal angle Sensors, etc.

5.18 Door

After repairing or replacing the window lift motor, it is necessary to perform relevant functions for calibration.

Door Window Calibration:

This routine learns the top position of the door window glass, which enables pinch protection and one touch up function. The



door window glass position can be learned by executing this routine.

5.19 Seat

After repairing or replacing the seat position drive motor, it is necessary to perform relevant functions for calibration.

Driver's Seat Calibration:

The routine will restore all the seat axis position values to default for the driver's seat module.

Passenger's Seat Calibration:

The routine will restore all the seat axis position values to default for the passenger seat module.

5.20 Engine Control Module

This function category definition includes the related maintenance functions of the engine system.

5.21 Air Bag

This function category definition includes related maintenance functions of airbag systems.

5.22 Odometer

This function is used to read or set mileage information.

5.23 Cylinder

This function is used for engine cylinder related maintenance functions.

5.24 ECM Correction

This function is used for data calibration of engine modules.

5.25 Immobilizer

This function is used for anti-theft module related maintenance functions, such as key programming, delete lost keys, etc.

5.26 Exhaust Gas Recirculation

This function is used for exhaust gas detection module related



ΕN

maintenance functions.

5.27 TPMS Programming

This function is used for programming or cloning tire pressure sensors for vehicles with tire pressure monitoring systems.

5.28 AdBlue

It is used for matching operation after replacing or filling diesel exhaust liquid (i.e. automotive urea).

5.29 Clutch

This function is used for clutch-related maintenance functions, such as clutch learning when removing the gearbox or replacing the clutch.

5.30 Water Pump

This function is used for pump related maintenance functions, such as matching after pump replacement.

5.31 Crankshaft

This function is used for crankshaft related maintenance functions, such as crankshaft position learning.

5.32 Gas Particulator Filter

This function is used for gasoline particulate filter related service functions such as GPF replacement and regeneration.

5.33 High Voltage Battery

This function is used for high voltage battery system related maintenance functions, such as high voltage battery replacement, high voltage battery status information monitoring.

5.34 Cruise Control System

This function is used for adaptive cruise system related maintenance functions, such as adaptive cruise personalization.

5.35 Language Setting

System language Settings for vehicle center console.



5.36 NOx Sensor

This function is used for nitrogen and oxygen sensor related maintenance functions.

5.37 Rain Sensor

This function is used for maintenance functions related to rain sensors

5.38 Stop And Start

This function is used to automatically start and stop related maintenance functions.

5.39 Turbocharger

This function is used for engine turbocharger related maintenance functions.

5.40 Head-Up Display

This function is used for learning and calibration of heads-up display.

5.41 Radar/Camera

This function is used for radar camera learning and calibration.

5.42 Vehicle Setup

This function is used for vehicle personalization.

5.43 Cylinder Shutoff Test

This function is used for engine cylinder break test, check the working condition of each cylinder of the engine by cutting off the oil circuit.

5.44 Cylinder Misfire Check

It is used for engine fire detection, when the vehicle has insufficient cylinder work such as weak acceleration, increased fuel consumption or serious jitter.

5.45 Speed Limit Assist





This function is used to set or remove the vehicle's maximum speed limit.

5.46 Control Unit Reset

This function is used to reset the control unit.

5.47 Oxygen Sensor

This function is used for oxygen sensor replacement, initializing the learning value of the three-way catalytic converter, etc.

5.48 Seat Belt

This function is used for seatbelt related maintenance functions.

5.49 Miscellaneous

This function is used for other types of service functions that are not yet classified

NOTE

Different models will have different menu modes. This manual is for reference. Everything in kind shall prevail. If there is any increase or decrease in the function of the product, the actual product shall prevail.

6 Upgrade

The Update application allows you to download the latest released software. The updates can improve the UR800 applications' capabilities, typically by adding new tests, new models, or enhanced applications.

The tablet automatically searches for available updates for the UR800 software when it is connected to the internet. Any updates that are found can be downloaded and installed on the device. This section describes installing an update to the UR800 System.





Figure 6-1 Sample Update Screen - for UR800

Navigation and Controls

- Back Button returns to the UR800 Job Menu.
- Update All downloads all available updates.
- Language option button select the language list to download.

② Status Bar

- Left Side displays the UR800 device model information and serial number.
- Right Side displays an update progress bar indicating the completion status.

3 Main Section

- Left Column –displays the name of the software, software version and size.
- Middle Column –displays a summary of software changes, including detailed information. Tap (i) button to open the information screen to view detailed information. Tap the (x) button to turn it off.
- Right Column controls software update. According to the status of the software download, a different titled button displays.
 - Tap the download icon to update the item you want to update.
 - b) Tap the (X) icon to cancel the software update.



To update the software and database

- Make sure the Display Tablet is connected to a power source with stable access to the internet.
- Tap the Upgrade application button from the UR800 Job Menu; or tap the update notification message when received; or tap the Upgrade icon on Vehicle Menu in Diagnostics application. The Update application screen displays.
- 3. Check all available updates:
 - If you decide to update all items of the software, please tap the "Download All" button.
 - If you only want to update one or some of the item(s), tap the **Update** button on the right column of the specific item(s).
- Tap the **download** button to start the update. Tap the

 button to cancel the update.

The software will be installed automatically once its download has completed. The previous version will be replaced.

7 Vehicle History

This function stores test vehicle history records, including vehicle information and the retrieved DTCs from previous diagnostic sessions. All information is displayed in summarized details. Tap on a record to resume a diagnostic session on a "stored vehicle".





Figure 7-1 Sample Vehicle History Screen

To activate a test session for the recorded vehicle

- Select Vehicle History application on the UR800 Job Menu.
- The drop-down button to the left of the list shows or hides the Historical Diagnostic Records thumbnail. Click on the thumbnail to go to the next level of historical diagnostic data detail page. The Diagnostics button in the upper right corner provides quick access to diagnostics.

To delete the historical diagnostic records, click on the tick box in the lower right corner of the thumbnail to select it, and then click on the Delete button in the upper left corner of the navigation bar.

8 User Data

The User Data application is used to store and view saved files. Contains images, play back, user manual, Fault Code, Report, DLC Location. Details are explained in the following sections.

8.1 Image Files

The Image section contains all captured screenshot images. The image section allows you to view all the screenshots.

8.2 Play Back

The playback section allows you to view diagnostic data, live data, and fault codes on the system.

To view live data:

 Tap the Play back icon on the User Data application. The screen display the data list of diagnostic data, live data, and fault codes.



ΕN



Figure 8-1 Sample Play Back Screen

2. Select a list, the screen will enter the data flow recording interface.



Figure 8-2 Sample Play Back Screen

Select the check box in the lower right corner of each list, tap the button in the upper right corner to execute PDF output function or delete.





Figure 8-3 Sample Play Back Screen

Perform PDF output function:

- Select one or more data lists and tap the button enter the interface. In this interface, you can still move up, down, and delete.
- 2) After the adjustment is completed, tap the button the upper right corner, and an interface for outputting the report to PDF appears. Fill in the file name, vehicle, customer, and operator, and press the save button.
- 3) After the save is complete, the screen will show a message indicating that the save is successful, and inform the user of the save path of the report. Return to the previous menu, you can view the converted PDF report in "Report".





Figure 8-4 Sample Play Back Screen

8.3 User Manual

The user manual section provides users to view the UR800 user manual, quick operation guide, how to create a report, how to perform feedback, etc.

8.4 Fault Code

Fault code allows you to query the fault history and information description according to the model fault code. Slide up and down to select the required model and code.

To access fault code

- 1. Tap the Fault Code application on the UR800 Job Menu.
- Slide up and down to select the required model and code.
- 3. Tap the **lookup button** in the upper right corner, and the query results will be displayed in the box below.
- 4. Tap the history button to view the relevant history.
- 5. Tap the information button to pop up the description of fault code information.



8.5 Report

In the Report option, view the report of the vehicle data in Play Back after the PDF is output.

8.6 Data Link Connector (DLC) Location

This function is to provide the location of the data link connector (DLC), represented by A, B, C, D, E respectively.

9 Setting

Selecting Settings application opens a setup screen to adjust the default setting and view information about the UR800 system. There are twelve system settings:

- Unit
- Language
- Data Log
- WIFI
- Data & time
- Brightness
- Screen Sleep
- Vehicle Sorted By
- Restore Default User Profiles
- Restore Factory Settings
- Screenshot Switch
- Privacy Policy

9.1 Unit

This option allows you to change the measurement unit for the diagnostic system. Select the required measurement unit, Metric or Imperial. A check mark will display on the right of the selected unit.

9.2 Language

This option allows you to adjust the display language of the UR800 application, which is available in several languages.

9.3 Data log





This option allows you to access the diagnostic system log. It's controlled by a slide switch. Turn on the switch, the diagnostic equipment will automatically backup the diagnostic files of the diagnostic system.

9.4 WIFI

This option allows you to enter the Android background WiFi option settings and select the available network settings.

9.5 Data & Time

This option allows you to enter the Android background time and date option to set the corresponding time and date.

9.6 Brightness

This option allows you to modify the brightness setting of the diagnostic system.

9.7 Screen Sleep

This option allows you to modify the screen lock time setting for the diagnostic system. There are 5 options, namely 1 minute, 2 minutes, 5 minutes, 10 minutes, 15 minutes. A check mark appears to the right of the selected cell.

9.8 Vehicle Sorted By

This option allows you to modify the vehicle classification settings. alphabetically or by frequency of use.

9.9 Restore Default User Profiles

This option allows you to return to Default User Profiles. This operation will initialize all data in the application settings, including unit, brightness, data switch, screen sleep, vehicle sorted by, data log, image, play back, vehicle history and report.

9.10 Restore Factory Settings

This option allows you to return to factory tablet system. This operation will restore the system version to the factory version and clear all data, including system and app data and settings, downloaded apps and other user data.

9.11 Screenshot Switch



This option allows you to take screenshots of the screen you need. It is controlled by a sliding switch. The screen capture button will appear on the interface in the form of a floating box when the switch is turned on.

9.12 Privacy Policy

This option allows you to view the privacy policy of the UR800 application.

10 Uninstall

This section allows you to manage the software applications installed on the UR800 Diagnostics System. Select this section to open a management screen, on which you can check all the available vehicle diagnostic applications.

By clicking on each line of car brand to select the car software to be removed, the selected item displays a red check in the check box on the right. Tap the **Delete** button on the top bar to remove the software from the system database.

11 Support

This application launches the Support platform which synchronizes iCarzone's on-line service base station with the Display Tablet. In order to synchronize the device to your on-line account, you need to register the product through the Internet when you use it for the first time. The Support application is connected to iCarzone's service channel and on-line communities which provides the quickest way for problem solutions, allowing you to submit complaints or sent help requests to obtain direct services and supports.

11.1 Data Log

The "Data Log" screen displays the data log stored when the diagnostic device performs the diagnosis. When the log switch in the "Settings" option is turned on, the data log will be automatically stored. Select the check box behind the log, you can delete, you can also provide information feedback.

 Select the check box behind the log, you can select multiple logs at the same time, tap the delete button in the





upper right corner to delete.

- Select the check box behind the log, you can select
 multiple logs at the same time, tap the
 button in the upper right corner. The interface for
 information feedback will appear.
- 3. Enter the title, description, vehicle information, etc. in the input box, "*" is required. Then tap the Upload button to submit feedback. You can also tap the "+" button to add up to 3 photos to submit together.

12 About

The About screen lists the UR800 version, hardware, and serial number, storage and etc.

13 Maintenance and Service

13.1 Maintenance Instructions

The following shows how to maintain your devices, together with precautions to take.

- Use a soft cloth and alcohol or a mild window cleaner to clean the touch screen on the tablet
- Do not use any abrasive cleansers, detergent, or automotive chemicals to the tablet.
- Only use the device in dry conditions within normal operating temperatures.
- Dry your hands before using the tablet. The touch screen of the tablet may not work if the touch screen is moist, or if you tap the touch screen with wet hands.
- Do not store the devices in humid, dusty or dirty areas.
- Before and after use, check the housing, wiring, and connectors for dirt and damage before and after each use.



- At the end of each work day, wipe the device housing, wiring, and connectors clean with a damp cloth.
- Do not attempt to disassemble your tablet or other accessories.
- Take care not drop the device or allow anything heavy to drop on the device.
- Use only authorized battery chargers and accessories. Any malfunction or damage caused by the use of unauthorized battery charger and accessories will void the limited product warranty.
- Ensure that the battery charger does not come in contact with conductive objects.
- Do not operate the tablet next to anything such as microwave oven, cordless phones and some medical or scientific instruments that might interfere with or prevent signal interference.

13.2 Troubleshooting Checklist

A. When the Display Tablet does not work properly:

- Make sure the tablet has been registered online.
- Make sure the system software and diagnostic application software are properly updated.
- Make sure the tablet is connected to the Internet.
- Check all cables, connections, and indicators to see if the signal is being received.

B. When battery life is shorter than usual:

 This may happen when you are in an area with low signal strength. Turn off your device when not in use.

C. When you cannot turn on the tablet:

 Make sure the tablet is connected to a power source or the battery is charged.

D. When you are unable to charge the tablet:

- Your charger maybe out of order. Contact your nearest dealer.
- You may be attempting to use the device in an overly hot/cold temperature. Try changing the charging environment.



 Your device may have not been connected to the charger properly. Check the connector.

NOTE

ΕN

If your problems persist, please contact iCarzone's technical support personnel or your local selling agent.

13.3 About Battery Usage

Your tablet is powered by a built-in Lithium-ion Polymer battery. This means that, unlike other forms of battery technology, you can recharge your battery while some charge remains without reducing your tablet's autonomy due to the "battery memory effect" inherent in those technologies.

DANGER

The built-in Lithium-ion Polymer battery is factory replaceable only; incorrect replacement or tampering with the battery pack may cause an explosion. Do not use a damaged battery charger.

- Do not disassemble or open crush, bend or deform, puncture or shred.
- Do not modify or remanufacture, attempt to insert foreign objects into the battery, expose to fire, explosion or other hazard.
- Make sure to use the charger and USB cables only that come together in the package. If you use the other charger and USB cables, you might incur malfunction or failure of the device.
- Only use the charging device that has been qualified with device per the standard. Use of an unqualified battery or charger may present a risk of fire, explosion, leakage, or other hazard.
- Avoid dropping the tablet. If the tablet is dropped, especially on a hard surface, and the user suspects damage, take it to a service center for inspection.
- The closer you are to your network's base station, the longer your tablet usage time because less battery power is consumed for the connection.
- The battery recharging time varies depending on the remaining battery capacity.
- Battery life inevitably shortens over time.



- Since over charging may shorten battery life, remove the tablet from its charger once it is fully charged. Unplug the charger, once charging is complete.
- Leaving the tablet in hot or cold places, especially inside a car in summer or winter, may reduce the capacity and life of the battery. Always keep the battery within normal temperatures.

13.4 Service Procedures

This section introduces information for technical support, repair service, and application for replacement or optional parts.

13.4.1 Technical Support

If you have any question or problem on the operation of the product, please contact us (see the following contact info) or your local distributor.

ICARZONE USA HQ

Website: www.icarzone.net

Email: support@icarzone.us

13.4.2 Repair Service

If it becomes necessary to return your device for repair, please download the repair service form from www.iCarzone.net, and fill it in. The following information must be included:

- Contact name
- Return address
- Telephone number
- Product name
- Complete description of the problem
- Proof-of-purchase for warranty repairs
- Preferred method of payment for non-warranty repairs



For non-warranty repairs, payment can be made with Visa, Master Card, or with approved credit terms.

Send the device to your local agent, please contact your dealer.

13.4.3 Other Services



ΕN

You can purchase the optional accessories directly from iCarzone's authorized tool suppliers, and/or your local distributor or agent.

Your purchase order should include the following information:

- Contact information
- Product or part name
- Purchase quantity

14 Compliance Information

FCC Requirement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

WARNING

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from



that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

RF WARNING STATEMENT

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

The term "IC" before the radio certification number only signifies that IC technical specifications were met.

Rohs Compliance

This device is declared to be in compliance with the European RoHS Directive 2011/65/EU&2015/863/EU.

CE COMPLIANCE

This product is declared to conform to the essential requirements of the following Directives and carries the CE mark accordingly:

EMC Directive

RED Directive

Low Voltage Directive

15 Warranty

15.1 Limited One Year Warranty

iCarzone Technology Inc. (the Company) warrants to the original retail purchaser of this UR800 Diagnostic Device, that should this product or any part thereof during normal consumer usage and conditions, be proven defective in material or workmanship that results in product failure within one (1) year period from the date of purchase, such defect(s) will be repaired, or replaced (with new or rebuilt parts) with Proof of Purchase, at the Company's option, without charge for parts or labor directly related to the defect(s).

The Company shall not be liable for any incidental or consequential damages arising from the use, misuse, or mounting





of the device. Some states do not allow limitation on how long an implied warranty lasts, so the above limitations may not apply to you.

This warranty does not apply to:

- a) Products subjected to abnormal use or conditions, accident, mishandling, neglect, unauthorized alteration, misuse, improper installation or repair or improper storage;
- Products whose mechanical serial number or electronic serial number has been removed, altered or defaced;
- Damage from exposure to excessive temperatures or extreme environmental conditions;
- Damage resulting from connection to, or use of any accessory or other product not approved or authorized by the Company;
- e) Defects in appearance, cosmetic, decorative or structural items such as framing and non-operative parts.
- f) Products damaged from external causes such as fire, dirt, sand, battery leakage, blown fuse, theft or improper usage of any electrical source.

IMPORTANT

All contents of the product may be deleted during the process of repair. You should create a back-up copy of any contents of your product before delivering the product for warranty service.

iCarzone Inc. www.icarzone.net All Rights Reserved