



# FCC TEST REPORT

## FCC Part 18

### FCC ID:2A4LH-PN-W36

**Report Number**.....: **ZKT-230418L2772E**

**Date of Test**.....: Apr. 13, 2023 to Apr. 23, 2023

**Date of issue**.....: Apr. 23, 2023

**Total number of pages**.....: 18

**Test Result** .....: PASS

**Testing Laboratory**.....: **Shenzhen ZKT Technology Co., Ltd.**

**Address** .....: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

**Applicant's name** .....: **Shenzhen Pannizhe Technology Co., Ltd.**

**Address** .....: 2nd Floor 7th Building Tiankou Industrial Park Huangtian  
Xixiang Town Baoan District Shenzhen, China 518128

**Manufacturer's name** .....: **Shenzhen Pannizhe Technology Co., Ltd.**

**Address** .....: 2nd Floor 7th Building Tiankou Industrial Park Huangtian  
Xixiang Town Baoan District Shenzhen, China 518128

**Test specification:**

**Standard**.....: FCC Part 18

**Test procedure**.....: /

**Non-standard test method** .....: N/A

**Test Report Form No.**.....: TRF-EL-117\_V0

**Test Report Form(s) Originator**.....: ZKT Testing

**Master TRF** .....: Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

**Product name**.....: Power Bank

**Trademark** .....: N/A

**Model/Type reference**.....: PN-W36

Capacity:1000mAh/3.7V

**Ratings**.....: Input : DC 5V 1A

Wireless Output: 5V/500mA



**Testing procedure and testing location:**

**Testing Laboratory**.....: **Shenzhen ZKT Technology Co., Ltd.**

**Address**.....: 1/F, No. 101, Building B, No. 6, Tangwei Community  
Industrial Avenue, Fuhai Street, Bao'an District,  
Shenzhen, China

**Tested by (name + signature)**.....: Alen He

**Reviewer (name + signature)**.....: Joe Liu

**Approved (name + signature)**.....: Lake Xie





## TABLE OF CONTENT

|                                                               | Page      |
|---------------------------------------------------------------|-----------|
| <b>1.VERSION .....</b>                                        | <b>4</b>  |
| <b>2.GENERAL INFORMATION .....</b>                            | <b>5</b>  |
| 2.1 Description of Device (EUT) .....                         | 5         |
| 2.2 Tested System Details .....                               | 5         |
| 2.3 Test Facility .....                                       | 5         |
| 2.4 MEASUREMENT UNCERTAINTY .....                             | 6         |
| 2.5 Test Instrument Used .....                                | 7         |
| <b>3.CONDUCTED EMISSION AT THE MAINS TERMINALS TEST .....</b> | <b>9</b>  |
| 3.1 Block Diagram Of Test Setup .....                         | 9         |
| 3.2 Test Standard .....                                       | 9         |
| 3.3 Power Line Conducted Emission Limit .....                 | 9         |
| 3.4 EUT Configuration on Test .....                           | 9         |
| 3.5 Operating Condition of EUT .....                          | 9         |
| 3.6 Test Procedure .....                                      | 9         |
| 3.7 Test Result .....                                         | 9         |
| <b>4.RADIATION EMISSION TEST .....</b>                        | <b>12</b> |
| 4.1 Block Diagram of Test Setup .....                         | 12        |
| 4.2 Test Standard .....                                       | 12        |
| 4.3 Radiation Limit .....                                     | 12        |
| 4.4 EUT Configuration on Test .....                           | 13        |
| 4.5 Operating Condition of EUT .....                          | 13        |
| 4.6 Test Procedure .....                                      | 13        |
| 4.7 Test Result .....                                         | 14        |
| <b>5.EUT PHOTOGRAPHS .....</b>                                | <b>18</b> |
| <b>6.EUT TEST PHOTOGRAPHS .....</b>                           | <b>18</b> |



1.VERSION

| Report No.       | Version | Description             | Approved      |
|------------------|---------|-------------------------|---------------|
| ZKT-230418L2772E | Rev.01  | Initial issue of report | Apr. 23, 2023 |
|                  |         |                         |               |
|                  |         |                         |               |



## 2.GENERAL INFORMATION

### 2.1 Description of Device (EUT)

|                  |   |                                                                                              |
|------------------|---|----------------------------------------------------------------------------------------------|
| EUT              | : | Power Bank                                                                                   |
| Trademark        | : | N/A                                                                                          |
| Model Number     | : | PN-W36                                                                                       |
| Model Difference | : | /                                                                                            |
| Power Supply     | : | DC 5V From adapter input AC 120V/60Hz for charging and DC 3.7V From Battery for Discharging. |

### 2.2 Tested System Details

None.

### 2.3 Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment  | Mfr/Brand | Model/Type No. | Series No. | Note      |
|------|------------|-----------|----------------|------------|-----------|
| E1   | Power Bank | N/A       | PN-W36         | N/A        | EUT       |
| E2   | Watch      | N/A       | CS01           | N/A        | Auxiliary |
| E3   | Adapter    | N/A       | PD-014         | N/A        | Auxiliary |
|      |            |           |                |            |           |

### 2.4 Test mode

| Test Modes:                                                                               |                                |            |
|-------------------------------------------------------------------------------------------|--------------------------------|------------|
| Mode 1                                                                                    | AC/DC Adapter + EUT (Charging) | Pre-tested |
| Mode 2                                                                                    | EUT+Watch (Discharging)        | Record     |
| Note: All test modes were pre-tested, but we only recorded the worst case in this report. |                                |            |



## 2.5 Test Facility

### Site Description

Name of Firm : Shenzhen ZKT Technology Co., Ltd.

Site Location : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225  
Designation Number: CN1299  
IC Registered No.: 27033

## 2.6 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| Test item                            | Value (dB) |
|--------------------------------------|------------|
| Conducted Emission (150K-30MHZ)      | 3.20       |
| Radiated disturbance (30MHz-1000MHz) | 4.80       |
|                                      |            |



## 2.7 Test Instrument Used

## Radiation Test equipment

| Item | Equipment                         | Manufacturer   | Type No.        | Serial No.        | Last calibration | Calibrated until |
|------|-----------------------------------|----------------|-----------------|-------------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz)  | KEYSIGHT       | 9020A           | MY55370835        | Oct. 28, 2022    | Oct. 27, 2023    |
| 2    | Spectrum Analyzer (10kHz-39.9GHz) | R&S            | FSQ             | 100363            | Oct. 28, 2022    | Oct. 27, 2023    |
| 3    | EMI Test Receiver (9kHz-7GHz)     | R&S            | ESCI7           | 101169            | Oct. 28, 2022    | Oct. 27, 2023    |
| 4    | Bilog Antenna (30MHz-1500MHz)     | Schwarzbeck    | VULB9168        | N/A               | Nov. 02, 2022    | Nov. 01, 2023    |
| 5    | Horn Antenna (1GHz-18GHz)         | Agilent        | AH-118          | 071145            | Nov. 01, 2022    | Oct. 31, 2023    |
| 6    | Horn Antenna (15GHz-40GHz)        | A.H.System     | SAS-574         | 588               | Oct. 28, 2022    | Oct. 27, 2023    |
| 7    | Loop Antenna                      | TESEQ          | HLA6121         | 58357             | Nov. 01, 2022    | Oct. 31, 2023    |
| 8    | Amplifier (30-1000MHz)            | EM Electronics | EM330 Amplifier | 060747            | Nov. 15, 2022    | Nov. 14, 2023    |
| 9    | Amplifier (1GHz-26.5GHz)          | Agilent        | 8449B           | 3008A00315        | Oct. 28, 2022    | Oct. 27, 2023    |
| 10   | Amplifier (500MHz-40GHz)          | 全聚达            | DLE-161         | 097               | Oct. 28, 2022    | Oct. 27, 2023    |
| 11   | Test Cable                        | N/A            | R-01            | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 12   | Test Cable                        | N/A            | R-02            | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 13   | Test Cable                        | N/A            | R-03            | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 14   | Test Cable                        | N/A            | RF-01           | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 15   | Test Cable                        | N/A            | RF-02           | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 16   | Test Cable                        | N/A            | RF-03           | N/A               | Oct. 28, 2022    | Oct. 27, 2023    |
| 17   | ESG Signal Generator              | Agilent        | E4421B          | N/A               | Oct. 21, 2022    | Oct. 20, 2023    |
| 18   | Signal Generator                  | Agilent        | N5182A          | N/A               | Oct. 21, 2022    | Oct. 20, 2023    |
| 19   | Magnetic Field Probe Tester       | Narda          | ELT-400         | 0-0344            | Nov. 15, 2022    | Nov. 14, 2023    |
| 20   | Wideband Radio Communication Test | R&S            | CMW500          | 106504            | Oct. 28, 2022    | Oct. 27, 2023    |
| 21   | MWRF Power Meter Test system      | MW             | MW100-RPCB      | N/A               | Oct. 21, 2022    | Oct. 20, 2023    |
| 22   | D.C. Power Supply                 | LongWei        | TPR-6405D       | N/A               | \                | \                |
| 23   | EMC Software                      | Frad           | EZ-EMC          | Ver.EMC-CON 3A1.1 | \                | \                |
| 24   | RF Software                       | MW             | MTS8310         | V2.0.0.0          | \                | \                |
| 25   | Turntable                         | MF             | MF-7802BS       | N/A               | \                | \                |
| 26   | Antenna tower                     | MF             | MF-7802BS       | N/A               | \                | \                |




Conduction Test equipment

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No.  | Last calibration | Calibrated until |
|------|-------------------|--------------|----------|-------------|------------------|------------------|
| 1    | LISN              | R&S          | ENV216   | 101471      | Oct. 28, 2022    | Oct. 27, 2023    |
| 2    | LISN              | CYBERTEK     | EM5040A  | E1850400149 | Oct. 28, 2022    | Oct. 27, 2023    |
| 3    | Test Cable        | N/A          | C01      | N/A         | Oct. 28, 2022    | Oct. 27, 2023    |
| 4    | Test Cable        | N/A          | C02      | N/A         | Oct. 28, 2022    | Oct. 27, 2023    |
| 5    | EMI Test Receiver | R&S          | ESRP3    | 101946      | Oct. 28, 2022    | Oct. 27, 2023    |
| 6    | Absorbing Clamp   | DZ           | ZN23201  | N/A         | Oct. 28, 2022    | Oct. 27, 2023    |



### 3.CONDUCTED EMISSION AT THE MAINS TERMINALS TEST

#### 3.1 Block Diagram Of Test Setup



#### 3.2 Test Standard

FCC PART 18

#### 3.3 Power Line Conducted Emission Limit

| Frequency<br>MHz | Limits dB(μV)    |               |
|------------------|------------------|---------------|
|                  | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50      | 66 ~ 56*         | 56 ~ 46*      |
| 0.50 ~ 5.00      | 56               | 46            |
| 5.00 ~ 30.00     | 60               | 50            |

Notes: 1. \*Decreasing linearly with logarithm of frequency.  
2. The lower limit shall apply at the transition frequencies.

#### 3.4 EUT Configuration on Test

The following equipments are installed on conducted emission test to meet FCC PART 18 requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

#### 3.5 Operating Condition of EUT

- 3.5.1 Setup the EUT and simulators as shown in Section 3.1.
- 3.5.2 Turn on the power of all equipments.
- 3.5.3 Let the EUT work in test modes and test it.

#### 3.6 Test Procedure

The EUT is put on the ground and connected to the AC mains through a Artificial Mains Network (AMN). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission levels according to the **FCC PART 18** regulations during conducted emission test.

The bandwidth of the test receiver (R&S Test Receiver ESCI) is set at 10KHz.  
The frequency range from 150 KHz to 30 MHz is investigated.


#### 3.7 Test Result

PASS

Please refer to the following page.




| Conducted Emission At The Mains Terminals Test Data |              |                    |        |
|-----------------------------------------------------|--------------|--------------------|--------|
| Temperature:                                        | 24.5 °C      | Relative Humidity: | 54%    |
| Pressure:                                           | 1009hPa      | Phase :            | Line   |
| Test Voltage :                                      | AC 120V/60Hz | Test Mode:         | Mode 1 |



| No. | Freq MHz | Cable Loss dB | LISN Factor dB/m | Receiver Reading dBuV | Emission Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark  |
|-----|----------|---------------|------------------|-----------------------|-----------------------|--------------|---------------|---------|
| 1.  | 0.166    | 0.00          | 9.54             | 23.27                 | 32.81                 | 55.16        | -22.35        | Average |
| 2.  | 0.166    | 0.00          | 9.54             | 35.43                 | 44.97                 | 65.16        | -20.19        | QP      |
| 3.  | 0.249    | 0.01          | 9.56             | 22.67                 | 32.24                 | 51.78        | -19.54        | Average |
| 4.  | 0.249    | 0.01          | 9.56             | 33.08                 | 42.65                 | 61.78        | -19.13        | QP      |
| 5.  | 0.334    | 0.01          | 9.56             | 21.52                 | 31.09                 | 49.35        | -18.26        | Average |
| 6.  | 0.334    | 0.01          | 9.56             | 30.75                 | 40.32                 | 59.35        | -19.03        | QP      |
| 7.  | 0.419    | 0.01          | 9.57             | 9.80                  | 19.38                 | 47.46        | -28.08        | Average |
| 8.  | 0.419    | 0.01          | 9.57             | 25.98                 | 35.56                 | 57.46        | -21.90        | QP      |
| 9.  | 0.502    | 0.01          | 9.57             | 16.71                 | 26.29                 | 46.00        | -19.71        | Average |
| 10. | 0.502    | 0.01          | 9.57             | 24.54                 | 34.12                 | 56.00        | -21.88        | QP      |
| 11. | 0.570    | 0.02          | 9.57             | 18.15                 | 27.74                 | 46.00        | -18.26        | Average |
| 12. | 0.570    | 0.02          | 9.57             | 24.78                 | 34.37                 | 56.00        | -21.63        | QP      |



| Conducted Emission At The Mains Terminals Test Data |              |                    |         |
|-----------------------------------------------------|--------------|--------------------|---------|
| Temperature:                                        | 24.5 °C      | Relative Humidity: | 54%     |
| Pressure:                                           | 1009hPa      | Phase :            | Neutral |
| Test Voltage :                                      | AC 120V/60Hz | Test Mode:         | Mode 1  |





| No. | Freq<br>MHz | Cable<br>Loss<br>dB | LISN<br>Factor<br>dB/m | Receiver<br>Reading<br>dBuV | Emission<br>Level<br>dBuV/m | Limit<br>dBuV/m | Over<br>Limit<br>dB | Remark  |
|-----|-------------|---------------------|------------------------|-----------------------------|-----------------------------|-----------------|---------------------|---------|
| 1.  | 0.162       | 0.00                | 9.54                   | 15.92                       | 25.46                       | 55.38           | -29.92              | Average |
| 2.  | 0.162       | 0.00                | 9.54                   | 33.69                       | 43.23                       | 65.38           | -22.15              | QP      |
| 3.  | 0.246       | 0.01                | 9.56                   | 19.53                       | 29.10                       | 51.91           | -22.81              | Average |
| 4.  | 0.246       | 0.01                | 9.56                   | 32.01                       | 41.58                       | 61.91           | -20.33              | QP      |
| 5.  | 0.332       | 0.01                | 9.56                   | 18.53                       | 28.10                       | 49.40           | -21.30              | Average |
| 6.  | 0.332       | 0.01                | 9.56                   | 29.80                       | 39.37                       | 59.40           | -20.03              | QP      |
| 7.  | 0.415       | 0.01                | 9.57                   | 10.27                       | 19.85                       | 47.55           | -27.70              | Average |
| 8.  | 0.415       | 0.01                | 9.57                   | 21.35                       | 30.93                       | 57.55           | -26.62              | QP      |
| 9.  | 0.494       | 0.01                | 9.58                   | 14.97                       | 24.56                       | 46.10           | -21.54              | Average |
| 10. | 0.494       | 0.01                | 9.58                   | 23.27                       | 32.86                       | 56.10           | -23.24              | QP      |
| 11. | 0.579       | 0.02                | 9.58                   | 15.12                       | 24.72                       | 46.00           | -21.28              | Average |
| 12. | 0.579       | 0.02                | 9.58                   | 23.86                       | 33.46                       | 56.00           | -22.54              | QP      |



## 4.RADIATION EMISSION TEST

### 4.1 Block Diagram of Test Setup



### 4.2 Test Standard

FCC PART 18

### 4.3 Radiation Limit

#### Limits for frequency below 30MHz

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in § 18.301, unless otherwise indicated, shall not exceed the following table:

| Frequency<br>MHz | Distance<br>Meters | Field Strengths Limit |            |
|------------------|--------------------|-----------------------|------------|
|                  |                    | dB $\mu$ V/m          | Remark     |
| 0.009~30MHz      | 3                  | 103.5                 | Quasi-peak |



Remark: (1) Emission level dB V/m for 0.009~30MHz =  $20\log(15) + 40\log(300/3)$  dB V/m; (2) Calculated according FCC 18.305. (3) The smaller limit shall apply at the cross point between two frequency bands. (4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

#### Limits for frequency Above 30MHz

| FREQUENCY<br>(MHz) | DISTANCE<br>(Meters) | FIELD STRENGTHS LIMITS<br>(dBμV/m) |
|--------------------|----------------------|------------------------------------|
| 30 ~ 1000          | 3                    | 63.5                               |

(1) Emission level dB V/m for above 30MHz =  $20\log(15) + 20\log(300/3)$  dB V/m

#### 4.4 EUT Configuration on Test

The FCC PART 18 regulations test method must be used to find the maximum emission during radiated emission test. The configuration of EUT is the same as used in conducted emission test. Please refer to Section 2.2.

#### 4.5 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 2.2 except the test set up replaced as Section 4.1.

#### 4.6 Test Procedure

##### 1) Sequence of testing 9 kHz to 30 MHz

###### Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

###### Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 2.0 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

###### Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

##### Sequence of testing 30 MHz to 1 GHz Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

###### Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 4 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find



the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored


#### 4.7 Test Result

PASS

Please refer to the following page.




| Radiation Emission Test Data |         |                    |        |
|------------------------------|---------|--------------------|--------|
| Temperature:                 | 26℃     | Relative Humidity: | 54%    |
| Pressure:                    | 1009hPa | Phase :            | /      |
| Test Voltage :               | DC 3.7V | Test Mode:         | Mode 2 |



| No. | Freq  | Cable Loss | AMP Factor | ANT Factor | Receiver Reading | Emission Level | Limit  | Over Limit | Remark |
|-----|-------|------------|------------|------------|------------------|----------------|--------|------------|--------|
|     | MHz   | dB         | dB/m       | dB/m       | dBμV             | dBμV/m         | dBμV/m | dB         |        |
| 1   | 0.009 | 0.12       | 30.2       | 19.9       | 72.08            | 61.90          | 103.50 | -41.60     | Peak   |
| 2   | 0.017 | 0.12       | 30.2       | 19.9       | 69.8             | 59.62          | 103.50 | -43.88     | Peak   |
| 3   | 0.026 | 0.12       | 30.2       | 19.9       | 70.29            | 60.11          | 103.50 | -43.39     | Peak   |
| 4   | 0.156 | 0.13       | 30.3       | 19.9       | 75.25            | 64.98          | 103.50 | -38.52     | Peak   |
| 5   | 0.970 | 0.15       | 30.5       | 19.7       | 64.9             | 54.25          | 103.50 | -49.25     | Peak   |
| 6   | 5.971 | 0.28       | 30.8       | 19.9       | 70.84            | 60.22          | 103.50 | -43.28     | Peak   |




| Radiation Emission Test Data |         |                    |            |
|------------------------------|---------|--------------------|------------|
| Temperature:                 | 26℃     | Relative Humidity: | 54%        |
| Pressure:                    | 1009hPa | Phase :            | Horizontal |
| Test Voltage :               | DC 3.7V | Test Mode:         | Mode 2     |



| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBμV | Emission<br>Level<br>dBμV/m | Limit<br>dBμV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|-----------------------------|-----------------|---------------------|--------|
| 1   | 41.277      | 0.36                | 12.53                 | 14.61                       | 27.50                       | 63.50           | -36.00              | QP     |
| 2   | 45.855      | 0.40                | 12.62                 | 14.18                       | 27.20                       | 63.50           | -36.30              | QP     |
| 3   | 108.267     | 0.73                | 11.18                 | 14.13                       | 26.04                       | 63.50           | -37.46              | QP     |
| 4   | 187.753     | 1.03                | 10.81                 | 15.26                       | 27.10                       | 63.50           | -36.40              | QP     |
| 5   | 304.610     | 1.29                | 14.38                 | 21.03                       | 36.70                       | 63.50           | -26.80              | QP     |
| 6   | 399.030     | 1.43                | 15.79                 | 18.70                       | 35.92                       | 63.50           | -27.58              | QP     |



| Radiation Emission Test Data |         |                    |          |
|------------------------------|---------|--------------------|----------|
| Temperature:                 | 26℃     | Relative Humidity: | 54%      |
| Pressure:                    | 1009hPa | Phase :            | Vertical |
| Test Voltage :               | DC 3.7V | Test Mode:         | Mode 2   |



| No. | Freq<br>MHz | Cable<br>Loss<br>dB | ANT<br>Factor<br>dB/m | Receiver<br>Reading<br>dBμV | Emission<br>Level<br>dBμV/m | Limit<br>dBμV/m | Over<br>Limit<br>dB | Remark |
|-----|-------------|---------------------|-----------------------|-----------------------------|-----------------------------|-----------------|---------------------|--------|
| 1   | 34.517      | 0.29                | 11.01                 | 14.76                       | 26.06                       | 63.50           | -37.44              | QP     |
| 2   | 56.197      | 0.47                | 12.06                 | 14.04                       | 26.57                       | 63.50           | -36.93              | QP     |
| 3   | 95.762      | 0.67                | 10.61                 | 14.41                       | 25.69                       | 63.50           | -37.81              | QP     |
| 4   | 168.414     | 0.97                | 9.22                  | 17.29                       | 27.48                       | 63.50           | -36.02              | QP     |
| 5   | 232.532     | 1.14                | 12.48                 | 14.01                       | 27.63                       | 63.50           | -35.87              | QP     |
| 6   | 317.701     | 1.31                | 14.60                 | 17.29                       | 33.20                       | 63.50           | -30.30              | QP     |



## 5. EUT PHOTOGRAPHS

Reference to the EUT Photo for details.

## 6.EUT TEST PHOTOGRAPHS

Reference to the Test Photo for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*