



# 시험성적서

## TEST REPORT

페이지(page) : ( 1 ) / ( 총(Total) 27 )

2024-12-30  
17:38:31  
KST

성적서 번호 Report No.	ICRT-TR-E243522-0B	
신청자 Client	기관명 Name	KOROT Co., Ltd.
	주 소 Address	5F, 54, 2-gil, Nonhyun-ro, Gangnam-gu Seoul South Korea 06313
시험대상품목 Sample description	Blood Pressure Monitor	
모델명 Type designation	KOROT V2 Doctor	
정격 Ratings	DC 5 V (Adapter Power), DC 3.6 V (Battery)	
시험장소 Place of test	<input checked="" type="checkbox"/> 고정시험실(Permanent Testing Lab) <input type="checkbox"/> 현장시험(On Site Testing) 주소지(Address): 112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea	
시험기간 Date of test	2024. 12. 04	
시험방법/항목 Test Method/Item	FCC 47 CFR Part 15, Subpart B / Other Class B digital devices & peripherals	
시험결과 Test Results	Refer to summary of test results	
확인 Affirmation	작성자 Tested by 성명 Name	기술책임자 Technical Manager 성명 Name
	오성빈 Oh, Sung bin(Signature)	박명철 Park, Myeongcheol (Signature)

 위 성적서는 고객이 제공한 시료에 대한 시험결과입니다.

This is certified that the above mentioned products have been tested for the sample.

 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다.

The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme.


 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다.

The test report is prohibited for some reproduction without the approval of the ICR.

2024. 12. 27

주식회사 아이씨알 대표이사

The head of INTERNATIONAL CERTIFICATION REGISTRAR



본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로 7번길 112 / Tel: 02-6351-9001 ~ 6









페이지(page) : ( 2 ) / ( 총(Total) 27 )

## Contents

1. Applicant Information.....	3
1.1 Applicant .....	3
1.2 Manufacture .....	3
2. Laboratory .....	3
2.1 Information.....	3
3. Revision History .....	3
4. EUT 4	
4.1 Used equipment.....	4
4.2 Test Configuration .....	4
4.3 Cable List.....	5
4.4 Mode of Operating during the test .....	5
4.5 Family Model Name .....	5
4.6 EUT Modifications .....	5
5. Summary of test result .....	6
5.1 Test Summary .....	6
6. Test Description .....	7
6.1 Facility .....	7
6.2 Test Procedure .....	7
7. EMISSION .....	9
7.1 Radiated emission.....	9
7.2 Conducted emission.....	17
Attachment I.....	20





페이지(page) : ( 3 ) / ( 총(Total) 27 )

## 1. Applicant Information

### 1.1 Applicant

Applicant : KOROT Co., Ltd.  
 Address : 5F, 54, 2-gil, Nonhyun-ro, Gangnam-gu Seoul South Korea 06313

### 1.2 Manufacture

Manufacture : KOROT Co., Ltd.  
 Address : 5F, 54, 2-gil, Nonhyun-ro, Gangnam-gu Seoul South Korea 06313


## 2. Laboratory

### 2.1 Information

Laboratory : ICR Co., Ltd  
 Address : 112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea  
 Telephone No. : +82-2-6351-9001  
 Facsimile No. : +82-2-6351-9007  
 KOLAS No. : KT652  
 RRA No. : KR0165

## 3. Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E243522-0A	2024. 12. 17	First issue.	-
ICRT-TR-E243522-0B	2024. 12. 27	Applicant Address Change and Addition of FCC ID	Page 1, 3, 4






페이지(page) : ( 4 ) / ( 총(Total) 27 )

## 4. EUT




### 4.1 Used equipment

Description	Model	Serial No.	Manufacturer	Comments
Blood Pressure Monitor	KOROT V2 Doctor	-	KOROT Co., Ltd.	EUT
Adapter	AS013Z-0502000KU	-	Shenzhen Andsmmps Electronic Technology Co., Ltd.	AE
Micro SD Card	-	-	SanDisk	AE

### 4.2 Test Configuration



—— : Signal line    —— : Power line    △ : GROUND    ● : Adapter





페이지(page) : ( 5 ) / ( 총(Total) 27 )

#### 4.3 Cable List

Equipment	Port	Equipment	Port	Length (m)	Shielded
EUT (MODE 1)	USB(Type-C)	Adapter	DC Out	1.0	Unshielded
	Micro SD Card Slot	Micro SD Card	-	Direct	-
EUT (MODE 2)	Micro SD Card Slot	Micro SD Card	-	Direct	-

#### 4.4 Mode of Operating during the test



Mode	Operating Description
1	It is tested with power supplied through the adapter and continuously operating the blood pressure measurement function in the EUT.
2	It is supplied with power through a built-in battery and tested with the blood pressure measurement function continuously operated in the EUT.

#### 4.5 Family Model Name

- KOROT P2 : The electrical specifications, structure, and circuit are the same as the basic model, and the model name is added due to differences in the seller.

#### 4.6 EUT Modifications

- None





페이지(page) : ( 6 ) / ( 총(Total) 27 )

## 5. Summary of test result

### 5.1 Test Summary

Standard	Test items	Applied	Results
FCC Part 15.109	Radiated emission	<input checked="" type="checkbox"/>	Pass
FCC Part 15.107	Conducted emission	<input checked="" type="checkbox"/>	Pass

\* The data in this test report are traceable to the national or international standards.

#### Frequency range to be scanned:

0.15 MHz to 30 MHz as Conducted measurement

5<sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower as Radiated measurement

#### Bandwidth:

Measured by the CISPR quasi-peak function Bandwidth is 9 kHz in the frequency 0.15 MHz ~ 30 MHz and 120 kHz in the frequency 30 MHz ~ 1 000 MHz.

Measured by the CISPR Peak function Bandwidth is 1 MHz in the frequency 1 GHz ~ 40 GHz.  
The EUT is powered by a vehicle battery, and the conduction disturbance test is excluded.

- FCC ID : 2BAK8-V2DOCTOR

- Maximum operating frequency: 2.4 GHz





페이지(page) : ( 7 ) / ( 총(Total) 27 )

## 6. Test Description

### 6.1 Facility

All the testing facilities are periodically serviced as a daily check for equipment and cables systems, an every 6 months facility check for the facilities and a monthly check and annual calibration for testing equipment according to ISO/IEC 17025. All the testing facilities are used as the same specifications shown below. There are descriptions both for radiated disturbance measurement and conducted disturbance measurement conformed by ANSI C 63.4-2014.

### 6.2 Test Procedure

#### 6.2.1 Radiated Disturbance Measurements – Below 1 GHz

- Test site is met the requirements of ANSI C 63.4-2014 and the distance between the EUT and the antenna is adjusted 3 m/10 m.
- The turntable can be rotated 360 degrees.
- The antenna can be adjusted between 1 m and 4 m in height above the ground.
- The EUT is placed on the non-conducting table with 0.8 m height on the turntable.
- Measurements are carried out using a EMI test receiver with peak detectors (100 kHz bandwidth) and an EMI receiver with quasi-peak detectors(120 kHz bandwidth).
- Refer to the list of test equipment used for the test.
- Trilog antenna are used as Broadband antenna.
- The Trilog antenna is used in the frequency range of 30 ~ 1 000MHz, the Horn antenna is used in the frequency range of 1 GHz ~ 18 GHz.
- A variable attenuator is used for verifying amplifier's linearity.
- Rotating the turntable and adjusting the height of the antenna are carried out by control buttons on the console.
- Refer to "Brief Information"(page 4-5) about details of the EUT and configuration of the cables.
- Measurement is carried out by a ICR operator as manual operation.
- searching for some of High disturbance frequency points than the other points with the following settings;  
bandwidth 100 kHz, frequency range 10 MHz between 30 MHz and 300 MHz and frequency range 50 MHz between 300 MHz and 1 GHz.
- searching the worst direction with the maximum level of the disturbance wave in rotating the turntable 360 degrees at each searched frequency point.
- setting the height of the antenna with the maximum level of the disturbance wave from 1 m ~ 4 m.
- reading the disturbance level by the EMI receiver with quasi-peak detectors (120 kHz bandwidth) according to ANSI C 63.4-2014.
- measuring to vertical and horizontal polarization.
- calculating the measurement result with the following formula or equation:  
[Measurement result= measured value + Antenna factor + Cable loss - (Amp.)]

#### 6.2.2 Radiated Disturbance Measurements – Above 1 GHz

- Test site is met the requirements of ANSI C 63.4-2014 and the distance between the EUT and the antenna is adjusted 3 m.
- The turntable can be rotated 360 degrees.
- The antenna can be adjusted between 1 m in height above the ground.
- The EUT is placed on the non-conducting table with 1 m height on the turntable.
- Measurements are carried out using a EMI test receiver with peak detectors (1 MHz bandwidth) and an EMI receiver with peak and average detectors(1 MHz bandwidth).
- Refer to the list of test equipment used for the test.
- HORN ANTENNA are used as WIDEBAND ANTENNA.
- The HORN ANTENNA is used in the frequency range of 1 GHz ~ 18 GHz.
- A variable attenuator is used for verifying amplifier's linearity.
- Rotating the turntable and adjusting the height of the antenna are carried out by control buttons on the console.
- Refer to "Brief Information"(page 4-5) about details of the EUT and configuration of the cables.





페이지(page) : ( 8 ) / ( 총(Total) 27 )

- Measurement is carried out by a ICR operator as manual operation.
- searching the worst direction with the maximum level of the disturbance wave in rotating the turntable 360 degrees at each searched frequency point.– setting the height of the antenna with the maximum level of the disturbance wave from 1 m
- reading the disturbance level by the EMI receiver with peak and average detectors (1 MHz bandwidth) according to ANSI C 63.4-2014.
- measuring to vertical and horizontal polarization.
- calculating the measurement result with the following formula or equation:  
[Measurement result= measured value + Antenna factor + Cable loss - (Amp.)]

### 6.2.3 Conducted Disturbance Measurements

- The measurement is carried out on an open site with horizontal and metallic ground plane.
- An AMN(Artificial Mains Network) with a nominal impedance ( $50 \Omega/50 \mu H$ ) as defined in ANSIC 63.4-2014., shall be utilized.
- The AMN is grounded on a horizontal metal ground plane.
- Measurement is carried out using an EMI receiver with quasi-peak detectors and average detector. (Refer to the List of test equipment used for the test.)
- The shortest distance between the EUT and the AMN is 0.8 m.
- The EUT is placed on the non-conducting table with 0.8 m height.
- A remote switch is used for changing phases between Line (L) and Neutral (N).
- Refer to "Brief Information"(page 4-5) about details of the EUT and configuration of the cables.
- Measurement is carried out as manual operation.
- detecting the maximized emission level using the maxhold function after setting the spectrum analyzer bandwidth 1 kHz and the frequency range from 150 kHz ~ 1 MHz, 1 MHz ~ 5 MHz and 5 MHz ~ 30 MHz.
- searching the maximum frequency point of the disturbance wave in each frequency range.
- reading the disturbance level of quasi-peak, average and Line (L) and Neutral (N) in 9 kHz bandwidth by the EMI receiver.
- calculating the measurement result with the following formula or equation.  
(Result = Reading + Corr)  
(Margin = Limit - Result)





페이지(page) : ( 9 ) / ( 총(Total) 27 )

## 7. EMISSION

### 7.1 Radiated emission

**Definition:**

The test assesses the ability of ancillary equipment to limit their internal noise from being radiated from the enclosure.

**Test environment:**

Test method	:	FCC Part 15.109
-------------	---	-----------------

[Below 1 GHz]

Test Date	:	2024. 12. 04
Temperature, Humidity	:	24 °C, 45 % R.H.
Measurement Distance	:	3 m
Measurement RBW	:	120 kHz
Measurement Frequency range	:	30 MHz ~ 1 GHz

[Above 1 GHz]

Test Date	:	2024. 12. 04
Temperature, Humidity	:	24 °C, 45 % R.H.
Measurement Distance	:	3 m
Measurement RBW	:	120 kHz
Measurement Frequency range	:	1 000 kHz

Test mode	:	MODE 1, 2 (refer to 4.4)
-----------	---	--------------------------

Ut	:	AC 120 V, 60 Hz (MODE 1), DC 3.6 V (MODE 2)
----	---	---

Result	:	Pass
--------	---	------

**A sample calculation:**

- Corr (correction factor) = Ant. Factor + Cable loss – (Amp.)

- Emission Level = meter reading + Corr

- Sample calculation ; Below 1 GHz (Quasi-Peak) : MODE 1

At Frequency : 263.964 MHz Result = Reading + Corr = 59.99 dB( $\mu$ V/m) + (-22.60) dB = 37.39 dB( $\mu$ V/m)

- Sample calculation ; Above 1 GHz (CAverage) : MODE 2

At Frequency : 17 724.000 MHz Result = Reading + Corr = 25.41 dB( $\mu$ V/m) + (14.83) dB = 40.24 dB( $\mu$ V/m)

- Measurement Data kept in ICR





페이지(page) : ( 10 ) / ( 총(Total) 27 )

**Limits of below 1 GHz - CLASS A**

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Distance (m)
30 ~ 88	90	10
88 ~ 216	150	
216 ~ 960	210	
Above 960	300	

**Limits of below 1 GHz - CLASS B**

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Distance (m)
30 ~ 88	100	3
88 ~ 216	150	
216 ~ 960	200	
Above 960	500	

**Used equipments:****[Below 1 GHz]**

Used	Equipment	Model name	Manufacturer	Serial No.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR26	R&S	101461	2025. 03. 28
<input checked="" type="checkbox"/>	TRILOG BROAD BAND ANTENNA	VULB 9162	SCHWARZBECK	120	2024. 12. 26
<input checked="" type="checkbox"/>	RF Pre Amplifier	SCU 08	R&S	100746	2025. 03. 28
<input checked="" type="checkbox"/>	HUMIDITY/TEMP. DATA RECORDER	MHT-381SD	LUTRON	AI.63107	2025. 01. 13

**[Above 1 GHz]**

Used	Equipment	Model name	Manufacturer	Serial No.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR26	R&S	101462	2025. 03. 28
<input checked="" type="checkbox"/>	HORN ANTENNA	HF907	R&S	102869	2025. 04. 04
<input checked="" type="checkbox"/>	RF Pre Amplifier	SCU18	R&S	102342	2025. 03. 28
<input checked="" type="checkbox"/>	HUMIDITY/TEMP. DATA RECORDER	MHT-381SD	LUTRON	AI.63106	2025. 01. 13

**Test Software:**

Used	Description	Model name	Manufacturer	Version.
<input checked="" type="checkbox"/>	EMI Test Software	EMC32	R & S	10.01.00

**Measurement Data:**

- Refer to the Next page.






페이지(page) : ( 11 ) / ( 총(Total) 27 )

## DATA 1 GHz Below (MODE 1)

### Test Report

#### Common Information

Test Description: 2024-5507  
 Operating Conditions: ICR 3 m Chamber  
 Operator Name: OSB  
 Comment: RE\_MODE 1



#### Final Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
159.204	26.08	43.50	17.42	1000.0	120.000	100.0	V	207.0	-27.80
167.934	26.73	43.50	16.77	1000.0	120.000	100.0	V	9.0	-27.50
263.964	37.39	46.00	8.61	1000.0	120.000	300.0	H	45.0	-22.60
311.979	35.62	46.00	10.38	1000.0	120.000	400.0	H	174.0	-21.40
384.729	29.60	46.00	16.40	1000.0	120.000	400.0	H	289.0	-18.90
456.024	34.93	46.00	11.07	1000.0	120.000	300.0	H	316.0	-17.80

2024-11-04






페이지(page) : ( 12 ) / ( 총(Total) 27 )

## DATA 1 GHz Below (MODE 2)

### Test Report

#### Common Information

Test Description: 2024-5507  
 Operating Conditions: ICR 3 m Chamber  
 Operator Name: OSB  
 Comment: RE\_MODE 2



#### Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
263.964	33.32	46.00	12.68	1000.0	120.000	400.0	H	255.0	-22.57
311.979	31.14	46.00	14.86	1000.0	120.000	300.0	H	68.0	-21.38
359.994	25.91	46.00	20.09	1000.0	120.000	300.0	H	214.0	-20.15
384.729	27.46	46.00	18.54	1000.0	120.000	400.0	H	255.0	-18.94
425.275	24.58	46.00	21.42	1000.0	120.000	100.0	V	0.0	-17.96
456.024	33.09	46.00	12.91	1000.0	120.000	100.0	V	201.0	-17.81

2024-12-04






페이지(page) : ( 13 ) / ( 총(Total) 27 )

## DATA 1 GHz Above (MODE 1)

### Test Report

#### Common Information

Test Description: 2024-5507  
 Test Site: ICR 3 m Chamber  
 Operator Name: OSB  
 Comment: RE ABOVE\_MODE 1



#### Final Result

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	CAverage (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
16068.000	52.54	---	74.00	21.46	7000.0	1000.000	99.7	V	0.0	12.44
16068.000	---	38.74	54.00	15.26	7000.0	1000.000	99.7	V	0.0	12.44
16230.000	---	38.13	54.00	15.87	7000.0	1000.000	99.7	V	126.0	12.42
16230.000	52.17	---	74.00	21.83	7000.0	1000.000	99.7	V	126.0	12.42
16378.800	---	37.37	54.00	16.63	7000.0	1000.000	99.7	V	29.0	12.36
16378.800	50.90	---	74.00	23.10	7000.0	1000.000	99.7	V	29.0	12.36
16952.400	---	37.96	54.00	16.04	7000.0	1000.000	99.7	V	228.0	12.81
16952.400	51.72	---	74.00	22.28	7000.0	1000.000	99.7	V	228.0	12.81
17283.600	52.92	---	74.00	21.08	7000.0	1000.000	99.7	H	190.0	14.12
17283.600	---	39.43	54.00	14.57	7000.0	1000.000	99.7	H	190.0	14.12
17640.000	53.37	---	74.00	20.63	7000.0	1000.000	99.7	V	97.0	14.66
17640.000	---	40.17	54.00	13.83	7000.0	1000.000	99.7	V	97.0	14.66
17677.200	53.58	---	74.00	20.42	7000.0	1000.000	99.7	V	126.0	14.69
17677.200	---	40.25	54.00	13.75	7000.0	1000.000	99.7	V	126.0	14.69
17724.000	53.35	---	74.00	20.65	7000.0	1000.000	99.7	V	97.0	14.83
17724.000	---	40.20	54.00	13.80	7000.0	1000.000	99.7	V	97.0	14.83
17763.600	---	39.84	54.00	14.16	7000.0	1000.000	99.7	H	0.0	14.83
17763.600	53.08	---	74.00	20.92	7000.0	1000.000	99.7	H	0.0	14.83
17812.800	---	39.55	54.00	14.45	7000.0	1000.000	99.7	H	56.0	14.66
17812.800	52.99	---	74.00	21.01	7000.0	1000.000	99.7	H	56.0	14.66

2024-12-04





페이지(page) : ( 14 ) / ( 총(Total) 27 )

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	CAverage (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
17930.400	53.00	---	74.00	21.00	7000.0	1000.000	99.7	V	63.0	14.83
17930.400	---	39.38	54.00	14.62	7000.0	1000.000	99.7	V	63.0	14.83
17996.400	---	39.85	54.00	14.15	7000.0	1000.000	99.7	H	56.0	15.36
17996.400	53.18	---	74.00	20.82	7000.0	1000.000	99.7	H	56.0	15.36

2024-12-04






페이지(page) : ( 15 ) / ( 총(Total) 27 )

## DATA 1 GHz Above (MODE 2)

### Test Report

#### Common Information


Test Description: 2024-5507  
 Test Site: ICR 3 m Chamber  
 Operator Name: OSB  
 Comment: RE ABOVE\_MODE 2



#### Final Result

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	CAverage (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
7206.000	53.93	---	74.00	20.07	7000.0	1000.000	100.0	V	200.0	2.40
7206.000	---	28.30	54.00	25.70	7000.0	1000.000	100.0	V	200.0	2.40
16459.200	---	39.11	54.00	14.89	7000.0	1000.000	100.0	H	134.0	12.63
16459.200	52.68	---	74.00	21.32	7000.0	1000.000	100.0	H	134.0	12.63
16473.600	52.29	---	74.00	21.71	7000.0	1000.000	100.0	V	304.0	12.69
16473.600	---	38.89	54.00	15.11	7000.0	1000.000	100.0	V	304.0	12.69
17301.600	---	39.52	54.00	14.48	7000.0	1000.000	100.0	H	0.0	14.14
17301.600	53.40	---	74.00	20.60	7000.0	1000.000	100.0	H	0.0	14.14
17630.400	53.61	---	74.00	20.39	7000.0	1000.000	100.0	V	337.0	14.64
17630.400	---	40.12	54.00	13.88	7000.0	1000.000	100.0	V	337.0	14.64
17650.800	53.42	---	74.00	20.58	7000.0	1000.000	100.0	H	309.0	14.68
17650.800	---	40.15	54.00	13.85	7000.0	1000.000	100.0	H	309.0	14.68
17685.600	---	40.20	54.00	13.80	7000.0	1000.000	100.0	V	167.0	14.69
17685.600	53.40	---	74.00	20.60	7000.0	1000.000	100.0	V	167.0	14.69
17703.600	54.76	---	74.00	19.24	7000.0	1000.000	100.0	H	98.0	14.71
17703.600	---	40.10	54.00	13.90	7000.0	1000.000	100.0	H	98.0	14.71
17724.000	---	40.24	54.00	13.76	7000.0	1000.000	100.0	H	0.0	14.83
17724.000	54.02	---	74.00	19.98	7000.0	1000.000	100.0	H	0.0	14.83
17779.200	53.11	---	74.00	20.89	7000.0	1000.000	100.0	V	268.0	14.75
17779.200	---	39.53	54.00	14.47	7000.0	1000.000	100.0	V	268.0	14.75

2024-12-04





페이지(page) : ( 16 ) / ( 총(Total) 27 )

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	CAverage (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
17816.400	53.13	---	74.00	20.87	7000.0	1000.000	100.0	H	276.0	14.66
17816.400	---	39.51	54.00	14.49	7000.0	1000.000	100.0	H	276.0	14.66
17844.000	53.15	---	74.00	20.85	7000.0	1000.000	100.0	H	66.0	14.69
17844.000	---	39.16	54.00	14.84	7000.0	1000.000	100.0	H	66.0	14.69
17940.000	---	39.17	54.00	14.83	7000.0	1000.000	100.0	V	0.0	14.98
17940.000	53.08	---	74.00	20.92	7000.0	1000.000	100.0	V	0.0	14.98

2024-12-04





페이지(page) : ( 17 ) / ( 총(Total) 27 )

## 7.2 Conducted emission

### Definition:

The test assesses the ability of the EUT to limit its internal noise from being present on the AC mains Power and Signal Line In / Output ports.

### Test environment:

Test method	:	FCC Part 15.107
Test Date	:	2024. 12. 04
Temperature, Humidity	:	24 °C, 45 % R.H.
Measurement Frequency range and RBW	:	150 kHz ~ 30 MHz
Test mode	:	MODE 1 (refer to 4.4)
<i>Ut</i>	:	AC 120 V, 60 Hz(MODE 1)
Result	:	Pass

### A sample calculation:

- Corr (correction factor) = LISN Insertion loss + Cable loss
- Emission Level = meter reading + Corr
- Sample calculation ;
- At Frequency: 0.443 MHz Result = Reading + Corr = 37.54 dB( $\mu$ V) + 9.94 dB = 47.48 dB( $\mu$ V)  
 Quasi-peak,  CISPR-Average
- Measurement Data kept in ICR





페이지(page) : ( 18 ) / ( 총(Total) 27 )

Limits for conducted emissions from the AC mains ports of class A equipment.

Applicable to AC mains power port		
Frequency Range (MHz)	Quasi-Peak [dB(μV)]	CISPR-Average [dB(μV)]
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

Limits for conducted emissions from the AC mains ports of class B equipment.

Applicable to AC mains power port		
Frequency Range (MHz)	Quasi-Peak [dB(μV)]	CISPR-Average [dB(μV)]
0.15 ~ 0.5	66 ~ 56*	56 ~ 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

Used equipments:

Used	Equipment	Model name	Manufacturer	Serial No.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR7	R&S	102034	2025. 03. 28
<input checked="" type="checkbox"/>	LISN(main)	ENV216	R&S	102195	2025. 09. 12
<input type="checkbox"/>	LISN(sub)	ENV216	R&S	102194	2025. 05. 27
<input checked="" type="checkbox"/>	HUMIDITY/TEMP. DATA RECORDER	MHT-381SD	LUTRON	AI.63101	2025. 01. 05

Test Software:

Used	Description	Model name	Manufacturer	Version.
<input checked="" type="checkbox"/>	EMI Test Software	EMC32	R & S	10.01.02

Measurement Data:

- Refer to the Next page.
- The maximum value was recorded by measuring LIVE and NEUTRAL respectively.






페이지(page) : ( 19 ) / ( 총(Total) 27 )

## DATA (MODE 1)

### Test Report

#### Common Information

Test Description: 2024-5507  
 Test Site: ICR Shield Room  
 Operator Name: OSB  
 Comment: CE



#### Final Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	CAverage (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.161	---	42.47	55.40	12.93	5000.0	9.000	L1	10.21
0.161	50.22	---	65.40	15.17	5000.0	9.000	L1	10.21
0.200	---	32.63	53.63	21.00	5000.0	9.000	L1	10.08
0.200	44.60	---	63.63	19.03	5000.0	9.000	L1	10.08
0.402	41.43	---	57.81	16.39	5000.0	9.000	N	9.93
0.402	---	29.25	47.81	18.56	5000.0	9.000	N	9.93
0.443	---	35.33	47.02	11.69	5000.0	9.000	N	9.94
0.443	47.48	---	57.02	9.53	5000.0	9.000	N	9.94
0.542	42.58	---	56.00	13.42	5000.0	9.000	L1	10.01
0.542	---	33.73	46.00	12.27	5000.0	9.000	L1	10.01
1.883	---	32.44	46.00	13.56	5000.0	9.000	N	9.72
1.883	40.07	---	56.00	15.93	5000.0	9.000	N	9.72

2024-12-04





페이지(page) : ( 20 ) / ( 총(Total) 27 )

## Attachment I

## PHOTOGRAPHS







페이지(page) : ( 21 ) / ( 총(Total) 27 )

### Radiated emission (Below 1 GHz) – [MODE 1]

[Front]



[Rear]






페이지(page) : ( 22 ) / ( 총(Total) 27 )

### Radiated emission (Below 1 GHz) – [MODE 2]

[Front]



[Rear]






페이지(page) : ( 23 ) / ( 총(Total) 27 )

### Radiated emission (Above 1 GHz) – [MODE 1]

[Front]



[Rear]









페이지(page) : ( 24 ) / ( 총(Total) 27 )

### Radiated emission (Above 1 GHz) – [MODE 2]

[Front]



[Rear]





페이지(page) : ( 25 ) / ( 총(Total) 27 )

### Conducted emission – [MODE 1]

[Front]



[Rear]





페이지(page) : ( 26 ) / ( 총(Total) 27 )

### EUT Photo

[Front]




[Rear]





페이지(page) : ( 27 ) / ( 총(Total) 27 )

[Inside]



- END -

