

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DLLYNXREN-2

Date : _03/24/2004_____ Tested by : _G.Barbato___ Approved by : __K.Addy_____

Test Sample (model) : _____LYNXREN-2_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	LPA # 365				729
345	H	75.00	1.4	16.95	46505.0	15%	6975.8	7292
690	H	29.87	2.2	21.18	459.7	15%	69.0	729
1035	H	27.67	2.8	25.51	629.5	15%	94.4	500
1380	V	28.00	3.7	29.91	1203.6	15%	180.5	500
1725	H	28.17	4.2	31.3	1525.8	15%	228.9	729
2070	H	28.33	4.7	27.91	1114.3	15%	167.1	729
2415	H	28.33	5.5	28.59	1321.3	15%	198.2	729
2760	V	28.67	6.1	29.45	1625.5	15%	243.8	729
3105	H	28.87	7.4	30.13	2089.3	15%	313.4	729
3450	H	28.87	9.1	30.28	2585.2	15%	387.8	729
4000			CABLE "A"	HORN #3127				