



# FCC PART 15C TEST REPORT No.I21Z61036-IOT07

for

**TCL Communication Ltd.**

**Vodafone Gigacube**

**HH500V**

**With**

**FCC ID: 2ACCJB157**

**Hardware Version: HH500\_MB\_C**

**Software Version: HH500V\_VDF\_V2.0.0B01**

**Issued Date: 2021-08-21**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

**Test Laboratory:**

**CTTL-Telecommunication Technology Labs, CAICT**

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)

## **REPORT HISTORY**

| Report Number   | Revision | Description                                                                                                                                                                                 | Issue Date |
|-----------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| I21Z61036-IOT07 | Rev.0    | 1st edition                                                                                                                                                                                 | 2021-08-02 |
| I21Z61036-IOT07 | Rev.1    | Add the information of attenuator.<br>Update the note of SISO maximum power.<br>Update the CDD/Beamforming statement.<br>Clarify the antenna of measurement results of radiated band edges. | 2021-08-21 |

## **CONTENTS**

|                                                                         |           |
|-------------------------------------------------------------------------|-----------|
| <b>1. TEST LABORATORY .....</b>                                         | <b>5</b>  |
| 1.1. INTRODUCTION & ACCREDITATION .....                                 | 5         |
| 1.2. TESTING LOCATION .....                                             | 5         |
| 1.3. TESTING ENVIRONMENT .....                                          | 6         |
| 1.4. PROJECT DATE.....                                                  | 6         |
| 1.5. SIGNATURE .....                                                    | 6         |
| <b>2. CLIENT INFORMATION .....</b>                                      | <b>7</b>  |
| 2.1. APPLICANT INFORMATION .....                                        | 7         |
| 2.2. MANUFACTURER INFORMATION .....                                     | 7         |
| <b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b> | <b>8</b>  |
| 3.1. ABOUT EUT.....                                                     | 8         |
| 3.2. INTERNAL IDENTIFICATION OF EUT .....                               | 8         |
| 3.3. INTERNAL IDENTIFICATION OF AE .....                                | 8         |
| 3.4. GENERAL DESCRIPTION .....                                          | 9         |
| 3.5. INTERPRETATION OF THE TEST ENVIRONMENT .....                       | 9         |
| <b>4. REFERENCE DOCUMENTS .....</b>                                     | <b>9</b>  |
| 4.1. DOCUMENTS SUPPLIED BY APPLICANT.....                               | 9         |
| 4.2. REFERENCE DOCUMENTS FOR TESTING .....                              | 9         |
| <b>5. TEST RESULTS.....</b>                                             | <b>10</b> |
| 5.1. SUMMARY OF TEST RESULTS .....                                      | 10        |
| 5.2. STATEMENTS.....                                                    | 10        |
| 5.3. TEST CONDITIONS .....                                              | 10        |
| <b>6. TEST FACILITIES UTILIZED .....</b>                                | <b>11</b> |
| <b>7. MEASUREMENT UNCERTAINTY .....</b>                                 | <b>12</b> |
| 7.1. MAXIMUM OUTPUT POWER.....                                          | 12        |
| 7.2. PEAK POWER SPECTRAL DENSITY .....                                  | 12        |
| 7.3. DTS 6-dB SIGNAL BANDWIDTH.....                                     | 12        |
| 7.4. BAND EDGES COMPLIANCE .....                                        | 12        |
| 7.5. TRANSMITTER SPURIOUS EMISSION .....                                | 12        |
| 7.6. AC POWER-LINE CONDUCTED EMISSION .....                             | 12        |
| <b>ANNEX A: DETAILED TEST RESULTS.....</b>                              | <b>13</b> |
| <b>A.1. MEASUREMENT METHOD.....</b>                                     | <b>13</b> |
| <b>A.2. MAXIMUM OUTPUT POWER.....</b>                                   | <b>14</b> |
| A.2.1. PEAK OUTPUT POWER-CONDUCTED .....                                | 14        |

|                                                       |            |
|-------------------------------------------------------|------------|
| <b>A.3. PEAK POWER SPECTRAL DENSITY .....</b>         | <b>20</b>  |
| <b>A.4. DTS 6-DB SIGNAL BANDWIDTH .....</b>           | <b>61</b>  |
| <b>A.5. BAND EDGES COMPLIANCE .....</b>               | <b>69</b>  |
| A.5.1 BAND EDGES COMPLIANCE – CONDUCTED .....         | 69         |
| A.5.2 BAND EDGES COMPLIANCE – RADIATED .....          | 96         |
| <b>A.6. TRANSMITTER SPURIOUS EMISSION.....</b>        | <b>105</b> |
| A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED ..... | 105        |
| A.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED .....  | 268        |
| <b>A.7. AC POWER-LINE CONDUCTED EMISSION .....</b>    | <b>283</b> |
| <b>ANNEX B: EUT PARAMETERS.....</b>                   | <b>288</b> |
| <b>ANNEX C: ACCREDITATION CERTIFICATE .....</b>       | <b>288</b> |

## **1. Test Laboratory**

### **1.1.Introduction & Accreditation**

**Telecommunication Technology Labs, CAICT** is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

### **1.2. Testing Location**

Location 1:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,  
Haidian District, Beijing, China

Location 2:CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China100191


### 1.3. Testing Environment

Normal Temperature: 15-25°C  
Relative Humidity: 20-75%

### 1.4. Project date


Testing Start Date: 2021-05-31  
Testing End Date: 2021-08-20

### 1.5. Signature



---

Xie Xiuzhen  
(Prepared this test report)



---

Zheng Wei  
(Reviewed this test report)



---

Hu Xiaoyu  
(Approved this test report)

## **2. Client Information**

### **2.1.Applicant Information**

Company Name: TCL Communication Ltd.  
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science  
Park, Shatin, NT, Hong Kong  
City: Hong Kong  
Postal Code: /  
Country: China  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### **2.2.Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science  
Park, Shatin, NT, Hong Kong  
City: Hong Kong  
Postal Code: /  
Country: China  
Telephone: 0086-755-36611722  
Fax: 0086-755-36612000-81722

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

|                     |                       |
|---------------------|-----------------------|
| Description         | Vodafone Gigacube     |
| Model name          | HH500V                |
| FCC ID              | 2ACCJB157             |
| With WLAN Function  | Yes                   |
| Frequency Band      | ISM 2400MHz~2483.5MHz |
| Type of Modulation  | DSSS/CCK/OFDM/OFDMA   |
| Number of Channels  | 11                    |
| Antenna             | Integral Antenna      |
| MAX Conducted Power | 25.75dBm              |
| Power Supply        | 12V                   |

#### 3.2. Internal Identification of EUT

| EUT ID* | SN or IMEI      | HW Version | SW Version           |
|---------|-----------------|------------|----------------------|
| EUT1    | 350364240200093 | HH500_MB_C | HH500V_VDF_V2.0.0B01 |
| EUT2    | 350364240200069 | HH500_MB_C | HH500V_VDF_V2.0.0B01 |
| EUT3    | 350364240200077 | HH500_MB_C | HH500V_VDF_V2.0.0B01 |
| EUT4    | 350364240200085 | HH500_MB_C | HH500V_VDF_V2.0.0B01 |

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE

| AE ID* | Description | SN |
|--------|-------------|----|
| AE1    | Charger     | /  |
| AE2    | Charger     | /  |

##### AE1

|              |                                   |
|--------------|-----------------------------------|
| Model        | CYSE36-120300E                    |
| Manufacturer | Jiangsu Chenyang Electron Co.,Ltd |

##### AE2

|              |                                   |
|--------------|-----------------------------------|
| Model        | CYSE36-120300UK                   |
| Manufacturer | Jiangsu Chenyang Electron Co.,Ltd |

\*AE ID: is used to identify the test sample in the lab internally.

### 3.4. General Description

The Equipment under Test (EUT) is a model of Vodafone Gigacube with integrated antenna. Samples undergoing test were selected by the client.

### 3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor  $k=2$ .

Measurement Uncertainty

| Parameter   | Uncertainty |
|-------------|-------------|
| temperature | 0.48°C      |
| humidity    | 2 %         |
| DC voltages | 0.003V      |

## 4. Reference Documents

### 4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

### 4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference      | Title                                                                                                                                                                                    | Version |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| FCC Part15     | FCC CFR 47, Part 15, Subpart C:                                                                                                                                                          | 2018    |
|                | 15.205 Restricted bands of operation;                                                                                                                                                    |         |
|                | 15.209 Radiated emission limits, general requirements;                                                                                                                                   |         |
| ANSI C63.10    | 15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.                                                                                                        | 2013    |
|                | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices                                                                                           |         |
| KDB 558074 D01 | Federal Communications Commission Office of Engineering and Technology Laboratory Division                                                                                               | 2019    |
|                | GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES |         |
| KDB-662911 D01 | Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g. MIMO Smart Antenna etc)                                                                                   | 2013    |

## 5. Test Results

### 5.1. Summary of Test Results

| SUMMARY OF MEASUREMENT RESULTS            | Sub-clause of Part15C  | Sub-clause of IC | Verdict |
|-------------------------------------------|------------------------|------------------|---------|
| Maximum Peak Output Power                 | 15.247 (b)             | /                | P       |
| Peak Power Spectral Density               | 15.247 (e)             | /                | P       |
| Occupied 6dB Bandwidth                    | 15.247 (a)             | /                | P       |
| Band Edges Compliance                     | 15.247 (d)             | /                | P       |
| Transmitter Spurious Emission - Conducted | 15.247 (d)             | /                | P       |
| Transmitter Spurious Emission - Radiated  | 15.247, 15.205, 15.209 | /                | P       |
| AC Powerline Conducted Emission           | 15.107, 15.207         | /                | P       |

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

|    |                                                                               |
|----|-------------------------------------------------------------------------------|
| P  | Pass, The EUT complies with the essential requirements in the standard.       |
| NP | Not Perform, The test was not performed by CTTL                               |
| NA | Not Applicable, The test was not applicable                                   |
| F  | Fail, The EUT does not comply with the essential requirements in the standard |

### 5.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

### 5.3. Test Conditions

|       |                    |
|-------|--------------------|
| T nom | Normal Temperature |
| T min | Low Temperature    |
| T max | High Temperature   |
| V nom | Normal Voltage     |

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

|             |       |        |
|-------------|-------|--------|
| Temperature | T nom | 26°C   |
| Voltage     | V nom | 12V    |
| Humidity    | H nom | 20-75% |

## 6. Test Facilities Utilized

### Conducted test system

| No. | Equipment              | Model   | Serial Number | Manufacturer    | Calibration Period | Calibration Due date |
|-----|------------------------|---------|---------------|-----------------|--------------------|----------------------|
| 1   | Vector Signal Analyzer | FSQ40   | 200089        | Rohde & Schwarz | 1 year             | 2022-05-24           |
| 2   | LISN                   | ENV216  | 101200        | Rohde & Schwarz | 1 year             | 2022-02-23           |
| 3   | Test Receiver          | ESCI    | 100344        | Rohde & Schwarz | 1 year             | 2022-05-30           |
| 4   | Shielding Room         | S81     | /             | ETS-Lindgren    | /                  | /                    |
| 5   | Attenuator             | 10dB/2W | /             | Rosenberger     | /                  | /                    |

### Radiated emission test system

| No. | Equipment                         | Model    | Serial Number | Manufacturer | Calibration Period | Calibration Due date |
|-----|-----------------------------------|----------|---------------|--------------|--------------------|----------------------|
| 1   | Test Receiver                     | ESU26    | 100235        | R&S          | 1 year             | 2022-02-23           |
| 2   | BiLog Antenna                     | VULB9163 | 483           | Schwarzbeck  | 1 year             | 2021-08-27           |
| 3   | Dual-Ridge Waveguide Horn Antenna | 3115     | 6914          | ETS-Lindgren | 1 year             | 2022-02-03           |
| 4   | Loop Antenna                      | HFH2-Z2  | 829324/007    | R&S          | 1 year             | 2021-12-10           |
| 5   | EMI Antenna                       | 3116     | 2661          | ETS-Lindgren | 1 year             | 2022-01-05           |

## 7. Measurement Uncertainty

### 7.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

### 7.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

### 7.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

### 7.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

### 7.5. Transmitter Spurious Emission

#### Conducted (k=1.96)

| Frequency Range                            | Uncertainty(dB) |
|--------------------------------------------|-----------------|
| $30\text{MHz} \leq f \leq 2\text{GHz}$     | 1.22            |
| $2\text{GHz} \leq f \leq 3.6\text{GHz}$    | 1.22            |
| $3.6\text{GHz} \leq f \leq 8\text{GHz}$    | 1.22            |
| $8\text{GHz} \leq f \leq 12.75\text{GHz}$  | 1.51            |
| $12.75\text{GHz} \leq f \leq 26\text{GHz}$ | 1.51            |
| $26\text{GHz} \leq f \leq 40\text{GHz}$    | 1.59            |

#### Radiated (k=2)

| Frequency Range                         | Uncertainty(dB) |
|-----------------------------------------|-----------------|
| 9kHz-30MHz                              | /               |
| $30\text{MHz} \leq f \leq 1\text{GHz}$  | 5.40            |
| $1\text{GHz} \leq f \leq 18\text{GHz}$  | 4.32            |
| $18\text{GHz} \leq f \leq 40\text{GHz}$ | 5.26            |

### 7.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB,k=2

## **ANNEX A: Detailed Test Results**

### **A.1. Measurement Method**

#### **A.1.1. Conducted Measurements**


Connect the EUT to the test system as Fig.A.1.1.1 shows.

Set the EUT to the required work mode.

Set the EUT to the required channel.

Set the Vector Signal Analyzer and start measurement.

Record the values. Vector Signal Analyzer




**Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements**

#### **A.1.2. Radiated Emission Measurements**

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



**Fig.A.1.2.1: Test Setup Diagram for Radiated Measurements**

## A.2. Maximum Output Power

**Method of Measurement:** See ANSI C63.10-2013-clause 11.9.1.2

- Set the RBW = 1 MHz.
- Set the VBW = 3 MHz.
- Set the span  $\geq [1.5 \times \text{DTS bandwidth}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector).

**Measurement Limit:**

| Standard               | Limit (dBm) |
|------------------------|-------------|
| FCC CRF Part 15.247(b) | < 30        |

**EUT ID:** EUT2/3/4

### A.2.1. Peak Output Power-conducted

The following data rate are selected as the worst condition; as the maximum power is got with these data rate. The following cases are performed with this condition.

W1:

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 1Mbps           | 6Mbps           | MCS0                 | MCS0                 | MCS0                  | MCS0                  |

W2

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 1Mbps           | 6Mbps           | MCS0                 | MCS0                 | MCS0                  | MCS0                  |

W3

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 1Mbps           | 6Mbps           | MCS0                 | MCS0                 | MCS0                  | MCS0                  |

W4

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 6Mbps           | MCS0                 | MCS0                 | MCS0                  | MCS0                  |

MIMO&CDD(W1&W2)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|

|        |        |      |      |       |       |
|--------|--------|------|------|-------|-------|
| 11Mbps | 54Mbps | MCS7 | MCS7 | MCS11 | MCS11 |
|--------|--------|------|------|-------|-------|

(W1&W2&W4)

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 11Mbps       | 54Mbps       | MCS7              | MCS7              | MCS11              | MCS11              |

(W1&W2&W3&W4)

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 11Mbps       | 54Mbps       | MCS7              | MCS7              | MCS11              | MCS11              |

All duty cycle of Worse case as following:

W1:

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 1Mbps        | 6Mbps        | MCS0              | MCS0              | MCS0               | MCS0               |
| 62%          | 94%          | 94%               | 89%               | 88%                | 64%                |

W2

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 1Mbps        | 6Mbps        | MCS0              | MCS0              | MCS0               | MCS0               |
| 62%          | 94%          | 95%               | 89%               | 90%                | 74%                |

W3

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 1Mbps        | 6Mbps        | MCS0              | MCS0              | MCS0               | MCS0               |
| 62%          | 94%          | 95%               | 89%               | 90%                | 74%                |

W4

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 11Mbps       | 6Mbps        | MCS0              | MCS0              | MCS0               | MCS0               |
| 32%          | 94%          | 94%               | 87%               | 91%                | 75%                |

(W1&W2-W1)

|              |              |                   |                   |                    |                    |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
| 11Mbps       | 54Mbps       | MCS7              | MCS7              | MCS11              | MCS11              |
| 33%          | 59%          | 90%               | 90%               | 85%                | 75%                |

(W1&amp;W2-W2)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 90%                   | 68%                   |

(W1&amp;W2&amp;W4-W1)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 88%                   | 76%                   |

(W1&amp;W2&amp;W4-W2)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 88%                   | 76%                   |

(W1&amp;W2&amp;W4-W4)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 88%                   | 76%                   |

(W1&amp;W2&amp;W3&amp;W4-W1)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 87%                   | 75%                   |

(W1&amp;W2&amp;W3&amp;W4-W2)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 87%                   | 75%                   |

(W1&amp;W2&amp;W3&amp;W4-W3)

|                 |                 |                      |                      |                       |                       |
|-----------------|-----------------|----------------------|----------------------|-----------------------|-----------------------|
| 802.11b<br>mode | 802.11g<br>mode | 802.11n-HT20<br>mode | 802.11n-HT40<br>mode | 802.11ax-HE20<br>mode | 802.11ax-HE40<br>mode |
| 11Mbps          | 54Mbps          | MCS7                 | MCS7                 | MCS11                 | MCS11                 |
| 33%             | 59%             | 90%                  | 90%                  | 87%                   | 75%                   |

(W1&amp;W2&amp;W3&amp;W4-W4)

| 802.11b mode | 802.11g mode | 802.11n-HT20 mode | 802.11n-HT40 mode | 802.11ax-HE20 mode | 802.11ax-HE40 mode |
|--------------|--------------|-------------------|-------------------|--------------------|--------------------|
| 11Mbps       | 54Mbps       | MCS7              | MCS7              | MCS11              | MCS11              |
| 33%          | 59%          | 90%               | 90%               | 87%                | 75%                |

802.11ax-HE20: tp-26x9\_20MHz

802.11ax-HE40: tp-52x2\_106\_242\_40MHz

802.11b/g supports CDD 802.11n support CDD and Beamforming.

| Tx Paths | Antenna Gain(dBi) | Beamforming DG(dBi) | CDD DG(Power)(dBi) |
|----------|-------------------|---------------------|--------------------|
| 2        | 3.8               | 6.81                | 3.8                |
| 3        | 3.8               | 8.57                | 3.8                |
| 4        | 3.8               | 9.82                | 3.8                |

## Measurement Results:

### SISO

| Result(dBm)   |       |       |       |        |
|---------------|-------|-------|-------|--------|
| 802.11b       | W1    | W2    | W3    | W4     |
| Channel\ rate | 1Mbps | 1Mbps | 1Mbps | 11Mbps |
| 1             | 16.53 | 18.21 | 17.32 | 17.67  |
| 6             | 16.41 | 17.81 | 17.37 | 16.76  |
| 11            | 16.18 | 17.11 | 16.92 | 17.14  |
| 802.11g       | W1    | W2    | W3    | W4     |
| Channel\ rate | 6Mbps | 6Mbps | 6Mbps | 6Mbps  |
| 1             | 22.49 | 22.49 | 21.52 | 21.94  |
| 6             | 22.64 | 22.07 | 21.65 | 21.57  |
| 11            | 22.64 | 21.54 | 21.42 | 21.94  |
| 802.11n-HT20  | W1    | W2    | W3    | W4     |
| Channel\ rate | MCS0  | MCS0  | MCS0  | MCS0   |
| 1             | 23.43 | 23.44 | 22.29 | 22.81  |
| 6             | 23.26 | 22.76 | 22.57 | 22.31  |
| 11            | 21.97 | 22.54 | 22.17 | 22.67  |
| 802.11n-HT40  | W1    | W2    | W3    | W4     |
| Channel\ rate | MCS0  | MCS0  | MCS0  | MCS0   |
| 3             | 22.52 | 22.56 | 21.74 | 23.29  |
| 6             | 23.52 | 23.16 | 22.87 | 22.81  |

|                      |           |           |           |           |
|----------------------|-----------|-----------|-----------|-----------|
| 9                    | 24.39     | 23.27     | 22.83     | 23.64     |
| <b>802.11ax-HE20</b> | <b>W1</b> | <b>W2</b> | <b>W3</b> | <b>W4</b> |
| Channel\ rate        | MCS0      | MCS0      | MCS0      | MCS0      |
| 1                    | 22.97     | 24.32     | 22.79     | 22.69     |
| 6                    | 22.23     | 23.73     | 21.68     | 22.70     |
| 11                   | 22.13     | 22.99     | 21.95     | 22.00     |
| <b>802.11ax-HE40</b> | <b>W1</b> | <b>W2</b> | <b>W3</b> | <b>W4</b> |
| Channel\ rate        | MCS0      | MCS0      | MCS0      | MCS0      |
| 3                    | 22.91     | 24.30     | 22.90     | 23.04     |
| 6                    | 22.31     | 23.91     | 22.23     | 22.91     |
| 9                    | 22.70     | 23.91     | 22.70     | 22.73     |

Note: The maximum power points for each mode of modulation are as follows:

The largest point of 802.11b/n20 is W2; 802.11g/n40 is W1; 802.11ax-HE20/40 is W2.

**(W1&W2)**

| Result(dBm)   |        |         |         |          |
|---------------|--------|---------|---------|----------|
| Mode          | Rate   | 2412MHz | 2437MHz | 2462 MHz |
| 802.11b       | 11Mbps | 18.95   | 18.54   | 18.34    |
| 802.11g       | 54Mbps | 23.02   | 22.98   | 22.70    |
| 802.11n-HT20  | MCS7   | 23.11   | 22.96   | 22.81    |
| 802.11ax-HE20 | MCS11  | 23.55   | 23.09   | 22.94    |

**802.11n-HT40**

| Result(dBm)   |       |         |         |          |
|---------------|-------|---------|---------|----------|
| Ant           | Rate  | 2422MHz | 2437MHz | 2452 MHz |
| 802.11n-HT40  | MCS7  | 23.66   | 23.58   | 23.85    |
| 802.11ax-HE40 | MCS11 | 23.51   | 23.16   | 23.24    |

Note: The maximum power points for each mode of modulation are as follows:

The largest point of 802.11b/g/n20/n40 is W1; 802.11ax-HE20/40 is W1.

**(W1&W2&W4)**

| Result(dBm)   |        |         |         |          |
|---------------|--------|---------|---------|----------|
| Mode          | Rate   | 2412MHz | 2437MHz | 2462 MHz |
| 802.11b       | 11Mbps | 19.10   | 18.14   | 18.66    |
| 802.11g       | 54Mbps | 22.11   | 21.86   | 21.99    |
| 802.11n-HT20  | MCS7   | 22.60   | 22.48   | 22.66    |
| 802.11ax-HE20 | MCS11  | 24.98   | 25.00   | 24.73    |

**802.11n-HT40**

| Result(dBm)   |       |         |         |          |
|---------------|-------|---------|---------|----------|
| Ant           | Rate  | 2422MHz | 2437MHz | 2452 MHz |
| 802.11n-HT40  | MCS7  | 22.85   | 22.58   | 23.08    |
| 802.11ax-HE40 | MCS11 | 25.34   | 25.10   | 25.29    |

Note: The maximum power points for each mode of modulation are as follows:

The largest point of 802.11b/g/n20/n40 is W1; 802.11ax-HE20/40 is W2.

**(W1&W2&W3&W4)**

| Result(dBm)   |        |         |         |          |
|---------------|--------|---------|---------|----------|
| Mode          | Rate   | 2412MHz | 2437MHz | 2462 MHz |
| 802.11b       | 11Mbps | 17.02   | 17.27   | 16.94    |
| 802.11g       | 54Mbps | 21.71   | 21.58   | 21.66    |
| 802.11n-HT20  | MCS7   | 22.94   | 22.76   | 22.72    |
| 802.11ax-HE20 | MCS11  | 24.73   | 25.44   | 25.25    |

**802.11n-HT40**

| Result(dBm)   |       |         |         |          |
|---------------|-------|---------|---------|----------|
| Ant           | Rate  | 2422MHz | 2437MHz | 2452 MHz |
| 802.11n-HT40  | MCS7  | 22.03   | 21.83   | 22.22    |
| 802.11ax-HE40 | MCS11 | 25.75   | 25.56   | 24.27    |

Note: The maximum power points for each mode of modulation are as follows:

The largest point of 802.11b/g/n20/n40 is W1; 802.11ax-HE20/40 is W2.

### A.3. Peak Power Spectral Density

**Method of Measurement:** See ANSI C63.10-2013-clause 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to  $RBW = 3 \text{ kHz}$ .
- Set the VBW = 10 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

#### Measurement Limit:

| Standard               | Limit         |
|------------------------|---------------|
| FCC CRF Part 15.247(e) | < 8 dBm/3 kHz |

#### Measurement Results:

SISO(802.11b/n20 is W2; 802.11g/n40 is W1)

#### 802.11b/g mode

| Mode    | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|---------|---------|-----------------------------------------|------------|
| 802.11b | 1       | -13.98                                  | P          |
|         | 6       | -14.42                                  | P          |
|         | 11      | -14.22                                  | P          |
| 802.11g | 1       | -14.14                                  | P          |
|         | 6       | -13.90                                  | P          |
|         | 11      | -14.13                                  | P          |

#### 802.11n-HT20 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT20) | 1       | -11.53                                  | P          |
|                   | 6       | -11.72                                  | P          |
|                   | 11      | -11.93                                  | P          |

#### 802.11n-HT40 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT40) | 3       | -15.07                                  | P          |
|                   | 6       | -14.79                                  | P          |
|                   | 9       | -13.58                                  | P          |

#### SISO-W2

#### 802.11ax-HE20 mode

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE20) | 1       | -13.49                                  | P          |
|                    | 6       | -14.56                                  | P          |
|                    | 11      | -14.39                                  | P          |

#### 802.11ax-HE40 mode

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE40) | 3       | -16.63                                  | P          |
|                    | 6       | -16.36                                  | P          |
|                    | 9       | -16.12                                  | P          |

#### (W1&W2)

#### 802.11b/g mode

| Mode    | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|---------|---------|-----------------------------------------|------------|
| 802.11b | 1       | -11.25                                  | P          |
|         | 6       | -11.65                                  | P          |
|         | 11      | -11.32                                  | P          |
| 802.11g | 1       | -12.45                                  | P          |
|         | 6       | -12.67                                  | P          |
|         | 11      | -12.36                                  | P          |

#### 802.11n-HT20 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT20) | 1       | -11.17                                  | P          |
|                   | 6       | -11.33                                  | P          |
|                   | 11      | -11.66                                  | P          |

#### 802.11n-HT40 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT40) | 3       | -14.15                                  | P          |
|                   | 6       | -14.64                                  | P          |
|                   | 9       | -14.33                                  | P          |

#### 802.11ax-HE20 mode

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE20) | 1       | -13.14                                  | P          |
|                    | 6       | -14.39                                  | P          |
|                    | 11      | -13.83                                  | P          |

**802.11ax-HE40 mode**

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE40) | 3       | -15.68                                  | P          |
|                    | 6       | -16.30                                  | P          |
|                    | 9       | -16.34                                  | P          |

(W1&W2&w4)

**802.11b/g mode**

| Mode    | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|---------|---------|-----------------------------------------|------------|
| 802.11b | 1       | -11.84                                  | P          |
|         | 6       | -11.68                                  | P          |
|         | 11      | -11.43                                  | P          |
| 802.11g | 1       | -13.62                                  | P          |
|         | 6       | -13.49                                  | P          |
|         | 11      | -13.29                                  | P          |

**802.11n-HT20 mode**

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT20) | 1       | -11.63                                  | P          |
|                   | 6       | -12.19                                  | P          |
|                   | 11      | -11.60                                  | P          |

**802.11n-HT40 mode**

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT40) | 3       | -14.99                                  | P          |
|                   | 6       | -15.14                                  | P          |
|                   | 9       | -14.51                                  | P          |

**802.11ax-HE20 mode**

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE20) | 1       | -12.82                                  | P          |
|                    | 6       | -12.51                                  | P          |
|                    | 11      | -12.46                                  | P          |

**802.11ax-HE40 mode**

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE40) | 3       | -15.06                                  | P          |
|                    | 6       | -14.79                                  | P          |

|  |   |        |   |
|--|---|--------|---|
|  | 9 | -15.24 | P |
|--|---|--------|---|

(W1&W2&W3&W4)

#### 802.11b/g mode

| Mode    | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|---------|---------|-----------------------------------------|------------|
| 802.11b | 1       | -12.36                                  | P          |
|         | 6       | -12.30                                  | P          |
|         | 11      | -12.48                                  | P          |
| 802.11g | 1       | -13.68                                  | P          |
|         | 6       | -13.63                                  | P          |
|         | 11      | -13.19                                  | P          |

#### 802.11n-HT20 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT20) | 1       | -11.44                                  | P          |
|                   | 6       | -11.89                                  | P          |
|                   | 11      | -11.63                                  | P          |

#### 802.11n-HT40 mode

| Mode              | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|-------------------|---------|-----------------------------------------|------------|
| 802.11n<br>(HT40) | 3       | -15.90                                  | P          |
|                   | 6       | -16.16                                  | P          |
|                   | 9       | -15.80                                  | P          |

#### 802.11ax-HE20 mode

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE20) | 1       | -11.81                                  | P          |
|                    | 6       | -12.09                                  | P          |
|                    | 11      | -12.38                                  | P          |


#### 802.11ax-HE40 mode

| Mode               | Channel | Power Spectral Density<br>( dBm/3 kHz ) | Conclusion |
|--------------------|---------|-----------------------------------------|------------|
| 802.11ax<br>(HE40) | 3       | -14.59                                  | P          |
|                    | 6       | -14.40                                  | P          |
|                    | 9       | -14.30                                  | P          |


**Conclusion: Pass**

**Test graphs as below:**


**siso**




**Fig.A.3.1 Power Spectral Density(802.11b,Ch1)**




**Fig.A.3.2 Power Spectral Density (802.11b, Ch 6)**




**Fig.A.3.3 Power Spectral Density (802.11b, Ch 11)**




**Fig.A.3.4 Power Spectral Density (802.11g, Ch 1)**




**Fig.A.3.5 Power Spectral Density (802.11g, Ch 6)**




**Fig.A.3.6 Power Spectral Density (802.11g, Ch 11)**




**Fig.A.3.7 Power Spectral Density (802.11n-HT20, Ch 1)**




**Fig.A.3.8 Power Spectral Density (802.11n-HT20, Ch 6)**




**Fig.A.3.9 Power Spectral Density (802.11n-HT20, Ch 11)**




**Fig.A.3.10 Power Spectral Density (802.11n-HT40, Ch 3)**




**Fig.A.3.11 Power Spectral Density (802.11n-HT40, Ch 6)**




**Fig.A.3.12 Power Spectral Density (802.11n-HT40, Ch 9)**




**Fig.A.3.13 Power Spectral Density (802.11ax-HE20, Ch 1)**




**Fig.A.3.14 Power Spectral Density (802.11ax-HE20, Ch 6)**



**Fig.A.3.15 Power Spectral Density (802.11ax-HE20, Ch 11)**



**Fig.A.3.16 Power Spectral Density (802.11ax-HE40, Ch 3)**



**Fig.A.3.17 Power Spectral Density (802.11ax-HE40, Ch 6)**




Fig.A.3.18 Power Spectral Density (802.11ax-HE40, Ch 9)

MIMO&CDD(W1&W2-W1)







Fig.A.3.19 Power Spectral Density(802.11b,Ch1)




**Fig.A.3.20 Power Spectral Density (802.11b, Ch 6)**




**Fig.A.3.21 Power Spectral Density (802.11b, Ch 11)**




**Fig.A.3.22 Power Spectral Density (802.11g, Ch 1)**




**Fig.A.3.23 Power Spectral Density (802.11g, Ch 6)**




**Fig.A.3.24 Power Spectral Density (802.11g, Ch 11)**




**Fig.A.3.25 Power Spectral Density (802.11n-HT20, Ch 1)**




**Fig.A.3.26 Power Spectral Density (802.11n-HT20, Ch 6)**




**Fig.A.3.27 Power Spectral Density (802.11n-HT20, Ch 11)**




**Fig.A.3.28 Power Spectral Density (802.11n-HT40, Ch 3)**



**Fig.A.3.29 Power Spectral Density (802.11n-HT40, Ch 6)**



**Fig.A.3.30 Power Spectral Density (802.11n-HT40, Ch 9)**



**Fig.A.3.31 Power Spectral Density (802.11ax-HE20, Ch 1)**




Fig.A.3.32 Power Spectral Density (802.11ax-HE20, Ch 6)






Fig.A.3.33 Power Spectral Density (802.11ax-HE20, Ch 11)



**Fig.A.3.34 Power Spectral Density (802.11ax-HE40, Ch 3)**



**Fig.A.3.35 Power Spectral Density (802.11ax-HE40, Ch 6)**




Fig.A.3.36 Power Spectral Density (802.11ax-HE40, Ch 9)

### MIMO&CDD(W1&W2&W4-W1)







Fig.A.3.37 Power Spectral Density(802.11b,Ch1)




**Fig.A.3.38 Power Spectral Density (802.11b, Ch 6)**




**Fig.A.3.39 Power Spectral Density (802.11b, Ch 11)**




**Fig.A.3.40 Power Spectral Density (802.11g, Ch 1)**




**Fig.A.3.41 Power Spectral Density (802.11g, Ch 6)**




**Fig.A.3.42 Power Spectral Density (802.11g, Ch 11)**




**Fig.A.3.43 Power Spectral Density (802.11n-HT20, Ch 1)**




**Fig.A.3.44 Power Spectral Density (802.11n-HT20, Ch 6)**



**Fig.A.3.45 Power Spectral Density (802.11n-HT20, Ch 11)**



**Fig.A.3.46 Power Spectral Density (802.11n-HT40, Ch 3)**



**Fig.A.3.47 Power Spectral Density (802.11n-HT40, Ch 6)**




Fig.A.3.48 Power Spectral Density (802.11n-HT40, Ch 9)

### MIMO&CDD(W1&W2&W4-W2)






Fig.A.3.49 Power Spectral Density (802.11ax-HE20, Ch 1)



**Fig.A.3.50 Power Spectral Density (802.11ax-HE20, Ch 6)**



**Fig.A.3.51 Power Spectral Density (802.11ax-HE20, Ch 11)**