

Report No. : FA432804-02



# **Radio Exposure Evaluation Report**

| FCC ID       | : 2AGMR-AP750NRE   |
|--------------|--|
| Equipment    | : 4-radio Narrow-Directional Outdoor Wi-Fi 7 Access Point                    |
| Brand Name   | : Everest Networks   |
| Model Name   | : AP750UNe   |
| Applicant    | : Everest Networks, Inc.<br>42808 Christy Street Suite 108 Fremont, CA 94538 |
| Manufacturer | : Everest Networks, Inc.<br>42808 Christy Street Suite 108 Fremont, CA 94538 |
| Standard     | : 47 CFR FCC Part 2 Subpart J, section 2.1091                                |

The product was received on Jul. 05, 2024, and testing was started from Aug. 07, 2024 and completed on Aug. 28, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



# Table of Contents

| RY OF THIS TEST REPORT                | .3   |
|---------------------------------------|--|
| ARY OF TEST RESULT                    | .4   |
| GENERAL DESCRIPTION                   | .5   |
| Information                           | .5   |
| Applicable Standards                  | .7   |
| Testing Location                      | .7   |
| MAXIMUM PERMISSIBLE EXPOSURE          | .8   |
| Limit of Maximum Permissible Exposure | .8   |
| RF Exposure Exempt Measurement        | .9   |
| Multiple RF Sources Exposure          | 10   |
| MPE Calculation Method                | 11   |
| Calculated Result and Limit           | 12   |
| raphs of EUT V01                      |  |
|                                       | BY OF THIS TEST REPORT   ARY OF TEST RESULT   GENERAL DESCRIPTION   Information   Applicable Standards   Testing Location   MAXIMUM PERMISSIBLE EXPOSURE   Limit of Maximum Permissible Exposure   RF Exposure Exempt Measurement   Multiple RF Sources Exposure   YPE Calculation Method   Calculated Result and Limit   raphs of EUT V01 |



# History of this test report

| Report No.  | Version | Description             | Issued Date   |
|-------------|---------|-------------------------|---------------|
| FA432804-02 | 01      | Initial issue of report | Sep. 02, 2024 |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |



# Summary of Test Result

| Report<br>Clause | Ref Std.<br>Clause | Test Items          | Result<br>(PASS/FAIL) | Remark |
|------------------|--------------------|---------------------|-----------------------|--------|
| 2                | -                  | Exposure evaluation | PASS                  | -      |

#### **Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

#### **Comments and Explanations:**

None

#### Reviewed by: Ben Tseng

Report Producer: Michelle Tsai



## **1** General Description

## 1.1 Information

#### 1.1.1 EUT General Information

| RF General Information |                                     |                                     |  |
|------------------------|-------------------------------------|-------------------------------------|--|
| Evaluation<br>Mode     | Frequency Range<br>(MHz)            | Operating<br>Frequency<br>(MHz)     | Modulation Type  |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5725-5850 | 5180-5240<br>5260-5320<br>5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM,<br>256QAM, 1024QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM,<br>256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM,<br>256QAM, 1024QAM, 4096QAM) |

#### 1.1.2 Antenna Information

| Ant. | Brand   | Model Name | Antenna Type | Connector | Support | Remark  |
|------|---------|------------|--------------|-----------|---------|---------|
| 1    | Everest | PCB-000034 | PCB          | I-PEX     |         | Dadia 1 |
| 2    | Everest | PCB-000034 | PCB          | I-PEX     | 50      | Radio I |
| 3    | Everest | PCB-000033 | PCB          | I-PEX     | 56      | Dadia 2 |
| 4    | Everest | PCB-000033 | PCB          | I-PEX     |         | Radio 2 |

| Ant  | Ant. Port | Gain (dBi) |          |         |  |
|------|-----------|------------|----------|---------|--|
| Ant. |           | U-NII-1    | U-NII-2A | U-NII-3 |  |
| 1    | 1         | -          | -        | 15      |  |
| 2    | 2         | -          | -        | 15      |  |
| 3    | 1         | 15         | 15       | -       |  |
| 4    | 2         | 15         | 15       | -       |  |

Note 1: The EUT has four antennas.

Note 2: The antenna is cross polarized.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax/be mode (2TX/2RX) <Radio 1>

Ant. 1~2 could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac/ax/be mode (2TX/2RX) <Radio 2>

Ant. 3~4 could transmit/receive simultaneously.



### 1.1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FR432804AN

Below is the table for the change of the product with respect to the original one.

| Modifications                              | Performance Checking |
|--|----------------------|
| 1.Add model name AP750UNe                  |                      |
| 2.Add same type of Antenna, PCB-000034 and |                      |
| PCB-000033.                                | All                  |
| 3.Antenna changes to 2TX.                  |                      |
| 4.Use software for closing Radio 3.        |                      |



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 2 Subpart J, section 2.1091
- KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- 47 CFR Part 1.1307
- 47 CFR Part 1.1310

## 1.3 Testing Location

| Test        | Test Lab. : Sporton International Inc. Hsinhua Laboratory |  |  |  |  |
|-------------|---|--|--|--|--|
| $\boxtimes$ | Hsinhua   | ADD: No.52, Huaya 1st Rd., Gui                 | ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) |  |  |
|             | (TAF: 3785)   | TEL: 886-3-327-3456                            | FAX: 886-3-327-0973  |  |  |
|             | Test site Designation No. TW3785 with FCC.                |  |  |  |  |
|             | Wen 33rd.St.  | <b>ADD:</b> No.14-1, Ln. 19, Wen 33rd (R.O.C.) | d St., Guishan Dist., Taoyuan City 333010, Taiwan                              |  |  |
|             | (TAF: 3785)   | TEL: 886-3-318-0787                            | FAX: 886-3-318-0287  |  |  |
|             |   | Test site Designation No. TW000                | 8 with FCC.  |  |  |



# 2 Maximum Permissible Exposure

## 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range<br>(MHz)                                  | Electric Field<br>Strength (E) (V/m) | Magnetic Field<br>Strength (H) (A/m) | Power Density (S)<br>(mW/ cm²) | Averaging Time<br> E ², H ² or S<br>(minutes) |
|---|--------------------------------------|--------------------------------------|--------------------------------|---|
| 0.3-3.0   | 614                                  | 1.63                                 | (100)*                         | 6   |
| 3.0-30  | 1842 / f                             | 4.89 / f                             | (900 / f <sup>2</sup> )*       | 6   |
| 30-300  | 61.4                                 | 0.163                                | 1.0                            | 6   |
| 300-1500  | -                                    | -                                    | F/300                          | 6   |
| 1500-100,000  | -                                    | -                                    | 5                              | 6   |
| (B) Limits for General Population / Uncontrolled Exposure |                                      |                                      |                                |   |
| Frequency Range   | Electric Field                       | Magnetic Field                       | Power Density (S)              | Averaging Time                                |

| Frequency Range<br>(MHz) | Electric Field<br>Strength (E) (V/m) | Magnetic Field<br>Strength (H) (A/m) | Power Density (S)<br>(mW/ cm²) | E ², H ² or S<br>(minutes) |
|--------------------------|--------------------------------------|--------------------------------------|--------------------------------|----------------------------|
| 0.3-1.34                 | 614                                  | 1.63                                 | (100)*                         | 30                         |
| 1.34-30                  | 824/f                                | 2.19/f                               | (180/f²)*                      | 30                         |
| 30-300                   | 27.5                                 | 0.073                                | 0.2                            | 30                         |
| 300-1500                 | -                                    | -                                    | F/1500                         | 30                         |
| 1500-100,000             | -                                    | -                                    | 1.0                            | 30                         |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

#### **Multiple Transmitters Condition**

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN)



# 2.2 RF Exposure Exempt Measurement

| Option | Refer Std.          | Exemption Exposure Thresholds (TL)  |
|--------|---------------------|---|
| А      | §1.1307(b)(3)(i)(A) | Available maximum time-averaged power is no more than 1 mW  |
| В      | §1.1307(b)(3)(i)(B) | $Pth(mW) = \begin{cases} ERP_{20cm} (d/20cm)^{x} \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and f is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f (mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$ |
| С      | §1.1307(b)(3)(i)(C) | $\begin{cases} 0.3 \sim 1.34 MHz \rightarrow ERP(W) = 1920R^{2} \\ 1.34 \sim 30 MHz \rightarrow ERP(W) = 3450R^{2} / f^{2} \\ 30 \sim 300 MHz \rightarrow ERP(W) = 3.83R^{2} \\ 300 \sim 1500 MHz \rightarrow ERP(W) = 0.0128R^{2} f \\ 1500 \sim 100000 MHz \rightarrow ERP(W) = 19.2R^{2} \\ f \text{ is in MHz; R is in m; } R > \lambda / 2\pi \end{cases}$               |



# 2.3 Multiple RF Sources Exposure

| Refer Std.           | Exemption Exposure Thresholds (TL)  |
|----------------------|---|
| §1.1307(b)(3)(ii)(A) | The available maximum time-averaged power of each source is no more than 1 mW<br>and there is a separation distance of two centimeters between any portion of a<br>radiating structure operating and the nearest portion of any other radiating structure in<br>the same device, except if the sum of multiple sources is less than 1 mW during the<br>time-averaging period, in which case they may be treated as a single source<br>(separation is not required)  |
| §1.1307(b)(3)(ii)(B) | $\begin{split} \sum_{i=1}^{a} \frac{P_i}{P_{ih,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{ih,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{ExposureLimit_k} \leq 1 \\ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.  b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.  c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.  P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).  P_{th,i} = the exemption threshold power ( P_{th} ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.  ERP_{ih,j} = the ERP of fixed, mobile, or portable RF source j.  ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source i, at a distance of at least \lambda/2\pi according to the applicable formula of paragraph §1.1307 (b)(3)(i)(C) of this section.Evaluated _k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source j, at a the location of exposure.Evaluated Limit _k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source fixed, mobile, or portable RF source I at the location of exposure.$ |



## 2.4 MPE Calculation Method

The MPE was calculated at 50 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$\mathsf{E}(\mathsf{V/m}) = \frac{\sqrt{30 \times P \times G}}{d}$$

Power Density: 
$$Pd(W/m^2) = \frac{E^2}{377}$$

- E = Electric field (V/m)P = RF output power (W)
- **G** = EUT Antenna numeric gain (numeric)
- **d** = Separation distance between radiator and human body (m)
- The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.5 Calculated Result and Limit

#### Exposure Environment: General Population / Uncontrolled Exposure

Radio 1 5GHz WLAN

| Mode     | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|---------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 5.8G;D1D | 15.00       | 20.46          | 35.46         | 0.50              | 2404.9719           | 50.00            | С      | 4800.000       | 0.5010   |

#### Radio 2 5GHz WLAN

| Mode     | DG    | Power | EIRP  | Tolerance | Tune-up ERP | Distance | Ontion | TL ERP   | TL Ratio |
|----------|-------|-------|-------|-----------|-------------|----------|--------|----------|----------|
|          | (dBi) | (dBm) | (dBm) | (dB)      | (mW)        | (cm)     | Option | (mW)     |          |
| 5.2G;D1D | 15.00 | 20.31 | 35.31 | 0.50      | 2323.3252   | 50.00    | С      | 4800.000 | 0.4840   |
| 5.3G;D1D | 15.00 | 14.49 | 29.49 | 0.50      | 608.2891    | 50.00    | С      | 4800.000 | 0.1267   |

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW) Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

#### Simultaneous Transmission Analysis Mode: Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN)

| Mode        | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|-------------|-------------|----------------|---------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 5.8G;D1D    | 15.00       | 20.46          | 35.46         | 0.50              | 2404.9719           | 50.00            | С      | 4800.000       | 0.5010   |
| 5.2G;D1D    | 15.00       | 20.31          | 35.31         | 0.50              | 2323.3252           | 50.00            | С      | 4800.000       | 0.4840   |
| Sum Ratio   | 0.9850      |                |               |                   |                     |                  |        |                |          |
| Ratio Limit | 1.00000     |                |               |                   |                     |                  |        |                |          |

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW) Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

| Option | Sum TL Ratio_B                        | Option | Sum TL Ratio_C                              | Option | Sum TL Ratio_E                                       |
|--------|---------------------------------------|--------|---|--------|--|
| В      | $\sum_{i=1}^{a} \frac{P_i}{P_{th,i}}$ | С      | $\sum_{j=1}^{b} \frac{ERP_{j}}{ERP_{th,j}}$ | E      | $\sum_{k=1}^{c} \frac{Evaluated_k}{ExposureLimit_k}$ |

Note: The above antenna gain was declared by manufacturer.

------THE END-----