

### **DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)** 1

### 1.1 General:

Product Name:	Convertible PC
Brand Name:	HP
Model No.:	TPN-C137
Hardware Version:	N/A
Software Version:	N/A
WWAN Module:	Model No.: L860-GL, Supplier: Fibocom, FCC ID: ZMOL860GL

### 1.2 Antenna Information:

Vendor	Advanced Wireless & Antenna Inc.						
Antenna		Main (PIFA)					
Part Number		AML6Y-10057(DC330024W00)					
Frequency(MHz)	699~716	699~716 777~798 814~849 1710~1780 1850~1915 2305~2315 2496~2690					2496~2690
Gain (dBi)	-1.87	-1.31	-3.02	2.39	2.48	2.33	-0.81

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有或明,此根告结果僅對測試之樣品負責,同時比揉品僅保留的天。本報告未是体公司者面許可,不可部分複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or annearcose of this document of fenders may be prosecuted to the fully extend to the fully and the time of the lawy. appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號

www.tw.sgs.com



#### 1.3 **Rated Power**

Operating Frequ	ency (MH	Max. Output Power (dBm)	Antenna Gain (dBi)	EIRP / ERP (dBi / dBd)		
WCDMA/HSDPA Band 2	1852.4	~	1907.6	24.50	2.48	26.98
WCDMA/HSDPA Band 4	1712.4	~	1752.6	24.50	2.39	26.89
WCDMA/HSDPA Band 5	826.4	~	846.6	24.50	-3.02	21.48
LTE-Band 2	1850.7	~	1909.9	24.00	2.48	26.48
LTE-Band 4	1710.7	~	1754.3	24.00	2.39	26.39
LTE-Band 5	824.7	~	848.3	25.00	-3.02	21.98
LTE-Band 7	2502.5	~	2567.5	24.00	-0.81	23.19
LTE-Band 12	699.7	~	715.3	24.00	-1.87	22.13
LTE-Band 13	779.5	~	784.5	24.00	-1.31	22.69
LTE-Band 14	788	~	798	24.00	-1.31	22.69
LTE-Band 17	706.5	~	713.5	24.00	-1.87	23.19
LTE-Band 25	1850.7	~	1914.3	24.00	2.48	26.48
LTE-Band 26	824.7	~	848.3	25.00	-3.02	21.98
LTE-Band 30	2307.5	~	2312.5	23.00	2.33	25.33
LTE-Band 38	2572.5	~	2617.5	24.00	-0.81	23.19
LTE-Band 41	2498.5	~	2687.5	25.00	-0.81	24.19
LTE-Band 66	1710.7	~	1779.3	24.00	2.39	26.39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅針測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134,WuckungRoad,NewTaipeindustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Operating Frequency (MHz)		Operation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm2)	Margin	Worst Case
WCDMA/HSPA Band 2	1852.4 ~ 1907.6	20	0.10	1.00	-0.90	
WCDMA/HSPA Band 4	1712.4 ~ 1752.6	20	0.10	1.00	-0.90	
WCDMA/HSPA Band 5	826.4 ~ 846.6	20	0.03	0.55	-0.52	
LTE-Band 2	1850.7 ~ 1909.3	20	0.09	1.00	-0.91	
LTE-Band 4	1710.7 ~ 1754.3	20	0.09	1.00	-0.91	
LTE-Band 5	824.7 ~ 848.3	20	0.03	0.55	-0.52	
LTE-Band 7	2502.5 ~ 2567.5	20	0.04	1.00	-0.96	
LTE-Band 12	699.7 ~ 715.3	20	0.03	0.47	-0.43	V
LTE-Band 13	779.5 ~ 784.5	20	0.04	0.52	-0.48	
LTE-Band 14	788 ~ 798	20	0.04	0.53	-0.49	
LTE-Band 17	706.5 ~ 713.5	20	0.03	0.47	-0.44	
LTE-Band 25	1850.7 ~ 1914.3	20	0.09	1.00	-0.91	
LTE-Band 26	824.7 ~ 848.3	20	0.03	0.55	-0.52	
LTE-Band 30	2307.5 ~ 2312.5	20	0.07	1.00	-0.93	
LTE-Band 38	2572.5 ~ 2617.5	20	0.04	1.00	-0.96	
LTE-Band 41	2498.5 ~ 2687.5	20	0.05	1.00	-0.95	
LTE-Band 66	1710.7 ~ 1779.3	20	0.09	1.00	-0.91	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅針測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134,WuckungRoad,NewTaipeindustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



# 2 FCC MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## 2.1 FCC Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time		
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)	(minute)		
	Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	/	f/1500	30		
1500-15000	/	/	1.0	30		

f = frequency in MHz

\* = Plane-wave equipment power density

Prediction of MPE limit at a given distance

S=PG/4πR<sup>2</sup>

Where: S = Power density

- P = Power input to antenna
- G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms\_and\_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms\_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. [No.134,WuKungRoad,NewTaipei/clustrialPark,WukubIstrict,NewTaipei/Cliy,Taiwan24803/新北市五股區新北產業園區五工路 134 號

www.tw.sgs.com

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## 2.2 Power Density Calculation (Worst Case)

Operation Mode	Evaluation Frequency (MHz)	Operation Distance (cm)	Max. output Power (dBm)	Antenna Gain (dBi)	Max. output Power EIRP (mW)	Power Density (PD) (mW/cm2)	Limit (mW/cm2)	Pass / Fail
WWAN	699.70	20	24	-1.87	163.31	0.033	0.466	Pass

## 2.3 Evaluating the mixed mobile and portable host platform exposure condition

When the device is operated in notebook mode, WWAN is belong to mobile condition because the separation distance between WWAN antenna and user is larger than 20cm, so MPE evaluation is required, besides, WLAN is belong to portable condition because the separation distance between WLAN antenna and user is less than 20cm, so SAR evaluation is required. Thus, this would be the mixed mobile and portable conditions when operating in notebook mode.

Based on KDB447498 D01v06 7.2, when one of the following test exclusion conditions is satisfied, the simultaneous transmission would be compliant.

a) The [ $\Sigma$  of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + [ $\Sigma$  of MPE ratios] is  $\leq$  1.0.

b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq 0.04$ , and the [ $\Sigma$  of MPE ratios] is  $\leq 1.0$ . According to the following evaluation, above a) can be satisfied, so the simultaneous transmission is compliant.

Scenario 1	WWAN + WLAN 2.4GHz TX1 + BT				
Worst case	WWAN	WLAN 2.4GHz TX1	BT		
Reported SAR or MPE	0.033	0.928	0.123		
Limit	0.466	1.6	1.6		
Exposure ratio	0.071	0.58	0.08		
Total exposure ratio	0.731				

Scenario 2	WWAN + WL	WWAN + WLAN 5GHz TX1 + BT				
Worst case	WWAN	WLAN 5GHz TX1	BT			
Reported SAR or MPE	0.033	1.055	0.123			
Limit	0.466	1.6	1.6			
Exposure ratio	0.071	0.66	0.08			
Total exposure ratio	0.811					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms\_and\_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms\_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Scenario 1	WWAN + WLAN 2.4GHz TX2		
Worst case	WWAN	WLAN 2.4GHz TX2	
Reported SAR or MPE	0.033	0.854	
Limit	0.466	1.6	
Exposure ratio	0.071	0.53	
Total exposure ratio	0.601		

Scenario 1	WWAN + WLAN 5GHz TX2		
Worst case	WWAN	WLAN 2.4GHz TX1	
Reported SAR or MPE	0.033	0.936	
Limit	0.466	1.6	
Exposure ratio	0.071	0.59	
Total exposure ratio	0.661		

Scenario 1	WWAN + WL	WWAN + WLAN 2.4GHz TX1 + WLAN 2.4GHz TX2 (MIMO)				
Worst case	WWAN	WLAN 2.4GHz TX1	WLAN 2.4GHz TX1			
Reported SAR or MPE	0.033	0.250	0.314			
Limit	0.466	1.6	1.6			
Exposure ratio	0.071	0.16	0.20			
Total exposure ratio	0.431					

Scenario 1	WWAN + WL	WWAN + WLAN 5GHz TX1 + WLAN 5GHz TX2 (MIMO)				
Worst case	WWAN	WLAN 5GHz TX1	WLAN 5GHz TX2			
Reported SAR or MPE	0.033	0.381	0.482			
Limit	0.466	1.6	1.6			
Exposure ratio	0.071	0.24	0.30			
Total exposure ratio	0.611					

### ~ End of Report ~

CLINE OF NEW CONTROL OF NEW CONTRO appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. 號

SGS Taiwan Ltd.	No.134,WuKungRoad,NewTaipe	iIndustrialPark,WukuDistrict,NewTaipeiCity,	laiwan24803/新北市五股區新	北產業園區五工路 134 號
台灣檢驗科技股份有限公司	t (886-2) 2299-3279	f (886-2) 2298-0488	www.tw.sgs.com	