

MPE CALCULATION
FCC ID BLE: SH6MDBT40

RF Exposure Requirements: 47 CFR §1.1307(b)
RF Radiation Exposure Limits: 47 CFR §1.1310
RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65

Limits for General Population/Uncontrolled Exposure in the band of:

Frequency Range (MHz)	Power Density (mW/cm ²)
1,500-100,000	1.0
300-1,500	f/1500

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20cm

Radio Mode	Ch Freq	Conducted Power(dBm)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Antenna Gain (dBi)	Measurement Distance (cm)	Power Density (mw/cm2)	MPE Limit (mw/cm2)	Pass / Fail
BLE	2440MHz	4.22	±1dB	5.22	1.3	20	0.000891	1	Pass

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Vijay Chaudhary



SIEMIC, Inc.

775 Montague Expressway, Milpitas, CA 95035

/Date: 05/17/2018