

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an AN000286 CANDY CLOWN with Bluetooth 5.4(EDR) function operating in 2402-2480MHz. The EUT is powered by DC 6.0V by adaptor. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK,  $\pi/4$ -DQPSK and 8-DPSK

Antenna Gain: 1dBi Max

Bluetooth Version: 5.4 (EDR)

The normal radiated output power (e.i.r.p) is: 5dBm (tolerance: +/- 3dB).

The normal conducted output power is 4dBm (tolerance: +/- 3dB).

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 102.9dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 7.67dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 99.9dB $\mu$ V/m at 3m in the frequency 2480MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 4.67dBm

which is within the production variation.

The maximum conducted output average power specified is 8dBm= 6.310mW

The source- based time-averaging conducted output power  
=6.310 mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt} (2.480)$  mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.