



EMC TEST REPORT

Product Name: Radio
FCC ID: 2BG9P-YX218
Trade mark: N/A
Model No.: YX218
S/N: /
Report No.: CTB25022106304E02
Applicant: Zhongshan YouXin Electronic Technology Co., Ltd.
Address: Zone D, Second Floor, Building A, NO.4 Jinkun Street, Pingnan Village, Sanxiang Town, Zhongshan City, Guangdong Province, China
Manufacturer: Zhongshan YouXin Electronic Technology Co., Ltd.
Address: Zone D, Second Floor, Building A, NO.4 Jinkun Street, Pingnan Village, Sanxiang Town, Zhongshan City, Guangdong Province, China
Prepared by: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Date of Receipt: Feb. 21, 2025
Date of Test(s): Feb. 21, 2025 to Mar. 12, 2025
Date of Issue: Mar. 12, 2025
Test Standard(s): CFR47, FCC Part 15 Subpart B, ANSI C63.4: 2014
Test Result: Pass

In the configuration tested, the EUT complied with the standards specified above.

Compiled by:

Michael Niu

Michael Niu

Reviewed by:

Bin Mei

Bin Mei

Approved by:



Rita Xiao

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "★" indicates the testing items were fulfilled by subcontracted lab. "※" indicates the items are not in CNAS accreditation scope.

Table of Contents

1.	Description of version	3
2.	Test summary	4
3.	Measurement uncertainty	5
4.	General information	6
4.1	Description of EUT	6
4.2	Description of accessory device	6
4.3	Test conditions	6
4.4	Block diagram of EUT configuration	6
4.5	Operating condition of EUT	6
5.	List of Test and Measurement Instruments	8
6.	Conducted Emission	10
6.1	Limit	10
6.2	Test setup	10
6.3	EMI test receiver setup	10
6.4	Test procedure	10
6.5	Test results	11
7.	Radiated emissions	13
7.1	Limit	13
7.2	Test setup	13
7.3	EMI test receiver setup and spectrum analyzer setup	14
7.4	Test procedure	14
7.5	Corrected Amplitude & Margin Calculation	14
7.6	Test results	15
8.	Photographs of test setup	18

1. Description of version

Report No.	Issue Date	Description	Approved
CTB25022106304E02	Mar. 12, 2025	Original	Valid

2. Test summary

Test procedures according to the technical standards:

Standard	Test Item	Test Result
§15.107	Conducted Emission	PASS
§15.109	Radiated Emission	PASS

3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

Test Item	Frequency	Expanded Uncertainty (U_{Lab})
Conducted Emission	150 kHz to 30 MHz	± 3.1 dB
Radiated Emission	30 MHz to 1000 MHz	± 4.1 dB
Radiated Emission	1000 MHz to 6000 MHz	± 4.8 dB

4. General information

4.1 Description of EUT

Product name	Radio
Trade mark	N/A
Model No.	YX218
Serial Model No.	N/A
Model Difference	N/A
Configuration	☒ Table-top ☐ Floor-standing
The highest frequency of the internal sources of the EUT	☐ below 1.705 MHz, the measurement shall only be made up to 30 MHz. ☒ between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz. ☐ between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. ☐ between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. ☐ above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower.
Ratings	DC 3.7V by battery

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


4.2 Description of accessory device

No.	Device Type	Brand	Model	Specification	Note
1	Adapter	JIYIN	JY-05100C	/	/

4.3 Test conditions

Temperature: 15-25°C
 Relative Humidity: 30-60 %
 Atmospheric pressure: 800hPa-1060hPa

4.4 Block diagram of EUT configuration



4.5 Operating condition of EUT

Operating condition	Mode 1*	FM receive mode	Test Voltage	DC 3.7V
	Mode 2	AM receive mode	Test Voltage	DC 3.7V
	Mode 3	Charging mode	Test Voltage	AC 120V

	Mode 4	USB output mode	Test Voltage	DC 3.7V
Note: This test covers all possible operating modes of the device, only the worst data are list in report. The worst data are shows (*) is the nearest standard limit which were recorded in this report.				

5. List of Test and Measurement Instruments

Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2027/6/21
2	AMN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/6/30
3	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	/	2025/6/28
4	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/6/30
5	Coaxial cable	ZDECL	Z302S	18091904	/	2025/6/30
6	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/30
7	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/10/25
8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
9	Current Probe	FCC	F-52B	199453	/	2025/5/27
10	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/6/28
11	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Radiated emission(No.2 Chamber)						
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2026/11/14
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/7/07
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/7/06
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/30
5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/23
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2024/11/27
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/6/28
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/
9	Coaxial cable	Rosenberg	8m	/	/	2024/11/27
10	Coaxial cable	Times	2m	/	/	2024/11/27
11	Coaxial cable	Times	2m	/	/	2024/11/27
12	Coaxial cable	Times	1m	/	/	2024/11/27
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/29
14	Communication test set	R&S	CMW500	108058	B.19.07	2025/6/28

					(E1962B)	
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/6/28

Note:the test lab designation number CN1276

6. Conducted Emission

6.1 Limit

Except for Class A devices:


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

For Class A devices:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	79	66
0.5-30	73	60

6.2 Test setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

6.3 EMI test receiver setup


Frequency Range	9kHz-30MHz
Resolution Bandwidth	200Hz (9kHz-150kHz) 9kHz (150kHz-30MHz)

6.4 Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

6.5 Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2300	32.54	10.69	43.23	62.45	-19.22	QP
2		0.2300	16.95	10.69	27.64	52.45	-24.81	AVG
3		0.5940	30.05	10.60	40.65	56.00	-15.35	QP
4	*	0.5940	21.53	10.60	32.13	46.00	-13.87	AVG
5		2.6740	30.15	11.73	41.88	56.00	-14.12	QP
6		2.6740	12.95	11.73	24.68	46.00	-21.32	AVG
7		4.3500	27.67	12.10	39.77	56.00	-16.23	QP
8		4.3500	11.39	12.10	23.49	46.00	-22.51	AVG
9		7.1620	21.81	12.96	34.77	60.00	-25.23	QP
10		7.1620	6.34	12.96	19.30	50.00	-30.70	AVG
11		15.6020	25.81	13.37	39.18	60.00	-20.82	QP
12		15.6020	8.59	13.37	21.96	50.00	-28.04	AVG

Note: Result=Reading + Factor
Over Limit=Result - Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1780	33.30	10.79	44.09	64.58	-20.49	QP
2		0.1780	18.76	10.79	29.55	54.58	-25.03	AVG
3		0.5940	25.78	10.60	36.38	56.00	-19.62	QP
4		0.5940	18.95	10.60	29.55	46.00	-16.45	AVG
5	*	2.5420	30.97	11.70	42.67	56.00	-13.33	QP
6		2.5420	15.25	11.70	26.95	46.00	-19.05	AVG
7		6.0620	23.61	12.61	36.22	60.00	-23.78	QP
8		6.0620	10.83	12.61	23.44	50.00	-26.56	AVG
9		8.7900	21.94	13.12	35.06	60.00	-24.94	QP
10		8.7900	8.00	13.12	21.12	50.00	-28.88	AVG
11		15.8860	26.84	13.38	40.22	60.00	-19.78	QP
12		15.8860	7.88	13.38	21.26	50.00	-28.74	AVG

Note: Result=Reading + Factor
Over Limit=Result – Limit

7. Radiated emissions

7.1 Limit

Except for Class A devices (at 3m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

For Class A devices (at 10m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	90	39
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

7.2 Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

7.3 EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz-1000MHz	100kHz	300kHz	120kHz	QP
Above 1GHz	1MHz	3MHz	/	PK
	1MHz	10Hz	/	AVG

7.4 Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

7.5 Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:


$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

2. The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

7.6 Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	59.8588	33.89	-14.80	19.09	40.00	-20.91	QP
2 *	139.8508	46.69	-14.19	32.50	43.50	-11.00	QP
3	189.7385	43.29	-15.68	27.61	43.50	-15.89	QP
4	254.7283	40.63	-14.58	26.05	46.00	-19.95	QP
5	406.0880	28.03	-11.08	16.95	46.00	-29.05	QP
6	860.0351	26.15	-1.83	24.32	46.00	-21.68	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	50.2324	43.02	-13.61	29.41	40.00	-10.59	QP
2	60.0691	45.89	-14.83	31.06	40.00	-8.94	QP
3 *	138.3873	50.51	-14.25	36.26	43.50	-7.24	QP
4	191.0738	39.74	-15.84	23.90	43.50	-19.60	QP
5	304.6099	31.17	-13.35	17.82	46.00	-28.18	QP
6	654.2318	27.82	-5.02	22.80	46.00	-23.20	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

8. EUT Photographs

External Photos

EUT Photo 1




EUT Photo 2




9. Photographs of test setup

RE



CE



End of report