



DIGI INTERNATIONAL
9350 Excelsior Blvd, Suite 700
Hopkins, MN 55343
952-912-3444 / 877-912-3444
www.digi.com

Antenna Information

Product: XBee 3 LTE Cat 1
FCC ID: MCQ-XB3C2
IC: 1846A-XB3C2

Bluetooth antennas

The following antennas are approved for use with the Bluetooth radio by FCC and by ISED.

Part number	Description	Type	Gain	Application
31000022-01	Integral antenna	PCB	-0.67 dBi	Fixed/Mobile
A24-HASM-450	Half-wave articulated RPSMA-4.5"	Dipole	2.1 dBi	Fixed/Mobile
A24-HABUF-P5I	Half-wave bulkhead mount U.FL w/ 5" pigtail	Dipole	2.0 dBi	Fixed/Mobile
A24-HASM-525	Half-wave articulated RPSMA-5.25"	Dipole	2.0 dBi	Fixed/Mobile
FXP74.07.0100A	Taoglas FXP74 Black Diamond antenna	Patch	4.0 dBi	Fixed/Mobile

Cellular antennas

Per cellular module grant, antenna gain must be below:

Frequency band	Maximum Antenna Gain			
	Global variant (55002112-03)		North American variant (55002112-02)	
	FCC limit	ISED limit	FCC limit	ISED limit
GSM/GPRS 850	5.00 dBi		N/A	
PCS1900	5.00 dBi		N/A	
WCDMA/LTE Band 2	5.00 dBi		8.01 dBi	
WCDMA/LTE Band 4	5.00 dBi		5.00 dBi	
WCDMA/LTE Band 5	5.00 dBi		9.40 dBi	6.10 dBi
LTE Band 7	5.00 dBi		N/A	
LTE Band 8	5.00 dBi		N/A	
LTE Band 12	5.00 dBi		8.70 dBi	5.61 dBi
LTE Band 13	5.00 dBi		9.16 dBi	5.93 dBi
LTE Band 14	N/A		9.23 dBi	N/A
LTE Band 26	5.00 dBi		9.30 dBi	6.10 dBi
LTE Band 38	5.00 dBi		N/A	
LTE Band 41	5.00 dBi		N/A	
LTE Band 66	5.00 dBi		5.00 dBi	
LTE Band 71	N/A		8.48 dBi	5.45 dBi

PASSIVE 3D ANTENNA PATTERN MEASUREMENTS



OTA 2018.01.04

EUT:	OTA
Serial Number:	2335
Customer:	Digi International Inc
Attendees:	None
Customer Project:	None
Tested By:	Christopher Heintzelman
Test Run Description:	Passive_2400-2500_Run2

Work Order:	DGII0462
Date:	9/27/2022
Temperature:	22.2 °C
Relative Humidity:	34.1% RH
Bar. Pressure:	1025 mbar
Job Site:	MN10

COMMENTS

None

Max dBi Gain -0.67


3D PATTERN DATA

Frequency (MHz)	2400	2402	2404	2406	2408	2410	2412	2414	2416	2418	2420	2422
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-8.74	-8.68	-8.59	-8.51	-8.44	-8.37	-8.29	-8.19	-8.13	-8.03	-7.93	-7.81
Peak EIRP (dBm)	-4.65	-4.61	-4.44	-4.52	-4.29	-4.25	-4.23	-4.24	-4.18	-4.04	-3.98	-3.98
Directivity (dBi)	4.08	4.07	4.14	3.99	4.15	4.12	4.06	3.96	3.95	3.99	3.95	3.83
Efficiency (dB)	-8.74	-8.68	-8.59	-8.51	-8.44	-8.37	-8.29	-8.19	-8.13	-8.03	-7.93	-7.81
Efficiency (%)	13.38	13.54	13.84	14.10	14.33	14.57	14.83	15.16	15.40	15.73	16.11	16.56
Gain (dBi)	-4.65	-4.61	-4.44	-4.52	-4.29	-4.25	-4.23	-4.24	-4.18	-4.04	-3.98	-3.98
Average Gain (dB)	-8.74	-8.68	-8.59	-8.51	-8.44	-8.37	-8.29	-8.19	-8.13	-8.03	-7.93	-7.81
E-Plane 3 dB BW (°)	39.00	40.00	39.00	42.00	39.00	40.00	40.00	42.00	40.00	40.00	40.00	42.00



Azimuth Cut (Theta Axis = 90°)

Elevation Cut (Phi Axis = 0°)


Elevation Cut (Phi Axis = 90°)



Antenna 31000022-01 (XBee 3 LTE Cat 1)



2424	2426	2428	2430	2432	2434	2436	2438	2440	2442	2444	2446	2448
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-7.72	-7.65	-7.56	-7.45	-7.37	-7.31	-7.21	-7.08	-6.96	-6.87	-6.78	-6.67	-6.57
-3.85	-3.79	-3.73	-3.63	-3.52	-3.44	-3.35	-3.18	-3.07	-2.93	-2.81	-2.74	-2.73
3.88	3.86	3.82	3.82	3.84	3.87	3.86	3.90	3.89	3.94	3.97	3.93	3.83
-7.72	-7.65	-7.56	-7.45	-7.37	-7.31	-7.21	-7.08	-6.96	-6.87	-6.78	-6.67	-6.57
16.89	17.17	17.54	17.99	18.33	18.59	19.00	19.58	20.12	20.57	20.99	21.53	22.05
-3.85	-3.79	-3.73	-3.63	-3.52	-3.44	-3.35	-3.18	-3.07	-2.93	-2.81	-2.74	-2.73
-7.72	-7.65	-7.56	-7.45	-7.37	-7.31	-7.21	-7.08	-6.96	-6.87	-6.78	-6.67	-6.57
41.00	49.00	40.00	48.00	49.00	49.00	49.00	49.00	48.00	48.00	49.00	49.00	50.00



Antenna 31000022-01 (XBee 3 LTE Cat 1)

2450	2452	2454	2456	2458	2460	2462	2464	2466	2468	2470	2472	2474
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-6.45	-6.37	-6.25	-6.15	-6.06	-5.98	-5.89	-5.81	-5.75	-5.69	-5.61	-5.53	-5.49
-2.52	-2.46	-2.31	-2.30	-2.16	-2.06	-1.97	-1.95	-1.89	-1.85	-1.69	-1.68	-1.62
3.93	3.91	3.94	3.86	3.90	3.92	3.92	3.86	3.87	3.84	3.92	3.84	3.87
-6.45	-6.37	-6.25	-6.15	-6.06	-5.98	-5.89	-5.81	-5.75	-5.69	-5.61	-5.53	-5.49
22.66	23.07	23.71	24.26	24.80	25.25	25.78	26.22	26.58	26.97	27.49	28.01	28.23
-2.52	-2.46	-2.31	-2.30	-2.16	-2.06	-1.97	-1.95	-1.89	-1.85	-1.69	-1.68	-1.62
-6.45	-6.37	-6.25	-6.15	-6.06	-5.98	-5.89	-5.81	-5.75	-5.69	-5.61	-5.53	-5.49
49.00	49.00	48.00	49.00	48.00	48.00	47.00	48.00	48.00	48.00	48.00	48.00	48.00


Antenna 31000022-01 (XBee 3 LTE Cat 1)

2476	2478	2480	2482	2484	2486	2488	2490	2492	2494	2496	2498	2500
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-5.46	-5.40	-5.34	-5.29	-5.24	-5.17	-5.06	-4.97	-4.87	-4.78	-4.68	-4.58	-4.48
-1.58	-1.56	-1.54	-1.41	-1.37	-1.35	-1.22	-1.11	-1.01	-0.91	-0.80	-0.72	-0.67
3.88	3.83	3.80	3.88	3.87	3.82	3.83	3.86	3.86	3.87	3.88	3.86	3.82
-5.46	-5.40	-5.34	-5.29	-5.24	-5.17	-5.06	-4.97	-4.87	-4.78	-4.68	-4.58	-4.48
28.42	28.87	29.25	29.59	29.94	30.39	31.22	31.83	32.56	33.27	34.05	34.84	35.60
-1.58	-1.56	-1.54	-1.41	-1.37	-1.35	-1.22	-1.11	-1.01	-0.91	-0.80	-0.72	-0.67
-5.46	-5.40	-5.34	-5.29	-5.24	-5.17	-5.06	-4.97	-4.87	-4.78	-4.68	-4.58	-4.48
47.00	47.00	48.00	47.00	48.00	48.00	49.00	47.00	48.00	48.00	48.00	48.00	49.00

Antenna A24-HASM-450

A1RFRD10

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD
1		修改model no,與P/N	Andy 9/19/03	
2		Drawing modification	Nicole 9/21/04	



NOTE:

ELECTRICAL PROPERTIES

1.DESCRPTION : 1/4 λ SWIVEL TYPE DIPOLE ANTENNA
ø9x82.5+ SMA

2.MODEL NO. : AN-A1-X0C

3.FREQUENCY : OPTION

4.IMPEDANCE : 50 Ohms nominal

5.V.S.W.R. : 2.0 max. IN BAND

6.GAIN : 1.14~2.14 dBi, VERTICAL DIRECTION

7.ADMITTED POWER RADLATION : 1W

8.TYPE OF RADLATION : TOROIDAL

9.POLARIZATION : VERTICAL

10.ELECTRICAL LENGTH : 1/4 λ ,DIPOLE

11.RADIATION : 0 mni

12.CONNECTOR TYPE : SMA (MALE/FEMALE OPTION)

MECHANICAL PROPERTIES

1.CABLE : RG-178, 50ohm

2.OPERATING TEMPERATURE RANGE : -20°C~+65°C

3.STORAGE TEMPERATURE RANGE : -30°C~+75°C

4.ANTENNA COVER : TPE

5.COLOR : OPTION

PART NUMBER : E421X-2000AX

CONNECTOR
C:R-SMA (FEMALE)
D:SMA (MALE)

COLOR
1:BLACK
3:GRAY
4:GRAY(PANTONE COOL GRAY 8C)
7:GRAY(PANTONE 429C)
8:GRAY(PANTONE Cool Gary 7C)

DETACHED LISTS	← MM →		DFTO Sam	DATE 9/27/02'	FULL RISE ELECTRONIC CO., LTD			
	TOLERANCES EXCEPT AS NOTED		CHKD Cha Chi	DATE 05/31/04'				
			MFO LMJ	DATE 05/31/04'				
			APPVL YUAN	DATE 05/31/04'				
	.0 ± 0.2 .00 ± 0.15 .000 ± 0.075				TITLE ANTENNA ø9+SMA CONNECTOR			
	ANGLES ± 0.5		QT'Y :					
			FINISH :		DRAWING NO. GE423A04		SIZE	REV
	THIRD ANGLE PROJECTION		SCALE : 2:1		/PART NO. SEE NOTE		A3	2
					DO NOT SCALE DRAWING		SHEET 1	OF 1

SPECIFICATION FOR PRELIMINARY**APPROVAL SIGNATURE****DATE :****CUSTOMER : DIGI PART NO : A24-HABUF-P5I REV.****DESCRIPTION : Antenna****PLEASE SIGN AND RETURN ONE COPY.****ALL PRODUCTION UNITS WILL BE BUILT ACCORDING
TO THIS SPECIFICATIONS.****MODEL NO: AN2400-37A19BX****AGENCY APPROVAL:****PRESENTED BY: NO.****CHECKED BY: Johnson Lin****APPROVED BY: Johnson Lin****DATE : 03/10/2014**

19F, NO.102, HSIN TAI WU ROAD SEC.1, HSIH-JR CITY, TAIPEI HSIEN, TAIWAN

TEL# (886)2-2696-0007

FAX# (886)2-2696-8786

WEBSITE: www.bobbintron.comEMAIL: sales@bobbintron.com

Index:

- 1. Specification / Page 2**
- 2. Characteristics and Reliability Test / Page 3**
- 3. Antenna - S Parameter Test Data / Page 4**
- 4. Antenna - Radiation Pattern Test Data / Page 5 ~ 6**
- 5. Mechanical and Packing Drawing / Page 7 ~ 8**
- 6. Material Description and RoHS Test Report / Page 9 ~ end**

1. Specification

Sample Photo



A. Electrical Characteristics

Frequency	2400 ~ 2500 MHz
S.W.R.	≤ 2.0
Antenna Gain	2 dBi
Polarization	Linear
Impedance	50 Ohm

B. Material & Mechanical Characteristics

Material of Radiator	Cu
Material of Plastic	Body: TPE Hinge: PC+ABS Holder: PC+ABS
Cable Type	O.D. 1.13 mm
Connector Type	I-PEX
Connector Pull Test	≥ 1 Kg
Connector Torque Test	/


C. Environmental

Operation Temperature	- 40 °C ~ + 65 °C
Storage Temperature	- 40 °C ~ + 80 °C

2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	MIL-STD-202G, 201A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol. ≤ 5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol. ≤ 5%
M3	Solderability	MIL-STD-202G, 210F, cond. A Solder iron: 350±10°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol. ≤ 5%
M5	Terminal-Torque Test	MIL-STD-202G, 211A, cond. E Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal	1. Directive DUT specification 2. Frequency Tol. ≤ 5%
M6	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	MIL-STD-202G, 101E, cond. B Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. ≤ 5%
E2	Humidity	MIL-STD-202G, 103B, cond. B Temp: 40°C; RH: ≥ 95%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. ≤ 5%
E3	Thermal Shock	1 Cycle: - 40°C (30 minutes) to + 80°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. ≤ 5%
E4	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 85°C; Time: 96 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. ≤ 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2002/95/EC
R2	PFOS	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC
R3	PFOA	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC

3. Antenna - S Parameter Test Data



4. Antenna - Radiation Pattern Test Data

Testing Equipment Specification:

Antenna Anechoic Chamber Dimension: 8 x 4 x 4 m


Quiet Zone: 600mm @1 GHz

Isolation: >100dB @ 1 MHz ~ 10 GHz

Testing Equipment: Agilent 5071B

Received Antenna: 0.7 ~ 6.0 GHz for Gain Calibration

Double Ridged Horn Antenna



5. Mechanical Drawing

See attached files

6. Material Description and RoHS Test Report

See attached files













Model : 2.4GHz Antenna
 Remark : H-Plane // Vertical Polarization
 Tested by : Antenna 3D Lab // Zhao Yao Rong

Location : Chamber
 Temperature (°C) : 22.00

Date : 2009/4/3
 Humidity (%) : 55.00

Time : 17:47:02.13:25
 Approved by :




Freq (MHz)	2380	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Peak Gain (dBi)	3.07	2.97	2.92	2.92	2.92	2.8	2.68	2.23	2.93	3.27	2.17	1.83
Peak Angle	338	332	332	321	320	320	314	305	305	302	295	289
AV Gain (dBi)	1.84	1.82	1.85	1.82	1.85	1.85	1.84	1.67	0.83	0.83	0.7	0.13



RoHS

Compatible

SN	DATE	DESCRIPTION	APPROVER
A	08.10.29	Add packing criterion	Roger
A	09.04.13	Change packing from 20" CASE bag to 110" CASE bag	Roger
A			



Note:

1. Dimension: Take * is the important dimension
2. Tolerance: Unmarked tolerance refer to the standard tolerance please
3. CONN orientation is as shown

No	Part Number	Description	Material	Finish	Qty
7	R-AN07-05-POM	Holder	POM	Black 180°	1
6	CH-113	Conn		Mini Conn	1
5	R-CB-113B	Cable		1.13mm Black	1
4	R-AN01-1213Z	Hinge Pin	Cu	Black Zn Plated	2
3	R-AN3701-01A	Base	PC+ABS	Black	1
2	R-AN57-05	Body-2	PC+ABS	Black	1
1	R-AN57-03	Body-1	TPE	Black	1

PART NAME: ANTENNA-2.4GHz-2B1			
PART NO.: AN2400-37A19BX			
DWG NAME: AN2400-37A19BX.dwg			
APPROVED BY	CHECKED BY	DESIGNED BY	UNITS: mm
Grant	Jack	Roger	SCALE: 1/1
2009/04/13	2009/04/13	2009/04/13	REV: 00/0
Tolerance			
XX .00.10			
XXX .00.05			
XV .01			

Part Number : AN2400-37A19BX	Revision : C
Name: AP ANTENNA	Customer : ALL

一、WITH THE ANT AND HOLDER INTO BAG


①



BAR CODE LABEL


1PCS / SELF-ADHESIVE BAG

②




100PCS/PE BAG

二、PACKING




1500PCS ANTENNA AND HOLDER / CARTON

三、SEALING



SIDE



FRONT



UNITS: mm


SMA Reverse Polarity Plug(female)

Electrical Properties:


Frequency Range: 2.4~2.5 GHz
 Impedance: 50Ω nominal
 VSWR: <2.0:1
 Gain: 2 dBi
 Radiation: Omni
 Polarization: Vertical
 Wave: Half Wave Dipole

Mechanical Properties:


Connector: **RPSMA Plug (male)**
 Material:
 Whip: Polyurethane(Black)
 Swivel Mechanism: Polycarbonate(Black)
 Connector: Brass with black chrome plating
 Operation Temp.: -20°C to +65°C
 Storage Temp.: -30°C to +75°C



E-Plane Pattern @ 2.45GHz



H-Plane Pattern @ 2.45GHz



TITLE	2.4GHz Swivel Ant		VER	
UNIT	DWG. NO.	A24-HASM-525		
in.(mm)	MaxStream, Inc.			
SCALE				
1:1				

SPECIFICATION

Patent Granted

FXP74 Black Diamond 2.4GHz Band Antenna

Part No. : **FXP74.07.0100A**

Product Name : FXP74 Black Diamond 2.4GHz Antenna

Feature : 4dBi Peak Gain
Flexible, Ultra Low Profile
IPEX MHF I Connector (U.FL compatible)
100mm 1.13 Mini-Coaxial Cable
47*7*0.1 mm
RoHS & Reach Compliant



1. Introduction

The FXP74 Black Diamond is a small ultra-low profile antenna for 2.4GHz band that includes Bluetooth, Zigbee and Wi-Fi single band application. The FXP74 has a peak gain of 4dBi at 2.4GHz and efficiencies of above 50%.

This Taoglas patent granted antenna is unique in the market with exceptionally stable performance different applications. It is made from a flexible polymer, has a tiny form factor (14mm*7.0mm*0.1mm) and has double-sided 3M tape for easy and robust “peel and stick” mounting.

The FXP74 is the ideal all-round antenna solution for fitting into narrow spaces and still maintaining high performance, for example on the inside top or adjacent side applied directly to the plastic housing of LCD monitors, tablets, smartphones, small AP routers, etc.

Many module manufacturers specify peak gain limits for any antennas that are to be connected to that module. Those peak gain limits are based on free-space conditions. In practice, the peak gain of an antenna tested in free-space can degrade by at least 1 or 2dBi when put inside a device. So ideally you should go for a slightly higher peak gain antenna than mentioned on the module specification to compensate for this effect, giving you better performance.

Upon testing of any of our antennas with your device and a selection of appropriate layout, integration technique, or cable, Taoglas can make sure any of our antennas' peak gain will be below the peak gain limits. Taoglas can then issue a specification and/or report for the selected antenna in your device that will clearly show it complying with the peak gain limits, so you can be assured you are meeting regulatory requirements for that module.

For example, a module manufacturer may state that the antenna must have less than 2dBi peak gain, but you don't need to select an embedded antenna that has a peak gain of less than 2dBi in free-space. This will give you a less optimized solution. It is better to go for a slightly higher free-space peak gain of 3dBi or more if available.

Once that antenna gets integrated into your device, performance will degrade below this 2dBi peak gain due to the effects of GND plane, surrounding components, and device housing. If you want to be absolutely sure, contact Taoglas and we will test. Choosing a Taoglas antenna with a higher peak gain than what is specified by the module manufacturer and enlisting our help will ensure you are getting the best performance possible without exceeding the peak gain limits.

2. Specification

Communication System	Bluetooth	WiFi	ZigBee	2.4GHz ISM
	2401-2480	2412-2462	2410-2480	2400-2483.5
Efficiency	50%			
Gain	4dBi			
Return Loss	< -10dB			
Impedance	50 Ohms			
VSWR	≤ 2:1			
Polarization	Linear			
Power Handled	5 W			
MECHANICAL				
Dimensions	47*7*0.1 mm			
Weight	1.2 g			
Connector	MHFI (U.FL Compatible)			
Cable Standard	Mini-Coax 1.13 mm			
Cable Length and color	100mm, Black			
Adhesive tape	3M 467			
ENVIRONMENTAL				
Operation Temperature	-40 °C ~ +85 °C			
Storage Temperature	-40 °C ~ +85 °C			
RoHS Compliant	Yes			


3. Antenna Characteristics

3.1. Test Setup


Rohde & Schwarz ZNB 8 Vector Network Analyzer




ETS 3D Radiation Scan System with Anechoic Chamber




3.2. Return Loss




3.3. Peak Gain



3.4. Average Gain




3.5. Efficiency




4. Antenna Radiation Pattern


XY-plane




XZ-plane



YZ-plane




5. Antenna Drawing




6. Packaging

100pcs FXP74.07.0100A per PE Bag
Dimensions: 150*100mm
Weight: 1.02Kg




1000pcs per Large Bag
Carton Dimensions: 250*200mm
Weight: 10.2Kg




7. Return Loss – environmental effects

7.1. Antenna on different ABS thickness (Cable Length 100mm)





7.2. Proximities to metal ground plane

(Cable Length 100mm, antenna stuck on 2mm ABS base)



7.3. Antenna with different cable type (Antenna stuck on 2mm ABS base)



Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

© Taoglas