

APPROVAL SHEET

CUSTOMER : NETGEAR

MODEL NO : Cable-SMA(Mu)-3M-SMA(Mu)

PART NO : ACC-10314-02

DESCRIPTION : Cable Assembly

HPF195 SMA(M)rp + 3M + SMA(M)rp

DATE : 2003/03/28 (Version:0.1)

Customer Approved

Issued	Checked	Approved
Jason Lee	Jac Lee	Damy Wu

SMA JACK

Electric properties

1. Frequency Range..... 0~8GHz
2. Impedance..... 50 OHMS $\pm$ 5 Ω
3. SWR..... ≤ 1.5
4. Working Voltage..... ≤ 250 Vrms
5. Dielectric Withstanding Voltage. ≤ 750 Vrms
6. Insulation Resistance..... ≥ 2000 Megohms
7. Contact Resistance..... 3.0 Milliohms(Max)
(Center contact)
8. Contact Resistance..... 2.5 Milliohms(Max)
(Outer contact)
9. Insertion Loss..... 0.2dB

Mechanical Properties

1. Recommended coupling nut torque..... 4.0 in.lbs.~8.8 in.lbs.
2. Coupling nut retention force..... ≥ 50 lbs
3. Contact captivation axial..... ≥ 5 lbs.
4. Operating Temperature..... -40°C~+80°C
5. Thermal Shock..... MIL-STD-202,Method107,ConditionB
6. Corrosion..... MIL-STD-202,Method101,ConditionB
7. Shock..... MIL-STD-202,Method213,Condition I
8. Vibration..... MIL-STD-202,Method204,ConditionD
9. Moisture Resistance..... MIL-STD-202,Method106

Material Properties

1. Body..... Brass Per JIS H3250 C3604 BD,
Gold Plated,Per MIL-G-45204
2. Contact..... Beryllium Copper Per QQ-C-530,
Gold Plated,Per MIL-G-45204
3. Insulator..... PTFE Fluorocarbon Per ASTM D 1710

CABLE HPF195



Rev	Change	By	Date

MASTER

Construction:

- A) Center Conductor:
Bare Copper
OD 0.0375" ± .0005"
- B) Dielectric:
Foam Polyethylene
OD 0.110" Nom.
- C) Inner Shield:
Bonded Aluminum Composite Tape
OD 0.116" Nom.
- D) Outer Shield:
36 AWG Tin Plated Copper
90% Minimum Coverage
OD 0.137" Nom.
- E) Jacket:
FRPVC(Black)
OD 0.195" ± 0.005"
Printed "Harbour Industries HPF195HFPVC CATVR
75C 18 AWG (UL)"

Electrical:

Impedance:	50 Ohms Nom.
Capacitance:	24.4 pF/ft Nom.
Velocity of Propagation:	80 % Nom.
Shielding Effectiveness:	>90 dB
Voltage Withstand:	2,500 VDC
VSWR(.45-6.00GHz):	<1.15:1 Typical 1.30:1 Maximum

Physical Properties:

Weight:	20.6 lbs/ 1000ft
Minimum Bend Radius:	1.0 in
Operating Temp. Range:	-40 to +75 °C

Attenuation	
Frequency	dB/100 Ft
GHz	Typical(Max.)
1.00	11.4(12.5)
2.00	16.3(18.0)
3.00	20.2(22.2)
4.00	23.5(25.9)
5.00	26.5(29.1)
6.00	29.2(32.1)

Drawn By: MTPiner

Approved By: MTPiner

Date:
01/27/03

Scale:
None

Part Number:
T80

Rev:

Sheet 1 of 1

Drawing Name:

HPF195HFPVC


Drawing Number:

012703_1

This drawing contains proprietary information and is issued in strict confidence and shall not be copied, reproduced, transmitted or disclosed to any third party without the prior written approval of Harbour Industries.

Dimension

Cable Length: 3000mm




Packages

Plastic Bag Size: 450(L) * 280(W) * 0.12(H) mm

Quantity : 1PCS/SET

Weight : 145g



Carton Size: 320(L) * 250(W) * 230(H) mm

Quantity : 20PCS/Carton

Weight : 3.7Kg

