

**Shenzhen Global Test Service Co.,Ltd.**

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT**FCC PART 15.407****Report Reference No.**.....: **GTS20190329001-1-27****FCC ID**.....: **2AQAA-EZBOXI3**

Compiled by

(position+printed name+signature)...: File administrators Jimmy ywang

Supervised by

(position+printed name+signature)...: Test Engineer Peter Xiao

Approved by

(position+printed name+signature)...: Manager Sam Wang

Date of issue.....: May. 31, 2019

Representative Laboratory Name .: **Shenzhen Global Test Service Co.,Ltd.**Address.....: 1F, Building No. 13A, Zhonghaixin Science and Technology City,
No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District,
Shenzhen, Guangdong**Applicant's name**.....: **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**Address: 101,102,201,301 No.13-2 Pingxi South Rd.,Pingxi
Community,Pingdi Street,Longgang
District,Shenzhen,GuangDong**Test specification**Standard: **FCC Part 15.407: UNLICENSED NATIONAL INFORMATION
INFRASTRUCTURE DEVICES**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: MINI PC

Trade Mark: N/A

Manufacturer: **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Model/Type reference.....: EZbox i3

Listed Models: N/A

Operation Frequency.....: From 5180MHz to 5240MHz/ 5745MHz to 5825MHz

Rating: DC 12V from adapter

Result.....: **PASS**

TEST REPORT

Test Report No. : GTS20190329001-1-27	May. 31, 2019
	Date of issue

Equipment under Test : MINI PC

Model /Type : EZbox i3

Listed Models : N/A

Applicant : **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Address : 101,102,201,301 No.13-2 Pingxi South Rd.,Pingxi
Community,Pingdi Street,Longgang District,Shenzhen,GuangDong

Manufacturer : **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Address : 101,102,201,301 No.13-2 Pingxi South Rd.,Pingxi
Community,Pingdi Street,Longgang District,Shenzhen,GuangDong

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment Under Test	6
2.4.	Short description of the Equipment under Test (EUT)	6
2.5.	EUT operation mode	6
2.6.	Block Diagram of Test Setup	6
2.7.	Related Submittal(s) / Grant (s)	7
2.8.	Special Accessories	7
2.9.	Modifications	7
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>8</u>
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Test Description	9
3.5.	Statement of the measurement uncertainty	10
3.6.	Equipments Used during the Test	11
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>12</u>
4.1.	AC Power Conducted Emission	12
4.2.	Radiated Emission.....	15
4.3.	Duty Cycle	22
4.4.	Maximum Average Output Power	26
4.5.	Power Spectral Density	29
4.6.	6dB Bandwidth	46
4.7.	26dBc Bandwidth.....	54
4.8.	Band Edge Compliance.....	62
4.9.	Antenna Requirement.....	73
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>74</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>75</u>

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02 v02r01](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	May. 15, 2019
Testing commenced on	:	May. 30, 2019
Testing concluded on	:	May. 30, 2019

2.2. Product Description

Product Name:	MINI PC
Trade Mark:	/
Model/Type reference:	EZbox i3
Antenna Type	FPC
Power supply:	DC 12V from adapter
Adapter information:	Model: JHD-AP036E-120300AA-A Input: AC 100-240V~50/60Hz 1.2A Output:DC 12V/3A
WIFI	
WLAN	Supported 802.11 a/b/g/n/ac
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac20/40/80: OFDM(64QAM, 16QAM, QPSK, BPSK)
Operation frequency	IEEE 802.11a:5180-5240MHz,5745-5825MHz IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz, 5180-5240MHz,5745-5825MHz IEEE 802.11n HT40:2422-2452MHz, 5190-5230MHz,5755-5795MHz IEEE 802.11ac:5180-5240MHz,5745-5825MHz IEEE 802.11ac40:5190-5230MHz,5755-5795MHz IEEE 802.11ac:5210MHz,5775MHz
Antenna gain	Antenna 0:1.11dBi for 2.4G WiFi/0.78dBi for 5G WiFi; Antenna 1:1.11dBi for 2.4G WiFi/0.78dBi for 5G WiFi;
BT/EDR	
Modulation Type	GFSK,8DPSK, $\pi/4$ -DQPSK
Operation frequency	2402-2480MHz
Antenna gain	1.11dBi Max
BLE	
Modulation Type	GFSK
Operation frequency	2402-2480MHz
Antenna gain	1.11dBi Max

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☒ 12 V DC	☐ 24 V DC
		☐ Other	

2.4. Short description of the Equipment under Test (EUT)

This is a MINI PC.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

NOTE:


Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used.

IEEE 802.11a/ac20/ac40/ac80/n20/n40:

UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AQAA-EZBOXI3** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
AOC	HDMI display	Satellite S40Dt-A	D26T	DOC

2.9. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.203	Antenna gain	802.11ac	☒ Lowest ☒ Middle ☒ Highest	802.11ac	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.407(a)	Power spectral density	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.407(a)	Spectrum bandwidth – 26 dB bandwidth	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.407(e)	Spectrum bandwidth – 6 dB bandwidth	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.407(a)	Maximum output power	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒ ☒	☐	☐	☐	complies
§15.407(b)	Band edge compliance conducted	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.407(b)	Band edge compliance radiated	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Highest	☒	☐	☐	☐	complies
§15.407(a)	TX spurious emissions conducted	-/-	-/-	-/-	-/-	☐	☐	☒	☐	complies
§15.407(a)	TX spurious emissions radiated	802.11a/ac20/ ac40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.407(g)	Frequency Stability	-/-	-/-	-/-	-/-	☒	☐	☐	☐	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	☐	☐	☒	☐	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	☒	☐	☐	☐	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	☒	☐	☐	☐	complies

Remark:

1. The measurement uncertainty is not included in the test result.

2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power	802.11a	6 Mbps
Power Spectral Density	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0
6dB Bandwidth		
26dB Bandwidth		
Radiated Emission30M~1GHz& Radiated Emission 1GHz~10 th Harmonic		
Band Edge	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2018/09/28	2019/09/27
LISN	R&S	ESH2-Z5	893606/008	2018/09/27	2019/09/26
By-log Antenna	SCHWARZBECK	VULB9163	000976	2018/09/29	2019/09/28
EMI Test Receiver	R&S	ESCI	101102	2018/09/26	2019/09/25
Spectrum Analyzer	Agilent	N9020A	MY48010425	2018/09/17	2019/09/16
Spectrum Analyzer	R&S	FSV40-N	101800	2018/09/17	2019/09/16
Controller	EM Electronics	Controller EM 1000	N/A	2018/09/21	2019/09/20
Double Ridged Horn Antenna (1~18GHz)	SCHWARZBECK	BBHA 9120D	01622	2018/09/19	2019/09/18
Double Ridged Horn Antenna	Rohde&Schwarz	HF907	100265	2018/09/19	2019/09/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2018/09/19	2019/09/18
Horn Antenna (18GHz~40GHz)	ETS	3116	00086467	2018/12/29	2019/12/28
Amplifier (26.5GHz~40GHz)	EMCI	EMC2654045	980028	2018/09/18	2019/09/17
Amplifier (0.1GHz~26.5GHz)	EMCI	EMC012645SE	980355	2018/09/19	2019/09/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2018/09/20	2019/09/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2018/09/20	2019/09/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2018/09/20	2019/09/19
Data acquisition card	Agilent	U2531A	TW53323507	2018/09/20	2019/09/19
Power Sensor	Agilent	U2021XA	MY5365004	2018/09/20	2019/09/19
RF Cable	HUBER+SUHNER	RG214	N/A	2018/09/20	2019/09/19
Conducted Emission Test Software	ES-K1	V1.71	N/A	N/A	N/A
Radiated Emission Test Software	JS32-RE	V2.5.0.9	N/A	N/A	N/A

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 5V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .


Power supply:

DC 12V from Adapter
AC 120V/60Hz

Polarization

L

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GTS190425148_fin"

4/25/2019 6:22PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	FE
0.375000	50.50	9.8	58	7.9	QP	L1	GND
0.379500	49.60	9.8	58	8.7	QP	L1	GND
1.365000	41.70	9.6	56	14.3	QP	L1	GND
2.476500	41.00	9.5	56	15.0	QP	L1	GND
5.284500	38.40	9.3	60	21.6	QP	L1	GND
12.466500	29.10	8.5	60	30.9	QP	L1	GND

MEASUREMENT RESULT: "GTS190425148_fin2"

4/25/2019 6:22PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	FE
0.370500	44.30	9.9	49	4.2	AV	L1	GND
0.375000	43.90	9.8	48	4.5	AV	L1	GND
1.405500	33.70	9.6	46	12.3	AV	L1	GND
2.449500	33.20	9.5	46	12.8	AV	L1	GND
5.275500	29.60	9.3	50	20.4	AV	L1	GND
12.687000	18.70	8.5	50	31.3	AV	L1	GND


Power supply:

DC 12V from Adapter
AC 120V/60Hz

Polarization

N

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GTS190425146_fin"

4/25/2019 6:17PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.379500	47.20	9.8	58	11.1	QP	N	GND
0.384000	45.90	9.8	58	12.3	QP	N	GND
0.757500	39.60	9.7	56	16.4	QP	N	GND
1.324500	37.20	9.6	56	18.8	QP	N	GND
3.552000	35.30	9.4	56	20.7	QP	N	GND
5.730000	34.30	9.2	60	25.7	QP	N	GND

MEASUREMENT RESULT: "GTS190425146_fin2"


4/25/2019 6:17PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.375000	32.20	9.8	48	16.2	AV	N	GND
0.379500	33.00	9.8	48	15.3	AV	N	GND
1.311000	25.60	9.6	46	20.4	AV	N	GND
2.346000	23.80	9.5	46	22.2	AV	N	GND
5.536500	21.40	9.2	50	28.6	AV	N	GND
12.525000	13.70	8.5	50	36.3	AV	N	GND


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 5825MHz.so radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$\text{Transd}=AF +CL-AG$$

RADIATION LIMIT


According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBμV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at all mode from 30MHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

For 30MHz-1GHz**Horizontal****Test Graph****Suspected List**

NO.	Freq. [MHz]	Polarity	Height [cm]	Angle [°]	Limit [dBμV/m]	Level [dBμV/m]	Factor [dB]	Readin d [dBμV/m]	Margin [dB]
1	191.505	Horizontal	100	168	43.50	26.16	-17.39	43.55	17.34
2	351.070	Horizontal	100	254	46.00	29.63	-12.92	42.55	16.37
3	391.325	Horizontal	100	90	46.00	33.61	-11.86	45.47	12.39
4	593.570	Horizontal	100	360	46.00	34.40	-7.89	42.29	11.60
5	823.460	Horizontal	100	81	46.00	37.03	-4.47	41.50	8.97
6	941.315	Horizontal	100	359	46.00	40.27	-3.62	43.89	5.73

Vertical**Test Graph****Suspected List**

NO.	Freq. [MHz]	Polarity	Height [cm]	Angle [°]	Limit [dBμV/m]	Level [dBμV/m]	Factor [dB]	Readin d [dBμV/m]	Margin [dB]
1	118.270	Vertical	100	99	43.50	32.40	-18.19	50.59	11.10
2	350.585	Vertical	100	347	46.00	31.18	-12.93	44.11	14.82
3	432.065	Vertical	100	1	46.00	37.29	-11.15	48.44	8.71
4	669.230	Vertical	100	347	46.00	34.36	-6.77	41.13	11.64
5	827.825	Vertical	100	74	46.00	37.58	-4.17	41.75	8.42
6	1000.00	Vertical	100	92	54.00	47.05	-3.06	50.11	6.95

For 1GHz to 40GHz

NOTE:the worst case was ant 0.

5150-5250MHz:

802.11a Mode Channel 36 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10360	35.14	38.55	33.13	11.26	51.82	68.2	16.38	Peak	Horizontal
1	10360	25.49	38.55	33.13	11.26	42.17	68.2	26.03	Peak	Vertical

802.11a Mode Channel 40 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10400	35.15	38.55	33.13	11.26	51.83	68.2	16.37	Peak	Horizontal
1	10400	24.56	38.55	33.13	11.26	41.24	68.2	26.96	Peak	Vertical

802.11a Mode Channel 48 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10480	34.95	38.55	33.13	11.26	51.63	68.2	16.57	Peak	Horizontal
1	10480	25.66	38.55	33.13	11.26	42.34	68.2	25.86	Peak	Vertical

802.11n20 Mode Channel 36 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10360	35.94	38.55	33.64	11.24	52.09	68.2	16.11	Peak	Horizontal
1	10360	35.49	38.55	33.64	11.24	51.64	68.2	16.56	Peak	Vertical

802.11n20 Mode Channel 40 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10400	35.15	38.55	33.13	11.26	51.83	68.2	16.37	Peak	Horizontal
1	10400	25.35	38.55	33.13	11.26	42.03	68.2	26.17	Peak	Vertical

802.11n20 Mode Channel 48 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10480	35.39	38.55	33.13	11.26	52.07	68.2	16.13	Peak	Horizontal
1	10480	24.55	38.55	33.13	11.26	41.23	68.2	26.97	Peak	Vertical

802.11n40 Mode Channel 38 5190 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10380	34.66	38.55	33.13	11.26	51.34	68.2	16.86	Peak	Horizontal
1	10380	23.93	38.55	33.13	11.26	40.61	68.2	27.59	Peak	Vertical

802.11n40 Mode Channel 46 5230 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10460	33.95	38.55	33.13	11.26	50.63	68.2	17.57	Peak	Horizontal
1	10460	24.03	38.55	33.13	11.26	40.71	68.2	27.49	Peak	Vertical

802.11ac20 Mode Channel 36 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10360	34.77	38.55	33.13	11.26	51.45	68.2	16.75	Peak	Horizontal
1	10360	25.45	38.55	33.13	11.26	42.13	68.2	26.07	Peak	Vertical

802.11ac20 Mode Channel 40 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10400	35.03	38.55	33.13	11.26	51.71	68.2	16.49	Peak	Horizontal
1	10400	24.69	38.55	33.13	11.26	41.37	68.2	26.83	Peak	Vertical

802.11ac20 Mode Channel 48 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10480	35.57	38.55	33.13	11.26	52.25	68.2	15.95	Peak	Horizontal
1	10480	25.57	38.55	33.13	11.26	42.25	68.2	25.95	Peak	Vertical

802.11ac40 Mode Channel 38 5190 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10380	34.07	38.55	33.13	11.26	50.75	68.2	17.45	Peak	Horizontal
1	10380	24.91	38.55	33.13	11.26	41.59	68.2	26.61	Peak	Vertical

802.11ac40 Mode Channel 46 5230 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10460	35.51	38.55	33.13	11.26	52.19	68.2	16.01	Peak	Horizontal
1	10460	24.81	38.55	33.13	11.26	41.49	68.2	26.71	Peak	Vertical

802.11ac80 Mode Channel 42 5210 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10420	35.21	38.55	33.13	11.26	51.89	68.2	16.31	Peak	Horizontal
1	10420	24.47	38.55	33.13	11.26	41.15	68.2	27.05	Peak	Vertical

5725-5850MHz:**802.11a Mode Channel 149 5745 MHz**

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11490	35.09	38.41	33.13	11.26	51.63	74	22.37	Peak	Horizontal
1	11490	24.43	38.41	33.13	11.26	40.97	54	13.03	av	Horizontal

802.11a Mode Channel 157 5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11570	35.65	38.41	33.13	11.26	52.19	74	21.81	Peak	Horizontal
1	11570	25.04	38.41	33.13	11.26	41.58	54	12.42	AV	Horizontal

802.11a Mode Channel 165 5825 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11650	34.64	38.41	33.13	11.26	51.18	74	22.82	Peak	Horizontal
1	11650	25.18	38.41	33.13	11.26	41.72	54	12.28	AV	Horizontal

802.11n20 Mode Channel 149 5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11490	34.72	38.41	33.13	11.26	51.26	74	22.74	Peak	Horizontal
1	11490	24.99	38.41	33.13	11.26	41.53	54	12.47	AV	Horizontal

802.11n20 Mode Channel 157 5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11570	34.68	38.41	33.13	11.26	51.22	74	22.78	Peak	Horizontal
1	11570	25.17	38.41	33.13	11.26	41.71	54	12.29	AV	Horizontal

802.11n20 Mode Channel 165 5825 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11650	35.01	38.41	33.13	11.26	51.55	74	22.45	Peak	Horizontal
1	11650	25.04	38.41	33.13	11.26	41.58	54	12.42	AV	Horizontal

802.11n40 Mode Channel 151 5755 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11510	35.75	38.41	33.13	11.26	52.29	74	21.71	Peak	Horizontal
1	11510	24.58	38.41	33.13	11.26	41.12	54	12.88	AV	Horizontal

802.11n40 Mode Channel 159 5795MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11590	34.21	38.41	33.13	11.26	50.75	74	23.25	Peak	Horizontal
1	11590	25.32	38.41	33.13	11.26	41.86	54	12.14	AV	Horizontal

802.11ac20 Mode Channel 149 5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11490	34.59	38.41	33.13	11.26	51.13	74	22.87	Peak	Horizontal
1	11490	25.81	38.41	33.13	11.26	42.35	54	11.65	AV	Horizontal

802.11ac20 Mode Channel 157 5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11570	34.61	38.41	33.13	11.26	51.15	74	22.85	Peak	Horizontal
1	11570	25.42	38.41	33.13	11.26	41.96	54	12.04	AV	Horizontal

802.11ac20 Mode Channel 165 5825 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11650	35.59	38.41	33.13	11.26	52.13	74	21.87	Peak	Horizontal
1	11650	25.63	38.41	33.13	11.26	42.17	54	11.83	AV	Horizontal

802.11ac40 Mode Channel 151 5755 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11510	34.77	38.41	33.13	11.26	51.31	74	22.69	Peak	Horizontal
1	11510	24.59	38.41	33.13	11.26	41.13	54	12.87	AV	Horizontal

802.11ac40 Mode Channel 159 5795MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11590	34.37	38.41	33.13	11.26	50.91	74	23.09	Peak	Horizontal
1	11590	24.01	38.41	33.13	11.26	40.55	54	13.45	AV	Horizontal

802.11ac80 Mode Channel 155 5775 MHz


Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11550	35.43	38.41	33.13	11.26	51.97	74	22.03	Peak	Horizontal
1	11550	25.32	38.41	33.13	11.26	41.86	54	12.14	AV	Horizontal

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. The other emission levels were very low against the limit.
3. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;

4.3. Duty Cycle

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 B Duty Cycle (x), Transmission Duration (T):

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq EBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

Antenna 0

802.11a Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11ac20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac80 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
42	5210	1.00	0

Antenna 1**802.11a Test Mode**

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11ac20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac40 Test Mode


Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac80 Test Mode


Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
42	5210	1.00	0

Antenna 0


802.11a




802.11n HT20




802.11ac20




802.11n HT40



802.11ac40




802.11ac80




Antenna 1


802.11a




802.11n HT20




802.11ac20




802.11n HT40



802.11ac40




802.11ac80



4.4. Maximum Average Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 Section E3 Measurement using a Power Meter (PM):

- a. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
 1. The EUT is configured to transmit continuously or to transmit with a constant duty cycle
 2. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 3. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b. If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B
- c. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed: 1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)

Note: The maximum e.i.r.p at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)

TEST RESULTS

Antenna 0

5150-5250MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
36	5180	10.82	0	10.82	24.00	PASS
40	5200	11.35	0	11.35	24.00	PASS
48	5240	11.53	0	11.53	24.00	PASS
802.11n20						
36	5180	11.12	0	11.12	24.00	PASS
40	5200	11.78	0	11.78	24.00	PASS
48	5240	11.54	0	11.54	24.00	PASS
802.11ac20						
36	5180	11.43	0	11.43	24.00	PASS
40	5200	10.92	0	10.92	24.00	PASS
48	5240	11.87	0	11.87	24.00	PASS
802.11n40						
38	5190	11.31	0	11.31	24.00	PASS
46	5230	11.38	0	11.38	24.00	PASS
802.11ac40						
38	5190	11.31	0	11.31	24.00	PASS
46	5230	11.38	0	11.38	24.00	PASS
802.11ac80						
42	5210	10.87	0	10.87	24.00	24.00

5725-5850MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
149	5745	10.71	0	10.71	30.00	PASS
157	5785	10.99	0	10.99	30.00	PASS
165	5825	11.03	0	11.03	30.00	PASS
802.11n20						
149	5745	11.34	0	11.34	30.00	PASS
157	5785	11.29	0	11.29	30.00	PASS
165	5825	11.33	0	11.33	30.00	PASS
802.11ac20						
149	5745	11.51	0	11.51	30.00	PASS
157	5785	10.44	0	10.44	30.00	PASS
165	5825	11.33	0	11.33	30.00	PASS
802.11n40						
151	5755	11.06	0	11.06	30.00	PASS
159	5795	11.02	0	11.02	30.00	PASS
802.11ac40						
151	5755	10.81	0	10.81	30.00	PASS
159	5795	10.90	0	10.90	30.00	PASS
802.11ac80						
155	5775	11.80	0	11.80	30.00	PASS

Antenna 1

5150-5250MHz:


Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
36	5180	10.69	0	10.69	24	PASS
40	5200	11.27	0	11.27	24	PASS
48	5240	11.70	0	11.70	24	PASS
802.11n20						
36	5180	11.19	0	11.19	24	PASS
40	5200	11.37	0	11.37	24	PASS
48	5240	11.29	0	11.29	24	PASS
802.11ac20						
36	5180	11.69	0	11.69	24	PASS
40	5200	10.95	0	10.95	24	PASS
48	5240	10.96	0	10.96	24	PASS
802.11n40						
38	5190	11.22	0	11.22	24	PASS
46	5230	11.52	0	11.52	24	PASS
802.11ac40						
38	5190	10.87	0	10.87	24	PASS
46	5230	11.12	0	11.12	24	PASS
802.11ac80						
42	5210	11.56	0	11.56	24	PASS

5725-5850MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
149	5745	10.91	0	10.91	30.00	PASS
157	5785	10.76	0	10.76	30.00	PASS
165	5825	11.29	0	11.29	30.00	PASS
802.11n20						
149	5745	11.37	0	11.37	30.00	PASS
157	5785	11.32	0	11.32	30.00	PASS
165	5825	11.38	0	11.38	30.00	PASS
802.11ac20						
149	5745	11.12	0	11.12	30.00	PASS
157	5785	11.52	0	11.52	30.00	PASS
165	5825	11.76	0	11.76	30.00	PASS
802.11n40						
151	5755	11.49	0	11.49	30.00	PASS
159	5795	11.23	0	11.23	30.00	PASS
802.11ac40						
151	5755	11.05	0	11.05	30.00	PASS
159	5795	10.84	0	10.84	30.00	PASS
802.11ac80						
155	5775	11.74	0	11.74	30.00	PASS

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 789033 D02 General UNII Test Procedures New Rules v01 F: The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...”. (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
 - b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
 - c. Make the following adjustments to the peak value of the spectrum, if applicable:
 1. If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 2.) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
 - d. The result is the Maximum PSD over 1 MHz reference bandwidth.
 - e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:
 1. Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
 2. Set $VBW \geq 3 RBW$.
 3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.
- Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.
- f. Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz

TEST RESULTS**Antenna 0****5150-5250MHz:****802.11a Test Mode**

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	2.174	0	0	2.174	17	PASS
40	5200	0.945	0	0	0.945	17	PASS
48	5240	0.490	0	0	0.490	17	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	0.408	0	0	0.408	17	PASS
40	5200	1.121	0	0	1.121	17	PASS
48	5240	0.081	0	0	0.081	17	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	1.201	0	0	1.201	17	PASS
40	5200	0.788	0	0	0.788	17	PASS
48	5240	0.277	0	0	0.277	17	PASS

802.11n40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-2.572	0	0	-2.572	17	PASS
46	5230	-2.824	0	0	-2.824	17	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-1.126	0	0	-1.126	17	PASS
46	5230	-2.889	0	0	-2.889	17	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
42	5210	-6.427	0	0	-6.427	17	PASS

5725-5850MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-4.592	0	2.2	-2.392	30	PASS
157	5785	-4.624	0	2.2	-2.424	30	PASS
165	5825	-3.478	0	2.2	-1.278	30	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-5.018	0	2.2	-2.818	30	PASS
157	5785	-4.883	0	2.2	-2.683	30	PASS
165	5825	-4.553	0	2.2	-2.353	30	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-4.593	0	2.2	-2.393	30	PASS
157	5785	-5.255	0	2.2	-3.055	30	PASS
165	5825	-3.648	0	2.2	-1.448	30	PASS

802.11n40Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-8.882	0	2.2	-6.682	30	PASS
157	5795	-7.862	0	2.2	-5.662	30	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-7.551	0	2.2	-5.351	30	PASS
157	5795	-7.782	0	2.2	-5.582	30	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
155	5775	-9.673	0	2.2	-7.473	30	PASS

Antenna 1

5150-5250MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	0.952	0	0	0.952	17	PASS
40	5200	0.282	0	0	0.282	17	PASS
48	5240	1.071	0	0	1.071	17	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-0.179	0	0	-0.179	17	PASS
40	5200	0.432	0	0	0.432	17	PASS
48	5240	0.322	0	0	0.322	17	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	0.006	0	0	0.006	17	PASS
40	5200	0.096	0	0	0.096	17	PASS
48	5240	0.500	0	0	0.500	17	PASS

802.11n40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-2.617	0	0	-2.617	17	PASS
46	5230	-2.758	0	0	-2.758	17	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-2.380	0	0	-2.175	17	PASS
46	5230	-2.831	0	0	-1.983	17	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
42	5210	-6.996	0	0	-5.459	17	PASS

5725-5850MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-3.628	0	2.2	-1.428	30	PASS
157	5785	-3.397	0	2.2	-1.197	30	PASS
165	5825	-3.277	0	2.2	-1.077	30	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-4.406	0	2.2	-2.206	30	PASS
157	5785	-3.970	0	2.2	-1.77	30	PASS
165	5825	-4.511	0	2.2	-2.311	30	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-4.194	0	2.2	-1.994	30	PASS
157	5785	-4.425	0	2.2	-2.225	30	PASS
165	5825	-4.532	0	2.2	-2.332	30	PASS

802.11n40Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-8.795	0	2.2	-6.595	30	PASS
157	5795	-7.725	0	2.2	-5.525	30	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-7.015	0	2.2	-4.815	30	PASS
157	5795	-7.767	0	2.2	-5.567	30	PASS

802.11ac80 Test Mode


Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
155	5775	-10.120	0	2.2	-7.92	30	PASS







Note:





1. The test results including the cable lose.

Antenna 0

5150-5250MHz:









5725-5850MHz:


802.11a




802.11n HT20




CH 149




CH 149



CH 157




CH 157



CH 165




CH 165




802.11ac20



CH 149




CH 157




CH 165


802.11n HT40





CH 151



CH 159






CH 151




CH 159

CH 155




Antenna 1

5150-5250MHz:




802.11ac20



802.11n HT40




CH 36




CH 38






CH 40




CH 46









CH 48





5725-5850MHz:






CH 165



CH 151



CH 159

CH 155

