

## FCC RF EXPOSURE REPORT

FCC ID: 2AG7CSPEED2

Project No. : 2011H044
Equipment : IP CAMERA

Brand Name : N/A

Test Model : Speed 2S

Series Model : Speed 2X ,WIFICO20CWT

**Applicant**: Hangzhou Meari Technology Co., Ltd.

Address : Room 604-605, Building 1, No. 768 Jianghong Road,

Changhe street, Binjiang District, Hangzhou, Zhejiang, China

**Manufacturer**: Hangzhou Meari Technology Co., Ltd.

Address: No. 91 Chutian Road, Xixing Street, Binjiang District,

Hangzhou, Zhejiang, China

**Factory** Hangzhou Meari Technology Co., Ltd.

Address No. 91 Chutian Road, Xixing Street, Binjiang District,

Hangzhou, Zhejiang, China

Date of Receipt : Nov. 26, 2020

**Date of Test** : Nov. 26, 2020~Dec. 10, 2020

**Issued Date** : Dec. 14, 2020

Report Version : R00

**Test Sample** : Engineering Sample No.: SH20201123168, SH20201123167

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Kyan. Wang

Approved by: Ryan Wang

IAC-MRA ACCREDITED

Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666 Web: www.newbtl.com



## **REPORT ISSUED HISTORY**

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 14, 2020





## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G:\_\_\_\_\_

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	FPC	N/A	3

Note:

The antenna gain is provided by the manufacturer.

## 2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result	
3.00	1.9953	26	398.1072	0.158030	1	Complies	

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

**End of Test Report**