

FCC ID: 2A5VZ-TWS-24

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: Chip antenna

Antenna Gain: 2.2dBi

Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.19	1.315	1±1	2.0	1.585	<5	0.49127	3.00	YES
	2.441	1.9	1.549	1±1	2.0	1.585	<5	0.49524	3.00	YES
	2.480	0.91	1.233	1±1	2.0	1.585	<5	0.49918	3.00	YES
$\pi/4$ -DQPSK	2.402	1.81	1.517	2±1	3.0	1.995	<5	0.61847	3.00	YES
	2.441	2.51	1.782	2±1	3.0	1.995	<5	0.62347	3.00	YES
	2.480	1.59	1.442	2±1	3.0	1.995	<5	0.62843	3.00	YES
8DPSK	2.402	2.48	1.770	3±1	4.0	2.512	<5	0.77860	3.00	YES
	2.441	3.21	2.094	3±1	4.0	2.512	<5	0.78490	3.00	YES
	2.480	2.31	1.702	3±1	4.0	2.512	<5	0.79114	3.00	YES

BR+EDR:

Right

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.23	1.327	1±1	2.0	1.585	<5	0.49127	3.00	YES
	2.441	1.84	1.528	1±1	2.0	1.585	<5	0.49524	3.00	YES
	2.480	0.95	1.245	1±1	2.0	1.585	<5	0.49918	3.00	YES
$\pi/4$ -DQPSK	2.402	1.8	1.514	2±1	3.0	1.995	<5	0.61847	3.00	YES
	2.441	2.51	1.782	2±1	3.0	1.995	<5	0.62347	3.00	YES
	2.480	1.62	1.452	2±1	3.0	1.995	<5	0.62843	3.00	YES
8DPSK	2.402	2.48	1.770	3±1	4.0	2.512	<5	0.77860	3.00	YES
	2.441	3.23	2.104	3±1	4.0	2.512	<5	0.78490	3.00	YES
	2.480	2.51	1.782	3±1	4.0	2.512	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.79114 \leq 3.0$ for 1-g SAR, No SAR is required.


Signature:**Date:** 2022-04-12**NAME AND TITLE** (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China