

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a SWGAS MOUSE DROID RC operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 96.3dBμV/m at 3m in the frequency 2422MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 1.07dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 94.4dBμV/m at 3m in the frequency 2472MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -0.83dBm  
which is within the production variation.

The maximum conducted output power specified is 4dBm = 2.512mW

The source- based time-averaging conducted output power  
= 2.512mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

=  $3.0 \cdot 5 / \sqrt{2.472}$  mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.