

FTLTE127 LTE, WiFi/BLE Antenna

Custom Built to Serve Your Unique Requirements

Features:

Type: Inverted-F Antenna (LDS)

Frequency Range:

890-900 MHz, 1680-2600 MHz

Carrier Dimensions¹:

39.46 x 30.30 x 7.97 mm

Suggested Applications:

- LTE/Cellular; WiFi/BLE

Contents	Page
Performance & Specifications	2
Efficiency & 1D Gain Radiation Patterns	3
2D & 3D Gain Radiation Patterns	4-5
Test Conditions & Equipment Calibration	5-6
Legal Notices	7

PN: FTLTEL127

Status: Released **Date:** 04/07/2025

1: LDS antenna is printed on carrier

Performance & Specifications

Antenna Performance				
Parameters	Results			
Frequency (GHz)	0.710	1.746	1.900	2.440
Efficiency (%)	21.45	17.28	33.65	71.60
Peak Gain (dBi)	-3.83	-1.59	1.00	3.68
VSWR	< 2.00			

General Specifications			
Antenna Type	Nominal Impedance	Power Handling	Polarization
LTE; WiFi/BLE	50 Ω	10 W	Linear

Mechanical Specifications	
Carrier ¹ Dimensions (L x W x H)	Material
39.46 x 30.30 x 7.97 mm	LDS Conductive Plating on Plastic

1: LDS antenna is printed on carrier

Efficiency




Fig 2. Typical Performance Efficiency

1D Gain Radiation Patterns





Fig. 3-5: 1D Gain Radiation Patterns

2D & 3D Gain Radiation Patterns






Fig. 9: 2D & 3D Gain Radiation Patterns, 2.4429 GHz

Test Conditions

Results were collected from a passive antenna measurement within a 5-meter fully anechoic antenna chamber equipped with a dual-pol quad-ridged horn receiver antenna and an EL-AZ positioner with laser positioner.

Test Conducted	03/24/2025
----------------	------------

Formula & Calculations

Gain:
$$G_{AUT} = \frac{[S_{21}]^2}{[G_{REF}]} \left(\frac{\lambda}{4\pi d} \right)^{-2}$$

Efficiency:
$$\varepsilon = \frac{\pi}{2NM} \sum_N \sum_M \frac{S_{21}^2(\theta_M, \phi_N)}{P_L G_T} \cos(\phi_N)$$

Software Name: Antenna Measurement Studio

Test Equipment Calibration Status

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Network Analyzer	Anritsu	MS46122B	2135304	8/25/2024	8/25/2025
Quad-Ridge Horn Antenna	ETS-Lindgreen	3164-10	217936	8/25/2024	8/25/2025
5 Meter Anechoic Chamber	Braden Shielding Systems	NA	F70331	NA	NA
RF Cable	ENS Microwave	S160-160-MKS-MKS	3042020	8/25/2024	8/25/2025
RF Cable	ENS Microwave	S160-120-MKS-MKS	12042018	8/25/2024	8/25/2025
RF Cable	ENS Microwave	EMC1-K1K1-72	1GVT4 19002201	8/25/2024	8/25/2025
RF Cable	ENS Microwave	EMC1-K1K1-72	1GVT4 19002202	8/25/2024	8/25/2025
RF Cable	ENS Microwave	EMC1-K1K1-216	1GVT4 19002202 001	8/25/2024	8/25/2025
RF Cable	ENS Microwave	EMC1-K1K1-216	1GVT4 19002202 002	8/25/2024	8/25/2025
DUT Positioner	DE LCC	D6025	NA	NA	NA
RF Switch	Mini-Circuits	RC-1SPDT-A18	1810010005	8/25/2024	8/25/2025

Legal Notices

This specification sheet shall not be duplicated, used, or disclosed, in whole or in part, for any purpose.

Field Theory Consulting Inc. and the Field Theory logo are registered trademarks. The information given herein, including drawings, illustrations, and schematics, are included for illustration purposes only and are believed to be accurate and reliable at the time of publishing. However, Field Theory makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Field Theory's obligations shall be as set forth in Field Theory's standard Terms and Conditions, found on the Field Theory website at www.fieldtheoryinc.com/terms-and-conditions/ and in no case will Field Theory be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misuse of the product.