

PROBE CALIBRATION CERTIFICATES

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **BACL-SZ (Auden)**

Certificate No: **ES3-3019_Aug18**

CALIBRATION CERTIFICATE

Object **ES3DV2 - SN:3019**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-12.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **August 20, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	05-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41468087	05-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	05-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Michael Weber	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: August 21, 2018			

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\theta = 0$ ($f < 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV2

SN:3019

Manufactured: December 5, 2002
Calibrated: August 20, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3019

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.01	1.13	0.93	$\pm 10.1\%$
DCP (mV) ^B	104.8	103.8	106.3	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^C (k=2)
0	CW	X	0.0	0.0	1.0	0.00	189.8	$\pm 3.0\%$
		Y	0.0	0.0	1.0		205.7	
		Z	0.0	0.0	1.0		205.8	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms} \cdot \text{V}^{-2}$	T2 $\text{ms} \cdot \text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	27.76	200.6	35.82	18.61	0.506	5.10	0.000	0.276	1.005
Y	28.17	203.3	35.77	18.85	0.706	5.10	0.000	0.137	1.010
Z	26.29	187.2	34.88	16.18	0.325	5.10	1.142	0.072	1.007

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^C Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3019

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^g (mm)	Unc (k=2)
150	52.3	0.76	7.67	7.67	7.67	0.05	1.50	± 13.3 %
450	43.5	0.87	7.18	7.18	7.18	0.15	1.60	± 13.3 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV2 - SN:3019

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^g (mm)	Unc (k=2)
150	61.9	0.80	7.30	7.30	7.30	0.07	1.50	± 13.3 %
450	56.7	0.94	7.10	7.10	7.10	0.10	1.50	± 13.3 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$



f=600 MHz,TEM



f=1800 MHz,R22


Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV2 - SN:3019**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-18,7
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB μ V	C	D dB	VR mV	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	189.8	± 3.0 %
		Y	0.00	0.00	1.00		205.7	
		Z	0.00	0.00	1.00		205.8	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	3.29	69.40	11.94	10.00	25.0	± 9.6 %
		Y	6.86	78.15	16.03		25.0	
		Z	3.55	70.52	12.29		25.0	
10011- CAB	UMTS-FDD (WCDMA)	X	0.86	67.55	14.41	0.00	150.0	± 9.6 %
		Y	1.00	69.15	15.56		150.0	
		Z	0.82	68.15	13.59		150.0	
10012- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.15	64.93	15.50	0.41	150.0	± 9.6 %
		Y	1.20	65.35	15.90		150.0	
		Z	1.13	64.32	14.98		150.0	
10013- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	4.63	67.61	17.39	1.46	150.0	± 9.6 %
		Y	4.69	67.72	17.52		150.0	
		Z	4.58	67.52	17.24		150.0	
10021- DAC	GSM-FDD (TDMA, GMSK)	X	100.00	114.84	27.74	9.39	50.0	± 9.6 %
		Y	100.00	117.82	29.54		50.0	
		Z	100.00	114.90	27.69		50.0	
10023- DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	100.00	113.96	27.45	9.57	50.0	± 9.6 %
		Y	100.00	117.23	29.30		50.0	
		Z	100.00	114.00	27.30		50.0	
10024- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	112.40	25.80	6.56	60.0	± 9.6 %
		Y	100.00	116.08	27.75		60.0	
		Z	100.00	113.76	26.24		60.0	
10025- DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	9.98	97.93	39.31	12.57	50.0	± 9.6 %
		Y	32.24	137.81	54.11		50.0	
		Z	7.11	87.72	35.09		50.0	
10026- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	14.40	104.70	37.60	9.56	60.0	± 9.6 %
		Y	21.43	115.81	41.75		60.0	
		Z	10.88	98.23	35.49		60.0	
10027- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	112.28	25.05	4.80	80.0	± 9.6 %
		Y	100.00	116.70	27.28		80.0	
		Z	100.00	114.64	25.92		80.0	
10028- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	112.94	24.67	3.55	100.0	± 9.6 %
		Y	100.00	118.58	27.39		100.0	
		Z	100.00	116.41	26.01		100.0	
10029- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	8.11	90.12	31.09	7.80	80.0	± 9.6 %
		Y	9.67	94.63	33.13		80.0	
		Z	6.66	85.92	29.56		80.0	
10030- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	100.00	109.77	24.16	5.30	70.0	± 9.6 %
		Y	100.00	113.94	26.30		70.0	
		Z	100.00	111.16	24.61		70.0	
10031- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	105.00	19.97	1.88	100.0	± 9.6 %
		Y	100.00	115.59	24.65		100.0	
		Z	100.00	108.86	21.47		100.0	

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	100.25	17.19	1.17	100.0	± 9.6 %
		Y	100.00	119.00	25.00		100.0	
		Z	100.00	106.97	19.82		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	100.00	117.31	28.80	5.30	70.0	± 9.6 %
		Y	100.00	119.34	29.96		70.0	
		Z	100.00	117.71	28.83		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	3.39	74.56	14.02	1.88	100.0	± 9.6 %
		Y	7.50	83.72	17.60		100.0	
		Z	2.76	72.78	13.27		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	1.52	67.61	10.81	1.17	100.0	± 9.6 %
		Y	2.55	73.11	13.53		100.0	
		Z	1.33	66.63	10.29		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	100.00	117.74	29.00	5.30	70.0	± 9.6 %
		Y	100.00	119.74	30.14		70.0	
		Z	100.00	118.21	29.05		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	2.81	72.76	13.37	1.88	100.0	± 9.6 %
		Y	5.49	80.47	16.60		100.0	
		Z	2.33	71.15	12.66		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	1.57	68.12	11.15	1.17	100.0	± 9.6 %
		Y	2.68	73.90	13.96		100.0	
		Z	1.36	66.99	10.57		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	0.51	60.81	6.58	0.00	150.0	± 9.6 %
		Y	0.63	62.47	8.01		150.0	
		Z	0.48	60.49	6.29		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	100.00	109.34	24.59	7.78	50.0	± 9.6 %
		Y	100.00	113.01	26.55		50.0	
		Z	100.00	110.01	24.73		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.06	123.26	6.55	0.00	150.0	± 9.6 %
		Y	0.00	117.23	6.07		150.0	
		Z	0.02	120.00	0.96		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	100.00	113.79	28.54	13.80	25.0	± 9.6 %
		Y	100.00	117.44	30.66		25.0	
		Z	100.00	112.50	27.83		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	100.00	113.10	27.30	10.79	40.0	± 9.6 %
		Y	100.00	116.50	29.24		40.0	
		Z	100.00	112.54	26.89		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	100.00	118.95	30.75	9.03	50.0	± 9.6 %
		Y	100.00	120.98	31.98		50.0	
		Z	100.00	119.02	30.62		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	5.91	83.19	27.57	6.55	100.0	± 9.6 %
		Y	6.56	85.60	28.82		100.0	
		Z	5.08	80.09	26.35		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.25	66.85	16.51	0.61	110.0	± 9.6 %
		Y	1.32	67.32	16.93		110.0	
		Z	1.20	65.88	15.84		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	100.00	134.06	33.85	1.30	110.0	± 9.6 %
		Y	100.00	136.81	35.28		110.0	
		Z	100.00	135.20	34.31		110.0	

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	15.36	108.05	30.50	2.04	110.0	± 9.6 %
		Y	15.08	108.15	30.91		110.0	
		Z	6.66	94.63	26.70		110.0	
10062-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.35	67.26	16.60	0.49	100.0	± 9.6 %
		Y	4.41	67.37	16.72		100.0	
		Z	4.30	67.18	16.44		100.0	
10063-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.38	67.45	16.75	0.72	100.0	± 9.6 %
		Y	4.44	67.56	16.88		100.0	
		Z	4.34	67.37	16.60		100.0	
10064-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	4.60	67.64	16.95	0.86	100.0	± 9.6 %
		Y	4.66	67.75	17.07		100.0	
		Z	4.55	67.56	16.80		100.0	
10065-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.51	67.57	17.11	1.21	100.0	± 9.6 %
		Y	4.57	67.68	17.23		100.0	
		Z	4.46	67.48	16.95		100.0	
10066-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	4.54	67.62	17.29	1.46	100.0	± 9.6 %
		Y	4.60	67.74	17.42		100.0	
		Z	4.48	67.51	17.12		100.0	
10067-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	4.84	68.00	17.84	2.04	100.0	± 9.6 %
		Y	4.91	68.15	17.99		100.0	
		Z	4.77	67.85	17.66		100.0	
10068-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	4.93	68.11	18.14	2.55	100.0	± 9.6 %
		Y	5.00	68.27	18.29		100.0	
		Z	4.86	68.00	17.98		100.0	
10069-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	4.97	68.10	18.30	2.67	100.0	± 9.6 %
		Y	5.05	68.27	18.47		100.0	
		Z	4.90	67.95	18.12		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	4.76	67.80	17.78	1.99	100.0	± 9.6 %
		Y	4.82	67.92	17.91		100.0	
		Z	4.71	67.71	17.63		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.74	68.13	18.04	2.30	100.0	± 9.6 %
		Y	4.81	68.27	18.18		100.0	
		Z	4.67	67.99	17.87		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	4.86	68.55	18.52	2.83	100.0	± 9.6 %
		Y	4.94	68.72	18.68		100.0	
		Z	4.79	68.40	18.35		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	4.92	68.71	18.79	3.30	100.0	± 9.6 %
		Y	5.01	68.89	18.96		100.0	
		Z	4.85	68.56	18.63		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	4.99	68.87	19.13	3.82	90.0	± 9.6 %
		Y	5.08	69.07	19.31		90.0	
		Z	4.91	68.70	18.96		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	5.04	68.76	19.33	4.15	90.0	± 9.6 %
		Y	5.14	69.00	19.53		90.0	
		Z	4.97	68.59	19.16		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	5.09	68.91	19.48	4.30	90.0	± 9.6 %
		Y	5.19	69.15	19.69		90.0	
		Z	5.01	68.73	19.30		90.0	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.33	60.00	5.42	0.00	150.0	± 9.6 %
		Y	0.37	60.39	6.25		150.0	
		Z	0.32	60.00	5.39		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-QPSK, Fullrate)	X	0.87	60.00	4.66	4.77	80.0	± 9.6 %
		Y	0.92	60.00	5.02		80.0	
		Z	0.79	60.00	4.55		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	112.50	25.87	6.56	60.0	± 9.6 %
		Y	100.00	116.14	27.80		60.0	
		Z	100.00	113.84	26.29		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.68	68.74	14.96	0.00	150.0	± 9.6 %
		Y	1.80	69.62	15.63		150.0	
		Z	1.59	67.84	14.37		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.64	68.69	14.95	0.00	150.0	± 9.6 %
		Y	1.77	69.59	15.63		150.0	
		Z	1.56	67.78	14.35		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	14.55	104.92	37.67	9.56	60.0	± 9.6 %
		Y	21.65	116.02	41.81		60.0	
		Z	10.99	98.46	35.57		60.0	
10100-CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	2.75	69.89	16.53	0.00	150.0	± 9.6 %
		Y	2.86	70.39	16.89		150.0	
		Z	2.65	69.26	16.15		150.0	
10101-CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	2.92	67.35	15.74	0.00	150.0	± 9.6 %
		Y	2.99	67.63	15.98		150.0	
		Z	2.87	67.07	15.50		150.0	
10102-CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.03	67.40	15.86	0.00	150.0	± 9.6 %
		Y	3.09	67.64	16.07		150.0	
		Z	2.98	67.15	15.62		150.0	
10103-CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	7.90	81.11	22.78	3.98	65.0	± 9.6 %
		Y	7.81	80.69	22.73		65.0	
		Z	7.06	79.54	22.21		65.0	
10104-CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	6.89	76.73	21.71	3.98	65.0	± 9.6 %
		Y	7.12	77.18	22.01		65.0	
		Z	6.50	75.95	21.35		65.0	
10105-CAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	6.51	75.50	21.48	3.98	65.0	± 9.6 %
		Y	6.52	75.32	21.50		65.0	
		Z	6.50	75.81	21.59		65.0	
10108-CAF	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.35	69.45	16.36	0.00	150.0	± 9.6 %
		Y	2.45	69.99	16.76		150.0	
		Z	2.25	68.74	15.91		150.0	
10109-CAF	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.55	67.44	15.50	0.00	150.0	± 9.6 %
		Y	2.63	67.76	15.78		150.0	
		Z	2.50	67.09	15.19		150.0	
10110-CAF	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	1.83	68.67	15.52	0.00	150.0	± 9.6 %
		Y	1.94	69.40	16.07		150.0	
		Z	1.74	67.81	14.96		150.0	
10111-CAF	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.27	68.67	15.34	0.00	150.0	± 9.6 %
		Y	2.35	69.06	15.70		150.0	
		Z	2.18	68.08	14.88		150.0	

10112-CAF	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	2.68	67.57	15.60	0.00	150.0	± 9.6 %
		Y	2.75	67.85	15.85		150.0	
		Z	2.62	67.25	15.31		150.0	
10113-CAF	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.40	66.84	15.47	0.00	150.0	± 9.6 %
		Y	2.48	69.17	15.79		150.0	
		Z	2.31	68.27	15.02		150.0	
10114-CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	4.78	67.32	16.48	0.00	150.0	± 9.6 %
		Y	4.84	67.44	16.60		150.0	
		Z	4.74	67.21	16.33		150.0	
10115-CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.03	67.47	16.54	0.00	150.0	± 9.6 %
		Y	5.08	67.57	16.65		150.0	
		Z	4.98	67.38	16.40		150.0	
10116-CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	4.86	67.52	16.51	0.00	150.0	± 9.6 %
		Y	4.91	67.64	16.62		150.0	
		Z	4.81	67.41	16.35		150.0	
10117-CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	4.76	67.19	16.44	0.00	150.0	± 9.6 %
		Y	4.81	67.30	16.55		150.0	
		Z	4.72	67.12	16.30		150.0	
10118-CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.08	67.58	16.61	0.00	150.0	± 9.6 %
		Y	5.14	67.72	16.74		150.0	
		Z	5.01	67.43	16.43		150.0	
10119-CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	4.86	67.54	16.52	0.00	150.0	± 9.6 %
		Y	4.92	67.66	16.64		150.0	
		Z	4.82	67.43	16.37		150.0	
10140-CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.03	67.44	15.76	0.00	150.0	± 9.6 %
		Y	3.10	67.70	15.99		150.0	
		Z	2.98	67.18	15.52		150.0	
10141-CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.16	67.67	15.99	0.00	150.0	± 9.6 %
		Y	3.23	67.88	16.18		150.0	
		Z	3.11	67.44	15.76		150.0	
10142-CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	1.50	67.65	13.86	0.00	150.0	± 9.6 %
		Y	1.64	68.71	14.65		150.0	
		Z	1.40	66.66	13.21		150.0	
10143-CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	1.79	66.97	12.89	0.00	150.0	± 9.6 %
		Y	1.94	67.90	13.60		150.0	
		Z	1.68	66.15	12.29		150.0	
10144-CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	1.50	64.00	10.77	0.00	150.0	± 9.6 %
		Y	1.60	64.68	11.38		150.0	
		Z	1.43	63.53	10.33		150.0	
10145-CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	0.50	60.00	5.08	0.00	150.0	± 9.6 %
		Y	0.53	60.00	5.45		150.0	
		Z	0.49	60.00	4.93		150.0	
10146-CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	0.66	60.00	4.66	0.00	150.0	± 9.6 %
		Y	0.67	60.00	5.08		150.0	
		Z	0.67	60.00	4.44		150.0	
10147-CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	0.67	60.00	4.71	0.00	150.0	± 9.6 %
		Y	0.60	58.92	4.43		150.0	
		Z	0.67	60.00	4.48		150.0	

10149-CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.56	67.52	15.55	0.00	150.0	± 9.6 %
		Y	2.64	67.83	15.83		150.0	
		Z	2.51	67.16	15.25		150.0	
10150-CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	2.69	67.64	15.65	0.00	150.0	± 9.6 %
		Y	2.76	67.91	15.90		150.0	
		Z	2.63	67.32	15.36		150.0	
10151-CAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.73	86.59	24.67	3.98	65.0	± 9.6 %
		Y	9.80	86.53	24.79		65.0	
		Z	8.83	85.34	24.25		65.0	
10152-CAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	6.54	77.11	21.21	3.98	65.0	± 9.6 %
		Y	6.78	77.59	21.55		65.0	
		Z	6.11	76.24	20.80		65.0	
10153-CAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	7.17	78.82	22.30	3.98	65.0	± 9.6 %
		Y	7.34	79.00	22.49		65.0	
		Z	6.72	77.97	21.92		65.0	
10154-CAF	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	1.87	69.05	15.75	0.00	150.0	± 9.6 %
		Y	1.98	69.74	16.28		150.0	
		Z	1.77	68.14	15.17		150.0	
10155-CAF	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.28	68.74	15.39	0.00	150.0	± 9.6 %
		Y	2.36	69.12	15.74		150.0	
		Z	2.19	68.15	14.93		150.0	
10156-CAF	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.22	66.13	12.34	0.00	150.0	± 9.6 %
		Y	1.36	67.41	13.29		150.0	
		Z	1.14	65.20	11.69		150.0	
10157-CAF	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	1.22	63.09	9.61	0.00	150.0	± 9.6 %
		Y	1.33	63.90	10.34		150.0	
		Z	1.15	62.61	9.16		150.0	
10158-CAF	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.41	68.95	15.54	0.00	150.0	± 9.6 %
		Y	2.49	69.27	15.85		150.0	
		Z	2.32	68.37	15.09		150.0	
10159-CAF	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	1.25	63.14	9.66	0.00	150.0	± 9.6 %
		Y	1.36	63.97	10.39		150.0	
		Z	1.18	62.64	9.19		150.0	
10160-CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.40	68.97	16.11	0.00	150.0	± 9.6 %
		Y	2.50	69.46	16.49		150.0	
		Z	2.30	68.28	15.65		150.0	
10161-CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	2.56	67.57	15.39	0.00	150.0	± 9.6 %
		Y	2.63	67.87	15.67		150.0	
		Z	2.50	67.21	15.07		150.0	
10162-CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	2.66	67.86	15.56	0.00	150.0	± 9.6 %
		Y	2.74	68.13	15.82		150.0	
		Z	2.60	67.51	15.24		150.0	
10166-CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	2.73	67.85	18.46	3.01	150.0	± 9.6 %
		Y	2.78	68.27	19.13		150.0	
		Z	2.81	68.48	18.76		150.0	
10167-CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	3.00	69.93	18.59	3.01	150.0	± 9.6 %
		Y	2.96	70.40	19.40		150.0	
		Z	3.25	71.67	19.34		150.0	

10168-CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	3.36	72.56	20.25	3.01	150.0	± 9.6 %
		Y	3.26	72.65	20.86		150.0	
		Z	3.76	74.98	21.27		150.0	
10169-CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	2.24	65.89	17.49	3.01	150.0	± 9.6 %
		Y	2.17	65.69	17.95		150.0	
		Z	2.39	67.30	18.17		150.0	
10170-CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	2.58	69.82	19.29	3.01	150.0	± 9.6 %
		Y	2.31	68.87	19.55		150.0	
		Z	3.10	73.74	20.99		150.0	
10171-AAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	2.20	66.63	16.66	3.01	150.0	± 9.6 %
		Y	2.04	66.46	17.32		150.0	
		Z	2.49	69.12	17.74		150.0	
10172-CAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	6.57	90.42	29.01	6.02	65.0	± 9.6 %
		Y	6.70	92.44	30.69		65.0	
		Z	5.30	87.29	28.20		65.0	
10173-CAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	16.42	104.67	31.45	6.02	65.0	± 9.6 %
		Y	22.05	113.86	35.25		65.0	
		Z	42.83	124.16	36.91		65.0	
10174-CAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	10.59	95.52	28.04	6.02	65.0	± 9.6 %
		Y	12.26	101.14	30.88		65.0	
		Z	27.69	114.18	33.55		65.0	
10175-CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	2.22	65.67	17.27	3.01	150.0	± 9.6 %
		Y	2.15	65.53	17.77		150.0	
		Z	2.36	67.03	17.92		150.0	
10176-CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	2.58	69.84	19.30	3.01	150.0	± 9.6 %
		Y	2.31	68.89	19.56		150.0	
		Z	3.11	73.77	21.00		150.0	
10177-CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	2.23	65.75	17.33	3.01	150.0	± 9.6 %
		Y	2.16	65.60	17.82		150.0	
		Z	2.37	67.12	17.98		150.0	
10178-CAF	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	2.57	69.75	19.24	3.01	150.0	± 9.6 %
		Y	2.31	68.83	19.52		150.0	
		Z	3.09	73.64	20.92		150.0	
10179-CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	2.36	68.14	17.85	3.01	150.0	± 9.6 %
		Y	2.16	67.70	18.38		150.0	
		Z	2.76	71.27	19.21		150.0	
10180-CAF	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	2.20	66.62	16.64	3.01	150.0	± 9.6 %
		Y	2.04	66.46	17.31		150.0	
		Z	2.49	69.10	17.72		150.0	
10181-CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	2.22	65.74	17.33	3.01	150.0	± 9.6 %
		Y	2.16	65.59	17.81		150.0	
		Z	2.37	67.11	17.98		150.0	
10182-CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	2.57	69.73	19.23	3.01	150.0	± 9.6 %
		Y	2.30	68.81	19.50		150.0	
		Z	3.09	73.61	20.91		150.0	
10183-AAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	2.20	66.60	16.63	3.01	150.0	± 9.6 %
		Y	2.04	66.44	17.30		150.0	
		Z	2.48	69.08	17.71		150.0	

10184-CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	2.23	65.77	17.34	3.01	150.0	± 9.6 %
		Y	2.16	65.62	17.83		150.0	
		Z	2.38	67.14	18.00		150.0	
10185-CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	2.58	69.79	19.27	3.01	150.0	± 9.6 %
		Y	2.31	68.86	19.54		150.0	
		Z	3.10	73.69	20.95		150.0	
10186-AAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	2.20	66.64	16.66	3.01	150.0	± 9.6 %
		Y	2.04	66.48	17.33		150.0	
		Z	2.50	69.14	17.74		150.0	
10187-CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	2.24	65.85	17.43	3.01	150.0	± 9.6 %
		Y	2.17	65.68	17.91		150.0	
		Z	2.39	67.25	18.10		150.0	
10188-CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	2.63	70.23	19.57	3.01	150.0	± 9.6 %
		Y	2.35	69.19	19.79		150.0	
		Z	3.20	74.34	21.34		150.0	
10189-AAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	2.24	66.93	16.89	3.01	150.0	± 9.6 %
		Y	2.07	66.73	17.54		150.0	
		Z	2.55	69.53	18.02		150.0	
10193-CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.17	67.12	16.09	0.00	150.0	± 9.6 %
		Y	4.22	67.24	16.23		150.0	
		Z	4.13	67.06	15.95		150.0	
10194-CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.28	67.28	16.23	0.00	150.0	± 9.6 %
		Y	4.34	67.40	16.36		150.0	
		Z	4.24	67.20	16.08		150.0	
10195-CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.31	67.25	16.23	0.00	150.0	± 9.6 %
		Y	4.37	67.38	16.36		150.0	
		Z	4.26	67.17	16.08		150.0	
10196-CAC	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.14	67.06	16.05	0.00	150.0	± 9.6 %
		Y	4.20	67.18	16.19		150.0	
		Z	4.10	67.00	15.90		150.0	
10197-CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.29	67.27	16.23	0.00	150.0	± 9.6 %
		Y	4.35	67.39	16.37		150.0	
		Z	4.25	67.20	16.08		150.0	
10198-CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.30	67.24	16.22	0.00	150.0	± 9.6 %
		Y	4.35	67.37	16.36		150.0	
		Z	4.25	67.16	16.07		150.0	
10219-CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.10	67.13	16.04	0.00	150.0	± 9.6 %
		Y	4.16	67.25	16.18		150.0	
		Z	4.06	67.07	15.89		150.0	
10220-CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.28	67.23	16.22	0.00	150.0	± 9.6 %
		Y	4.34	67.35	16.35		150.0	
		Z	4.24	67.16	16.07		150.0	
10221-CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.32	67.21	16.22	0.00	150.0	± 9.6 %
		Y	4.38	67.33	16.35		150.0	
		Z	4.27	67.14	16.07		150.0	
10222-CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	4.74	67.21	16.43	0.00	150.0	± 9.6 %
		Y	4.79	67.33	16.55		150.0	
		Z	4.70	67.12	16.29		150.0	

10223- CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	4.94	67.26	16.45	0.00	150.0	± 9.6 %
		Y	5.00	67.37	16.57		150.0	
		Z	4.90	67.18	16.32		150.0	
10224- CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	4.78	67.35	16.43	0.00	150.0	± 9.6 %
		Y	4.83	67.47	16.55		150.0	
		Z	4.74	67.26	16.29		150.0	
10225- CAE	UMTS-FDD (HSPA+)	X	2.38	66.08	14.04	0.00	150.0	± 9.6 %
		Y	2.46	66.40	14.36		150.0	
		Z	2.33	65.77	13.68		150.0	
10226- CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	18.80	107.39	32.33	6.02	65.0	± 9.6 %
		Y	25.18	116.67	36.12		65.0	
		Z	56.86	129.79	38.42		65.0	
10227- CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	17.62	104.50	30.74	6.02	65.0	± 9.6 %
		Y	24.98	114.46	34.69		65.0	
		Z	53.65	126.02	36.59		65.0	
10228- CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	8.84	96.76	31.22	6.02	65.0	± 9.6 %
		Y	10.52	102.26	33.97		65.0	
		Z	8.68	97.67	31.80		65.0	
10229- CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	16.55	104.80	31.49	6.02	65.0	± 9.6 %
		Y	22.16	113.92	35.27		65.0	
		Z	43.51	124.44	36.98		65.0	
10230- CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	15.38	101.98	29.94	6.02	65.0	± 9.6 %
		Y	21.58	111.59	33.84		65.0	
		Z	40.32	120.70	35.19		65.0	
10231- CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	8.23	95.17	30.61	6.02	65.0	± 9.6 %
		Y	9.84	100.68	33.39		65.0	
		Z	8.03	95.88	31.12		65.0	
10232- CAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	16.51	104.77	31.48	6.02	65.0	± 9.6 %
		Y	22.12	113.91	35.27		65.0	
		Z	43.30	124.37	36.97		65.0	
10233- CAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	15.29	101.88	29.92	6.02	65.0	± 9.6 %
		Y	21.43	111.49	33.81		65.0	
		Z	39.84	120.51	35.15		65.0	
10234- CAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	7.86	94.06	30.11	6.02	65.0	± 9.6 %
		Y	9.46	99.67	32.94		65.0	
		Z	7.64	94.69	30.59		65.0	
10235- CAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	16.57	104.86	31.51	6.02	65.0	± 9.6 %
		Y	22.25	114.05	35.31		65.0	
		Z	43.57	124.50	37.01		65.0	
10236- CAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	15.56	102.14	29.98	6.02	65.0	± 9.6 %
		Y	22.01	111.92	33.92		65.0	
		Z	41.07	120.98	35.26		65.0	
10237- CAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.24	95.23	30.63	6.02	65.0	± 9.6 %
		Y	9.87	100.80	33.43		65.0	
		Z	8.02	95.91	31.14		65.0	
10238- CAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	16.49	104.76	31.48	6.02	65.0	± 9.6 %
		Y	22.11	113.92	35.28		65.0	
		Z	43.22	124.35	36.97		65.0	

10239-CAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	15.23	101.82	29.90	6.02	65.0	± 9.6 %
		Y	21.33	111.42	33.80		65.0	
		Z	39.55	120.41	35.13		65.0	
10240-CAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	8.24	95.24	30.63	6.02	65.0	± 9.6 %
		Y	9.87	100.81	33.44		65.0	
		Z	8.02	95.92	31.14		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	8.99	67.82	28.29	6.98	65.0	± 9.6 %
		Y	9.75	90.67	30.00		65.0	
		Z	9.34	89.67	29.13		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	7.89	85.15	27.21	6.98	65.0	± 9.6 %
		Y	8.15	86.79	28.48		65.0	
		Z	8.92	88.81	28.75		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	6.23	80.61	26.36	6.98	65.0	± 9.6 %
		Y	6.55	82.23	27.61		65.0	
		Z	5.44	78.21	25.48		65.0	
10244-CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	3.42	67.77	12.33	3.98	65.0	± 9.6 %
		Y	4.29	71.02	14.35		65.0	
		Z	3.28	67.61	12.06		65.0	
10245-CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	3.32	67.21	12.00	3.98	65.0	± 9.6 %
		Y	4.07	70.09	13.87		65.0	
		Z	3.17	66.99	11.70		65.0	
10246-CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	4.43	73.96	15.64	3.98	65.0	± 9.6 %
		Y	5.08	75.78	16.72		65.0	
		Z	3.85	72.56	14.95		65.0	
10247-CAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	4.99	72.28	15.77	3.98	65.0	± 9.6 %
		Y	4.91	73.13	16.39		65.0	
		Z	4.19	71.34	15.21		65.0	
10248-CAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	4.34	71.14	15.26	3.98	65.0	± 9.6 %
		Y	4.65	72.00	15.89		65.0	
		Z	3.96	70.19	14.69		65.0	
10249-CAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	10.92	88.36	22.53	3.98	65.0	± 9.6 %
		Y	10.64	88.09	22.75		65.0	
		Z	9.25	86.32	21.79		65.0	
10250-CAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	7.53	81.41	22.33	3.98	65.0	± 9.6 %
		Y	7.46	80.99	22.30		65.0	
		Z	6.98	80.48	21.90		65.0	
10251-CAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	6.21	76.79	20.02	3.98	65.0	± 9.6 %
		Y	6.42	77.16	20.35		65.0	
		Z	5.76	75.88	19.56		65.0	
10252-CAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	13.32	93.66	26.46	3.98	65.0	± 9.6 %
		Y	12.73	92.76	26.36		65.0	
		Z	11.46	91.61	25.80		65.0	
10253-CAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	6.41	76.60	20.76	3.98	65.0	± 9.6 %
		Y	6.65	77.06	21.12		65.0	
		Z	6.00	75.76	20.37		65.0	
10254-CAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	6.93	77.96	21.66	3.98	65.0	± 9.6 %
		Y	7.09	78.16	21.87		65.0	
		Z	6.50	77.15	21.27		65.0	

10255-CAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	9.17	85.70	24.40	3.98	65.0	± 9.6 %
		Y	9.28	85.72	24.56		65.0	
		Z	8.31	84.42	23.94		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	2.33	63.37	8.84	3.98	65.0	± 9.6 %
		Y	2.70	65.07	10.21		65.0	
		Z	2.17	63.01	8.43		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	2.30	63.01	8.53	3.98	65.0	± 9.6 %
		Y	2.62	64.47	9.78		65.0	
		Z	2.14	62.65	8.12		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	2.37	65.48	10.54	3.98	65.0	± 9.6 %
		Y	2.73	66.98	11.62		65.0	
		Z	2.13	64.74	10.00		65.0	
10259-CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	5.73	75.91	18.25	3.98	65.0	± 9.6 %
		Y	5.92	76.29	18.63		65.0	
		Z	5.25	74.96	17.74		65.0	
10260-CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	5.61	75.26	17.97	3.98	65.0	± 9.6 %
		Y	5.82	75.68	18.36		65.0	
		Z	5.16	74.34	17.46		65.0	
10261-CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	11.22	89.48	23.72	3.98	65.0	± 9.6 %
		Y	10.83	88.93	23.80		65.0	
		Z	9.64	87.55	23.03		65.0	
10262-CAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	7.47	81.24	22.23	3.98	65.0	± 9.6 %
		Y	7.42	80.85	22.22		65.0	
		Z	6.92	80.30	21.81		65.0	
10263-CAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	6.20	76.77	20.02	3.98	65.0	± 9.6 %
		Y	6.41	77.14	20.34		65.0	
		Z	5.75	75.86	19.56		65.0	
10264-CAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	12.97	93.14	26.27	3.98	65.0	± 9.6 %
		Y	12.47	92.36	26.20		65.0	
		Z	11.18	91.12	25.61		65.0	
10265-CAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	6.54	77.12	21.22	3.98	65.0	± 9.6 %
		Y	6.78	77.60	21.56		65.0	
		Z	6.11	76.24	20.81		65.0	
10266-CAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	7.17	78.80	22.29	3.98	65.0	± 9.6 %
		Y	7.33	78.99	22.48		65.0	
		Z	6.72	77.95	21.91		65.0	
10267-CAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.68	86.48	24.63	3.98	65.0	± 9.6 %
		Y	9.76	86.44	24.75		65.0	
		Z	8.79	85.24	24.21		65.0	
10268-CAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	7.07	76.76	21.77	3.98	65.0	± 9.6 %
		Y	7.29	77.15	22.04		65.0	
		Z	6.70	76.06	21.43		65.0	
10269-CAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	7.03	76.29	21.59	3.98	65.0	± 9.6 %
		Y	7.24	76.69	21.87		65.0	
		Z	6.68	75.64	21.27		65.0	
10270-CAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	8.04	80.94	22.90	3.98	65.0	± 9.6 %
		Y	8.18	81.04	23.04		65.0	
		Z	7.56	80.22	22.63		65.0	

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.26	66.83	14.19	0.00	150.0	± 9.6 %
		Y	2.35	67.29	14.60		150.0	
		Z	2.19	66.41	13.80		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.38	68.12	14.71	0.00	150.0	± 9.6 %
		Y	1.51	69.22	15.51		150.0	
		Z	1.30	67.09	14.07		150.0	
10277-CAA	PHS (QPSK)	X	2.05	61.14	6.20	9.03	50.0	± 9.6 %
		Y	2.35	62.20	7.24		50.0	
		Z	1.85	60.65	5.69		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Roll-off 0.5)	X	3.29	66.09	10.86	9.03	50.0	± 9.6 %
		Y	3.79	67.79	12.16		50.0	
		Z	3.05	65.55	10.36		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Roll-off 0.38)	X	3.33	68.19	10.97	9.03	50.0	± 9.6 %
		Y	3.82	67.86	12.26		50.0	
		Z	3.09	65.64	10.46		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	0.45	60.00	5.81	0.00	150.0	± 9.6 %
		Y	0.54	61.10	6.94		150.0	
		Z	0.44	60.00	5.71		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.32	60.00	5.40	0.00	150.0	± 9.6 %
		Y	0.36	60.31	6.19		150.0	
		Z	0.32	60.00	5.37		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	0.31	60.00	5.66	0.00	150.0	± 9.6 %
		Y	0.42	62.09	7.53		150.0	
		Z	0.31	60.00	5.64		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	0.40	61.64	7.04	0.00	150.0	± 9.6 %
		Y	0.72	66.90	10.33		150.0	
		Z	0.39	61.43	6.90		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	100.00	115.65	29.78	9.03	50.0	± 9.6 %
		Y	100.00	117.45	30.86		50.0	
		Z	100.00	115.39	29.51		50.0	
10297-AAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.36	69.57	16.44	0.00	150.0	± 9.6 %
		Y	2.47	70.10	16.83		150.0	
		Z	2.27	68.85	15.99		150.0	
10298-AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	0.67	61.00	7.40	0.00	150.0	± 9.6 %
		Y	0.76	61.94	8.33		150.0	
		Z	0.64	60.66	7.04		150.0	
10299-AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	0.84	60.11	6.12	0.00	150.0	± 9.6 %
		Y	0.94	61.36	7.42		150.0	
		Z	0.84	60.07	5.83		150.0	
10300-AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	0.73	59.08	4.84	0.00	150.0	± 9.6 %
		Y	0.79	59.77	5.75		150.0	
		Z	0.72	58.92	4.50		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	4.80	68.05	17.95	4.17	80.0	± 9.6 %
		Y	5.02	68.71	18.39		80.0	
		Z	4.55	67.08	17.32		80.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	5.05	67.52	18.12	4.96	80.0	± 9.6 %
		Y	5.33	68.60	18.81		80.0	
		Z	4.89	67.04	17.75		80.0	

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	4.87	67.42	17.96	4.96	80.0	± 9.6 %
		Y	5.17	68.58	18.70		80.0	
		Z	4.71	66.92	17.58		80.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.66	67.21	17.45	4.17	80.0	± 9.6 %
		Y	4.92	68.23	18.08		80.0	
		Z	4.51	66.75	17.09		80.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	5.30	72.82	20.07	6.02	50.0	± 9.6 %
		Y	6.32	76.30	21.85		50.0	
		Z	4.76	70.90	19.01		50.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	5.08	70.37	19.67	6.02	50.0	± 9.6 %
		Y	5.60	72.42	20.88		50.0	
		Z	4.78	69.24	18.95		50.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	5.03	70.60	19.63	6.02	50.0	± 9.6 %
		Y	5.59	72.82	20.90		50.0	
		Z	4.70	69.37	18.87		50.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	5.07	71.06	19.88	6.02	50.0	± 9.6 %
		Y	5.69	73.45	21.23		50.0	
		Z	4.72	69.74	19.09		50.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	5.09	70.41	19.77	6.02	50.0	± 9.6 %
		Y	5.60	72.49	20.99		50.0	
		Z	4.78	69.29	19.05		50.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	5.08	70.63	19.76	6.02	50.0	± 9.6 %
		Y	5.64	72.78	21.01		50.0	
		Z	4.77	69.45	19.03		50.0	
10311-AAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	2.71	68.65	16.12	0.00	150.0	± 9.6 %
		Y	2.82	69.11	16.45		150.0	
		Z	2.61	68.03	15.74		150.0	
10313-AAA	IDEN 1:3	X	10.35	86.29	20.64	6.99	70.0	± 9.6 %
		Y	11.44	88.28	21.75		70.0	
		Z	11.02	88.24	21.45		70.0	
10314-AAA	IDEN 1:6	X	62.09	120.10	33.12	10.00	30.0	± 9.6 %
		Y	24.40	106.12	30.15		30.0	
		Z	80.12	126.18	34.93		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.03	64.62	15.28	0.17	150.0	± 9.6 %
		Y	1.09	65.04	15.69		150.0	
		Z	1.02	64.04	14.75		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.22	67.15	16.29	0.17	150.0	± 9.6 %
		Y	4.28	67.28	16.43		150.0	
		Z	4.18	67.07	16.13		150.0	
10317-AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.22	67.15	16.29	0.17	150.0	± 9.6 %
		Y	4.28	67.28	16.43		150.0	
		Z	4.18	67.07	16.13		150.0	
10400-AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.21	67.17	16.16	0.00	150.0	± 9.6 %
		Y	4.27	67.33	16.31		150.0	
		Z	4.16	67.06	15.98		150.0	
10401-AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	4.99	67.22	16.39	0.00	150.0	± 9.6 %
		Y	5.03	67.29	16.49		150.0	
		Z	5.00	67.34	16.35		150.0	

10402-AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.31	67.53	16.47	0.00	150.0	± 9.6 %
		Y	5.36	67.64	16.59		150.0	
		Z	5.27	67.47	16.35		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	0.45	60.00	5.81	0.00	115.0	± 9.6 %
		Y	0.54	61.10	6.94		115.0	
		Z	0.44	60.00	5.71		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	0.45	60.00	5.81	0.00	115.0	± 9.6 %
		Y	0.54	61.10	6.94		115.0	
		Z	0.44	60.00	5.71		115.0	
10406-AAB	CDMA2000, RC3, SC32, SCH0, Full Rate	X	100.00	115.64	25.77	0.00	100.0	± 9.6 %
		Y	100.00	128.79	31.14		100.0	
		Z	100.00	106.07	21.60		100.0	
10410-AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	X	100.00	125.78	31.11	3.23	80.0	± 9.6 %
		Y	100.00	134.61	35.21		80.0	
		Z	100.00	126.61	31.37		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	0.93	63.35	14.45	0.00	150.0	± 9.6 %
		Y	0.98	63.79	14.89		150.0	
		Z	0.93	62.96	14.01		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.15	67.03	16.15	0.00	150.0	± 9.6 %
		Y	4.21	67.15	16.28		150.0	
		Z	4.11	66.96	15.99		150.0	
10417-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.15	67.03	16.15	0.00	150.0	± 9.6 %
		Y	4.21	67.15	16.28		150.0	
		Z	4.11	66.96	15.99		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.14	67.26	16.23	0.00	150.0	± 9.6 %
		Y	4.20	67.39	16.37		150.0	
		Z	4.10	67.18	16.07		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.16	67.18	16.21	0.00	150.0	± 9.6 %
		Y	4.22	67.31	16.34		150.0	
		Z	4.12	67.11	16.05		150.0	
10422-AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.26	67.14	16.22	0.00	150.0	± 9.6 %
		Y	4.32	67.27	16.35		150.0	
		Z	4.22	67.07	16.07		150.0	
10423-AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.36	67.37	16.29	0.00	150.0	± 9.6 %
		Y	4.42	67.49	16.43		150.0	
		Z	4.31	67.29	16.14		150.0	
10424-AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.29	67.30	16.26	0.00	150.0	± 9.6 %
		Y	4.35	67.43	16.40		150.0	
		Z	4.25	67.21	16.11		150.0	
10425-AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	4.96	67.44	16.53	0.00	150.0	± 9.6 %
		Y	5.01	67.55	16.65		150.0	
		Z	4.91	67.33	16.37		150.0	
10426-AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.01	67.66	16.64	0.00	150.0	± 9.6 %
		Y	5.07	67.78	16.75		150.0	
		Z	4.96	67.54	16.48		150.0	

10427-AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	4.95	67.36	16.48	0.00	150.0	± 9.6 %
		Y	5.01	67.47	16.60		150.0	
		Z	4.91	67.28	16.35		150.0	
10430-AAC	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.06	73.07	17.88	0.00	150.0	± 9.6 %
		Y	3.94	72.28	17.62		150.0	
		Z	3.97	72.74	17.53		150.0	
10431-AAC	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	3.70	67.58	15.79	0.00	150.0	± 9.6 %
		Y	3.77	67.74	15.97		150.0	
		Z	3.64	67.41	15.56		150.0	
10432-AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.05	67.44	16.13	0.00	150.0	± 9.6 %
		Y	4.11	67.58	16.28		150.0	
		Z	4.00	67.33	15.96		150.0	
10433-AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.31	67.34	16.29	0.00	150.0	± 9.6 %
		Y	4.37	67.47	16.42		150.0	
		Z	4.27	67.26	16.14		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	3.89	72.67	16.88	0.00	150.0	± 9.6 %
		Y	3.81	72.16	16.78		150.0	
		Z	3.70	71.97	16.35		150.0	
10435-AAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	125.45	30.96	3.23	80.0	± 9.6 %
		Y	100.00	134.26	35.05		80.0	
		Z	100.00	126.27	31.22		80.0	
10447-AAC	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	2.79	66.54	13.72	0.00	150.0	± 9.6 %
		Y	2.89	66.90	14.06		150.0	
		Z	2.70	66.17	13.34		150.0	
10448-AAC	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.58	67.39	15.68	0.00	150.0	± 9.6 %
		Y	3.65	67.57	15.87		150.0	
		Z	3.53	67.23	15.46		150.0	
10449-AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	3.91	67.27	16.04	0.00	150.0	± 9.6 %
		Y	3.97	67.41	16.19		150.0	
		Z	3.86	67.16	15.86		150.0	
10450-AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.14	67.12	16.15	0.00	150.0	± 9.6 %
		Y	4.20	67.25	16.28		150.0	
		Z	4.10	67.04	15.99		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	2.45	65.46	12.35	0.00	150.0	± 9.6 %
		Y	2.56	65.93	12.76		150.0	
		Z	2.35	65.03	11.91		150.0	
10456-AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99% duty cycle)	X	6.45	69.52	17.52	0.00	150.0	± 9.6 %
		Y	6.40	69.35	17.50		150.0	
		Z	6.48	69.67	17.50		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.58	65.94	15.92	0.00	150.0	± 9.6 %
		Y	3.63	66.05	16.05		150.0	
		Z	3.57	65.91	15.77		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	2.65	67.20	13.29	0.00	150.0	± 9.6 %
		Y	2.77	67.71	13.74		150.0	
		Z	2.45	66.19	12.51		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	4.33	68.48	16.53	0.00	150.0	± 9.6 %
		Y	4.22	67.81	16.25		150.0	
		Z	4.21	68.13	16.10		150.0	

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.82	69.31	15.66	0.00	150.0	± 9.6 %
		Y	0.95	71.24	16.99		150.0	
		Z	0.74	67.22	14.49		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	131.81	33.89	3.29	80.0	± 9.6 %
		Y	100.00	142.15	38.65		80.0	
		Z	100.00	134.02	35.12		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.90	62.21	8.81	3.23	80.0	± 9.6 %
		Y	100.00	110.30	23.82		80.0	
		Z	0.87	62.36	8.52		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	7.04	3.23	80.0	± 9.6 %
		Y	1.91	69.61	11.91		80.0	
		Z	0.66	60.00	6.66		80.0	
10464-AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	127.95	31.95	3.23	80.0	± 9.6 %
		Y	100.00	139.33	37.13		80.0	
		Z	100.00	131.02	33.15		80.0	
10465-AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.82	61.38	8.35	3.23	80.0	± 9.6 %
		Y	100.00	109.29	23.38		80.0	
		Z	0.77	61.39	8.02		80.0	
10466-AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	7.00	3.23	80.0	± 9.6 %
		Y	1.22	65.67	10.37		80.0	
		Z	0.67	60.00	6.62		80.0	
10467-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	128.47	32.18	3.23	80.0	± 9.6 %
		Y	100.00	139.85	37.36		80.0	
		Z	100.00	131.59	33.40		80.0	
10468-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.85	61.72	8.54	3.23	80.0	± 9.6 %
		Y	100.00	109.79	23.59		80.0	
		Z	0.81	61.80	8.24		80.0	
10469-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	7.00	3.23	80.0	± 9.6 %
		Y	1.26	65.97	10.50		80.0	
		Z	0.66	60.00	6.63		80.0	
10470-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	128.50	32.19	3.23	80.0	± 9.6 %
		Y	100.00	139.93	37.39		80.0	
		Z	100.00	131.64	33.41		80.0	
10471-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.84	61.66	8.50	3.23	80.0	± 9.6 %
		Y	100.00	109.89	23.54		80.0	
		Z	0.80	61.73	8.19		80.0	
10472-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	6.99	3.23	80.0	± 9.6 %
		Y	1.24	65.80	10.41		80.0	
		Z	0.66	60.00	6.61		80.0	
10473-AAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	128.47	32.17	3.23	80.0	± 9.6 %
		Y	100.00	139.91	37.37		80.0	
		Z	100.00	131.60	33.40		80.0	
10474-AAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.84	61.63	8.49	3.23	80.0	± 9.6 %
		Y	100.00	109.69	23.54		80.0	
		Z	0.80	61.70	8.18		80.0	
10475-AAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	6.99	3.23	80.0	± 9.6 %
		Y	1.23	65.75	10.39		80.0	
		Z	0.66	60.00	6.61		80.0	

10477-AAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.82	61.39	8.34	3.23	80.0	± 9.6 %
		Y	100.00	109.29	23.36		80.0	
		Z	0.77	61.40	8.01		80.0	
10478-AAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.71	60.00	6.98	3.23	80.0	± 9.6 %
		Y	1.20	65.55	10.30		80.0	
		Z	0.66	60.00	6.60		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	125.63	32.26	3.23	80.0	± 9.6 %
		Y	100.00	131.75	35.27		80.0	
		Z	100.00	127.84	33.13		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	19.63	91.54	20.27	3.23	80.0	± 9.6 %
		Y	100.00	115.20	27.34		80.0	
		Z	100.00	108.55	24.07		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.49	72.42	13.95	3.23	80.0	± 9.6 %
		Y	100.00	111.30	25.48		80.0	
		Z	5.91	77.84	15.53		80.0	
10482-AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.67	65.33	11.27	2.23	80.0	± 9.6 %
		Y	2.30	68.66	13.07		80.0	
		Z	1.38	63.63	10.34		80.0	
10483-AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.25	60.06	7.80	2.23	80.0	± 9.6 %
		Y	1.97	64.67	10.70		80.0	
		Z	1.19	60.00	7.59		80.0	
10484-AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.27	60.00	7.74	2.23	80.0	± 9.6 %
		Y	1.80	63.53	10.14		80.0	
		Z	1.22	60.00	7.56		80.0	
10485-AAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.81	81.43	19.42	2.23	80.0	± 9.6 %
		Y	6.11	82.25	20.03		80.0	
		Z	4.06	77.04	17.81		80.0	
10486-AAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.34	66.39	12.56	2.23	80.0	± 9.6 %
		Y	2.71	68.04	13.57		80.0	
		Z	2.02	64.93	11.73		80.0	
10487-AAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.25	65.64	12.18	2.23	80.0	± 9.6 %
		Y	2.60	67.18	13.15		80.0	
		Z	1.96	64.31	11.39		80.0	
10488-AAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.09	80.09	21.16	2.23	80.0	± 9.6 %
		Y	5.16	80.10	21.33		80.0	
		Z	4.19	77.34	20.09		80.0	
10489-AAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.01	73.05	18.07	2.23	80.0	± 9.6 %
		Y	4.07	73.07	18.23		80.0	
		Z	3.64	71.81	17.45		80.0	
10490-AAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.98	72.48	17.82	2.23	80.0	± 9.6 %
		Y	4.06	72.53	17.99		80.0	
		Z	3.63	71.32	17.22		80.0	
10491-AAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.41	75.53	19.94	2.23	80.0	± 9.6 %
		Y	4.53	75.73	20.14		80.0	
		Z	3.93	73.90	19.24		80.0	
10492-AAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.05	71.20	18.08	2.23	80.0	± 9.6 %
		Y	4.14	71.29	18.22		80.0	
		Z	3.79	70.37	17.63		80.0	

10493-AAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.07	70.90	17.94	2.23	80.0	± 9.6 %
		Y	4.15	71.00	18.07		80.0	
		Z	3.82	70.11	17.49		80.0	
10494-AAE	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.91	77.32	20.61	2.23	80.0	± 9.6 %
		Y	5.04	77.50	20.80		80.0	
		Z	4.30	75.42	19.85		80.0	
10495-AAE	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.09	71.47	18.41	2.23	80.0	± 9.6 %
		Y	4.17	71.55	18.53		80.0	
		Z	3.83	70.60	17.95		80.0	
10496-AAE	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.13	71.08	18.26	2.23	80.0	± 9.6 %
		Y	4.21	71.17	18.38		80.0	
		Z	3.88	70.29	17.84		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	0.96	60.00	6.99	2.23	80.0	± 9.6 %
		Y	0.98	60.00	7.40		80.0	
		Z	0.92	60.00	6.79		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.14	60.00	5.73	2.23	80.0	± 9.6 %
		Y	1.15	60.00	6.09		80.0	
		Z	1.11	60.00	5.47		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.17	60.00	5.57	2.23	80.0	± 9.6 %
		Y	1.18	60.00	5.92		80.0	
		Z	1.15	60.00	5.29		80.0	
10500-AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.67	81.49	20.32	2.23	80.0	± 9.6 %
		Y	5.74	81.66	20.65		80.0	
		Z	4.28	77.81	18.94		80.0	
10501-AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.25	70.19	15.15	2.23	80.0	± 9.6 %
		Y	3.52	71.13	15.78		80.0	
		Z	2.82	68.60	14.33		80.0	
10502-AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.16	69.49	14.76	2.23	80.0	± 9.6 %
		Y	3.44	70.48	15.41		80.0	
		Z	2.76	67.99	13.96		80.0	
10503-AAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.96	79.69	20.99	2.23	80.0	± 9.6 %
		Y	5.06	79.77	21.19		80.0	
		Z	4.10	76.98	19.93		80.0	
10504-AAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.96	72.85	17.97	2.23	80.0	± 9.6 %
		Y	4.04	72.91	18.14		80.0	
		Z	3.60	71.62	17.35		80.0	
10505-AAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.94	72.31	17.73	2.23	80.0	± 9.6 %
		Y	4.03	72.40	17.91		80.0	
		Z	3.60	71.15	17.13		80.0	
10506-AAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.85	77.09	20.51	2.23	80.0	± 9.6 %
		Y	4.98	77.30	20.71		80.0	
		Z	4.25	75.22	19.75		80.0	
10507-AAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.07	71.38	18.36	2.23	80.0	± 9.6 %
		Y	4.16	71.48	18.49		80.0	
		Z	3.81	70.52	17.90		80.0	

10508-AAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.11	70.96	18.20	2.23	80.0	± 9.6 %
		Y	4.19	71.08	18.33		80.0	
		Z	3.86	70.19	17.78		80.0	
10509-AAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.80	74.18	19.50	2.23	80.0	± 9.6 %
		Y	4.92	74.37	19.67		80.0	
		Z	4.40	73.00	18.99		80.0	
10510-AAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.38	70.21	18.17	2.23	80.0	± 9.6 %
		Y	4.48	70.36	18.31		80.0	
		Z	4.17	69.55	17.82		80.0	
10511-AAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.44	69.97	18.09	2.23	80.0	± 9.6 %
		Y	4.54	70.12	18.23		80.0	
		Z	4.23	69.36	17.75		80.0	
10512-AAE	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.12	75.85	20.03	2.23	80.0	± 9.6 %
		Y	5.25	76.05	20.20		80.0	
		Z	4.61	74.40	19.43		80.0	
10513-AAE	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.29	70.38	18.28	2.23	80.0	± 9.6 %
		Y	4.39	70.55	18.43		80.0	
		Z	4.07	69.67	17.91		80.0	
10514-AAE	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.31	69.92	18.12	2.23	80.0	± 9.6 %
		Y	4.40	70.08	18.26		80.0	
		Z	4.10	69.28	17.77		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.89	63.54	14.50	0.00	150.0	± 9.6 %
		Y	0.94	64.02	14.97		150.0	
		Z	0.89	63.10	14.03		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.63	73.54	17.73	0.00	150.0	± 9.6 %
		Y	0.85	77.87	20.24		150.0	
		Z	0.50	68.63	15.41		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.73	65.48	15.07	0.00	150.0	± 9.6 %
		Y	0.80	66.38	15.85		150.0	
		Z	0.72	64.47	14.31		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.14	67.16	16.15	0.00	150.0	± 9.6 %
		Y	4.20	67.29	16.29		150.0	
		Z	4.10	67.09	16.00		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.26	67.30	16.23	0.00	150.0	± 9.6 %
		Y	4.32	67.42	16.36		150.0	
		Z	4.22	67.22	16.07		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.12	67.21	16.14	0.00	150.0	± 9.6 %
		Y	4.18	67.34	16.28		150.0	
		Z	4.08	67.13	15.98		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.05	67.13	16.10	0.00	150.0	± 9.6 %
		Y	4.11	67.26	16.24		150.0	
		Z	4.01	67.03	15.93		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.08	67.17	16.14	0.00	150.0	± 9.6 %
		Y	4.14	67.31	16.28		150.0	
		Z	4.03	67.05	15.96		150.0	

10523-AAB	IEEE 802.11a/n WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.05	67.38	16.19	0.00	150.0	± 9.6 %
		Y	4.12	67.52	16.33		150.0	
		Z	4.01	67.29	16.03		150.0	
10524-AAB	IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.05	67.25	16.21	0.00	150.0	± 9.6 %
		Y	4.11	67.39	16.35		150.0	
		Z	4.00	67.15	16.04		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.12	66.42	15.87	0.00	150.0	± 9.6 %
		Y	4.18	66.55	16.00		150.0	
		Z	4.08	66.34	15.71		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.20	66.62	15.96	0.00	150.0	± 9.6 %
		Y	4.27	66.76	16.09		150.0	
		Z	4.15	66.52	15.79		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.15	66.61	15.90	0.00	150.0	± 9.6 %
		Y	4.21	66.75	16.04		150.0	
		Z	4.10	66.51	15.74		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.16	66.61	15.93	0.00	150.0	± 9.6 %
		Y	4.22	66.75	16.07		150.0	
		Z	4.11	66.51	15.76		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.16	66.61	15.93	0.00	150.0	± 9.6 %
		Y	4.22	66.75	16.07		150.0	
		Z	4.11	66.51	15.76		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.11	66.58	15.88	0.00	150.0	± 9.6 %
		Y	4.17	66.72	16.02		150.0	
		Z	4.06	66.47	15.71		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.01	66.45	15.81	0.00	150.0	± 9.6 %
		Y	4.07	66.59	15.95		150.0	
		Z	3.96	66.35	15.65		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.16	66.72	15.94	0.00	150.0	± 9.6 %
		Y	4.22	66.86	16.08		150.0	
		Z	4.11	66.61	15.77		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.75	66.52	16.05	0.00	150.0	± 9.6 %
		Y	4.81	66.64	16.16		150.0	
		Z	4.71	66.44	15.91		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	4.78	66.63	16.11	0.00	150.0	± 9.6 %
		Y	4.84	66.75	16.22		150.0	
		Z	4.74	66.54	15.96		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.68	66.60	16.07	0.00	150.0	± 9.6 %
		Y	4.73	66.73	16.19		150.0	
		Z	4.63	66.52	15.93		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.77	66.73	16.14	0.00	150.0	± 9.6 %
		Y	4.83	66.85	16.25		150.0	
		Z	4.72	66.63	15.99		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	4.79	66.55	16.08	0.00	150.0	± 9.6 %
		Y	4.85	66.67	16.20		150.0	
		Z	4.75	66.46	15.94		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.73	66.52	16.09	0.00	150.0	± 9.6 %
		Y	4.79	66.64	16.21		150.0	
		Z	4.69	66.43	15.95		150.0	

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.73	66.49	16.05	0.00	150.0	± 9.6 %
		Y	4.79	66.60	16.16		150.0	
		Z	4.69	66.41	15.91		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	4.87	66.56	16.10	0.00	150.0	± 9.6 %
		Y	4.93	66.68	16.22		150.0	
		Z	4.83	66.49	15.97		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	4.95	66.68	16.20	0.00	150.0	± 9.6 %
		Y	5.00	66.80	16.31		150.0	
		Z	4.89	66.58	16.05		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.13	66.53	16.04	0.00	150.0	± 9.6 %
		Y	5.19	66.64	16.15		150.0	
		Z	5.10	66.46	15.91		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.32	67.06	16.27	0.00	150.0	± 9.6 %
		Y	5.37	67.18	16.39		150.0	
		Z	5.26	66.93	16.12		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.16	66.63	16.06	0.00	150.0	± 9.6 %
		Y	5.21	66.74	16.17		150.0	
		Z	5.12	66.56	15.93		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.32	67.06	16.27	0.00	150.0	± 9.6 %
		Y	5.37	67.16	16.38		150.0	
		Z	5.27	66.95	16.13		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.33	67.26	16.36	0.00	150.0	± 9.6 %
		Y	5.39	67.41	16.48		150.0	
		Z	5.26	67.08	16.18		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.31	67.19	16.36	0.00	150.0	± 9.6 %
		Y	5.36	67.30	16.47		150.0	
		Z	5.26	67.08	16.21		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.13	66.55	16.00	0.00	150.0	± 9.6 %
		Y	5.18	66.66	16.11		150.0	
		Z	5.09	66.49	15.88		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.13	66.67	16.05	0.00	150.0	± 9.6 %
		Y	5.19	66.78	16.16		150.0	
		Z	5.09	66.61	15.93		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.17	66.57	16.03	0.00	150.0	± 9.6 %
		Y	5.23	66.69	16.14		150.0	
		Z	5.14	66.52	15.91		150.0	
10554-AAB	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.59	66.85	16.12	0.00	150.0	± 9.6 %
		Y	5.64	66.96	16.23		150.0	
		Z	5.55	66.79	16.00		150.0	
10555-AAB	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.66	67.06	16.21	0.00	150.0	± 9.6 %
		Y	5.71	67.17	16.32		150.0	
		Z	5.62	66.97	16.09		150.0	
10556-AAB	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.73	67.28	16.32	0.00	150.0	± 9.6 %
		Y	5.79	67.40	16.43		150.0	
		Z	5.68	67.17	16.18		150.0	
10557-AAB	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.65	67.02	16.20	0.00	150.0	± 9.6 %
		Y	5.70	67.14	16.31		150.0	
		Z	5.61	66.94	16.08		150.0	

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.62	66.96	16.19	0.00	150.0	± 9.6 %
		Y	5.67	67.08	16.30		150.0	
		Z	5.57	66.88	16.06		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.65	66.95	16.22	0.00	150.0	± 9.6 %
		Y	5.71	67.07	16.33		150.0	
		Z	5.61	66.87	16.10		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.60	66.94	16.24	0.00	150.0	± 9.6 %
		Y	5.65	67.07	16.36		150.0	
		Z	5.55	66.86	16.11		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.63	67.07	16.31	0.00	150.0	± 9.6 %
		Y	5.69	67.19	16.42		150.0	
		Z	5.59	66.99	16.18		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.78	67.23	16.36	0.00	150.0	± 9.6 %
		Y	5.83	67.32	16.46		150.0	
		Z	5.76	67.23	16.28		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.46	67.18	16.31	0.46	150.0	± 9.6 %
		Y	4.52	67.32	16.46		150.0	
		Z	4.42	67.11	16.17		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.63	67.58	16.63	0.46	150.0	± 9.6 %
		Y	4.69	67.69	16.75		150.0	
		Z	4.59	67.52	16.49		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.47	67.37	16.42	0.46	150.0	± 9.6 %
		Y	4.54	67.50	16.57		150.0	
		Z	4.43	67.29	16.28		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.52	67.79	16.83	0.46	150.0	± 9.6 %
		Y	4.57	67.86	16.92		150.0	
		Z	4.48	67.72	16.69		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.34	66.96	16.07	0.46	150.0	± 9.6 %
		Y	4.41	67.16	16.26		150.0	
		Z	4.29	66.85	15.90		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.53	68.16	17.05	0.46	150.0	± 9.6 %
		Y	4.58	68.21	17.13		150.0	
		Z	4.49	68.10	16.91		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.49	67.82	16.87	0.46	150.0	± 9.6 %
		Y	4.55	67.90	16.97		150.0	
		Z	4.45	67.74	16.72		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.16	65.70	15.86	0.46	130.0	± 9.6 %
		Y	1.22	66.16	16.29		130.0	
		Z	1.13	64.93	15.27		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.18	66.44	16.31	0.46	130.0	± 9.6 %
		Y	1.24	66.88	16.72		130.0	
		Z	1.14	65.55	15.67		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	15.28	116.08	30.90	0.46	130.0	± 9.6 %
		Y	37.29	132.13	35.54		130.0	
		Z	2.39	87.75	23.05		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.45	74.49	20.17	0.46	130.0	± 9.6 %
		Y	1.51	74.69	20.49		130.0	
		Z	1.27	71.67	18.75		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.27	67.06	16.39	0.46	130.0	± 9.6 %
		Y	4.33	67.20	16.53		130.0	
		Z	4.23	66.99	16.23		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.31	67.33	16.51	0.46	130.0	± 9.6 %
		Y	4.37	67.44	16.64		130.0	
		Z	4.26	67.25	16.36		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.44	67.51	16.64	0.46	130.0	± 9.6 %
		Y	4.50	67.62	16.76		130.0	
		Z	4.39	67.44	16.49		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.36	67.69	16.78	0.46	130.0	± 9.6 %
		Y	4.41	67.76	16.87		130.0	
		Z	4.32	67.61	16.63		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.10	66.72	15.92	0.46	130.0	± 9.6 %
		Y	4.17	66.93	16.12		130.0	
		Z	4.05	66.61	15.75		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.11	66.69	15.89	0.46	130.0	± 9.6 %
		Y	4.18	66.91	16.09		130.0	
		Z	4.05	66.55	15.69		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.30	67.88	16.81	0.46	130.0	± 9.6 %
		Y	4.35	67.96	16.92		130.0	
		Z	4.25	67.78	16.65		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.01	66.47	15.69	0.46	130.0	± 9.6 %
		Y	4.09	66.72	15.92		130.0	
		Z	3.96	66.34	15.50		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.27	67.06	16.39	0.46	130.0	± 9.6 %
		Y	4.33	67.20	16.53		130.0	
		Z	4.23	66.99	16.23		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.31	67.33	16.51	0.46	130.0	± 9.6 %
		Y	4.37	67.44	16.64		130.0	
		Z	4.26	67.25	16.36		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.44	67.51	16.64	0.46	130.0	± 9.6 %
		Y	4.50	67.62	16.76		130.0	
		Z	4.39	67.44	16.49		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.36	67.69	16.78	0.46	130.0	± 9.6 %
		Y	4.41	67.76	16.87		130.0	
		Z	4.32	67.61	16.63		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.10	66.72	15.92	0.46	130.0	± 9.6 %
		Y	4.17	66.93	16.12		130.0	
		Z	4.05	66.61	15.75		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.11	66.69	15.89	0.46	130.0	± 9.6 %
		Y	4.18	66.91	16.09		130.0	
		Z	4.05	66.55	15.69		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.30	67.88	16.81	0.46	130.0	± 9.6 %
		Y	4.35	67.96	16.92		130.0	
		Z	4.25	67.78	16.65		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.01	66.47	15.69	0.46	130.0	± 9.6 %
		Y	4.09	66.72	15.92		130.0	
		Z	3.96	66.34	15.50		130.0	

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.43	67.18	16.55	0.46	130.0	± 9.6 %
		Y	4.49	67.29	16.68		130.0	
		Z	4.39	67.12	16.41		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.52	67.42	16.66	0.46	130.0	± 9.6 %
		Y	4.58	67.53	16.78		130.0	
		Z	4.48	67.35	16.51		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.45	67.30	16.51	0.46	130.0	± 9.6 %
		Y	4.51	67.43	16.65		130.0	
		Z	4.40	67.23	16.36		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.50	67.49	16.69	0.46	130.0	± 9.6 %
		Y	4.56	67.59	16.81		130.0	
		Z	4.46	67.41	16.54		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.47	67.48	16.61	0.46	130.0	± 9.6 %
		Y	4.53	67.60	16.74		130.0	
		Z	4.42	67.40	16.45		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.39	67.39	16.57	0.46	130.0	± 9.6 %
		Y	4.45	67.52	16.71		130.0	
		Z	4.33	67.28	16.41		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.35	67.24	16.40	0.46	130.0	± 9.6 %
		Y	4.41	67.39	16.55		130.0	
		Z	4.30	67.15	16.24		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.36	67.56	16.72	0.46	130.0	± 9.6 %
		Y	4.42	67.64	16.83		130.0	
		Z	4.32	67.48	16.57		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.28	68.07	17.13	0.46	130.0	± 9.6 %
		Y	5.31	68.10	17.21		130.0	
		Z	5.25	68.02	17.00		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.26	68.02	17.07	0.46	130.0	± 9.6 %
		Y	5.32	68.16	17.21		130.0	
		Z	5.18	67.83	16.88		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.19	67.88	17.02	0.46	130.0	± 9.6 %
		Y	5.24	68.00	17.15		130.0	
		Z	5.13	67.77	16.87		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.23	67.74	16.87	0.46	130.0	± 9.6 %
		Y	5.29	67.89	17.01		130.0	
		Z	5.16	67.59	16.70		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.22	67.79	17.04	0.46	130.0	± 9.6 %
		Y	5.28	67.91	17.16		130.0	
		Z	5.16	67.66	16.88		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.14	67.45	16.84	0.46	130.0	± 9.6 %
		Y	5.19	67.55	16.95		130.0	
		Z	5.09	67.38	16.70		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.18	67.64	16.94	0.46	130.0	± 9.6 %
		Y	5.24	67.79	17.08		130.0	
		Z	5.12	67.50	16.77		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.10	67.52	16.72	0.46	130.0	± 9.6 %
		Y	5.15	67.65	16.86		130.0	
		Z	5.05	67.41	16.57		130.0	

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.29	66.54	16.21	0.46	130.0	± 9.6 %
		Y	4.34	66.66	16.33		130.0	
		Z	4.24	66.47	16.06		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.39	66.80	16.33	0.46	130.0	± 9.6 %
		Y	4.45	66.92	16.46		130.0	
		Z	4.34	66.71	16.18		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.29	66.63	16.15	0.46	130.0	± 9.6 %
		Y	4.36	66.77	16.28		130.0	
		Z	4.24	66.54	15.98		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.35	66.83	16.34	0.46	130.0	± 9.6 %
		Y	4.41	66.94	16.46		130.0	
		Z	4.30	66.73	16.18		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.25	66.59	16.16	0.46	130.0	± 9.6 %
		Y	4.32	66.72	16.29		130.0	
		Z	4.20	66.49	15.99		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.22	66.65	16.17	0.46	130.0	± 9.6 %
		Y	4.29	66.81	16.32		130.0	
		Z	4.17	66.52	15.99		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.22	66.46	15.99	0.46	130.0	± 9.6 %
		Y	4.29	66.63	16.15		130.0	
		Z	4.17	66.34	15.82		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.22	66.76	16.30	0.46	130.0	± 9.6 %
		Y	4.28	66.86	16.41		130.0	
		Z	4.17	66.66	16.13		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.24	66.41	15.90	0.46	130.0	± 9.6 %
		Y	4.31	66.60	16.08		130.0	
		Z	4.19	66.31	15.73		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	4.93	66.65	16.40	0.46	130.0	± 9.6 %
		Y	4.98	66.76	16.51		130.0	
		Z	4.88	66.57	16.26		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	4.95	66.75	16.43	0.46	130.0	± 9.6 %
		Y	5.01	66.87	16.55		130.0	
		Z	4.90	66.65	16.28		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	4.86	66.79	16.47	0.46	130.0	± 9.6 %
		Y	4.92	66.89	16.57		130.0	
		Z	4.82	66.72	16.33		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	4.94	66.81	16.41	0.46	130.0	± 9.6 %
		Y	5.00	66.95	16.54		130.0	
		Z	4.88	66.69	16.25		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	4.94	66.58	16.33	0.46	130.0	± 9.6 %
		Y	5.00	66.71	16.46		130.0	
		Z	4.89	66.47	16.18		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	4.96	66.73	16.54	0.46	130.0	± 9.6 %
		Y	5.02	66.81	16.63		130.0	
		Z	4.92	66.66	16.41		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	4.95	66.82	16.59	0.46	130.0	± 9.6 %
		Y	5.00	66.92	16.68		130.0	
		Z	4.90	66.73	16.45		130.0	

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	4.87	66.45	16.24	0.46	130.0	± 9.6 %
		Y	4.92	66.58	16.37		130.0	
		Z	4.82	66.36	16.10		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.04	66.65	16.42	0.46	130.0	± 9.6 %
		Y	5.09	66.77	16.53		130.0	
		Z	4.99	66.56	16.27		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.15	66.91	16.62	0.46	130.0	± 9.6 %
		Y	5.20	67.00	16.72		130.0	
		Z	5.10	66.84	16.48		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.29	66.59	16.34	0.46	130.0	± 9.6 %
		Y	5.34	66.70	16.45		130.0	
		Z	5.25	66.53	16.22		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.52	67.29	16.67	0.46	130.0	± 9.6 %
		Y	5.58	67.41	16.78		130.0	
		Z	5.47	67.18	16.52		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.27	66.55	16.22	0.46	130.0	± 9.6 %
		Y	5.33	66.68	16.34		130.0	
		Z	5.23	66.47	16.09		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.51	67.21	16.55	0.46	130.0	± 9.6 %
		Y	5.56	67.34	16.68		130.0	
		Z	5.45	67.08	16.40		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.53	67.47	16.69	0.46	130.0	± 9.6 %
		Y	5.60	67.63	16.83		130.0	
		Z	5.44	67.24	16.49		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.53	67.60	16.95	0.46	130.0	± 9.6 %
		Y	5.58	67.67	17.02		130.0	
		Z	5.48	67.48	16.80		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.65	67.90	17.12	0.46	130.0	± 9.6 %
		Y	5.69	67.95	17.19		130.0	
		Z	5.59	67.77	16.96		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.28	66.62	16.30	0.46	130.0	± 9.6 %
		Y	5.34	66.72	16.40		130.0	
		Z	5.25	66.56	16.18		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.32	66.86	16.47	0.46	130.0	± 9.6 %
		Y	5.37	66.95	16.56		130.0	
		Z	5.29	66.80	16.35		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.16	66.03	15.76	0.46	130.0	± 9.6 %
		Y	5.23	66.21	15.93		130.0	
		Z	5.12	65.96	15.63		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.75	66.94	16.43	0.46	130.0	± 9.6 %
		Y	5.81	67.05	16.54		130.0	
		Z	5.72	66.87	16.31		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	5.87	67.25	16.58	0.46	130.0	± 9.6 %
		Y	5.92	67.36	16.69		130.0	
		Z	5.82	67.15	16.45		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	5.94	67.47	16.67	0.46	130.0	± 9.6 %
		Y	5.99	67.59	16.78		130.0	
		Z	5.89	67.37	16.53		130.0	

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.83	67.14	16.54	0.46	130.0	± 9.6 %
		Y	5.88	67.25	16.65		130.0	
		Z	5.78	67.06	16.42		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.74	66.89	16.36	0.46	130.0	± 9.6 %
		Y	5.80	67.03	16.49		130.0	
		Z	5.70	66.81	16.23		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	5.90	67.16	16.52	0.46	130.0	± 9.6 %
		Y	5.96	67.30	16.65		130.0	
		Z	5.84	67.04	16.37		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	5.88	67.23	16.72	0.46	130.0	± 9.6 %
		Y	5.93	67.31	16.81		130.0	
		Z	5.84	67.16	16.60		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.73	66.90	16.44	0.46	130.0	± 9.6 %
		Y	5.79	67.04	16.57		130.0	
		Z	5.68	66.81	16.31		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	5.78	67.07	16.55	0.46	130.0	± 9.6 %
		Y	5.84	67.20	16.67		130.0	
		Z	5.74	66.99	16.42		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	5.92	67.19	16.58	0.46	130.0	± 9.6 %
		Y	5.97	67.31	16.69		130.0	
		Z	5.89	67.17	16.48		130.0	
10646-AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	13.61	107.81	37.87	9.30	60.0	± 9.6 %
		Y	25.75	125.86	44.42		60.0	
		Z	9.90	101.38	36.12		60.0	
10647-AAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	11.23	103.89	36.78	9.30	60.0	± 9.6 %
		Y	19.74	119.98	42.91		60.0	
		Z	8.22	97.43	34.92		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.30	60.00	4.87	0.00	150.0	± 9.6 %
		Y	0.33	60.00	5.44		150.0	
		Z	0.30	60.00	4.85		150.0	
10652-AAC	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.70	69.20	16.78	2.23	80.0	± 9.6 %
		Y	3.79	69.35	16.97		80.0	
		Z	3.51	68.59	16.38		80.0	
10653-AAC	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	4.13	67.83	17.08	2.23	80.0	± 9.6 %
		Y	4.22	67.99	17.23		80.0	
		Z	4.00	67.46	16.80		80.0	
10654-AAC	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.14	67.26	17.12	2.23	80.0	± 9.6 %
		Y	4.22	67.42	17.27		80.0	
		Z	4.03	66.92	16.87		80.0	
10655-AAD	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.22	67.03	17.14	2.23	80.0	± 9.6 %
		Y	4.30	67.21	17.29		80.0	
		Z	4.11	66.70	16.90		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	100.00	111.26	26.36	10.00	50.0	± 9.6 %
		Y	100.00	114.45	28.17		50.0	
		Z	100.00	110.83	26.00		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	100.00	108.50	24.19	6.99	60.0	± 9.6 %
		Y	100.00	112.09	26.11		60.0	
		Z	100.00	108.95	24.23		60.0	

10660- AAA	Pulse Waveform (200Hz, 40%)	X	100.00	106.32	22.04	3.96	80.0	± 9.6 %
		Y	100.00	111.36	24.50		80.0	
		Z	100.00	107.90	22.58		80.0	
10661- AAA	Pulse Waveform (200Hz, 60%)	X	100.00	103.65	19.77	2.22	100.0	± 9.6 %
		Y	100.00	112.12	23.59		100.0	
		Z	100.00	106.59	20.90		100.0	
10662- AAA	Pulse Waveform (200Hz, 80%)	X	100.00	90.92	13.24	0.97	120.0	± 9.6 %
		Y	100.00	110.88	21.41		120.0	
		Z	100.00	97.17	15.68		120.0	

^c Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DIPOLE CALIBRATION CERTIFICATES

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **BACL**

Certificate No: **CLA150-4020_Nov16**

CALIBRATION CERTIFICATE

Object **CLA150 - SN: 4020**

Calibration procedure(s) **QA CAL-15.v8**
Calibration procedure for system validation sources below 700 MHz

Calibration date: **November 08, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 30 dB Attenuator	SN: 5129 (30b)	05-Apr-16 (No. 217-02294)	Apr-17
Type-N mismatch combination	SN: 5047.2 / 06327	05-Apr-16 (No. 217-02295)	Apr-17
Reference Probe EX3DV4	SN: 3877	31-Dec-15 (No. EX3-3877_Dec15)	Dec-16
DAE4	SN: 654	12-Aug-16 (No. DAE4-654_Aug16)	Aug-17

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (No. 217-02285/02284)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (No. 217-02285)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (No. 217-02284)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Claudio Leubler** **Laboratory Technician**

Signature

Approved by: **Katja Poković** **Technical Manager**

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: November 10, 2016

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The source is mounted in a touch configuration below the center marking of the flat phantom.
- Return Loss:** This parameter is measured with the source positioned under the liquid filled phantom (as described in the measurement condition clause). The Return Loss ensures low reflected power. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness: 2 ± 0.2 mm
EUT Positioning	Touch Position	
Zoom Scan Resolution	$dx, dy = 4.0$ mm, $dz = 1.4$ mm	Graded Ratio = 1.4 (Z direction)
Frequency	150 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	52.3	0.76 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	50.1 ± 6 %	$0.75 \text{ mho/m} \pm 6$ %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	1 W input power	3.64 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	3.64 W/kg $\pm$ 18.4 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	1 W input power	2.46 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	2.47 W/kg $\pm$ 18.0 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	61.9	0.80 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	61.4 ± 6 %	$0.82 \text{ mho/m} \pm 6$ %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	1 W input power	3.81 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	3.73 W/kg $\pm$ 18.4 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	1 W input power	2.57 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	2.52 W/kg $\pm$ 18.0 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	44.4 Ω - 1.8 j Ω
Return Loss	- 24.1 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	45.9 Ω - 6.0 j Ω
Return Loss	- 22.5 dB

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 25, 2015

DASY5 Validation Report for Head TSL

Date: 07.11.2016

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: CLA-150; Type: CLA-150; Serial: 4020

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used: $f = 150$ MHz; $\sigma = 0.75$ S/m; $\epsilon_r = 50.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3877; ConvF(12.02, 12.02, 12.02); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 12.08.2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan

(81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.06 W/kg

CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan,


dist=1.4mm (8x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 81.89 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 6.81 W/kg

SAR(1 g) = 3.64 W/kg; SAR(10 g) = 2.46 W/kg

Maximum value of SAR (measured) = 5.06 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 08.11.2016

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: CLA-150; Type: CLA-150; Serial: 4020

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used: $f = 150$ MHz; $\sigma = 0.82$ S/m; $\epsilon_r = 61.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3877; ConvF(11.44, 11.44, 11.44); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 12.08.2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan

(81x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 5.32 W/kg

CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan,


dist=1.4mm (8x10x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 80.95 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 7.02 W/kg

SAR(1 g) = 3.81 W/kg; SAR(10 g) = 2.57 W/kg

Maximum value of SAR (measured) = 5.27 W/kg



Impedance Measurement Plot for Body TSL

