

FCC Part 15C Compliance Test Report

Test Report no.:	Tre_0544_02.doc	Date of Report:	14.11.2005
Number of pages:	36	Customer's Contact person:	Ernest Mayer
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Client:	Nokia Corporation Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934
FCC listing no.:	94436		
IC recognition no.:	3608		
Tested devices/ accessories:	GSM phone RM-79 / Battery BP-6M, Headset HS-23, AC charger AC-4U, Memory card MU-16		
FCC ID:	QTKRM-79	IC:	661AD-RM79
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), IC standards RSS-GEN and RSS-210. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			
	Jari Jantunen, System Manager		

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	1.11.2005
Testing completed	8.11.2005
The customer's contact person	Ernest Mayer
Test Plan referred to	\\EMC\\TESTPLAN\\
Notes	-
Document name	T:\\Projects\\RM-79\\EMC\\Results\\FCC\\Tre_0544_02.doc

1.1. EUT and Accessory Information

The EUT is a quadri band (GSM850/1800/1900 and WCDMA1900) mobile phone with GPRS, EGPRS and Bluetooth. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-79	004400721743126	0510	-	03.09	40419
Phone	RM-79	004400721743142	0510	-	03.09	40420
Battery	BP-6M	-	-	-	-	40429
Battery	BP-6M	-	-	-	-	40430
Memory card	MU-16	ST5JB001396	-	-	-	40423
Memory card	MU-16	ST5JB001365	-	-	-	40422
Headset	HS-23	GM2950741C	-	-	-	40427
AC charger	AC-4U	-	-	-	-	40425

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Peak output power	Passed
15.247(c)	A8.5	Band edge compliance of RF emissions	Passed
15.247(c)	A8.5	Spurious RF conducted emissions	Passed
15.247(c), 15.209	A8.5	Spurious radiated emissions	Passed
15.207	7.2.2	AC powerline conducted emissions	Passed
15.247(a)(1)	A8.1 (1)	20 dB bandwidth	Passed
15.247(a)(1)	A8.1 (2)	Carrier frequency separation	Passed
15.247(a)(1)(iii)	A8.1 (4)	Number of hopping frequencies	Passed
15.247(a)(1)(iii)	A8.1 (4)	Time of occupancy	Passed

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups.....	5
2.1. Conducted RF test setup	5
2.2. AC powerline conducted emissions test setup.....	5
2.3. Spurious radiated emissions test setup	5
3. Peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))	6
3.1. Test method and limit.....	6
3.2. Bluetooth Test results	6
4. Band edge compliance of RF emissions (FCC §15.247(c), RSS-210 A8.5).....	9
4.1. Test method and limit.....	9
4.2. Bluetooth Test results	10
5. Spurious RF conducted emissions (FCC §15.247(c), RSS-A8.5)	14
5.1. Test method and limit.....	14
5.2. Bluetooth Test results	14
6. Spurious radiated emissions (FCC §15.247(c), §15.209, RSS-210 A8.5)	18
6.1. Test method and limit.....	18
6.2. Bluetooth Test results	19
7. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2).....	22
7.1. Test method and limit.....	22
7.2. Bluetooth Test results	23
8. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))	25
8.1. Test method and limit.....	25
8.2. Bluetooth Test results	25
9. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))	29
9.1. Test method and limit.....	29
9.2. Bluetooth Test results	30
10. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))	31
10.1. Test method and limit.....	31
10.2. Bluetooth Test results	32
11. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4)).....	33


11.1.	Test method and limit	33
11.2.	Bluetooth test results	34
12.	Test Equipment	36
12.1.	Conducted measurements	36
12.2.	Radiated measurements	36

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Spurious radiated emissions test setup



3. Peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

3.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

3.2. Bluetooth Test results


3.2.1 GSKF modulation, PRBS packet type

Channel	P [dBm]	P [mW]	Result
0	0.00	1.000	Passed
40	0.40	1.096	Passed
78	0.50	1.122	Passed


Channel 0 (Peak detector, RBW: 1 MHz)



Channel 40 (Peak detector, RBW: 1 MHz)



Channel 78 (Peak detector, RBW: 1 MHz)




3.2.2


3.2.3 8DPSK modulation, PRBS packet type

Channel	P [dBm]	P [mW]	Result
0	-0.40	0.912	Passed
40	-1.60	0.692	Passed
78	1.30	1.349	Passed


Channel 0 (Peak detector, RBW: 1 MHz)



Channel 39 (Peak detector, RBW: 1 MHz)



Channel 78 (Peak detector, RBW: 1 MHz)



4. Band edge compliance of RF emissions (FCC §15.247(c), RSS-210 A8.5)

EUT with DUT number	RM-79 DUT 40420
Accessories with DUT numbers	BP-6M 40430, HS-23 40427, AC-4U 40425, MU-16 40422
Operation Voltage [V] / [Hz]	115 / 60
Result	Pass
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22-23 / 42-43 / 101.4-101.5
Date of measurements	1, 7.11.2005
Measured by	Jari Jantunen

4.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	≤ 54	≤ 74

4.2. Bluetooth Test results

4.2.1 GFSK modulation, PRBS packet type


Average (RBW: 1 MHz)

Channel	E [dB μ V/m]	Result
0	30.15	PASSED
78	38.49	PASSED
Hopping on, low end	28.60	PASSED
Hopping on, high end	29.28	PASSED


Peak (RBW: 1 MHz)

Channel	E [dB μ V/m]	Result
0	43.46	PASSED
78	52.88	PASSED
Hopping on, low end	42.93	PASSED
Hopping on, high end	51.53	PASSED


Channel 0




Channel 78



Hopping on, low end



Hopping on, high end



4.2.2 π 8DPSK modulation, PRBS packet type


Average (RBW: 1 MHz)

Channel	E [dB μ V/m]	Result
0	31.50	PASSED
78	43.50	PASSED
Hopping on, low end	28.95	PASSED
Hopping on, high end	31.54	PASSED


Peak (RBW: 1 MHz)

Channel	E [dB μ V/m]	Result
0	45.44	PASSED
78	56.97	PASSED
Hopping on, low end	43.97	PASSED
Hopping on, high end	54.99	PASSED


Channel 0




Channel 78



Hopping on, low end



Hopping on, high end



5. Spurious RF conducted emissions (FCC §15.247(c), RSS-A8.5)

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

5.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	≤ -20

5.2. Bluetooth Test results


5.2.1 GFSK modulation, PRBS packet type

Channel 0




Frequency [MHz]	P [dBc]	Result
4985.576923	-42.929530	Passed
7290.946154	-42.629530	Passed
7500.000000	-43.729530	Passed

Channel 40



Frequency [MHz]	P [dBc]	Result
4930.128205	-44.393916	Passed
7498.557692	-43.993916	Passed
7500.000000	-42.293916	Passed


Channel 78



Frequency [MHz]	P [dBc]	Result
4941.666667	-44.553405	Passed
7327.403846	-44.553405	Passed
7500.000000	-43.553405	Passed


5.2.2 8DPSK modulation, PRBS packet type

Channel 0




Frequency [MHz]	P [dBc]	Result
4944.701282	-43.217880	Passed
7329.657692	-43.117880	Passed
7499.950000	-42.617880	Passed

Channel 39



Frequency [MHz]	P [dBc]	Result
4955.769231	-41.917775	Passed
5000.000000	-41.817775	Passed
7300.000000	-40.017775	Passed

Channel 78



Frequency [MHz]	P [dBc]	Result
4982.371795	-44.170008	Passed
5000.000000	-45.170008	Passed
7310.576923	-44.370008	Passed

6. Spurious radiated emissions (FCC §15.247(c), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-79 DUT 40420
Accessories with DUT numbers	BP-6M 40430, HS-23 40427, AC-4U 40425, MU-16 40422
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23 / 43 / 101.4
Date of measurements	7.11.2005
Measured by	Jari Jantunen

6.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

6.2. Bluetooth Test results

6.2.1 GFSK modulation, PRBS packet type

Channel 0

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	54.40	524.81	54.70	-0.30	VERTICAL	PASSED
7206.000000	46.30	206.54	43.30	3.00	HORIZONTAL	PASSED
9608.000000	47.00	223.87	37.70	9.30	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	46.40	208.93	46.70	-0.30	VERTICAL	PASSED
7206.000000	34.90	55.59	31.90	3.00	VERTICAL	PASSED
9608.000000	34.50	53.09	25.20	9.30	HORIZONTAL	PASSED

Channel 40

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
2928.857715	48.60	269.15	50.10	-1.50	VERTICAL	PASSED
7420.333667	45.00	177.83	40.50	4.50	VERTICAL	PASSED
17939.887776	56.10	638.26	34.40	21.70	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
7418.333667	32.10	40.27	27.60	4.50	VERTICAL	PASSED
17946.387776	42.80	138.04	21.10	21.70	HORIZONTAL	PASSED

Channel 78

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	55.20	575.44	55.30	-0.10	VERTICAL	PASSED

7440.000000	48.60	269.15	44.20	4.40	VERTICAL	PASSED
9920.000000	48.00	251.19	38.80	9.20	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	44.40	165.96	44.50	-0.10	VERTICAL	PASSED
7440.000000	35.70	60.95	31.30	4.40	VERTICAL	PASSED
9920.000000	34.40	52.48	25.20	9.20	HORIZONTAL	PASSED

6.2.2 8DPSK modulation, PRBS packet type

Channel 0

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	49.80	309.03	50.10	-0.30	VERTICAL	PASSED
7206.000000	43.00	141.25	40.00	3.00	HORIZONTAL	PASSED
9608.000000	46.80	218.78	37.50	9.30	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	34.80	54.95	35.10	-0.30	VERTICAL	PASSED
7206.000000	30.70	34.28	27.70	3.00	HORIZONTAL	PASSED
9608.000000	33.60	47.86	24.30	9.30	HORIZONTAL	PASSED

Channel 40

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.000000	42.80	138.04	43.50	-0.70	HORIZONTAL	PASSED
7326.000000	44.00	158.49	40.60	3.40	HORIZONTAL	PASSED
9768.000000	46.60	213.80	38.10	8.50	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.000000	30.00	31.62	30.70	-0.70	VERTICAL	PASSED
7326.000000	31.00	35.48	27.60	3.40	VERTICAL	PASSED
9768.000000	32.90	44.16	24.40	8.50	HORIZONTAL	PASSED

Channel 78

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	49.50	298.54	49.60	-0.10	VERTICAL	PASSED
7440.000000	44.50	167.88	40.10	4.40	VERTICAL	PASSED
9920.000000	46.80	218.78	37.60	9.20	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	34.00	50.12	34.10	-0.10	VERTICAL	PASSED
7440.000000	32.10	40.27	27.70	4.40	VERTICAL	PASSED
9920.000000	33.90	49.55	24.70	9.20	HORIZONTAL	PASSED

7. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-79 DUT 40420
Accessories with DUT numbers	BP-6M 40430, HS-23 40427, AC-4U 40425, MU-16 40422
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	18 / 50 / 101.9
Date of measurements	8.11.2005
Measured by	Jari Jantunen

7.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

7.2. Bluetooth Test results

7.2.1 GFSK modulation, PRBS packet type

Channel 40



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
2.162325	13.40	L1	PASSED
2.426854	13.10	L1	PASSED
2.691383	14.40	L1	PASSED
2.961924	12.50	L1	PASSED
3.484970	12.20	L1	PASSED
4.525050	14.30	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.468838	5.10	L1	PASSED
1.117635	4.30	N	PASSED
1.173246	3.90	L1	PASSED
2.168337	4.90	L1	PASSED
2.697395	5.10	L1	PASSED
2.961924	4.90	L1	PASSED

7.2.2 8DPSK modulation, PRBS packet type

Channel 40



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
2.060120	26.10	L1	PASSED
2.168337	20.50	L1	PASSED
2.318637	22.40	L1	PASSED
2.739479	29.40	L1	PASSED
2.769539	29.40	L1	PASSED
2.919840	26.60	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
2.060120	13.40	N	PASSED
2.180361	13.10	L1	PASSED
2.709419	14.10	L1	PASSED
2.739479	12.60	N	PASSED
2.829659	13.30	L1	PASSED
2.847695	8.70	N	PASSED

8. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

8.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

8.2. Bluetooth Test results


8.2.1 GFSK modulation, PRBS packet type

Channel	20 dB bandwidth [kHz]	Result
0	663.462	
40	660.256	
78	660.256	


Channel 0



Channel 39




Channel 78




8.2.2 8DPSK modulation, PRBS packet type

Channel	20 dB bandwidth [kHz]	Result
0	1112.179	Passed
39	1112.179	Passed
78	1105.769	Passed


Channel 0



Channel39



Channel 78



9. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

9.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or $2/3$ of the 20 dB bandwidth

9.2. Bluetooth Test results

9.2.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1017.628	Passed


Hopping on, carrier frequency separation of channels 39 and 40



9.2.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1017.628	Passed

Hopping on, carrier frequency separation of channels 39 and 40



10. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

10.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

10.2. Bluetooth Test results

10.2.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
79	Passed


Hopping on, number of hopping frequencies



10.2.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
79	Passed

Hopping on, number of hopping frequencies



11. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	Phone: DUT 40419
Accessories with DUT numbers	Battery: DUT 40429, Memory card: DUT 40423
Operation Voltage [V] / [Hz]	-
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/51/101.4
Date of measurements	02.11.2005
Measured by	Jan-Erik Lilja

11.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210 as follows:

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

11.2. Bluetooth test results


11.2.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
59	2967.949	0.175109	Passed

Hopping on, number of transmissions, channel 40




Hopping on, duration of one transmission, channel 40




11.2.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
108	2980.769	0.321923	Passed

Hopping on, number of transmissions, channel 40



Hopping on, duration of one transmission, channel 40



12. Test Equipment

12.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM37610	Spectrum analyzer	FSU	R&S	15C,22/24
TM37678	Radio communication tester	CMU-200	R&S	15C,22/24
	Attenuator 10 dB	6251.17.A	Huber+Suhner AG	15C,22/24
TM22901	Step attenuator 110dB	8496A	Agilent	15C,22/24
TM37499	Power splitter	11667A	Agilent	15C,22/24
	Temperature chamber	VT4002	Vötsch	15C,22/24
TM38112	DC power supply	6632A	Agilent	15C,22/24
TM38111	Multimeter	34401A	Agilent	15C,22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C
TM37773	Radio communication tester	CMU-200	R&S	15B,15C
TM38631	Signal generator	83640L	Agilent	15B,15C
TM38114	DC power supply	6632A	Agilent	15B,15C
TM22835	Multimeter	87	Fluke	15B,15C
TM30600	Pulse Limiter	ESH3-Z2	R&S	15B,15C
TM26490	LISN 50 µH	ESH3-Z5/	R&S	15B,15C
TM30636	LISN 50 µH	L2-16/	PMM	15B,15C

12.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	15B,15C, 22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C, 22/24
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	15B,15C, 22/24
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	15B,15C, 22/24
TM37516	Biconilog antenna	HL562	R&S	15B,15C, 22/24
TM26496	Double ridged waveguide antenna	3115	EMCO	15B,15C, 22/24
TM39158	Horn antenna	3116	EMCO	15B,15C, 22/24
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	15B,15C, 22/24
TM37501	Dipole antenna	3125-870	EMCO	22/24
TM37502	Dipole antenna	3125-1880	EMCO	22/24
TM37773	Radio communication tester	CMU-200	R&S	15B,15C, 22/24
TM38631	Signal generator	83640L	Agilent	15B,15C, 22/24
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	15B,15C, 22/24
	High pass filter	WHK2010-10SS	Trilithic	15B,15C, 22/24
	Low pass filter	WLK1750-10SS	Trilithic	15B,15C, 22/24
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Turntable controller	HD-100	Deisel	15B,15C, 22/24
TM26500	Turntable	DS412	Deisel	15B,15C, 22/24
TM38842	Antenna mast controller	2090	EMCO	15B,15C, 22/24
TM38843	Antenna mast	2075	EMCO	15B,15C, 22/24
TM38114	DC power supply	6632A	Agilent	15B,15C, 22/24
TM22835	Multimeter	87	Fluke	15B,15C, 22/24