

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	2.5	1.78	16.50	44.67	20	0.0158	1.0
802.11g		2.5	1.78	19.50	89.13	20	0.0316	1.0
802.11n-HT20		2.5	1.78	20.00	100.00	20	0.0354	1.0
802.11n-HT40	2422~2452	2.5	1.78	16.00	39.81	20	0.0141	1.0
802.11a	5150~5250	4.4	2.75	13.50	22.39	20	0.0122	1.0
	5725~5850	4.4	2.75	14.50	28.18	20	0.0154	1.0
802.11n20	5150~5250	4.4	2.75	13.50	22.39	20	0.0122	1.0
	5725~5850	4.4	2.75	15.00	31.62	20	0.0173	1.0
802.11n40	5150~5250	4.4	2.75	9.00	7.94	20	0.0043	1.0
	5725~5850	4.4	2.75	15.00	31.62	20	0.0173	1.0

Note: 1. For the above tune up power were declared by the manufacturer.
 2. 2.4G Wi-Fi and 5G Wi-Fi can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance.