



RF EXPOSURE REPORT

Applicant	:	Cooler Master Technology Inc.		
Address of Applicant	:	7F., No.398, Xinhu 1st Rd., Neihu Dist., Taipei City 114065, Taiwan		
Manufacturer		Dong Guan IONE Electronic Technology Co., Ltd.		
Address of Manufacturer	:	Building 3 No.76, Yongjun 2nd, Road, HuangJiang Town, DongGuan City, GuangDong Province, China		
Equipment under Test	••	Dongle		
Model No.		CMHS-D		
FCC ID	:	2AR8X-CMHS-D		
Test Standard(s) : KDB447498 D01 General RF Exposure Guidar		KDB447498 D01 General RF Exposure Guidance v06		
Report No.	: DDT-RE24050708-2E10			
Issue Date	: 2024/08/14			
Issue By	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808			

REPORT

Table of Contents

1.	General Test Information	5
1.1.	Description of EUT	5
1.2.	Accessories of EUT	5
1.3.	Test laboratory	5
2.	RF Exposure evaluation for FCC	6
2.1.	Assessment procedure	6
2.2.	Assess result	6

Test Report Declare

Applicant	:	Cooler Master Technology Inc.		
Address of Applicant :		7F., No.398, Xinhu 1st Rd., Neihu Dist., Taipei City 114065, Taiwan		
Equipment under Test	:	Dongle		
Model No.	:	CMHS-D		
Manufacturer	: Dong Guan IONE Electronic Technology Co., Ltd.			
Address of Manufacturer	ŀ	Building 3 No.76, Yongjun 2nd, Road, HuangJiang Town, DongGuan City, GuangDong Province, China		

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DD1-RE2405070	08-2E10		
Date of Receipt:	2024/07/16	Date of Test:	2024/07/16~2024/08/07	
Pi	repared By:		Approved By:	

Bobo Chen Damon Mu

Bobo Chen/Engineer Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
	Initial issue	2024/08/14	8
	X X X X X	*	

1. General Test Information

1.1. Description of EUT

EUT Name	:	Dongle	
Model Number	:	CMHS-D	
EUT Function Description	:	Please reference user manual of this device	
Power Supply	:	DC 5V	7

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

"⊠" means to be chosen or applicable; "□" means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Gaming Headset	Dong Guan IONE Electronic Technology Co., Ltd.	CH351	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

End Report-

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.2. Assess result

Worse case is as below: [2402 MHz, 6.35 dBm, (4.32 mW) output power]

 $(4.32/5) \cdot [\sqrt{2.402}(GHz)] = 1.339 < 3.0 \text{ for } 1-g \text{ SAR}$

Then SAR evaluation is not required.

Note: Ant1 and Ant2 don't support synchronous transmission.

