

RF Exposure Evaluation Report

Product : SMART SENSE Situational Awareness
Bluetooth® Earbuds

Trade mark : **KLEIN
TOOLS**

Model/Type reference : AESEB1S

Serial Number : N/A

Report Number : EED32P80449002

FCC ID : 2AI28-AESEB1S

Date of Issue : May 15, 2023
: 47 CFR Part 1.1307
: 47 CFR Part 2.1093

Test Standards : KDB447498D01 General RF
Exposure Guidance v06

Test result : PASS

Prepared for:

Klein Tools, Inc.

450 Bond St. Lincolnshire, IL 60069 USA

Prepared by:

Centre Testing International Group Co., Ltd.

**Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

mark.chen

Mark Chen

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

May 15, 2023

Check No.: 6131030423



1 Version

Version No.	Date	Description
00	May 15, 2023	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 TEST LOCATION	5
3.5 DEVIATION FROM STANDARDS	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Standard Requirement	6
4.1.2 EUT RF Exposure	7

3 General Information

3.1 Client Information

Applicant:	Klein Tools, Inc.
Address of Applicant:	450 Bond St. Lincolnshire, IL 60069 USA
Manufacturer:	Klein Tools, Inc.
Address of Manufacturer:	450 Bond St. Lincolnshire, IL 60069 USA
Factory:	Concord Intelligent Technology (Huizhou) Ltd.
Address of Factory:	25, Ping An Rd, Shuikou Street, Hui Cheng District, Huizhou City, Guangdong Province, China

3.2 General Description of EUT

Product Name:	SMART SENSE Situational Awareness Bluetooth® Earbuds
Model No.(EUT):	AESEB1S
Trade mark:	KLEIN TOOLS
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Power Supply:	Battery DC 3.7V
Test Voltage:	DC 3.7V
Sample Received Date:	Apr. 03, 2023
Sample tested Date:	Apr. 03, 2023 to Apr. 11, 2023
Remark:	Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Antenna Type:	FPC Antenna
Antenna Gain:	Left ear : -1.7 dBi Right ear : -2.0 dBi

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.2 EUT RF Exposure

1) For BT Classic

Measurement Data

The data of ear right is worst, only the worst case is recorded in the report.

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.98	1.0±1	2.0	1.585
Middle(2441MHz)	1.47	1.0±1	2.0	1.585
Highest(2480MHz)	1.92	1.0±1	2.0	1.585
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.02	1.0±1	2.0	1.585
Middle(2441MHz)	1.45	1.0±1	2.0	1.585
Highest(2480MHz)	1.79	1.0±1	2.0	1.585
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.62	1.0±1	2.0	1.585
Middle(2441MHz)	1.43	1.0±1	2.0	1.585
Highest(2480MHz)	1.91	1.0±1	2.0	1.585

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.98	1.0±1	2.0	1.585	0.499	3.0
Middle (2441MHz)	1.47	1.0±1	2.0	1.585	0.499	
Highest (2480MHz)	1.92	1.0±1	2.0	1.585	0.499	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32P80449001.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***