

FCC 47 CFR MPE REPORT

TCL OVERSEAS MARKETING LTD

Party Speaker

Model Number: TP200K

Additional Model: TP201K, TP202K, TP200L, TP200K-A, TP200K-B, TP200K-J,
TP200K-JN, TP200L-A, TP200L-B, TP200L-J, TP200L-JN, TP200L-C, TP2*****

(*can be any numerica number "0~9" or alphebtical number "A~Z" or blank)

FCC ID: 2BEHETP200K

| | |
|--------------------------|--|
| Applicant: | TCL OVERSEAS MARKETING LTD |
| Address: | Unit 1905, 19/F, Nan Fung Centre, 264-298 Castle Peak Road, |
| | Tsuen Wan, New Territories, Hong Kong |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 | |

| | |
|-----------------|------------------------------|
| Report Number: | ESTE-R2502146 |
| Date of Test: | Jan. 17, 2025~ Mar. 04, 2025 |
| Date of Report: | Mar. 06, 2025 |

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) |
|----------------|-----------------|-------------------------|------------------------|
| GFSK | 2402 | 7.18 | 5.224 |
| | 2441 | 5.39 | 3.459 |
| | 2480 | 5.25 | 3.350 |
| $\pi/4$ -DQPSK | 2402 | 8.8 | 7.586 |
| | 2441 | 6.96 | 4.966 |
| | 2480 | 6.86 | 4.853 |
| 8-DPSK | 2402 | 9 | 7.943 |
| | 2441 | 7.17 | 5.212 |
| | 2480 | 7.06 | 5.082 |
| BLE 1M | 2402 | 6.75 | 4.732 |
| | 2440 | 5.21 | 3.319 |
| | 2480 | 5.06 | 3.206 |
| BLE 2M | 2402 | 6.98 | 4.989 |
| | 2440 | 5.43 | 3.491 |
| | 2480 | 5.21 | 3.319 |

3. Calculated Result and Limit

| Mode | Peak output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain | | Power Density (S) (mW /cm ²) | Limited of Power Density (S) (mW /cm ²) | Test Result |
|-----------|-------------------------|--------------------|------------------------|--------------|----------|--|---|-------------|
| | | | | (dBi) | (Linear) | | | |
| 2.4G Band | | | | | | | | |
| GFSK | 7.18 | 7±1 | 8 | 3.99 | 2.506 | 0.00315 | 1 | Complies |
| π/4-DQPSK | 8.80 | 8±1 | 9 | 3.99 | 2.506 | 0.00396 | 1 | Complies |
| 8-DPSK | 9 | 9±1 | 10 | 3.99 | 2.506 | 0.00499 | 1 | Complies |
| BLE 1M | 6.75 | 6±1 | 7 | 3.99 | 2.506 | 0.00250 | 1 | Complies |
| BLE 2M | 6.98 | 6±1 | 7 | 3.99 | 2.506 | 0.00250 | 1 | Complies |

End of Test Report