Fangguang Inspection & Testing Co., Ltd.





MEASUREMENT REPORT FCC PART 15.247 WLAN 802.11b/g/n

Report No.: S20230809559505-G1Issue Date:01-02-2024

Applicant: IGEN TECH CO.,Ltd.

Address: Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R.

China

- FCC ID: 2A4FR-MW-4E
- Product: WiFi Module
- Model No.: MW-4E
- **FCC Classification:** Digital Transmission System (DTS)
- FCC Rule Part(s): Part 15 Subpart C (15.247)

Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v05r02

Result: Pass

Receipt date: Aug. 24, 2023

Test Date: Sep. 13~ Sep. 17, 2023

Guang Ze Dirg

Compiled By

(Guangze Ding) Senior, Test Engineer

Approved By



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

 Headquarters Add.: Area B of the 3rd floor, XEDA Sci-Tech Park, Xiqing Economic Development Area, Tianjin, China

 Tel:+86-020-66289500-8260
 Email: fygd@grgtest.com

 TRF No.:FG.WI-07- ANSI C63.10-2013
 http://www.fgtest.com



Revision History

Report No.	Version	Description	Issue Date
S20230809559505	Rev. 01	1	10-07-2023
S20230809559505-G1	Rev. 02	1. This report shall be replaced by report S20230809559505, which shall be invalid immediately upon the issuance of this report. 2. The initial issuance date of report S20230809559505 was Oct 07, 2023, and the first amendment to the report was made on Dec 29, 2023, change the address to Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China on page 1&5.	01-02-2024



CONTENTS

Des	scriptio	n	Page
§2. 1	033 Ge	eneral Information	5
1.	INTRO	DDUCTION	6
	1.1.	Scope	6
	1.2.	Fangguang Test Location	6
2.	PROD	OUCT INFORMATION	7
	2.1.	Equipment Description	7
	2.2.	Product Specification Subjective to this Report	7
	2.3.	Operation Frequency / Channel List	7
	2.4.	Description of Available Antennas	8
	2.5.	Device Capabilities	9
	2.6.	Description of Test Software	14
	2.7.	Test Mode	14
	2.8.	Test Configuration	14
	2.9.	EMI Suppression Device(s)/Modifications	14
	2.10.	Labeling Requirements	14
3.	DESC	RIPTION OF TEST	15
	3.1.	Evaluation Procedure	15
	3.2.	AC Line Conducted Emissions	15
	3.3.	Radiated Emissions	16
4.	ANTE	NNA REQUIREMENTS	17
5.	TEST	EQUIPMENT CALIBRATION DATE	18
6.	MEAS	UREMENT UNCERTAINTY	19
7.	TEST	RESULT	20
	7.1.	Summary	20
	7.2.	6dB Bandwidth Measurement	22
	7.2.1.	Test Limit	22
	7.2.2.	Test Procedure used	
	7.2.3.	Test Setting	22
	7.2.4.	Test Setup	22
	7.2.5.	Test Result	23
	7.3.	Output Power Measurement	
	7.3.1.	Test Limit	33



8.

7.3.2.	Test Procedure Used	33
7.3.3.	Test Setting	33
7.3.4.	Test Setup	34
7.3.5.	Test Result	35
7.4.	Power Spectral Density Measurement	41
7.4.1.	Test Limit	41
7.4.2.	Test Procedure Used	41
7.4.3.	Test Setting	41
7.4.4.	Test Setup	42
7.4.5.	Test Result	43
7.5.	Conducted Band Edge and Out-of-Band Emissions	43
7.5.1.	Test Limit	48
7.5.2.	Test Procedure Used	48
7.5.3.	Test Settitng	48
7.5.4.	Test Setup	48
7.5.5.	Test Result	49
7.6.	Radiated Spurious Emission Measurement	53
7.6.1.	Test Limit	67
7.6.2.	Test Procedure Used	67
7.6.3.	Test Setting	67
7.6.4.	Test Setup	69
7.6.5.	Test Result	71
7.7.	Restricted Band Edge Measurement	76
7.7.1.	Test Limit	76
7.7.2.	Test Procedure Used	77
7.7.3.	Test Setting	77
7.7.4.	Test Setup	78
7.7.5.	Test Result	79
7.8.	AC Conducted Emissions Measurement	80
7.8.1.	Test Limit	86
7.8.2.	Test Setup	86
7.8.3.	Test Result	86
CONC	CLUSION	87



§2.1033 General Information

Applicant:	IGEN TECH CO.,Ltd.			
Applicant Address:	Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China			
Manufacturer:	IGEN TECH CO.,Ltd.			
Manufacturer Address:	Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China			
Test Site:	Fangguang Inspection & Testing Co., Ltd.			
LAB ID:	CN5037			
Test Site Address:	G9 Building, China Sensor Network International Innovation Park			
	No.200, Linghu Avenue Wuxi, Jiangsu 214000 China			
FCC Rule Part(s):	Part 15 Subpart C (15.247)			
FCC ID:	2A4FR-MW-4E			
S/N.:402A8F27BD1B				
Test Device Serial No.:	□ Production ⊠ Pre-Production □ Engineering			
FCC Classification:	Digital Transmission System (DTS)			



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2. Fangguang Test Location

These measurement tests were performed at the Fangguang Inspection and testing Co.,LTD located at 200 Linghu Avenue, Xinwu District, Wuxi City. The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.4-2014.



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	WiFi Module
Model Name:	MW-4E
Trade Mark:	/
Input Voltage Range:	DC 5V
Wi-Fi Specification:	802.11b/g/n20

2.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n20: 2412 ~ 2462MHz
Channel Number:	802.11b/g/n20: 11
Type of Modulation:	802.11b: DSSS
	802.11g/n: OFDM
Data Rate:	802.11b: 1/2/5.5/11Mbps
	802.11g: 6/9/12/18/24/36/48/54Mbps
	802.11n/: MCS0~MCS7
Antenna Type:	Rod Antenna
Antenna Gain:	3.16dBi

2.3. Operation Frequency / Channel List

802.11b/g/n20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz		



2.4. Description of Available Antennas

Antenna	Frequency Band	Product	Ty Pothe	Antenna
Antenna	(MHz)	Number	TA Fauls	Antenna
Rod Antenna	2400 ~2483	19-0062-002	1	Ant 1

Antenna	Frequency Band (MHz)	Tx Paths	Per Chain Max Antenna Gain (dBi) Ant 1	Beam Forming Directional Gain (dBi)	CDD Directional Gain (dBi)
Rod Antenna	2400 ~2483	1	3.16	NA	NA

Note:

Unequal Antenna gains, with equal transmit powers. For Antenna gains given by $G_1, G_2, ..., G_N dBi$ transmit signals are correlated, then

Directional gain = 10*log[(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})²/N_{ANT}] dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]



2.5. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS)

Note: 2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths. The maximum achievable duty cycle was determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles:

Test Made	Antonno		Transmission	Transmission	Duty Cycle
Test Mode	Antenna	Frequency[ivinz]	Duration [ms]	Period [ms]	[%]
		2412	1.23	2.01	61.19
11B	Ant1	2437	1.22	2.00	61.00
		2462	1.22	2.02	60.40
		2412	0.55	1.88	29.26
11G	Ant1	2437	0.55	1.03	53.40
		2462	0.54	1.00	54.00
		2412	0.55	0.99	55.56
11N20SISO	Ant1	2437	0.54	1.01	53.47
		2462	0.55	1.00	55.00

Test Graphs



2.6. Description of Test Software

The test utility software used during testing was "BLDevCube", Power Parameter Value:

Test Mode	ANT1
В	17
G	16
N20	15

2.7. Test Mode

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n20

2.8. Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.9. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.10. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50$ uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. The turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-25GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

• Use a unique coupling to the intentional radiator.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	FWXGJC-2016-181	1 year	2024/03/14
Two-Line V-Network	R&S	ENV 216	FWXGJC-2016-182	1 year	2024/05/14
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-385	1 year	2024/03/21

Radiated Emission

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Loop Antenna	Schwarzbeck	FMZB 1519B	FWXGJC-2018-015	3 year	2024/08/13
Bi-Log Antenna	R&S	HL562E	FWXGJC-2016-267-06	1 year	2024/03/10
Broadband Horn Antenna	R&S	HF907	FWXGJC-2016-267-07	1 year	2024/03/02
Broadband Horn Antenna	Schwarzbeck	BBHA9170	FWXGJC-2018-016	3 year	2024/06/04
EMI Receiver	R&S	ESR26	FWXGJC-2016-267-01	1 year	2023/11/08
Pre-Amplifier	R&S	SCU-18D	FWXGJC-2016-267-05	1 year	2023/11/17
Pre-Amplifier	R&S	EMC184055 SE	FWXGJC-2018-018	3 year	2025/04/13
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-386	1 year	2023/11/21
Anechoic Chamber	Aimuke	EMCCT-3	FWXGJC-2016-270	3 year	2025/06/07

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Keysight	N9010B	FWXGJC-2018-010	1 year	2024/03/13
RF Control Unit	Toncend	JS0806-2	FWXGJC-2018-013	1 year	2024/05/14
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-385	1 year	2024/03/21

Test Software	Manufacturer	Version	Asset No.	Function
EMI Test Software	tonscend	V2.5.0.0	FWXWA-2018-004	Emission Test
RF Test Software	Tonscend	3.2.22	/	/

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
2.05dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
30MHz-1GHz: 3.06dB
1GHz-12.75GHz: 4.13dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
30MHz-1GHz: 1.00 dB
1GHz-26.5GHz: 1.30 dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
0.60dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
0.80dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
0.20MHz

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.203	Antenna Requirement	/	1	Pass	Section 4
15.247(a)(2)	6dB Bandwidth	≥ 500kHz		Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 30dBm		Pass	Section 7.3
15.247(e)	Power Spectral Density	≤ 8dBm/3kHz		Pass	Section 7.4
15.247(d)	Band Edge	≥ 20dBc		Pass	Section 7.5
15.247(d)	Out-of-Band Emissions	≥ 20dBc Conducte		Pass	Section 7.5
15.205	Restricted Bands	Emissions in restricted bands must meet the radiated limits detailed in 15.205		Pass	Section 7.7
15.209	General Field Strength Limits (Radiated Emission Limits)	Radiated Emission must meet the radiated limits detailed in 15.209 (RSS GEN [8.9])	Radiated	Pass	Section 7.6
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	AC Line Conducted	NA	Section 7.8

Notes:

- All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.2.2. Test Procedure used

ANSI C63.10-2013 Section 11.8.2 Option 1

KDB 558074 D01 v05r02 - Section 8.2

7.2.3. Test Setting

- 1. Set RBW = 100 kHz
- 2. VBW ≥ 3 × RBW
- 3. Detector = peak
- 4. Trace mode = max hold
- 5. Sweep = auto couple
- 6. Allow the trace was allowed to stabilize
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.2.4. Test Setup

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	99%BW	Verdict
		2412	9.080	2407.480	2416.560	0.5	13.505	PASS
11B	Ant1	2437	9.560	2432.480	2442.040	0.5	13.515	PASS
		2462	9.560	2457.000	2466.560	0.5	13.672	PASS
11G A	Ant1	2412	16.360	2403.840	2420.200	0.5	17.094	PASS
		2437	16.320	2428.880	2445.200	0.5	17.165	PASS
		2462	16.360	2453.800	2470.160	0.5	17.223	PASS
11N20SISO	Ant1	2412	17.040	2403.480	2420.520	0.5	17.814	PASS
		2437	16.680	2428.880	2445.560	0.5	17.813	PASS
		2462	17.120	2453.400	2470.520	0.5	17.878	PASS

7.2.5. Test Result

Test Graphs of 6dB Bandwidth

Test Graphs of Occupied Channel Bandwidth

