## 1. Main antenna


(a) Main antenna information

Manufacturer: Shenzhen Bogesi Communication Ttechnology co., Ltd.


Address: Room 308, Building B, Sabenol Building, No.19, Kekezhong 1st Road,

Nanshan District, Shenzhen, Guangdong, China.

Antenna type: FPC




#### (b)VSWR





## (c)antenna passive data


Freq	Effi	Gain	Freq	Effi	Gain	Freq	Effi	Gain
(MHz)	(%)	(dBi)	(MHz)	(%)	(dBi)	(MHz)	(%)	(dBi)
700	33. 58	-1.54	1700	47.57	-0.94	2240	63. 93	1.66
710	37.75	-1.62	1720	52.11	-0.58	2260	63.01	2.03
720	39.7	-2.08	1740	50.8	0.07	2280	62. 97	1.96
730	40.25	-2.23	1760	53. 25	0.31	2300	59.4	1.78
740	45. 44	-1.64	1780	53.04	-0.08	2320	62.36	1.9
750	46.03	-1.27	1800	54.05	0.34	2340	65.07	2.1
760	46.08	-0.85	1820	54.8	0.97	2360	65. 94	2.39
770	46.71	-0.52	1840	51.74	1.39	2380	65. 65	2.41
780	42.2	-0.81	1860	52. 53	1.35	2400	66.09	1.99
790	41.05	-0.7	1880	54.76	1.31	2420	67.09	2. 7
800	40.45	-0.57	1900	52.12	1.66	2440	70.66	2.99
810	39. 27	-0.66	1920	50.33	1.94	2460	65.08	2.46
820	38. 73	-0.88	1940	50.45	2.13	2480	64.54	2.42
830	38. 82	-1.16	1960	51.38	2.15	2500	66.1	2.04
840	40.8	-0.59	1980	51.16	1.96	2520	66. 28	1.52
850	40.67	-0.49	2000	51.04	1.85	2540	63. 28	1.4
860	39. 36	-0.65	2020	52.17	1.9	2560	58. 23	1.06
870	38. 54	-0.68	2040	50.83	1.86	2580	58. 43	1.48
880	37.85	-0.63	2060	50.32	1.57	2600	63. 92	2.12
890	37. 75	-0.54	2080	53. 85	1.3	2620	55. 64	1.75
900	37.14	-0.95	2100	57.34	1.62	2640	55. 53	1.41
910	36.9	-1.38	2120	59.34	1.6	2660	56.6	1.85
920	35. 73	-1.81	2140	58. 28	1.39	2680	57. 41	1.3
930	33.88	-1.84	2160	58.5	1.08	2700	56. 26	0.63
940	34.27	-1.92	2180	60.56	0.62			
950	33. 9	-1.71	2200	60.42	0.26			
960	34.83	-1.96	2220	65. 36	0.99			

# (d) Directional diagram at 700MHz













#### at 960MHz













#### at 1700MHz













#### at 2200MHz













#### at 2700MHz









## 2. WIFI&BT&GPS antenna


#### (a) Main antenna information

Manufacturer: Shenzhen Bogesi Communication Ttechnology co.,Ltd.


Address: Room 308, Building B, Sabenol Building, No.19, Kekezhong 1st Road,

Nanshan District, Shenzhen, Guangdong, China.

**Antenna type:** FPC



#### (b)VSWR



## (c)antenna passive data

Freq	Effi	Gain	Freq	Effi	Gain	Freq	Effi	Gain	Freq	Effi	Gain
(MHz)	(%)	(dBi)	$(\mathtt{MHz})$	(%)	(dBi)	(MHz)	(%)	(dBi)	$(\mathtt{MHz})$	(%)	(dBi)
2400	57. 15	1.31	5100	51.13	0.9	5560	56.37	2. 54	1560	36. 67	-4.48
2410	63.09	2.02	5120	50.51	1.17	5580	56.3	2.18	1561	36. 89	-4.45
2420	63. 91	2. 32	5140	50.47	1.3	5600	59.49	2.17	1562	36.2	-4.41
2430	62.09	2.68	5160	47.87	0.98	5620	55. 22	1.43	1563	36.43	-4.39
2440	63. 25	2.8	5180	49.67	1.19	5640	58.35	2.07	1564	36.7	-4.35
2450	62.8	2. 72	5200	52.12	1.37	5660	60.67	2.54	1565	36. 94	-4.33
2460	61.05	2.5	5220	50.87	1.01	5680	53.81	2.12	1570	37. 78	-4.23
2470	60. 23	2.37	5240	51.25	0.71	5700	54.78	2. 37	1571	37. 76	-4.23
2480	61.84	2.42	5260	51.92	0.74	5720	53.03	2.17	1572	37.74	-4.23
2490	61.56	2. 25	5280	51.29	0.92	5740	51.96	1.97	1573	37. 77	-4.23
2500	62.89	1.78	5300	53.44	1.31	5760	58.07	2.67	1574	37.79	-4.23
			5320	56. 22	1.55	5780	58.92	3.09	1575	39. 85	-4.22
			5340	57.51	1.62	5800	60.69	3.12	1576	39.93	-4.21
			5360	60.03	1.73	5820	65.24	3. 37	1577	39.08	-4.19
			5380	59. 94	1.46	5840	62. 22	3.12	1578	40.25	-4.17
			5400	57.15	1.08	5860	56.87	2. 59	1579	40.31	-4.17
			5420	58. 39	1.39				1580	41.35	-4.16
			5440	52. 27	1.13				1600	41.67	-3.22
			5460	53.07	1.67				1601	42.06	-3.18
			5480	56.68	2.38				1602	43.3	-3.16
			5500	54.48	2. 32				1603	44.42	-3.15
			5520	55.06	2. 52				1604	44.36	-3.16
			5540	56. 27	2. 68				1605	45.23	-3.17

## (d) Directional diagram

