


## FCC RADIO TEST REPORT

Applicant..... : Acrox Technologies Co., Ltd  
Address..... : 4F., No.89, Minshan St., Neihu Dist., Taipei City 114, Taiwan, R.O.C  
Manufacturer..... : Acrox Technologies Co., Ltd  
Address..... : 4F., No.89, Minshan St., Neihu Dist., Taipei City 114, Taiwan, R.O.C  
Factory..... : Acrox Technologies Co., Ltd  
Address..... : Hsinmin Industrial, Changan Town, Dongguan City, Guangdong, China  
Product Name..... : 2.4GHz Wireless Mouse  
Brand Name..... : Amazon Basics  
Model No. .... : G74, G6K-B01, B08P6PL5R3 (For model difference refer to section 2)  
FCC ID..... : PRDMU93  
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.249)  
Receipt Date of Samples.... : November 11, 2020  
Date of Tested..... : November 12, 2020 to January 21, 2021  
Date of Report..... : February 03, 2021

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.

  
Prepared by  
Louisa Huang / Project Engineer

  
Approved by  
Ioff Fan / Authorized Signatory

## Table of Contents

1. Summary of Test Result.....	4
2. General Description of EUT .....	5
3. Test Channels and Modes Detail .....	7
4. Configuration of EUT .....	7
5. Modification of EUT .....	7
6. Description of Support Device.....	8
7. Test Facility and Location .....	9
8. Applicable Standards and References.....	9
9. Deviations and Abnormalities from Standard Conditions .....	10
10. Test Conditions .....	10
11. Measurement Uncertainty .....	11
12. Sample Calculations .....	12
13. Test Items and Results .....	13
13.1 Conducted Emissions Measurement.....	13
13.2 Radiated Spurious Emissions and Restricted Bands Measurement.....	15
13.3 20dB Bandwidth Measurement.....	23
13.4 Antenna Requirement.....	25
14. Test Equipment List.....	26

## Revision History

[illegible]

## 1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Conducted Emission	---	Not applicable
§15.249(a)/ 15.209	Radiated Emissions	PASS	---
§15.249(d)/ 15.205	Band Edge	PASS	---
§15.215(c)	20dB Bandwidth	PASS	---
§15.203	Antenna Requirement	PASS	---

## 2. General Description of EUT

Product Information	
Product Name:	2.4GHz Wireless Mouse
Main Model Name:	G74
Additional Model Name:	G6K-B01, B08P6PL5R3
Model Difference:	These models have the same circuitry, electrical mechanical, PCB Layout and physical construction. The differences is model number due to marketing purpose.
S/N:	L21A00050
Brand Name:	Amazon Basics
Hardware Version:	V1.0
Software Version:	V1.0
Rating:	2* DC 1.5V AAA battery
Typical arrangement:	Table-top
I/O Port:	N/A
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A
Additional Information	
Note:	According to these model difference, all tests were carried on model G74.
Remark:	<p>1. The EUT contains Mouse and USB Dongle two parts, and this report only applies to Mouse.</p> <p>2. All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.</p>

Technical Specification	
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK
Number of Channel:	40 (refer to following channel list for details)
Channel Space:	2MHz
Antenna Type:	PCB antenna
Antenna Gain:	0.9 dBi (Declared by the manufacturer)

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	15	2430	29	2458
2	2404	16	2432	30	2460
3	2406	17	2434	31	2462
4	2408	18	2436	32	2464
5	2410	19	2438	33	2466
6	2412	20	2440	34	2468
7	2414	21	2442	35	2470
8	2416	22	2444	36	2472
9	2418	23	2446	37	2474
10	2420	24	2448	38	2476
11	2422	25	2450	39	2478
12	2424	26	2452	40	2480
13	2426	27	2454	-	-
14	2428	28	2456	-	-

### 3. Test Channels and Modes Detail

Mode		Channel		Frequency (MHz)	Modulation	Data Rate (Mbps)
1	TX	Low	1	2402	GFSK	1
2	TX	Mid	20	2440	GFSK	1
3	TX	High	40	2480	GFSK	1
4.	Normal	---	---	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

### 4. Configuration of EUT

#### TX Mode

EUT

#### Normal Mode

EUT

laptop

Dongle

Note: The support device is kept in a remote area for normal mode.

### 5. Modification of EUT

No modifications are made to the EUT during all test items.

## 6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
1.	Laptop	Lenovo	02213DC	0A33012	Power cord, 1.8m, unshielded	---
2.	Power supply (Laptop)	Delta	92P1154	N/A		---
3.	Dongle	---	---	---	---	Provided by the manufacturer

No.	Test Software	Modulation	Power Setting
1.	No test software was used. The EUT was programmed a test firmware which used for testing.	GFSK	Default



## 7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	<p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2024</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2021</p> <p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number is 907417</p> <p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number is 46405-9743A</p> <p>The CAB identifier number is CN0015</p>
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

## 8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

### Test Standards:

47 CFR Part 15, Subpart C, 15.249

ANSI C63.10-2013

### References Test Guidance:

N/A

## 9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

## 10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	---	---	---	---
2.	Radiated Emissions	4	DC 3V	Ray Ding	See note 1
3.	Band Edge	1-3	DC 3V	Ray Ding	See note 1
4.	20dB Bandwidth	1-3	DC 3V	Ray Ding	See note 1
5.	Antenna Requirement	---	---	---	See note 1


### Note:

- The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35℃, 30~70%, 86~106kPa
- As the EUT can be operated multiple positions, all X,Y,Z axis were considered during the test and only the worst case X was recorded.


X Plane



Y Plane



Z Plane



- Only the worst case was recorded in the report.

## 11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	$\pm 2.52$ dB	---
2.	Radiated Emission Test	9kHz ~ 30MHz	$\pm 2.60$ dB	---
		30MHz ~ 1GHz	$\pm 4.68$ dB	---
		1GHz ~ 18GHz	$\pm 5.14$ dB	---
		18GHz ~ 40GHz	$\pm 5.14$ dB	---

**Note:**

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

## 12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB)	Measurement (dBUV)	Limit (dBUV)	Over (dB)	Detector
0.1900	30.10	10.60	40.70	79.00	-38.30	QP
<p>Where,</p> <p>Freq. = Emission frequency in MHz</p> <p>Reading Level = Uncorrected Analyzer/Receiver reading</p> <p>Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation</p> <p>Measurement = Reading + Corrector Factor</p> <p>Limit = Limit stated in standard</p> <p>Margin = Measurement - Limit</p> <p>Detector = Reading for Quasi-Peak / Average / Peak</p>						

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB/m)	Measurement (dBUV/m)	Limit (dBUV/m)	Over (dB)	Detector
60.0700	45.88	-18.38	27.50	49.00	-21.50	QP
<p>Where,</p> <p>Freq. = Emission frequency in MHz</p> <p>Reading Level = Uncorrected Analyzer/Receiver reading</p> <p>Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier</p> <p>Measurement = Reading + Corrector Factor</p> <p>Limit = Limit stated in standard</p> <p>Over = Margin, which calculated by Measurement - Limit</p> <p>Detector = Reading for Quasi-Peak / Average / Peak</p>						

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

## 13. Test Items and Results

### 13.1 Conducted Emissions Measurement


#### LIMIT

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
  2. The lower limit shall apply at the transition frequencies.
  3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

#### BLOCK DIAGRAM OF TEST SETUP



---

## TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

## TEST RESULTS

Not applicable.

## 13.2 Radiated Spurious Emissions and Restricted Bands Measurement

### LIMIT

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		$\mu\text{V/m}$	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		mV/m (Field strength of fundamental)	$\mu\text{V/m}$ (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500

Remark: (1) Emission level (dB) $\mu\text{V}$  = 20 log Emission level  $\mu\text{V/m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.


(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.


(5) §15.249(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

## BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.





## TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:  
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

---

## TEST RESULTS

PASS

Please refer to the following pages.

M/N: G74

Testing Voltage: DC 3V

Polarization: Horizontal

Detector: QP


Test Mode: 4

Distance: 3m

## Radiated Emission Measurement

Date: 2020/11/15

Time: 11:06:36



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	60.0700	25.96	-7.26	18.70	40.00	-21.30	QP
2	265.7100	26.08	-6.08	20.00	46.00	-26.00	QP
3	462.6200	25.95	-2.35	23.60	46.00	-22.40	QP
4	616.8500	25.51	0.89	26.40	46.00	-19.60	QP
5 *	806.9699	24.71	4.09	28.80	46.00	-17.20	QP
6	974.7800	24.58	6.42	31.00	54.00	-23.00	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: G74	Testing Voltage: DC 3V
Polarization: Vertical	Detector: QP
Test Mode: 4	Distance: 3m

## Radiated Emission Measurement

Date: 2020/11/15

Time: 11:13:52



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	52.3100	27.00	-7.30	19.70	40.00	-20.30	QP
2	198.7800	26.00	-8.80	17.20	43.50	-26.30	QP
3	399.5700	26.04	-4.34	21.70	46.00	-24.30	QP
4	590.6599	25.14	-0.54	24.60	46.00	-21.40	QP
5	776.9000	24.56	3.54	28.10	46.00	-17.90	QP
6 *	901.0600	25.53	4.97	30.50	46.00	-15.50	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Modulation: GFSK				Test Result: PASS			Test frequency range: 1-25GHz			
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
2402	V	67.85	29.77	0.13	67.98	29.90	114.00	94.00	-46.02	-64.10
4804	V	54.09	16.01	6.30	60.39	22.31	74.00	54.00	-13.61	-31.69
7206	V	47.82	9.74	10.44	58.26	20.18	74.00	54.00	-15.74	-33.82
---										
2402	H	83.28	45.20	0.13	83.41	45.33	114.00	94.00	-30.59	-48.67
4804	H	56.65	18.57	6.30	62.95	24.87	74.00	54.00	-11.05	-29.13
7206	H	49.02	10.94	10.44	59.46	21.38	74.00	54.00	-14.54	-32.62
---										
Operation Mode: TX Mode (Mid)										
2440	V	69.98	31.90	0.23	70.21	32.13	114.00	94.00	-43.79	-61.87
4880	V	52.31	14.23	6.60	58.91	20.83	74.00	54.00	-15.09	-33.17
7320	V	46.22	8.14	10.55	56.77	18.69	74.00	54.00	-17.23	-35.31
---										
2440	H	85.16	47.08	0.23	85.39	47.31	114.00	94.00	-28.61	-46.69
4880	H	54.84	16.76	6.60	61.44	23.36	74.00	54.00	-12.56	-30.64
7320	H	45.88	7.80	10.55	56.43	18.35	74.00	54.00	-17.57	-35.65
---										
Operation Mode: TX Mode (High)										
2480	V	74.60	36.52	0.34	74.94	36.86	114.00	94.00	-39.06	-57.14
4960	V	51.37	13.29	6.89	58.26	20.18	74.00	54.00	-15.74	-33.82
7440	V	45.63	7.55	10.60	56.23	18.15	74.00	54.00	-17.77	-35.85
---										
2480	H	83.18	45.10	0.34	83.52	45.44	114.00	94.00	-30.48	-48.56
4960	H	56.19	18.11	6.89	63.08	25.00	74.00	54.00	-10.92	-29.00
7440	H	46.35	8.27	10.60	56.95	18.87	74.00	54.00	-17.05	-35.13
---										

Remark: Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.

Band edge										
2390.000	H	67.23	29.15	0.09	67.32	29.24	74.00	54.00	-6.68	-24.76
2390.000	V	48.32	10.24	0.09	48.41	10.33	74.00	54.00	-25.59	-43.67
2398.000	H	70.08	31.93	0.13	70.21	32.06	74.00	54.00	-3.79	-21.94
2398.000	V	50.00	12.22	0.13	50.13	12.35	74.00	54.00	-23.87	-41.65
2483.500	H	59.63	21.55	0.34	59.97	21.89	74.00	54.00	-14.03	-32.11
2483.500	V	52.69	14.61	0.34	53.03	14.95	74.00	54.00	-20.97	-39.05

Note: Other band edge, the emissions are lower than 20dB below the allowable limit.




### 13.3 20dB Bandwidth Measurement

#### LIMIT

There is no limit.

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

The 20dB bandwidth of the emission was contained within the frequency band designated which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered, FCC Rule 15.215(c):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the tested channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

#### TEST RESULTS

PASS

Please refer to the following table.

GFSK				
Channel	Frequency (MHz)	Data Rate (Mbps)	20dB Bandwidth (MHz)	Result
1	2402	1	1.732	PASS
20	2440	1	1.789	PASS
40	2480	1	1.799	PASS
2402MHz		2440MHz		
				
2480MHz				



---

## 13.4 Antenna Requirement

### STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### ANTENNA CONNECTED CONSTRUCTION

The antenna is PCB antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 0.9dBi, Therefore, the antenna is consider meet the requirement.

## 14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Mar. 13, 2020	1 Year
2.	Antenna	Schwarzbeck	VULB9162	9162-010	Mar. 23, 2020	1 Year
3.	Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	Mar. 13, 2020	1 Year
4.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Mar. 13, 2020	1 Year
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	101094	Mar. 13, 2020	1 Year
6.	Horn Antenna	Schwarzbeck	BBHA9170	9170-172	Mar. 22, 2019	2 Year
7.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Mar. 13, 2020	1 Year
8.	Communication Tester	Rohde & Schwarz	CMW500	149004	Mar. 13, 2020	1 Year
9.	Horn Antenna	COM-Power	AH-118	071078	Mar. 23, 2020	1 Year
10.	Pre-Amplifier	HP	HP 8449B	3008A00964	Mar. 13, 2020	1 Year
11.	Pre-Amplifier	HP	HP 8447D	1145A00203	Mar. 13, 2020	1 Year
12.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Mar. 23, 2020	1 Year
13.	Test Receiver	Rohde & Schwarz	ESCI	101152	Mar. 14, 2020	1 Year
14.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Mar. 13, 2020	1 Year
15.	L.I.S.N	Rohde & Schwarz	ESH2-Z5	893606/014	Mar. 13, 2020	1 Year
16.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Mar.13, 2020	1 Year
17.	Temperature & Humidity Chamber	REMAFEE	SYHR225L	N/A	Mar. 13, 2020	1 Year
18.	DC Source	Maynuo	MY8811	N/A	Mar. 13, 2020	1 Year
19.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
20.	Chamber	SAEMC	9*7*7m	N/A	Jun. 20, 2019	2 Year
21.	Test Software	EZ	EZ_EM C	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---