

# FCC TEST REPORT

**FCC ID: 2BFX6-QB07**

**Report No.** : SSP25010129-1E

**Applicant** : Wuyi Jinheng Household goods Co., Ltd

**Product Name** : Game boxing disc

**Model Name** : QB07

**Test Standard** : FCC Part 15.247

**Date of Issue** : 2025-01-17




**Shenzhen CCUT Quality Technology Co., Ltd.**

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,  
Guangdong, China; (Tel.:+86-755-23406590 website: [www.ccuttest.com](http://www.ccuttest.com))

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

**Test Report Basic Information**

<b>Applicant</b> .....:	Wuyi Jinheng Household goods Co., Ltd No.9, Weijiu East Road, Tongqin Industrial Zone, Wuyi County, Jinhua, China, Address of Applicant.....: 570100	
<b>Manufacturer</b> .....:	Wuyi Jinheng Household goods Co., Ltd No.9, Weijiu East Road, Tongqin Industrial Zone, Wuyi County, Jinhua, China, Address of Manufacturer.....: 570100	
<b>Product Name</b> .....:	Game boxing disc	
<b>Brand Name</b> .....:	-	
<b>Main Model</b> .....:	QB07	
<b>Series Models</b> .....:	Q1, QB02, QB03, QB04, QB05, QB06	
<b>Test Standard</b> .....:	FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2013	
<b>Date of Test</b> .....	2025-01-13 to 2025-01-17	
<b>Test Result</b> .....:	PASS	
<b>Tested By</b> .....	<u>Coke Huang</u> (Coke Huang)	
<b>Reviewed By</b> .....:	<u>Lieber Ouyang</u> (Lieber Ouyang)	
<b>Authorized Signatory</b> .....:	<u>Lahm Peng</u> (Lahm Peng)	
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.		

## CONTENTS

<b>1. General Information.....</b>	<b>5</b>
1.1 Product Information .....	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments .....	8
1.6 Measurement Uncertainty .....	9
<b>2. Summary of Test Results .....</b>	<b>10</b>
<b>3. Antenna Requirement.....</b>	<b>11</b>
3.1 Standard and Limit.....	11
3.2 Test Result.....	11
<b>4. Conducted Emissions .....</b>	<b>12</b>
4.1 Standard and Limit.....	12
4.2 Test Procedure.....	12
4.3 Test Data and Results .....	13
<b>5. Radiated Emissions .....</b>	<b>16</b>
5.1 Standard and Limit.....	16
5.2 Test Procedure.....	16
5.3 Test Data and Results .....	18
<b>6. Band-edge Emissions(Radiated) .....</b>	<b>22</b>
6.1 Standard and Limit.....	22
6.2 Test Procedure.....	22
6.3 Test Data and Results .....	22
<b>7. Frequency Hopping System.....</b>	<b>24</b>
7.1 Standard and Limit.....	24
7.2 Test Procedure.....	24
7.3 Test Data and Results .....	25
<b>8. Dwell Time.....</b>	<b>26</b>
8.1 Standard and Limit.....	26
8.2 Test Procedure.....	26
8.3 Test Data and Results .....	27
<b>9. Maximum Peak Conducted Output Power .....</b>	<b>31</b>
9.1 Standard and Limit.....	31
9.2 Test Procedure.....	31
9.3 Test Data and Results .....	31
<b>10. Occupied Bandwidth(-20dB) .....</b>	<b>34</b>
10.1 Standard and Limit.....	34
10.2 Test Procedure.....	34
10.3 Test Data and Results .....	34
<b>11. Carrier Frequencies Separation.....</b>	<b>38</b>
11.1 Standard and Limit.....	38
11.2 Test Procedure.....	38
11.3 Test Data and Results .....	38
<b>12. Number of Hopping Channel.....</b>	<b>41</b>
12.1 Standard and Limit.....	41
12.2 Test Procedure.....	41
12.3 Test Data and Results .....	41
<b>13. Band-edge Emission(Conducted).....</b>	<b>43</b>
13.1 Standard and Limit.....	43
13.2 Test Procedure.....	43
13.3 Test Data and Results .....	43
<b>14. Conducted RF Spurious Emissions.....</b>	<b>49</b>
14.1 Standard and Limit.....	49
14.2 Test Procedure.....	49
14.3 Test Data and Results .....	49

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-01-17	Initial Release	Lahm Peng

## 1. General Information

### 1.1 Product Information

Product Name:	Game boxing disc
Trade Name:	-
Main Model:	QB07
Series Models:	Q1, QB02, QB03, QB04, QB05, QB06
Rated Voltage:	DC 3.7V by battery, USB 5V Charging
Power Adapter:	-
Battery:	DC 3.7V, 1200mAh
Test Sample No:	SSP25010129-1
Hardware Version:	1.0
Software Version:	1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The model name of the listed series of models is different from the main model, but the circuit and electronic structure are the same, which is declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BR/EDR
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	2.59dBm
Number of Channel:	79
Channel Separation:	1MHz
Modulation:	GFSK, Pi/4 DQPSK, 8DPSK
Antenna Gain:	0.56dBi
Type of Antenna:	PCB Antenna
Type of Device:	<input checked="" type="checkbox"/> Portable Device <input type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

## 1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Lowest Channel	2402MHz(DH5/2DH5/3DH5)	
TM2	Middle Channel	2441MHz(DH5/2DH5/3DH5)	
TM3	Highest Channel	2480MHz(DH5/2DH5/3DH5)	
TM4	Hopping	2402MHz~2480MHz	
TM5	Charging	AC 120V/60Hz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	HUAWEI	HW-110600C02	JL28L4P2D06114
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	21	2422	41	2442	61	2462
02	2403	22	2423	42	2443	62	2463
03	2404	23	2424	43	2444	63	2464
04	2405	24	2425	44	2445	64	2465
05	2406	25	2426	45	2446	65	2466
~	~	~	~	~	~	~	~
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

### 1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

### 1.4 Test Facilities

Laboratory Name:	<b>Shenzhen CCUT Quality Technology Co., Ltd.</b> 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

## 1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
<b>Conducted Emissions</b>					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
<b>Radiated Emissions</b>					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
<b>Conducted RF Testing</b>					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A



## 1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB

## 2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(a)(1), (g), (h)	Frequency Hopping System	Passed
FCC Part 15.247(a)(1)(iii)	Dwell Time	Passed
FCC Part 15.247(b)(1)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.215(c)	Occupied Bandwidth(-20dB)	Passed
FCC Part 15.247(a)(1)	Carrier Frequencies Separation	Passed
FCC Part 15.247(a)(1)(iii)	Number of Hopping Channel	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

### **3. Antenna Requirement**

---

#### **3.1 Standard and Limit**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Test Result**

This product has an PCB antenna, fulfill the requirement of this section.

## 4. Conducted Emissions

### 4.1 Standard and Limit

According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz  
Note 2: The lower limit applies at the band edges

### 4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

### **4.3 Test Data and Results**

All of the modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


## Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2084	24.75	9.23	33.98	63.27	-29.29	QP	P	
2	0.2084	12.37	9.23	21.60	53.27	-31.67	AVG	P	
3	0.5700	23.31	9.37	32.68	56.00	-23.32	QP	P	
4	0.5700	13.02	9.37	22.39	46.00	-23.61	AVG	P	
5	0.8655	28.82	9.39	38.21	56.00	-17.79	QP	P	
6 *	0.8655	19.67	9.39	29.06	46.00	-16.94	AVG	P	
7	1.7070	21.07	9.45	30.52	56.00	-25.48	QP	P	
8	1.7070	11.35	9.45	20.80	46.00	-25.20	AVG	P	
9	4.7670	15.12	9.56	24.68	56.00	-31.32	QP	P	
10	4.7670	2.81	9.56	12.37	46.00	-33.63	AVG	P	
11	27.8610	17.84	10.08	27.92	60.00	-32.08	QP	P	
12	27.8610	6.17	10.08	16.25	50.00	-33.75	AVG	P	


## Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2983	23.51	9.59	33.10	60.29	-27.19	QP	P	
2	0.2983	13.80	9.59	23.39	50.29	-26.90	AVG	P	
3	0.5413	26.80	9.58	36.38	56.00	-19.62	QP	P	
4	0.5413	16.18	9.58	25.76	46.00	-20.24	AVG	P	
5	0.8610	33.55	9.58	43.13	56.00	-12.87	QP	P	
6 *	0.8610	23.86	9.58	33.44	46.00	-12.56	AVG	P	
7	1.5540	26.08	9.64	35.72	56.00	-20.28	QP	P	
8	1.5540	16.17	9.64	25.81	46.00	-20.19	AVG	P	
9	2.6655	23.37	9.68	33.05	56.00	-22.95	QP	P	
10	2.6655	12.86	9.68	22.54	46.00	-23.46	AVG	P	
11	5.6400	18.73	9.76	28.49	60.00	-31.51	QP	P	
12	5.6400	8.33	9.76	18.09	50.00	-31.91	AVG	P	

## 5. Radiated Emissions

### 5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

*Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.*


### 5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.






Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:  
Span = wide enough to fully capture the emission being measured  
RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$ , 10kHz for  $f < 30\text{MHz}$   
VBW  $\geq$  RBW, Sweep = auto  
Detector function = peak  
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


### 5.3 Test Data and Results

All of the GFSK,  $\pi/4$  DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case GFSK\_2402MHz as below:


Remark: Level = Reading + Factor, Margin = Level - Limit

## Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	40.4172	27.60	-8.30	19.30	40.00	-20.70	QP	199	348	P	
2	191.7450	44.91	-11.31	33.60	43.50	-9.90	QP	199	277	P	
3	256.5211	43.84	-9.73	34.11	46.00	-11.89	QP	100	62	P	
4 !	320.0020	51.74	-7.27	44.47	46.00	-1.53	QP	100	41	P	
5 *	384.0118	50.81	-6.12	44.69	46.00	-1.31	QP	100	297	P	
6	638.3686	39.40	-1.02	38.38	46.00	-7.62	QP	199	348	P	



Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
4804	78.17	-14.72	63.45	74	-10.55	H	PK
4804	60.56	-14.72	45.84	54	-8.16	H	AV
7206	64.19	-8.41	55.78	74	-18.22	H	PK
7206	50.14	-8.41	41.73	54	-12.27	H	AV
4804	76.34	-14.72	61.62	74	-12.38	V	PK
4804	58.1	-14.72	43.38	54	-10.62	V	AV
7206	64.88	-8.41	56.47	74	-17.53	V	PK
7206	47.23	-8.41	38.82	54	-15.18	V	AV
Lowest Channel (GFSK_2441MHz)							
4882	74.9	-14.64	60.26	74	-13.74	H	PK
4882	60.5	-14.64	45.86	54	-8.14	H	AV
7323	63.97	-8.28	55.69	74	-18.31	H	PK
7323	47.19	-8.28	38.91	54	-15.09	H	AV
4882	78.62	-14.64	63.98	74	-10.02	V	PK
4882	58.42	-14.64	43.78	54	-10.22	V	AV
7323	65.48	-8.28	57.2	74	-16.8	V	PK
7323	45.72	-8.28	37.44	54	-16.56	V	AV
Lowest Channel (GFSK_2480MHz)							
4960	79.27	-14.53	64.74	74	-9.26	H	PK
4960	60.09	-14.53	45.56	54	-8.44	H	AV
7440	64.38	-8.13	56.25	74	-17.75	H	PK
7440	48.83	-8.13	40.7	54	-13.3	H	AV
4960	74.52	-14.53	59.99	74	-14.01	V	PK
4960	57.45	-14.53	42.92	54	-11.08	V	AV
7440	64.2	-8.13	56.07	74	-17.93	V	PK
7440	50.16	-8.13	42.03	54	-11.97	V	AV

Note 1: All of the GFSK,  $\pi/4$  DQPSK and 8DPSK modes have been tested. This EUT was tested in 3 orthogonal positions and the worst case position data of GFSK was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

## 6. Band-edge Emissions(Radiated)

### 6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### 6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

### 6.3 Test Data and Results

All of the GFSK,  $\pi/4$  DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case GFSK as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
2310	67.31	-21.34	45.97	74	-28.03	H	PK
2310	52.13	-21.34	30.79	54	-23.21	H	AV
2390	66.42	-20.96	45.46	74	-28.54	H	PK
2390	49.68	-20.96	28.72	54	-25.28	H	AV
2400	71.26	-20.91	50.35	74	-23.65	H	PK
2400	53.47	-20.91	32.56	54	-21.44	H	AV
2310	69.54	-21.34	48.2	74	-25.8	V	PK
2310	51.63	-21.34	30.29	54	-23.71	V	AV
2390	69.13	-20.96	48.17	74	-25.83	V	PK
2390	51.98	-20.96	31.02	54	-22.98	V	AV
2400	74.71	-20.91	53.8	74	-20.2	V	PK
2400	56.18	-20.91	35.27	54	-18.73	V	AV
Highest Channel (GFSK_2480MHz)							
2483.50	72.29	-20.51	51.78	74	-22.22	H	PK
2483.50	56.72	-20.51	36.21	54	-17.79	H	AV
2500	68.51	-20.43	48.08	74	-25.92	H	PK
2500	49.68	-20.43	29.25	54	-24.75	H	AV
2483.50	67.59	-20.51	47.08	74	-26.92	V	PK
2483.50	53.77	-20.51	33.26	54	-20.74	V	AV
2500	64.65	-20.43	44.22	74	-29.78	V	PK
2500	52.49	-20.43	32.06	54	-21.94	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

## 7. Frequency Hopping System

---

### 7.1 Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 7.2 Test Procedure

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.



### 7.3 Test Data and Results

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 8. Dwell Time

### 8.1 Standard and Limit

According to 15.247 (a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed..

### 8.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- 3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- 4) Sweep Time is more than once pulse time.
- 5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- 6) Measure the maximum time duration of one single pulse.
- 7) Set the EUT for packet transmitting.
- 8) Measure the maximum time duration of one single pulse.
- 9) The EUT was set to the Hopping Mode for Dwell Time Test.



Test Setup Block Diagram

### 8.3 Test Data and Results


Test Mode	Data Packet	Channel (MHz)	Pulse Duration (ms)	Burst Count	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	2441	0.382	319	121.858	<400	Pass
	DH3	2441	1.638	172	281.736	<400	Pass
	DH5	2441	2.887	93	268.491	<400	Pass
Pi/4 DQPSK	2DH1	2441	0.391	319	124.729	<400	Pass
	2DH3	2441	1.643	154	253.022	<400	Pass
	2DH5	2441	2.892	110	318.12	<400	Pass
8DPSK	3DH1	2441	0.392	319	125.048	<400	Pass
	3DH3	2441	1.642	163	267.646	<400	Pass
	3DH5	2441	2.893	91	263.263	<400	Pass

Note:


1. Pulse Duration\*Burst Count= Dwell Time

## GFSK (2441MHz)


Burst(DH1)




Accumulate(DH1)




Burst(DH3)




Accumulate(DH3)



Burst(DH5)




Accumulate(DH5)






## Pi/4 DQPSK (2441MHz)


Burst(2DH1)




Accumulate(2DH1)




Burst(2DH3)




Accumulate(2DH3)



Burst(2DH5)




Accumulate(2DH5)




## 8DPSK (2441MHz)


Burst(3DH1)




Accumulate(3DH1)




Burst(3DH3)




Accumulate(3DH3)



Burst(3DH5)



Accumulate(3DH5)





## 9. Maximum Peak Conducted Output Power

### 9.1 Standard and Limit

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### 9.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

### 9.3 Test Data and Results

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	1.61	21	Pass
	2441	0.33	21	Pass
	2480	-2.18	21	Pass
Pi/4 DQPSK	2402	2.29	21	Pass
	2441	1.11	21	Pass
	2480	-1.37	21	Pass
8DPSK	2402	2.59	21	Pass
	2441	1.47	21	Pass
	2480	-0.96	21	Pass

## GFSK

2402MHz



## Pi/4 DQPSK

2402MHz



2441MHz



2441MHz



2480MHz



2480MHz





## 8DPSK

2402MHz



2441MHz



2480MHz



## 10. Occupied Bandwidth(-20dB)

### 10.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 10.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.


- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

### 10.3 Test Data and Results

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (kHz)
GFSK	2402	1.034	902.39
	2441	1.015	881.15
	2480	1.011	897.62
Pi/4 DQPSK	2402	1.303	1196.8
	2441	1.302	1192.9
	2480	1.328	1193.6
8DPSK	2402	1.297	1204.4
	2441	1.3	1205
	2480	1.304	1198.1



## 8DPSK

2402MHz



2441MHz



2480MHz





## 11. Carrier Frequencies Separation

### 11.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 11.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto, Detector = Peak.
- 4) By using the Max Hold function, record the separation of two adjacent channels.
- 5) Measure the frequency difference of these two adjacent channels by spectrum analyzer mark function. and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat above procedures until all frequencies measured were complete.



### 11.3 Test Data and Results

Test Mode	Test Channel	Test Freq. 1 (MHz)	Test Freq. 2 (MHz)	CFS (MHz)	Limit (MHz)
GFSK	Lowest	2401.968	2402.934	0.966	0.689
	Middle	2440.948	2441.956	1.008	0.677
	Highest	2478.964	2479.964	1	0.674
Pi/4 DQPSK	Lowest	2401.966	2402.958	0.992	0.869
	Middle	2440.8	2441.804	1.004	0.868
	Highest	2478.8	2479.802	1.002	0.885
8DPSK	Lowest	2401.968	2402.958	0.99	0.865
	Middle	2441.086	2441.98	0.894	0.867
	Highest	2478.794	2479.954	1.16	0.869

Note: CFS(Channel Frequency Separation) = Test Freq. 2 - Test Freq. 1


## GFSK

Lowest



## Pi/4 DQPSK


Lowest



Middle




Middle



Highest



Highest




## 8DPSK


## Lowest



## Middle



## Highest





## 12. Number of Hopping Channel

### 12.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 12.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Set the spectrum analyzer on Max hold mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- 5) Set the spectrum analyzer on View mode and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

### 12.3 Test Data and Results


Test Mode	Number of Hopping Channel	Limit	Test Result
GFSK	79	15	Pass
Pi/4 DQPSK	79	15	Pass
8DPSK	79	15	Pass

## Number of Hopping Channel


## GFSK



## Pi/4 DQPSK



## 8DPSK



## 13. Band-edge Emission(Conducted)

### 13.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### 13.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

### 13.3 Test Data and Results


Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
No-Hopping					
GFSK	Lowest	2402	-54.61	-20	Pass
	Highest	2480	-53.52	-20	Pass
Pi/4 DQPSK	Lowest	2402	-50.65	-20	Pass
	Highest	2480	-52.63	-20	Pass
8DPSK	Lowest	2402	-50.35	-20	Pass
	Highest	2480	-50.17	-20	Pass
Hopping					
GFSK	Lowest	2402	-52.23	-20	Pass
	Highest	2480	-51.76	-20	Pass
Pi/4 DQPSK	Lowest	2402	-52.31	-20	Pass
	Highest	2480	-51.55	-20	Pass
8DPSK	Lowest	2402	-51.95	-20	Pass
	Highest	2480	-50.89	-20	Pass

## No-Hopping GFSK Lowest

Reference Power




Band-edge Emission




## No-Hopping GFSK Highest

Reference Power




Band-edge Emission




## No-Hopping Pi/4 DQPSK Lowest

Reference Power




Band-edge Emission






## No-Hopping Pi/4 DQPSK Highest

Reference Power




Band-edge Emission




## No-Hopping 8DPSK Lowest

Reference Power




Band-edge Emission




## No-Hopping 8DPSK Highest


Reference Power



Band-edge Emission



## Reference Power



Keysight Spectrum Analyzer - Sweet 25

Center Freq 2.356000000 GHz

Ref Offset 1.69 dB  
Ref 20.00 dBm

Mkr1 2.404 8 GHz  
1.404 dBm


Start 2.30600 GHz  
#Res BW 100 kHz

#VBW 300 kHz

Stop 2.40600 GHz  
Sweep 9.600 ms (1001 pts)

Marker	Hz	dBm
1	2.404 8 GHz	1.404 dBm
2	2.400 9 GHz	-51.943 dBm
3	2.390 0 GHz	-56.819 dBm
4	2.378 0 GHz	-51.273 dBm

## Reference Power



Center Freq 2.526000000 GHz


Avg Type: RMS

Sweep 9.000 ms (1001 pts)

Mkr1 2.476 0 GHz -2.367 dBm

LINE	MODE	FREQ	CLL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.476 0 GHz	-2.367 dBm			
2	N	1	f	2.483 5 GHz	-56.077 dBm			
3	N	1	f	2.500 0 GHz	-55.863 dBm			
4	N	1	f	2.495 9 GHz	-54.289 dBm			

## Reference Power



Keysight Spectrum Analyzer - Sweet 5X

Center Freq 2.356000000 GHz

Ref Offset 1.69 dB  
Ref 70.00 dBm

Mkr1 2.4058 GHz  
1.289 dBm

Start 2.30600 GHz  
#Res BW 100 kHz

#VBW 300 kHz

Stop 2.40600 GHz  
Sweep 2.600 ms (1001 pts)

Marker	Freq (GHz)	Amplitude (dBm)
1	2.4058 GHz	1.289 dBm
2	2.4009 GHz	-56.512 dBm
3	2.3993 GHz	-55.873 dBm
4	2.3728 GHz	-51.369 dBm




## Hopping Pi/4 DQPSK Highest

Reference Power




Band-edge Emission




## Hopping 8DPSK Lowest

Reference Power




Band-edge Emission




## Hopping 8DPSK Highest

Reference Power



Band-edge Emission





## 14. Conducted RF Spurious Emissions


### 14.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### 14.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
- 6) Repeat above procedures until all measured frequencies were complete.



Test Setup Block Diagram


### 14.3 Test Data and Results

*Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.*


## Reference Power




## Spurious Emissions



## Reference Power




## Spurious Emissions



## Reference Power



## Spurious Emissions




## Pi/4 DQPSK Lowest

Reference Power



Spurious Emissions




## Pi/4 DQPSK Middle

Reference Power



Spurious Emissions




## Pi/4 DQPSK Highest

Reference Power




Spurious Emissions






## 8DPSK Lowest

Reference Power



Spurious Emissions




## 8DPSK Middle

Reference Power




Spurious Emissions




## 8DPSK Highest

Reference Power



Spurious Emissions



\*\*\*\*\* END OF REPORT \*\*\*\*\*